

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 May 2002 (10.05.2002)

PCT

(10) International Publication Number
WO 02/37488 A1

(51) International Patent Classification⁷: **G11B 9/00**,
G01B 7/34

(21) International Application Number: PCT/IB01/01688

(22) International Filing Date:
17 September 2001 (17.09.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
00123992.0 3 November 2000 (03.11.2000) EP

(71) Applicant (for all designated States except US): **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NY 10504 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **BINNIG, Gerd, K.** [DE/CH]; Felsenstrasse 72, CH-8832 Wollerau (CH). **DESPONT, Michel** [CH/CH]; Eggstrasse 9, CH-8134 Adliswil (CH). **VETTIGER, Peter** [CH/CH]; Langmoosstrasse 33, CH-8135 Langnau am Albis (CH).

(74) Agent: **WILLIAMS, Julian, David**; International Business Machines Corporation, Saeumerstrasse 4, CH-8803 Rueschlikon (CH).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: AFM-BASED DATA STORAGE AND MICROSCOPY



(57) Abstract: Read/write components for AFM-based data storage devices are provided. In particular embodiments, a read/write component (30, 45, 50, 65, 80) comprises lever means (31, 51, 66, 82) and a support structure (32, 52, 67, 81), the lever means being connected to the support structure for substantially pivotal movement. The lever means (31, 51, 66, 82) provides first and second current paths between a pair of electrical supply lines (R, C) on the support structure via which the lever means can be connected in use to power supply means operable in a write mode and a read mode. A write-mode heater (36, 47, 56, 73) is provided on the lever means in the first current path, and a read/write tip (37, 57, 74, 84) is provided on the write-mode heater. A read-mode heater (39, 46, 58, 75, 83) is provided on the lever means in the second current path. Decoupling means (38a, 38b, 40a, 40b, 60, 61, 77a, 77b, 78a, 78b) is arranged to inhibit current flow to the write-mode heater via the first current path in use when the power supply means is operated in the read mode. The component, with separate write and read-mode heaters, can thus be addressed in both the write and read modes via a single pair of supply lines.

Other embodiments provide read/write components (100) employing a thermal decoupling mechanism, and read/write components (80) where read-sensing is performed by a proximity sensing arrangement between the lever means and the support structure. Sensing apparatus (115) for atomic force microscopes is also provided where tip movement can be detected via similar proximity sensing arrangements.



(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.