

**METHOD AND DEVICE FOR SEPARATING HYDROCARBONS AND
CONTAMINANTS WITH A HEATING MECHANISM TO DESTABILIZE AND/OR
PREVENT ADHESION OF SOLIDS**

5 CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the priority benefit of United States patent application number 61/912,986 filed December 6, 2013 entitled METHOD AND DEVICE FOR SEPARATING HYDROCARBONS AND CONTAMINANTS WITH A HEATING MECHANISM TO DESTABILIZE AND/OR PREVENT ADHESION OF SOLIDS, the
10 entirety of which is incorporated by reference herein.

[0002] This application is related to but does not claim priority to U.S. Provisional patent application numbers: 61/912,957 filed December 6, 2013 entitled METHOD AND DEVICE FOR SEPARATING HYDROCARBONS AND CONTAMINANTS WITH A SPRAY ASSEMBLY; 62/044,770 filed September 2, 2014 entitled METHOD AND DEVICE FOR
15 SEPARATING HYDROCARBONS AND CONTAMINANTS WITH A SPRAY ASSEMBLY; 61/912,959 filed on December 6, 2013 entitled METHOD AND SYSTEM OF MAINTAINING A LIQUID LEVEL IN A DISTILLATION TOWER; 61/912,964 filed on December 6, 2013 entitled METHOD AND DEVICE FOR SEPARATING A FEED STREAM USING RADIATION DETECTORS; 61/912,970 filed on December 6, 2013
20 entitled METHOD AND SYSTEM OF DEHYDRATING A FEED STREAM PROCESSED IN A DISTILLATION TOWER; 61/912,975 filed on December 6, 2013 entitled METHOD AND SYSTEM FOR SEPARATING A FEED STREAM WITH A FEED STREAM DISTRIBUTION MECHANISM; 61/912,978 filed on December 6, 2013 entitled METHOD AND SYSTEM FOR PREVENTING ACCUMULATION OF SOLIDS IN A
25 DISTILLATION TOWER; 61/912,983 filed on December 6, 2013 entitled METHOD OF REMOVING SOLIDS BY MODIFYING A LIQUID LEVEL IN A DISTILLATION TOWER; 61/912,984 filed on December 6, 2013 entitled METHOD AND SYSTEM OF MODIFYING A LIQUID LEVEL DURING START-UP OPERATIONS; 61/912,987 filed on December 6, 2013 entitled METHOD AND DEVICE FOR SEPARATING
30 HYDROCARBONS AND CONTAMINANTS WITH A SURFACE TREATMENT MECHANISM.

BACKGROUND

Fields of Disclosure

[0003] The disclosure relates generally to the field of fluid separation. More specifically, the disclosure relates to the cryogenic separation of contaminants, such as acid gas, from a hydrocarbon.

Description of Related Art

[0004] This section is intended to introduce various aspects of the art, which may be associated with the present disclosure. This discussion is intended to provide a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

[0005] The production of natural gas hydrocarbons, such as methane and ethane, from a reservoir oftentimes carries with it the incidental production of non-hydrocarbon gases. Such gases include contaminants, such as at least one of carbon dioxide (“CO₂”), hydrogen sulfide (“H₂S”), carbonyl sulfide, carbon disulfide and various mercaptans. When a feed stream being produced from a reservoir includes these contaminants mixed with hydrocarbons, the stream is oftentimes referred to as “sour gas.”

[0006] Many natural gas reservoirs have relatively low percentages of hydrocarbons and relatively high percentages of contaminants. Contaminants may act as a diluent and lower the heat content of hydrocarbons. Some contaminants, like sulfur-bearing compounds, are noxious and may even be lethal. Additionally, in the presence of water some contaminants can become quite corrosive.

[0007] It is desirable to remove contaminants from a stream containing hydrocarbons to produce sweet and concentrated hydrocarbons. Specifications for pipeline quality natural gas typically call for a maximum of 2 – 4% CO₂ and ¼ grain H₂S per 100 scf (4 ppmv) or 5 mg/Nm³ H₂S. Specifications for lower temperature processes such as natural gas liquefaction plants or nitrogen rejection units typically require less than 50 ppm CO₂.

[0008] The separation of contaminants from hydrocarbons is difficult and consequently significant work has been applied to the development of hydrocarbon/contaminant separation methods. These methods can be placed into three general classes: absorption by solvents (physical, chemical and hybrids), adsorption by solids, and distillation.

- [0009] Separation by distillation of some mixtures can be relatively simple and, as such, is widely used in the natural gas industry. However, distillation of mixtures of natural gas hydrocarbons, primarily methane, and one of the most common contaminants in natural gas, carbon dioxide, can present significant difficulties. Conventional distillation principles and conventional distillation equipment are predicated on the presence of only vapor and liquid phases throughout the distillation tower. The separation of CO₂ from methane by distillation involves temperature and pressure conditions that result in solidification of CO₂ if a pipeline or better quality hydrocarbon product is desired. The required temperatures are cold temperatures typically referred to as cryogenic temperatures.
- 10 [0010] Certain cryogenic distillations can overcome the above mentioned difficulties. These cryogenic distillations provide the appropriate mechanism to handle the formation and subsequent melting of solids during the separation of solid-forming contaminants from hydrocarbons. The formation of solid contaminants in equilibrium with vapor-liquid mixtures of hydrocarbons and contaminants at particular conditions of temperature and pressure takes place in a controlled freeze zone section.
- 15 [0011] Sometimes solids can adhere to an internal (e.g., controlled freeze zone wall) of the controlled freeze zone section rather than falling to the bottom of the controlled freeze zone section.
- [0012] The adherence is disadvantageous. The adherence, if uncontrolled, can interfere with the proper operation of the controlled freeze zone and the effective separation of methane from the contaminants.
- 20 [0013] A need exists for improved technology to destabilize and/or prevent any adhesion of solids to surface(s) in the controlled freeze zone section.

SUMMARY

- 25 [0014] The present disclosure provides a device and method for separating contaminants from hydrocarbons and destabilizing and/or preventing the adhesion of solids to surface(s) in the controlled freeze section, among other things.
- [0015] The method for separating a feed stream in a distillation tower comprises introducing a feed stream into one of a stripper section and a controlled freeze zone section of a distillation tower, the feed stream comprising a hydrocarbon and a contaminant; separating the feed stream in the stripper section into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the hydrocarbon,
- 30

at a temperature and pressure at which no solid forms; contacting the freezing zone vapor stream in the controlled freeze zone section with a freezing zone liquid stream, comprising the hydrocarbon, at a temperature and pressure at which a solid, comprising the contaminant forms, and a vapor stream, further enriched in the hydrocarbon emerges; directly applying
5 heat to the controlled freeze zone wall of the controlled freeze zone section with a heating mechanism coupled to at least one of a controlled freeze zone internal surface of the controlled freeze zone wall and a controlled freeze zone external surface of the controlled freeze zone wall; and at least one of destabilizing and preventing adhesion of the solid to the controlled freeze zone wall with the heating mechanism.

- 10 **[0016]** The distillation tower that separates a contaminant in a feed stream from a hydrocarbon in the feed stream comprises a stripper section constructed and arranged to separate a feed stream, comprising a contaminant and a hydrocarbon, into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the hydrocarbon, at a temperature and pressure at which no solids form; a
15 controlled freeze zone section comprising: a melt tray assembly at a bottom section of the controlled freeze zone section that is constructed and arranged to melt a solid, comprising the contaminant, formed in the controlled freeze zone section; a heating mechanism coupled to at least one of a controlled freeze zone internal surface of a controlled freeze zone wall of the controlled freeze zone section and a controlled freeze zone external surface of the controlled
20 freeze zone wall that at least one of destabilizes and prevents adhesion of the solid to the controlled freeze zone wall, wherein the heating mechanism is in an upper section of the controlled freeze zone section that directly abuts and is separate from the bottom section.

- [0017]** A method for producing hydrocarbons may comprise extracting a feed stream comprising a hydrocarbon and a contaminant from a reservoir; introducing the feed stream
25 into one of a stripper section and a controlled freeze zone section of a distillation tower; separating the feed stream in the stripper section into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the hydrocarbon, at a temperature and pressure at which no solid forms; contacting the freezing zone vapor stream in the controlled freeze zone section with a freezing zone liquid stream, comprising the hydrocarbon, at a temperature and pressure at which the freezing zone vapor stream forms a solid, comprising the contaminant, and a hydrocarbon-enriched vapor stream, comprising the hydrocarbon; directly applying heat to a controlled freeze zone wall of the
30 controlled freeze zone section with a heating mechanism coupled to at least one of a

controlled freeze zone internal surface of the controlled freeze zone wall and a controlled freeze zone external surface of the controlled freeze zone wall; at least one of destabilizing and preventing adhesion of the solid to the controlled freeze zone wall with the heating mechanism; removing the hydrocarbon-enriched vapor stream from the distillation tower; and
5 producing the hydrocarbon-enriched vapor stream extracted from the distillation tower.

[0018] The foregoing has broadly outlined the features of the present disclosure so that the detailed description that follows may be better understood. Additional features will also be described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

10 [0019] These and other features, aspects and advantages of the disclosure will become apparent from the following description, appending claims and the accompanying drawings, which are briefly described below.

[0020] Figure 1 is a schematic diagram of a tower with sections within a single vessel.

[0021] Figure 2 is a schematic diagram of a tower with sections within multiple vessels.

15 [0022] Figure 3 is a schematic diagram of a tower with sections within a single vessel.

[0023] Figure 4 is a schematic diagram of a tower with sections within multiple vessels.

[0024] Figure 5 is a schematic, cross-sectional diagram of the controlled freeze zone section of a distillation tower.

20 [0025] Figure 6 is a schematic diagram of section 38 of Figure 5 when the heating mechanism comprises a heating coil.

[0026] Figure 7 is a schematic diagram of section 38 of Figure 5 when the heating mechanism comprises an electrical conductor.

[0027] Figure 8 is a flowchart of a method within the scope of the present disclosure.

25 [0028] It should be noted that the figures are merely examples and no limitations on the scope of the present disclosure are intended thereby. Further, the figures are generally not drawn to scale, but are drafted for purposes of convenience and clarity in illustrating various aspects of the disclosure.

DETAILED DESCRIPTION

30 [0029] For the purpose of promoting an understanding of the principles of the disclosure, reference will now be made to the features illustrated in the drawings and specific language

will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Any alterations and further modifications, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one skilled in the art to which the disclosure relates.

5 It will be apparent to those skilled in the relevant art that some features that are not relevant to the present disclosure may not be shown in the drawings for the sake of clarity.

[0030] As referenced in this application, the terms “stream,” “gas stream,” “vapor stream,” and “liquid stream” refer to different stages of a feed stream as the feed stream is processed in a distillation tower that separates methane, the primary hydrocarbon in natural
10 gas, from contaminants. Although the phrases “gas stream,” “vapor stream,” and “liquid stream,” refer to situations where a gas, vapor, and liquid is mainly present in the stream, respectively, there may be other phases also present within the stream. For example, a gas may also be present in a “liquid stream.” In some instances, the terms “gas stream” and “vapor stream” may be used interchangeably.

15 **[0031]** The disclosure relates to a system and method for separating a feed stream in a distillation tower. The system and method may destabilize solids that may adhere and/or accumulate in the controlled freeze zone section. The system and method may prevent solids that may adhere and accumulate in the controlled freeze zone section from adhering and/or accumulating. Figures 1-8 of the disclosure display various aspects of the system and
20 method.

[0032] The system and method may separate a feed stream having methane and contaminants. The system may comprise a distillation tower **104, 204** (Figures 1-4). The distillation tower **104, 204** may separate the contaminants from the methane.

[0033] The distillation tower **104, 204** may be separated into three functional sections: a
25 lower section **106**, a middle controlled freeze zone section **108** and an upper section **110**. The distillation tower **104, 204** may incorporate three functional sections when the upper section **110** is needed and/or desired. The distillation tower **104, 204** may incorporate only two functional sections when the upper section **110** is not needed and/or desired. When the distillation tower does not include an upper section **110**, a portion of vapor leaving the middle
30 controlled freeze zone section **108** may be extracted from the distillation tower **104, 204** as line **21** for disposing the vapors off the middle controlled freeze zone section while they are off specification with too high a contaminant content or for use as fuel or for other purposes, with the remaining vapor not extracted in line **14**. Note that line **23** and line **14** are directly

connected in Figures 2 and 4 in this instance. Line **14** enters the condenser **122** where a portion of the vapor may be condensed and returned as a liquid spray stream via a spray assembly **129**. Moreover, lines **18** and **20** in Figures 1 and 3 or line **18** in Figures 2 and 4 may be eliminated, elements **124** and **126** in Figures 1 and 3 may be one and the same, and
5 elements **150** and **128** in Figures 1 and 3 may be one and the same. The stream in line **14** in Figures 1 and 3, now taking the vapors leaving the middle controlled freeze section **108**, directs these vapors to the condenser **122**.

[0034] The lower section **106** may also be referred to as a stripper section. The middle controlled freeze zone section **108** may also be referred to as a controlled freeze zone section.
10 The upper section **110** may also be referred to as a rectifier section.

[0035] The sections of the distillation tower **104** may be housed within a single vessel (Figures 1 and 3). For example, the lower section **106**, the middle controlled freeze zone section **108**, and the upper section **110** may be housed within a single vessel **164**.

[0036] The sections of the distillation tower **204** may be housed within a plurality of
15 vessels to form a split-tower configuration (Figures 2 and 4). Each of the vessels may be separate from the other vessels. Piping and/or another suitable mechanism may connect one vessel to another vessel. In this instance, the lower section **106**, middle controlled freeze zone section **108** and upper section **110** may be housed within two or more vessels. For example, as shown in Figures 2 and 4, the upper section **110** may be housed within a single
20 vessel **254** and the lower and middle controlled freeze zone sections **106**, **108** may be housed within a single vessel **264**. When this is the case, a liquid stream exiting the upper section **110**, may exit through a liquid outlet bottom **260**. The liquid outlet bottom **260** is at the bottom of the upper section **110**. Although not shown, each of the sections may be housed within its own separate vessel, or one or more section may be housed within separate vessels,
25 or the upper and middle controlled freeze zone sections may be housed within a single vessel and the lower section may be housed within a single vessel, etc. When sections of the distillation tower are housed within vessels, the vessels may be side-by-side along a horizontal line and/or above each other along a vertical line.

[0037] The split-tower configuration may be beneficial in situations where the height of
30 the distillation tower, motion considerations, and/or transportation issues, such as for remote locations, need to be considered. This split-tower configuration allows for the independent operation of one or more sections. For example, when the upper section is housed within a single vessel and the lower and middle controlled freeze zone sections are housed within a

single vessel, independent generation of reflux liquids using a substantially contaminant-free, largely hydrocarbon stream from a packed gas pipeline or an adjacent hydrocarbon line, may occur in the upper section. And the reflux may be used to cool the upper section, establish an appropriate temperature profile in the upper section, and/or build up liquid inventory at the bottom of the upper section to serve as an initial source of spray liquids for the middle controlled freeze zone section. Moreover, the middle controlled freeze zone and lower sections may be independently prepared by chilling the feed stream, feeding it to the optimal location be that in the lower section or in the middle controlled freeze zone section, generating liquids for the lower and the middle controlled freeze zone sections, and disposing the vapors off the middle controlled freeze zone section while they are off specification with too high a contaminant content. Also, liquid from the upper section may be intermittently or continuously sprayed, building up liquid level in the bottom of the middle controlled freeze zone section and bringing the contaminant content in the middle controlled freeze zone section down and near steady state level so that the two vessels may be connected to send the vapor stream from the middle controlled freeze zone section to the upper section, continuously spraying liquid from the bottom of the upper section into the middle controlled freeze zone section and stabilizing operations into steady state conditions. The split tower configuration may utilize a sump of the upper section as a liquid receiver for the pump **128**, therefore obviating the need for a liquid receiver **126** in Figures 1 and 3.

[0038] The system may also include a heat exchanger **100** (Figures 1-4). The feed stream **10** may enter the heat exchanger **100** before entering the distillation tower **104**, **204**. The feed stream **10** may be cooled within the heat exchanger **100**. The heat exchanger **100** helps drop the temperature of the feed stream **10** to a level suitable for introduction into the distillation tower **104**, **204**.

[0039] The system may include an expander device **102** (Figures 1-4). The feed stream **10** may enter the expander device **102** before entering the distillation tower **104**, **204**. The feed stream **10** may be expanded in the expander device **102** after exiting the heat exchanger **100**. The expander device **102** helps drop the temperature of the feed stream **10** to a level suitable for introduction into the distillation tower **104**, **204**. The expander device **102** may be any suitable device, such as a valve. If the expander device **102** is a valve, the valve may be any suitable valve that may aid in cooling the feed stream **10** before it enters the distillation tower **104**, **204**. For example, the expander device **102** may comprise a Joule-Thompson (J-T) valve.

[0040] The system may include a feed separator **103** (Figures 3-4). The feed stream may enter the feed separator before entering the distillation tower **104, 204**. The feed separator may separate a feed stream having a mixed liquid and vapor stream into a liquid stream and a vapor stream. Lines **12** may extend from the feed separator to the distillation tower **104, 204**.

5 One of the lines **12** may receive the vapor stream from the feed separator. Another one of the lines **12** may receive the liquid stream from the feed separator. Each of the lines **12** may extend to the same and/or different sections (i.e. middle controlled freeze zone, and lower sections) of the distillation tower **104, 204**. The expander device **102** may or may not be downstream of the feed separator **103**. The expander device **102** may comprise a plurality of
10 expander devices **102** such that each line **12** has an expander device **102**.

[0041] The system may include a dehydration unit **261** (Figures 1-4). The feed stream **10** may enter the dehydration unit **261** before entering the distillation tower **104, 204**. The feed stream **10** enters the dehydration unit **261** before entering the heat exchanger **100** and/or the expander device **102**. The dehydration unit **261** removes water from the feed stream **10** to
15 prevent water from later presenting a problem in the heat exchanger **100**, expander device **102**, feed separator **103**, or distillation tower **104, 204**. The water can present a problem by forming a separate water phase (i.e., ice and/or hydrate) that plugs lines, equipment or negatively affects the distillation process. The dehydration unit **261** dehydrates the feed stream to a dew point sufficiently low to ensure a separate water phase does not form at any
20 point downstream during the rest of the process. The dehydration unit may be any suitable dehydration mechanism, such as a molecular sieve or a glycol dehydration unit.

[0042] The system may include a filtering unit (not shown). The feed stream **10** may enter the filtering unit before entering the distillation tower **104, 204**. The filtering unit may remove undesirable contaminants from the feed stream before the feed stream enters the
25 distillation tower **104, 204**. Depending on what contaminants are to be removed, the filtering unit may be before or after the dehydration unit **261** and/or before or after the heat exchanger **100**.

[0043] The system may include a line **12** (Figures 1-4). The line may also be referred to as an inlet channel **12**. The feed stream **10** may be introduced into the distillation tower **104, 204** through the line **12**. The line **12** may extend to the lower section **106** or the middle controlled freeze zone section **108** of the distillation tower **104, 204**. For example, the line **12** may extend to the lower section **106** such that the feed stream **10** may enter the lower section
30 **106** of the distillation tower **104, 204** (Figures 1-4). The line **12** may directly or indirectly

extend to the lower section **106** or the middle controlled freeze zone section **108**. The line **12** may extend to an outer surface of the distillation tower **104**, **204** before entering the distillation tower.

[0044] The lower section **106** is constructed and arranged to separate the feed stream **10** into an enriched contaminant bottom liquid stream (i.e., liquid stream) and a freezing zone vapor stream (i.e., vapor stream). The lower section **106** separates the feed stream at a temperature and pressure at which no solids form. The liquid stream may comprise a greater quantity of contaminants than of methane. The vapor stream may comprise a greater quantity of methane than of contaminants. In any case, the vapor stream is lighter than the liquid stream. As a result, the vapor stream rises from the lower section **106** and the liquid stream falls to the bottom of the lower section **106**.

[0045] The lower section **106** may include and/or connect to equipment that separates the feed stream. The equipment may comprise any suitable equipment for separating methane from contaminants, such as one or more packed sections **181**, or one or more distillation trays with perforations, downcomers, and weirs (Figures 1-4).

[0046] The equipment may include components that apply heat to the stream to form the vapor stream and the liquid stream. For example, the equipment may comprise a first reboiler **112** that applies heat to the stream. The first reboiler **112** may be located outside of the distillation tower **104**, **204**. The equipment may also comprise a second reboiler **172** that applies heat to the stream. The second reboiler **172** may be located outside of the distillation tower **104**, **204**. Line **117** may lead from the distillation tower to the second reboiler **172**. Line **17** may lead from the second reboiler **172** to the distillation tower. Additional reboilers, set up similarly to the second reboiler described above, may also be used.

[0047] The first reboiler **112** may apply heat to the liquid stream that exits the lower section **106** through a liquid outlet **160** of the lower section **106**. The liquid stream may travel from the liquid outlet **160** through line **28** to reach the first reboiler **112** (Figures 1-4). The amount of heat applied to the liquid stream by the first reboiler **112** can be increased to separate more methane from contaminants. The more heat applied by the first reboiler **112** to the stream, the more methane separated from the liquid contaminants, though more contaminants will also be vaporized.

[0048] The first reboiler **112** may also apply heat to the stream within the distillation tower **104**, **204**. Specifically, the heat applied by the first reboiler **112** warms up the lower

section **106**. This heat travels up the lower section **106** and supplies heat to warm solids entering a melt tray assembly **139** (Figures 1-4) of the middle controlled freeze zone section **108** so that the solids form a liquid and/or slurry mix.

[0049] The second reboiler **172** applies heat to the stream within the lower section **106**.
5 This heat is applied closer to the middle controlled freeze zone section **108** than the heat applied by the first reboiler **112**. As a result, the heat applied by the second reboiler **172** reaches the middle controlled freeze zone section **108** faster than the heat applied by the first reboiler **112**. The second reboiler **172** also helps with energy integration.

[0050] The equipment may include a chimney assembly **135** (Figures 1-4). While falling
10 to the bottom of the lower section **106**, the liquid stream may encounter one or more of the chimney assemblies **135**.

[0051] Each chimney assembly **135** includes a chimney tray **131** that collects the liquid stream within the lower section **106**. The liquid stream that collects on the chimney tray **131** may be fed to the second reboiler **172**. After the liquid stream is heated in the second reboiler
15 **172**, the stream may return to the middle controlled freeze zone section **106** to supply heat to the middle controlled freeze zone section **106** and/or the melt tray assembly **139**. Unvaporized stream exiting the second reboiler **172** may be fed back to the distillation tower **104**, **204** below the chimney tray **131**. Vapor stream exiting the second reboiler **172** may be routed under or above the chimney tray **131** when the vapor stream enters the distillation
20 tower **104**, **204**.

[0052] The chimney tray **131** may include one or more chimneys **137**. The chimney **137** serves as a channel that the vapor stream in the lower section **106** traverses. The vapor stream travels through an opening in the chimney tray **131** at the bottom of the chimney **137** to the top of the chimney **137**. The opening is closer to the bottom of the lower section **106**
25 than it is to the bottom of the middle controlled freeze zone section **108**. The top is closer to the bottom of the middle controlled freeze zone section **108** than it is to the bottom of the lower section **106**.

[0053] Each chimney **137** has attached to it a chimney cap **133**. The chimney cap **133** covers a chimney top opening **138** of the chimney **137**. The chimney cap **133** prevents the
30 liquid stream from entering the chimney **137**. The vapor stream exits the chimney assembly **135** via the chimney top opening **138**.

[0054] After falling to the bottom of the lower section **106**, the liquid stream exits the

distillation tower **104, 204** through the liquid outlet **160**. The liquid outlet **160** is within the lower section **106** (Figures 1-4). The liquid outlet **160** may be located at the bottom of the lower section **106**.

5 **[0055]** After exiting through the liquid outlet **160**, the feed stream may travel via line **28** to the first reboiler **112**. The feed stream may be heated by the first reboiler **112** and vapor may then re-enter the lower section **106** through line **30**. Unvaporized liquid may continue out of the distillation process via line **24**.

10 **[0056]** The system may include an expander device **114** (Figures 1-4). After entering line **24**, the heated liquid stream may be expanded in the expander device **114**. The expander device **114** may be any suitable device, such as a valve. The valve **114** may be any suitable valve, such as a J-T valve.

15 **[0057]** The system may include a heat exchanger **116** (Figures 1-4). The liquid stream heated by the first reboiler **112** may be cooled or heated by the heat exchanger **116**. The heat exchanger **116** may be a direct heat exchanger or an indirect heat exchanger. The heat exchanger **116** may comprise any suitable heat exchanger.

20 **[0058]** The vapor stream in the lower section **106** rises from the lower section **106** to the middle controlled freeze zone section **108**. The middle controlled freeze zone section **108** is constructed and arranged to separate the feed stream **10** introduced into the middle controlled freeze zone section, or into the top of lower section **106**, into a solid and a vapor stream. The solid may be comprised more of contaminants than of methane. The vapor stream (i.e., methane-enriched vapor stream) may comprise more methane than contaminants.

25 **[0059]** The middle controlled freeze zone section **108** includes a lower section **40** and an upper section **39** (Figure 5). The lower section **40** is below the upper section **39**. The lower section **40** directly abuts the upper section **39**. The lower section **40** is primarily but not exclusively a heating section of the middle controlled freeze zone section **108**. The upper section **39** is primarily but not exclusively a cooling section of the middle controlled freeze zone section **108**. The temperature and pressure of the upper section **39** are chosen so that the solid can form in the middle controlled freeze zone section **108**.

30 **[0060]** The middle controlled freeze zone section **108** may comprise a melt tray assembly **139** that is maintained in the middle controlled freeze zone section **108** (Figures 1-4). The melt tray assembly **139** is within the lower section **40** of the middle controlled freeze zone section **108**. The melt tray assembly **139** is not within the upper section **39** of the middle

controlled freeze zone section **108**.

[0061] The melt tray assembly **139** is constructed and arranged to melt a solid formed in the middle controlled freeze zone section **108**. When the warm vapor stream rises from the lower section **106** to the middle controlled freeze zone section **108**, the vapor stream
5 immediately encounters the melt tray assembly **139** and supplies heat to melt the solids. The melt tray assembly **139** may comprise at least one of a melt tray **118**, a bubble cap **132**, a liquid **130** and heat mechanism(s) **134**.

[0062] The melt tray **118** may collect a liquid and/or slurry mix. The melt tray **118** divides at least a portion of the middle controlled freeze zone section **108** from the lower
10 section **106**. The melt tray **118** is at the bottom **45** of the middle controlled freeze zone section **108**.

[0063] One or more bubble caps **132** may act as a channel for the vapor stream rising from the lower section **106** to the middle controlled freeze zone section **108**. The bubble cap
132 may provide a path for the vapor stream up the riser **140** and then down and around the
15 riser **140** to the melt tray **118**. The riser **140** is covered by a cap **141**. The cap **141** prevents the liquid **130** from travelling into the riser and it also helps prevent solids from travelling into the riser **140**. The vapor stream's traversal through the bubble cap **132** allows the vapor stream to transfer heat to the liquid **130** within the melt tray assembly **139**.

[0064] One or more heat mechanisms **134** may further heat up the liquid **130** to facilitate
20 melting of the solids into a liquid and/or slurry mix. The heat mechanism(s) **134** may be located anywhere within the melt tray assembly **139**. For example, as shown in Figures 1-4, a heat mechanism **134** may be located around bubble caps **132**. The heat mechanism **134** may be any suitable mechanism, such as a heat coil. The heat source of the heat mechanism **134** may be any suitable heat source.

[0065] The liquid **130** in the melt tray assembly **139** is heated by the vapor stream. The liquid **130** may also be heated by the one or more heat mechanisms **134**. The liquid **130** helps melt the solids formed in the middle controlled freeze zone section **108** into a liquid and/or slurry mix. Specifically, the heat transferred by the vapor stream heats up the liquid, thereby enabling the heat to melt the solids. The liquid **130** is at a level sufficient to melt the
30 solids.

[0066] While in the liquid **130**, hydrocarbons may be separated from the contaminants. The hydrocarbons separated from the contaminants may form part of the vapor stream (i.e.,

the hydrocarbon-enriched vapor stream), and may rise from the lower section **40** to the upper section **39** of the middle controlled freeze zone section **108**.

[0067] The middle controlled freeze zone section **108** may include a heating mechanism **36, 136**. The heating mechanism **36, 136** may be coupled to at least one of a controlled freeze zone internal surface **31** (Figure 5) of a controlled freeze zone wall **46** (Figure 5) and a controlled freeze zone external surface **47** (Figures 5-7) of the controlled freeze zone wall **46**.

[0068] The controlled freeze zone internal surface **31** is the inside surface of the middle controlled freeze zone section **108** (Figure 5). The controlled freeze zone internal surface **31** may not be the innermost inside surface of the middle controlled freeze zone section **108** when the heating mechanism is coupled to the controlled freeze zone internal surface **31**. The heating mechanism may be the innermost inside surface of the middle controlled freeze zone section **108**.

[0069] The controlled freeze zone external surface **47** is the outside surface of the middle controlled freeze zone section **108** (Figure 5). The controlled freeze zone external surface **47** may not be the outermost surface of the middle controlled freeze zone section **108**.

[0070] Insulation **34** and its cladding **35** may be on top of the controlled freeze zone external surface **47** (Figure 5). The insulation **34** and its cladding **35** may be the outermost surface of the middle controlled freeze zone section **108**. The insulation **34** may be on top of the controlled freeze zone external surface **47** such that the controlled freeze zone external surface **47** may be on an outer surface of the middle controlled freeze zone section **108**.

[0071] The heating mechanism **36, 136** may be controlled in a manner to provide optimal amount of heat to destabilize and/or prevent adhesion of solids in the middle controlled freeze zone section **108**. The heating mechanism **36, 136** may be controlled in a manner to prevent any adverse effects from excessive heat input into the middle controlled freeze zone section **108**. In essence, the coupling is controlled such that heat emitted by the heating mechanism **36, 136** is localized to the controlled freeze zone wall **46** where solids adhere.

[0072] To provide an optimal amount of heat, the heating mechanism **36, 136** may be controlled by a temperature controller or by an electrical power controller. The temperature controller controls the temperature of the heating mechanism **36, 136**. The electrical power controller controls the electrical power of the heating mechanism **36, 136**.

[0073] The heating mechanism **36, 136** may be above and/or below the uppermost portion of the melt tray assembly **139** of the middle controlled freeze zone section **108**. The

heating mechanism **36, 136** may be in the uppermost section **39** of the middle controlled freeze zone section **108**.

[0074] The heating mechanism **36, 136** may comprise one or more heating mechanisms **36, 136**. For example, as shown in Figures 5-7, the heating mechanism **36, 136** may
5 comprise three heating mechanisms. Each of the heating mechanisms **36, 136** may be directly adjacent to another of the heating mechanisms. One or more of the heating mechanisms **36, 136** may be within a heating zone of the middle controlled freeze zone section **108**. Each of the heating mechanisms **36, 136** within the heating zone is responsible for heating the portion of the controlled freeze zone wall **46** within the heating zone. There
10 may be a plurality of heating zones.

[0075] When the heating mechanism **36, 136** comprises multiple heating mechanisms, one or more of the heating mechanisms may or may not be connected together. When heating mechanisms are connected, the heating mechanisms may be operated together. When heating mechanisms are not connected, the heating mechanisms may be operated
15 independently. The independent operation of heating mechanisms may allow for optimal heating control of one or more heating zones of the middle controlled freeze zone section **108**. The independent operation of heating mechanisms may allow less total heating of the middle controlled freeze zone section **108**, thereby improving the efficiency of the distillation tower **104, 204**. When the heating mechanisms are connected, the heating mechanisms may
20 be operated dependently. The dependent operation of the heating mechanisms may allow for the heating mechanisms to be operated more simplistically than independent operation of the heating mechanism.

[0076] The amount and/or size of heating mechanisms **36, 136** in the middle controlled freeze zone section **108** may depend on a variety of factors. The factors may include the size
25 of the distillation tower **104, 204**, the thickness of the controlled freeze zone wall **46**, the temperature of the liquid spray stream being sprayed from the spray assembly **129**, the flow rate of the feed stream **10**, and/or the temperature outside of the distillation tower **104, 204**. The more feed stream **10** that enters the distillation tower **104, 204**, the more liquid spray stream sprayed. The thicker the controlled freeze zone wall **46** and/or lower the temperature
30 outside of the distillation tower **104, 204**, the more heat the heating mechanism **36, 136** may need to produce.

[0077] The heating mechanism **36, 136** destabilizes and/or prevents adhesion of the solids to the controlled freeze zone wall **46**. When fully heated, the temperature of the heating

mechanism 36, 136 is above the solidification temperature of the solid. Consequently, the ability of the solid to accumulate and/or adhere to the controlled freeze zone wall 46 is reduced because the adhesion of the solids to the controlled freeze zone wall 46 is prevented and/or adhered solids are destabilized by the heating mechanism 36, 136. To the extent that
5 any solid has adhered to the controlled freeze zone wall 46, such as before the heating mechanism 36, 136 is turned on or has heated up to be a temperature above the solidification temperature of the solid, or because of an operational upset, the heating mechanism 36, 136 causes the solid to detach from the controlled freeze zone wall 46 after the heating mechanism 36, 136 is at a temperature above the solidification temperature of the solid.

10 [0078] The heating mechanism 36, 136 may completely extend around at least one of an internal circumference 49 of the controlled freeze zone internal surface 31 and an external circumference 51 of the controlled freeze zone external surface 47. Alternatively, the heating mechanism 36, 136 may extend around a portion of at least one of the internal circumference 49 and the external circumference 51. The amount of the internal or external circumference
15 that the heating mechanism 36, 136 extends around depends on the amount of the controlled freeze zone wall 46 heated by the heating mechanism 36, 136.

[0079] The heating mechanism 36, 136 may be any suitable heating mechanism 36, 136. For example, the heating mechanism 36, 136 may be one of a coil 42 (Figure 6) and an electrical conductor 43 (Figure 7). When the heating mechanism 36, 136 is coupled to the
20 controlled freeze zone internal surface 31, the heating mechanism 36, 136 may be any source of heat that can be safely deployed inside a distillation tower without, for example, being a potential source of combustion.

[0080] When the heating mechanism 36, 136 is a coil, the coil 42 may receive a fluid at a temperature above the solidification temperature of the solid. The fluid within the coil 42
25 transfers heat to at least one of the controlled freeze zone wall 46, the inside of the upper section 39 of the middle controlled freeze zone section 108, and the liquid on the melt tray 118. The transferred heat destabilizes and/or prevents the adhesion of the solid to the controlled freeze zone wall 46. The fluid within the coil 42 directly transfers heat to the controlled freeze zone wall 46 when the coil 42 is coupled to the controlled freeze zone
30 external surface 47 or the controlled freeze zone internal surface 31. When the heating mechanism 36, 136 is coupled to the controlled freeze zone internal surface 31, the heating mechanism 36, 136 is a coil 42 to avoid the potential of a fire occurring inside the distillation tower 104, 204. The fluid within the coil may be any suitable fluid. For example, the fluid

may be any fluid whose inlet temperature and/or flow rate can be controlled, and whose freezing point is substantially lower than that of the freezing CO₂. Examples of fluid include, but are not limited to, propane, methanol, and/or other commercially-available low-melting temperature heat transfer fluids.

5 **[0081]** When the heating mechanism **36, 136** is an electrical conductor **43**, the electrical conductor operates at a temperature above the solidification temperature of the solid. The electrical conductor **43** may be any suitable electrical conductor **43**. For example, the electrical conductor **43** may comprise aluminum solid alloy or copper. The heating mechanism **36, 136** may be an electrical conductor **43** when the heating mechanism **36, 136**
10 is coupled to the controlled freeze zone external surface **47** and not the controlled freeze zone internal surface **31** to avoid the potential of a fire occurring inside the distillation tower.

[0082] A certain amount of heat may be applied by the heating mechanism **36, 136** to ensure destabilization of solids and/or to prevent adhesion of solids within the middle controlled freeze zone section **108**. The certain amount of heat is enough heat to bring an
15 internal surface of the middle controlled freeze zone section **108** to a temperature slightly above the freezing point of CO₂. The certain amount of heat is not excessive so as to not to impact negatively the normal operation of the middle controlled freeze zone section **108**.

[0083] Previous technology did not supply heat by a heating mechanism **36, 136** within a middle controlled freeze zone section **108** because it was not expected that solids would
20 adhere to the middle controlled freeze zone section. Instead it was expected that solids would fall to the melt tray assembly **139** without adhering to the middle controlled freeze zone section. It was also not expected that the elements within the middle controlled freeze zone section would interfere with the pathway of the solids such that the solids would adhere to the middle controlled freeze zone section instead of falling to the melt tray assembly **139**.

25 **[0084]** A temperature of the heating mechanism **36, 136** and/or the controlled freeze zone wall **46** may be detected with a temperature sensor **142, 243** (Figures 6-7). When the middle controlled freeze zone section **108** includes multiple heating mechanisms **36, 136**, the temperature of one or more of the heating mechanism **36, 136** may be detected with the temperature sensors.

30 **[0085]** The middle controlled freeze zone section **108** may include the temperature sensor **142, 243**. The temperature sensor **142, 243** may be on any surface of the middle controlled freeze zone section **108**. For example, the temperature sensor may be at least one of coupled

to the controlled freeze zone internal surface **31** (Figure 5), the controlled freeze zone external surface **47** and the insulation **34**. Surfaces of the middle controlled freeze zone section **108** include the controlled freeze zone internal surface **31**, the controlled freeze zone external surface **47**, the insulation **34**, surfaces of the spray assembly **129**, surfaces of the melt tray assembly **139**, etc. The temperature sensor **142, 243** may be within at least one of the lower section **40** and the upper section **39** of the middle controlled freeze zone section **108**. Temperature sensors may be spaced at intervals throughout the middle controlled freeze zone section **108**.

[0086] The temperature sensor **142, 243** detects temperature at and/or around the area surrounding the temperature sensor **142, 243**. A baseline temperature for each temperature sensor **142, 243** is determined while the middle controlled freeze zone section **108** is properly functioning. A temperature deviation outside of an expected temperature range of the temperature detected by the temperature sensor **142, 243** (i.e., the detected temperature) from the baseline temperature may indicate that the middle controlled freeze zone section **108** is not properly functioning. The temperature deviation may be about 2 to 10 degrees C or 2 to 10 degrees C.

[0087] The middle controlled freeze zone section **108** may be deemed to be not properly functioning if one or more of a variety of circumstances occur. The variety of circumstances may include if solids build-up on the controlled freeze zone wall **46**, if the middle controlled freeze zone section **108** is too warm to form solids, if the middle controlled freeze zone section **108** is too cold to melt the solids in the melt tray assembly **139**, etc. For example, if the temperature sensor **142, 243** is coupled to the controlled freeze zone external surface **47** within the upper section **39** of the middle controlled freeze zone section **108** then the temperature sensor **142, 243** is expected to detect a fairly cold temperature that is close to the actual temperature of the liquid spray stream within the middle controlled freeze zone section **108**. If the temperature sensor **142, 243** detects a rise in temperature from that expected of the actual temperature of the liquid spray stream, then the rise in temperature may indicate that solids have built-up on the controlled freeze zone wall **46**. The solid acts as an insulator so solid build-up on the controlled freeze zone wall **46** is determined when there is an unexpected rise in temperature read by the temperature sensor **142, 243**.

[0088] As it relates to the heating mechanism, the detected temperature helps determine whether the heating mechanism **36, 136** is working in a manner to destabilize and/or prevent adhesion of solid on the controlled freeze zone wall **46**. If the temperature detected by the

temperature sensor **142, 243** falls outside of the expected temperature range, the temperature sensor **142, 243** may indicate that the heating mechanism **36, 136** is not working in a manner to destabilize and/or prevent adhesion of solid on the controlled freeze zone wall **46**. In this instance, the heating mechanism **36, 136** may be manipulated to apply more heat to the controlled freeze zone wall **46**. In addition or alternatively, measures may be taken to destabilize and/or prevent adhesion of the solid to the controlled freeze zone wall **46**. The measures may include at least one of (a) applying a treatment mechanism and (b) using a modified spray assembly, such as those described in the applications entitled “Method and Device for Separating Hydrocarbons and Contaminants with a Surface Treatment Mechanism” (USSN 61/912,987) and “Method and Device for Separating Hydrocarbons and Contaminants with a Spray Assembly,” (USSN 61/912,957) respectively, each by Jaime Valencia, et al. and filed on the same day as the instant application.

[0089] The temperature sensor **142, 243** may be any suitable temperature sensor. For example, the temperature sensor may comprise a thermocouple, platinum resistance thermometer, RTD and/or thermistor.

[0090] The temperature sensor **142, 243** may comprise a plurality of temperature sensors **142, 243**. Each of the plurality of temperature sensors **142, 243** may be coupled to the same or different surface of the middle controlled freeze zone section **108**. One or more of the temperature sensors **142, 243** may comprise an array of temperature sensors. One or more of the temperature sensors may be coupled to a surface of the middle controlled freeze zone section **108** at the same or different elevation of the middle controlled freeze zone section **108**. While the temperature sensor **142, 243** is generally referred to as part of the middle controlled freeze zone section **108**, a temperature sensor **142, 243** could be included in one or more of the lower section **106** and the upper section **110**.

[0091] When the middle controlled freeze zone section **108** includes a heating mechanism **36, 136**, the controlled freeze zone internal surface **31** may not have a treatment mechanism, such as the treatment mechanism described in the application entitled “Method and Device for Separating Hydrocarbons and Contaminants with a Surface Treatment Mechanism” (USSN 61/912,987) by Jaime Valencia, et al and filed on the same day as the instant application. The middle controlled freeze zone section **108** including the heating mechanism **36, 136** may not use the treatment mechanism because the heating mechanism **36, 136** may adequately destabilize and/or prevent the adhesion of solids to the controlled freeze zone wall **46** without also being treated by the treatment mechanism. Alternatively, the

middle controlled freeze zone section **108** including the heating mechanism **36**, **136** may have the controlled freeze zone internal surface **31** treated with the treatment mechanism. Having the heating mechanism **36**, **136** and controlled freeze zone internal surface **31** treated with the treatment mechanism may allow for a reduced energy input.

5 **[0092]** The middle controlled freeze zone section **108** may also comprise a spray assembly **129**. The spray assembly **129** cools the vapor stream that rises from the lower section **40**. The spray assembly **129** sprays liquid, which is cooler than the vapor stream, on the vapor stream to cool the vapor stream. The spray assembly **129** is within the upper section **39**. The spray assembly **129** is not within the lower section **40**. The spray assembly
10 **129** is above the melt tray assembly **139**. In other words, the melt tray assembly **139** is below the spray assembly **129**.

[0093] The spray assembly **129** includes one or more spray nozzles **120** (Figures 1-4). Each spray nozzle **120** sprays liquid on the vapor stream. The spray assembly **129** may also include a spray pump **128** (Figures 1-4) that pumps the liquid. Instead of a spray pump **128**,
15 gravity may induce flow in the liquid.

[0094] The liquid sprayed by the spray assembly **129** contacts the vapor stream at a temperature and pressure at which solids form. Solids, containing mainly contaminants, form when the sprayed liquid contacts the vapor stream, **502** (Figure 8). The solids fall toward the melt tray assembly **139**.

20 **[0095]** The temperature in the middle controlled freeze zone section **108** cools down as the vapor stream travels from the bottom of the middle controlled freeze zone section **108** to the top of the middle controlled freeze zone section **108**. The methane in the vapor stream rises from the middle controlled freeze zone section **108** to the upper section **110**. Some contaminants may remain in the methane and also rise. The contaminants in the vapor stream
25 tend to condense or solidify with the colder temperatures and fall to the bottom of the middle controlled freeze zone section **108**.

[0096] The solids form the liquid and/or slurry mix when in the liquid **130**. Some of the liquid and/or slurry mix flows from the middle controlled freeze zone section **108** to the lower section **106**. This liquid and/or slurry mix flows from the bottom of the middle
30 controlled freeze zone section **108** to the top of the lower section **106** via a line **22** (Figures 1-4). The line **22** may be an exterior line. The line **22** may extend from the distillation tower **104**, **204**. The line **22** may extend from the middle controlled freeze zone section **108**. The

line may extend to the lower section **106**. The line **22** may extend from an outer surface of the distillation tower **104, 204**.

[0097] The vapor stream that rises in the middle controlled freeze zone section **108** and does not form solids or otherwise fall to the bottom of the middle controlled freeze zone section **108**, rises to the upper section **110**. The upper section **110** operates at a temperature and pressure and contaminant concentration at which no solid forms. The upper section **110** is constructed and arranged to cool the vapor stream to separate the methane from the contaminants. Reflux in the upper section **110** cools the vapor stream. The reflux is introduced into the upper section **110** via line **18**. Line **18** may extend to the upper section **110**. Line **18** may extend from an outer surface of the distillation tower **104, 204**.

[0098] After contacting the reflux in the upper section **110**, the feed stream forms a vapor stream and a liquid stream. The vapor stream mainly comprises methane. The liquid stream comprises relatively more contaminants. The vapor stream rises in the upper section **110** and the liquid falls to a bottom of the upper section **110**.

[0099] To facilitate separation of the methane from the contaminants when the stream contacts the reflux, the upper section **110** may include one or more mass transfer devices **176**. Each mass transfer device **176** helps separate the methane from the contaminants. Each mass transfer device **176** may comprise any suitable separation device, such as a tray with perforations, or a section of random or structured packing to facilitate contact of the vapor and liquid phases.

[0100] After rising, the vapor stream may exit the distillation tower **104, 204** through line **14**. The line **14** may emanate from an upper part of the upper section **110**. The line **14** may extend from an outer surface of the upper section **110**.

[0101] From line **14**, the vapor stream may enter a condenser **122**. The condenser **122** cools the vapor stream to form a cooled stream. The condenser **122** at least partially condenses the stream.

[0102] After exiting the condenser **122**, the cooled stream may enter a separator **124**. The separator **124** separates the vapor stream into liquid and vapor streams. The separator may be any suitable separator that can separate a stream into liquid and vapor streams, such as a reflux drum.

[0103] Once separated, the vapor stream may exit the separator **124** as sales product. The sales product may travel through line **16** for subsequent sale to a pipeline and/or condensation

to be liquefied natural gas.

[0104] Once separated, the liquid stream may return to the upper section **110** through line **18** as the reflux. The reflux may travel to the upper section **110** via any suitable mechanism, such as a reflux pump **150** (Figures 1 and 3) or gravity (Figures 2 and 4).

5 [0105] The liquid stream (i.e., freezing zone liquid stream) that falls to the bottom of the upper section **110** collects at the bottom of the upper section **110**. The liquid may collect on tray **183** (Figures 1 and 3) or at the bottommost portion of the upper section **110** (Figures 2 and 4). The collected liquid may exit the distillation tower **104, 204** through line **20** (Figures 1 and 3) or outlet **260** (Figures 2 and 4). The line **20** may emanate from the upper section
10 **110**. The line **20** may emanate from a bottom end of the upper section **110**. The line **20** may extend from an outer surface of the upper section **110**.

[0106] The line **20** and/or outlet **260** connect to a line **41**. The line **41** leads to the spray assembly **129** in the middle controlled freeze zone section **108**. The line **41** emanates from the holding vessel **126**. The line **41** may extend to an outer surface of the middle controlled
15 freeze zone section **110**.

[0107] The line **20** and/or outlet **260** may directly or indirectly (Figures 1-4) connect to the line **41**. When the line **20** and/or outlet **260** directly connect to the line **41**, the liquid spray may be sent to the spray nozzle(s) **120** via any suitable mechanism, such as the spray pump **128** or gravity. When the line **20** and/or outlet **260** indirectly connect to the line **41**, the
20 lines **20, 41** and/or outlet **260** and line **41** may directly connect to a holding vessel **126** (Figures 1 and 3). The holding vessel **126** may house at least some of the liquid spray before it is sprayed by the nozzle(s). The liquid spray may be sent from the holding vessel **126** to the spray nozzle(s) **120** via any suitable mechanism, such as the spray pump **128** (Figures 1-4) or gravity. The holding vessel **126** may be needed when there is not a sufficient amount of
25 liquid stream at the bottom of the upper section **110** to feed the spray nozzles **120**.

[0108] Persons skilled in the technical field will readily recognize that in practical applications, the use of one or more heating mechanisms to destabilize and/or prevent the adhesion of solids to a surface may be used in other apparatuses and/or systems beside distillation towers. For example, one or more heating mechanisms may be used in a physical
30 removal process.

[0109] As shown in Figure 8, a method for separating a feed stream **10** in the distillation tower **104, 204** and/or producing hydrocarbons may include introducing **500** the feed stream

10 into a section **106, 108** of the distillation tower **104, 204**. As previously discussed in the instant application, the feed stream **10** is introduced into one of the sections **106, 108** via line **12**. The method may also include separating **501** the feed stream **10** in the lower section **106** into the enriched contaminant bottom liquid stream and the freezing zone vapor stream at a temperature and pressure at which no solid forms. The lower section **106** operates as previously discussed in the instant application. Additionally, the method may include contacting **502** the freezing zone vapor stream in the middle controlled freeze zone section **108** with the freezing zone liquid stream at a temperature and pressure at which the freezing zone vapor stream forms the solid and the hydrocarbon-enriched vapor stream. The middle controlled freeze zone section **108** operates as previously discussed in the instant application. Moreover, the method may include directly applying heat **503** to the controlled freeze zone wall **46** and destabilizing and/or preventing **504** adhesion of the solid to the controlled freeze zone wall **46** with the heating mechanism **36, 136**. The heating mechanism **36, 136** operates as previously discussed in the instant application.

15 [0110] The method may also include detecting a temperature of at least one of the heating mechanism **36, 136** and the controlled freeze zone wall **46**. The temperature may be detected using the temperature sensor **142, 243** previously described. Information detected by the temperature sensor **142, 243** may be used as previously described.

20 [0111] The method may include maintaining an upper section **110**. The upper section **110** operates as previously discussed in the instant application. The method may also include separating the feed stream in the upper section **110** as previously discussed in the instant application.

25 [0112] The method may include stabilizing the distillation tower **104, 204** via a suitable operational action if large amounts of solid are destabilized and fall into the melt tray assembly **139**. One example of a suitable operational action includes, but is not limited to, controlling the liquid level in the melt tray assembly **139**. One example of controlling the liquid level in the melt tray assembly **139** is described in the application entitled “A Method and System of Maintaining a Liquid Level in a Distillation Tower” (USSN 61/912,959) by Jaime Valencia and filed on the same day as the instant application.

30 [0113] It is important to note that the steps depicted in Figure 8 are provided for illustrative purposes only and a particular step may not be required to perform the inventive methodology. The claims, and only the claims, define the inventive system and methodology.

[0114] Disclosed aspects may be used in hydrocarbon management activities. As used herein, “hydrocarbon management” or “managing hydrocarbons” includes hydrocarbon extraction, hydrocarbon production, hydrocarbon exploration, identifying potential hydrocarbon resources, identifying well locations, determining well injection and/or extraction rates, identifying reservoir connectivity, acquiring, disposing of and/ or abandoning hydrocarbon resources, reviewing prior hydrocarbon management decisions, and any other hydrocarbon-related acts or activities. The term “hydrocarbon management” is also used for the injection or storage of hydrocarbons or CO₂, for example the sequestration of CO₂, such as reservoir evaluation, development planning, and reservoir management. The disclosed methodologies and techniques may be used in extracting hydrocarbons from a subsurface region and processing the hydrocarbons. Hydrocarbons and contaminants may be extracted from a reservoir and processed. The hydrocarbons and contaminants may be processed, for example, in the distillation tower previously described. After the hydrocarbons and contaminants are processed, the hydrocarbons may be extracted from the processor, such as the distillation tower, and produced. The contaminants may be discharged into the Earth, etc. For example, as shown in Figure 8, the method for producing hydrocarbons may also include removing 505 the hydrocarbon-enriched vapor stream from the distillation tower; and producing 506 the hydrocarbon-enriched vapor stream extracted from the distillation tower. The initial hydrocarbon extraction from the reservoir may be accomplished by drilling a well using hydrocarbon drilling equipment. The equipment and techniques used to drill a well and/or extract these hydrocarbons are well known by those skilled in the relevant art. Other hydrocarbon extraction activities and, more generally, other hydrocarbon management activities, may be performed according to known principles.

[0115] As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numeral ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described are considered to be within the scope of the disclosure.

[0116] For the purpose of this disclosure, the term “coupled” means the joining of two

members directly or indirectly to one another. Such joining may be stationary or moveable in nature. Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another. Such joining may be permanent in nature or may be removable or releasable in nature.

[0117] It should be understood that numerous changes, modifications, and alternatives to the preceding disclosure can be made without departing from the scope of the disclosure. The preceding description, therefore, is not meant to limit the scope of the disclosure. Rather, the scope of the disclosure is to be determined only by the appended claims and their equivalents. It is also contemplated that structures and features in the present examples can be altered, rearranged, substituted, deleted, duplicated, combined, or added to each other.

[0118] The articles “the”, “a” and “an” are not necessarily limited to mean only one, but rather are inclusive and open ended so as to include, optionally, multiple such elements.

15

CLAIMS

1. A method for separating a feed stream in a distillation tower comprising:
 - providing a distillation tower comprising a stripper section and a controlled freeze zone section, wherein the controlled freeze zone section comprises a lower section and an upper section, and wherein the controlled freeze zone section comprises a melt tray assembly in the lower section of the controlled freeze zone section;
 - introducing a feed stream into one of the stripper section and the controlled freeze zone section of the distillation tower, the feed stream comprising a hydrocarbon and a contaminant;
 - separating the feed stream in the stripper section into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the hydrocarbon, at a temperature and pressure at which no solid forms;
 - contacting the freezing zone vapor stream in the controlled freeze zone section with a freezing zone liquid stream, comprising the hydrocarbon, at a temperature and pressure at which a solid, comprising the contaminant, and a hydrocarbon-enriched vapor stream, comprising the hydrocarbon, form;
 - directly applying heat to a controlled freeze zone vertical wall of the controlled freeze zone section with a heating mechanism coupled to at least one of a controlled freeze zone internal surface of the controlled freeze zone vertical wall and a controlled freeze zone external surface of the controlled freeze zone vertical wall, wherein the heating mechanism is coupled to the controlled freeze zone vertical wall above the melt tray assembly; and
 - at least one of destabilizing and preventing adhesion of the solid to the controlled freeze zone vertical wall with the heating mechanism.
2. The method of claim 1, wherein applying heat includes heating separate sections of the controlled freeze zone vertical wall with the heating mechanism.
3. The method of claim 1, wherein applying heat includes heating the upper section of the controlled freeze zone section.

4. The method of claim 1, wherein the heating mechanism comprises one of (a) a coil containing a fluid and (b) an electrical conductor.
5. The method of claim 1, further comprising detecting a temperature of the heating mechanism with a temperature sensor that is adjacent to the heating mechanism and coupled to at least one of the controlled freeze zone internal surface and the controlled freeze zone external surface.
6. The method of claim 1, further comprising melting or vaporizing the solid in the upper section of the controlled freeze zone section.
7. The method of claim 6, wherein the lower section of the controlled freeze zone section directly abuts and is separate from the upper section of the controlled freeze zone section and wherein the upper section of the controlled freeze zone section directly abuts and is separate from the lower section of the controlled freeze zone section.
8. The method of claim 1, further comprising producing the freezing zone liquid stream in a rectifier section of the distillation tower at a temperature and pressure at which substantially no solid forms.
9. The method of claim 8, wherein the distillation tower further comprises a rectifier section, and wherein at least one of the stripping section, the controlled freeze zone section, and the rectifier section are in a first vessel and another of the at least one of the stripping section, the controlled freeze zone section, and the rectifier section are in a second vessel that is separate from the first vessel.
10. A distillation tower that separates a contaminant in a feed stream from a hydrocarbon in the feed stream, the distillation tower comprising:
 - a stripper section constructed and arranged to separate a feed stream, comprising a contaminant and a hydrocarbon, into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the

hydrocarbon, at a temperature and pressure at which no solids form; and

a controlled freeze zone section constructed and arranged to receive the freezing zone vapor stream from the stripper section and to contact the freezing zone vapor stream with a freezing zone liquid stream at a temperature and pressure at which a solid, comprising the contaminant, is formed;

wherein the controlled freeze zone section comprises a lower section and an upper section, where the upper section directly abuts and is separate from the lower section, and wherein the controlled freeze zone section further comprises:

a melt tray assembly in the lower section of the controlled freeze zone section that is constructed and arranged to melt a solid, comprising the contaminant, formed in the controlled freeze zone section;

a heating mechanism coupled to at least one of a controlled freeze zone internal surface of a controlled freeze zone vertical wall of the controlled freeze zone section and a controlled freeze zone external surface of the controlled freeze zone vertical wall that at least one of destabilizes and prevents adhesion of the solid to the controlled freeze zone vertical wall, wherein the heating mechanism is above the melt tray assembly and is in the upper section of the controlled freeze zone section.

11. The distillation tower of claim 10, wherein the heating mechanism comprises one of (a) a coil containing a fluid and (b) an electrical conductor, and wherein the distillation tower further comprises a temperature sensor adjacent to the heating mechanism and coupled to the controlled freeze zone internal surface or the controlled freeze zone external surface.
12. The distillation tower of claim 10, wherein the heating mechanism extends around an internal circumference of the controlled freeze zone internal surface or an external circumference of the controlled freeze zone external surface.
13. The distillation tower of claim 10, wherein the heating mechanism comprises a plurality of heating mechanisms, wherein each of the heating mechanisms is coupled to one of the controlled freeze zone internal surface and the controlled freeze zone external surface.

14. The distillation tower of claim 10, wherein the heating mechanism comprises a plurality of heating mechanisms and wherein at least one of the plurality of heating mechanisms is connected to another one of the plurality of heating mechanism.
15. The distillation tower of claim 10, further comprising a rectifier section constructed and arranged to operate at a temperature and pressure at which substantially no solid forms.
16. The distillation tower of claim 15, wherein at least one of the stripping section, the controlled freeze zone section, and the rectifier section are in a first vessel and another of the at least one of the stripping section, the controlled freeze zone section, and the rectifier section are in a second vessel that is separate from the first vessel.
17. The distillation tower of claim 16, wherein the stripping section and the controlled freeze zone section are in the first vessel and the rectifier section is in the second vessel that is separate from the first vessel.
18. A method for producing hydrocarbons comprising:
 - extracting a feed stream comprising a hydrocarbon and a contaminant from a reservoir;
 - introducing the feed stream into one of a stripper section and a controlled freeze zone section of a distillation tower;
 - separating the feed stream in the stripper section into an enriched contaminant bottom liquid stream, comprising the contaminant, and a freezing zone vapor stream, comprising the hydrocarbon, at a temperature and pressure at which no solid forms;
 - contacting the freezing zone vapor stream in the controlled freeze zone section with a freezing zone liquid stream, comprising the hydrocarbon, at a temperature and pressure at which the freezing zone vapor stream forms a solid, comprising the contaminant, and a hydrocarbon-enriched vapor stream, comprising the hydrocarbon;
 - accumulating at least a portion of the freezing zone liquid stream in a melt tray assembly in the controlled freeze zone section;

directly applying heat to a controlled freeze zone vertical wall of the controlled freeze zone section with a heating mechanism coupled to at least one of a controlled freeze zone internal surface of the controlled freeze zone vertical wall and a controlled freeze zone external surface of the controlled freeze zone vertical wall, wherein the heating mechanism is coupled to the controlled freeze zone vertical wall above the melt tray assembly;

at least one of destabilizing and preventing adhesion of the solid to the controlled freeze zone vertical wall with the heating mechanism;

removing the hydrocarbon-enriched vapor stream from the distillation tower; and

producing the hydrocarbon-enriched vapor stream extracted from the distillation tower.

19. The method of claim 18, wherein the heating mechanism comprises a plurality of heating mechanism and wherein applying heat includes heating separate sections of the controlled freeze zone vertical wall with the heating mechanisms.
20. The method of claim 18, wherein applying heat includes heating the upper section of the controlled freeze zone section.
21. The method of claim 18, wherein the heating mechanism comprises one of (a) a coil containing a fluid and (b) an electrical conductor.
22. The method of claim 18, further comprising detecting a temperature of the heating mechanism with a temperature sensor that is adjacent to the heating mechanism and coupled to at least one of the controlled freeze zone internal surface and the controlled freeze zone external surface.
23. The method of claim 18, further comprising melting or vaporizing the solid in at least one of a lower section of the controlled freeze zone section and an upper section of the controlled freeze zone section.

24. The method of claim 23, wherein applying heat includes heating the at least one of the lower section and the upper section of the controlled freeze zone section, wherein the lower section directly abuts and is separate from the upper section of the controlled freeze zone section and wherein the upper section directly abuts and is separate from the lower section of the controlled freeze zone section.
25. The method of claim 18, further comprising producing the freezing zone liquid stream in a rectifier section of the distillation tower at a temperature and pressure at which substantially no solid forms.
26. The method of claim 25, wherein at least one of the stripping section, the controlled freeze zone section and the rectifier section are in a first vessel and another of the at least one of the stripping section, the controlled freeze zone section and the rectifier section are in a second vessel that is separate from the first vessel.