

A conveyor line for moulds, for example, for lines for handling food products 1705

The present invention relates to conveyor lines for moulds and has been developed with particular attention to its possible use in the field of equipment for handling food products.

In this context, the products being processed are frequently located in moulds which have recesses for housing them. For example, European patent application EP-A-0 083 324 describes a mould which can be used to produce food products each constituted by two hemispherical wafer shells which are intended to be joined to each other so as to fit together frontally after a mass of creamy or pasty filling has been placed in the half shells. For this purpose, the two wafer half shells are inserted in respective (half) moulds in order to receive the corresponding portion of filling. The two moulds are then turned over onto one another in a generally hinged arrangement to bring the two filled half shells to the connection position, encouraging them to join together, also as a result of the connection between the respective portions of filling.

The same solution may, of course, also be used for different products. For example, the moulds may have cells which can create chocolate shells or eggs (hollow and/or filled) and other products.

Naturally, in order to obtain a wholly satisfactory result, it is necessary to arrange for the moulds with the products within them to advance in an orderly manner through the various stations of the production line (for example, for the wafer half shells to be



inserted in the moulds, for the mass of filling to be poured in, for the moulds to be joined together, for the moulds to be opened, etc., possibly with intermediate cooling and curing stages) at a precisely predetermined and controlled rate and in conditions in which they are reliably aligned with the zones of operation of the various stations.

In conventional equipment, it is usual to ensure that these conditions are respected with the use of conveyor lines on which the moulds advance in engagement with positive entrainment members such as chains, grippers or entrainment teeth or dogs, etc., which are intended coercively to locate each mould precisely in space and time within the conveyor line, particularly in correspondence with the processing stations.

However, this solution gives rise to considerable practical difficulties, particularly in the regions where it is necessary to slow down and, in particular, to stop the advance of the moulds (for example, in correspondence with the stations where the masses of filling are poured into the products or where the products are decorated). Clearly, with the use of direct and positive entrainment of the moulds, it is necessary to provide either for a momentary stoppage of the conveyor line (which therefore advances in steps) or for the momentary disengagement of the mould from the conveyor line.

The same requirements also arise, often in an even more critical manner when, instead of being stopped, the moulds are "followed" by the processing stations.

Neither of the solutions described above can be



considered wholly satisfactory; the first since it usually involves the need to stop and/or slow down not only the mould which is being processed at the time in question but also other closely adjacent moulds in the flow; the second since it can create considerable practical complications within the equipment.

The object of the present invention is to provide a conveyor line for products housed in moulds which radically overcomes the problems set out above.

According to the present invention, this object is achieved by virtue of a conveyor line having the specific characteristics recited in Claim 1. Advantageous developments of the invention form the subject matter of the subclaims which follow.

The invention will now be described, purely by way of non-limiting example, with reference to the appended drawings, in which:

Figure 1 is a schematic, perspective view of a conveyor line formed according to the invention, and

Figure 2 shows, in greater detail the structure of one of the moulds to be used in the conveyor line according to the invention, from a viewpoint corresponding approximately to that indicated by the arrow II in Figure 1.

In Figure 1, a conveyor line for moulds is generally indicated 1.

By way of example, these may be moulds 2 having holes or cells 3 which can house hemispherical wafer shells



which, in turn, are intended to house masses of pasty or creamy filling so as to give rise to a generally spherical food product as a result of the frontal connection of the two filled half shells. Moulds of this type are described, for example, in European patent application EP-A-0 083 324 already mentioned above.

As already stated, this indication of a possible use should in no way be interpreted in a limiting sense: the moulds 2 may in fact be configured with a view to use in conjunction with different products such as chocolate shells or eggs (hollow and/or filled).

It should also be noted that the conveyor line 1 shown in Figure 1 is generally a double line, in the sense that it actually comprises two paired conveyor lines which travel parallel and closely adjacent to each other. For simplicity of illustration, the profile of one of the lines is shown in broken outline and the following description will be given with specific reference solely to the line shown in continuous outline: it is nevertheless intended that what is stated for one of the lines also applies almost identically to the line paired therewith.

The presence of two lines side by side, on which the moulds (or, more correctly, the half-moulds) 2 advance in two paired and coordinated rows is advantageous in any situation in which it is necessary to join respective male and female (half) moulds together in order to produce a product.

One of the paired conveyor lines thus carries the male half-moulds and the other carries the female

This Sheet Has Been Replaced



half-moulds. Turning devices (not shown) are disposed along the paired lines for turning the male half-moulds over onto ~~respective female~~ half-moulds and then reopening the moulds by turning the male half-moulds upwardly again. This is all in accordance with criteria which do not need to be described in detail herein, since they are not relevant for the purposes of an understanding of the invention.

The main characteristic of the solution according to the invention is that the moulds 2 do not move along the respective conveyor line as a result of a positive entrainment effect exerted by hooking or engagement members such as grippers, teeth, dogs, etc., but simply because they are supported on movable entrainment formations which, in the embodiment illustrated, are constituted by the upper passes of two endless belts 4 disposed side by side and extending around respective end pulleys 5 with horizontal axes. In particular, at least in correspondence with one end of the loops formed by the belts 4, the pulleys 5 are rotated by a drive device constituted, for example, by a direct-current electric motor 6. Naturally, Figure 1 shows only one of the many portions in cascade which can make up a more complex conveyor line: the profiles of two adjacent portions disposed upstream and downstream respectively are shown schematically in broken outline in the drawings.

It will be noted, in particular, that the belts 4 are preferably belts with rectangular cross-sections. Although this selection is preferred, it should not be considered limiting. In fact, the belts 4 could even be replaced by other equivalent formations for this

This Sheet Has Been Replaced



purpose, for example belts with circular cross-sections (so-called polycords). In general, however, the selection of belts with flattened, rectangular cross-sections is considered preferable in order to ensure that the moulds 2 are supported correctly on the belts 4.

In the solution according to the invention, in fact, the moulds 2 are unrestrained, so to speak, in the sense that they travel simply supported on the upper passes of the belts 4 and are therefore advanced by the belts 4 as a result of the frictional relationship in which the lower faces of the moulds 2 are supported on the upper passes of the belts 4.

For this purpose, the undersides of the moulds 2 have grooves 7 the shapes of which are complementary to the cross-sections of the belts 4 and which extend in the direction in which the moulds 2 are to be advanced. By way of example, the belts 4 may have rectangular cross-sections approximately 15-25 mm x 4-5 mm. The grooves 5 in the undersides of the moulds 2 have corresponding cross-sections (naturally leaving a small clearance).

The fact that the grooves 7 extend in the direction of advance of the moulds 2 ensures that, once the moulds are fitted securely on the belts 4 with the latter extending within their respective grooves 7, each mould 2 is positioned precisely and is safe from any risk of misalignment relative to the direction of advance.

At the same time, the existence of a certain clearance between the belts 4 and the grooves 7 prevents sticking: from this point of view, the use of a

This Sheet Has Been Replaced



7

rectangular cross-section is preferable to a circular cross-section, since circular belts show a greater tendency to stick against the walls of the grooves 7.

The moulds 2 may advantageously be made of moulded plastics material. Their production by moulding facilitates the provision of the cells 3 and, possibly, of formations 8 for facilitating the exact superposing and joining together of complementary (half) moulds. More precisely these are formations 8 which project upwardly from the upper or front faces of the male moulds (which are transported on the conveyor structure shown in continuous outline) and can engage corresponding holes 9 in the female moulds (which are transported on the line shown in broken outline). This ensures that the moulds are superposed in precise alignment in the condition in which they are joined together frontally when the male moulds are turned over onto the female moulds.

Moreover, the presence of the projecting formations 8 allows for the male moulds to be stacked, possibly with products housed within them, for example, with a view to locating them temporarily on cooling, conditioning or curing lines, or simply in order to store the moulds.

In the first place, the fact that the moulds 2 are simply supported on the upper passes of the belts 4 offers the advantage that the moulds 2 can be loaded onto and unloaded from the conveyor line simply by a lowering or raising movement relative to the upper passes of the belts 4 and hence without the need for complex operations for engaging or disengaging entrainment formations.

Moreover, at least within certain limits, the initial positions in which the moulds 2 are housed on the upper passes of the belts 4 is not particularly critical: the moulds 2 can then be positioned precisely longitudinally of the belts 4 by being made to slide along them.

The fact that the moulds 2 can slide relative to the upper passes of the belts 4 is thus used, in the solution according to the invention, in order to stop the moulds 2 on the conveyor line.

For this purpose, there are one or more stop units 10 along the line, preferably beneath the moulds 2 and in the space between the belts 4. Two stop units are usually disposed adjacent the belts 4 so that they can operate symmetrically on the opposite ends (transverse the direction of advance) of the moulds 2.

The units 10 are preferably constituted by jack-type devices having pins or fingers 11 which are movable selectively (under the action of a fluid or electromagnetic operating member which in turn is controlled by the processing device - for example, a PLC which controls the operation of the conveyor line) between rest positions, in which they are retracted downwardly (shown in broken outline in the drawings), and raised, operative positions (shown in continuous outline).

In the downwardly-retracted position, the pins or fingers 11 do not interfere with the advance of the moulds 2 along the line 1.

In the raised position, however, the pins 11 (which act



as engagement elements) can engage corresponding formations 12 on the lower portions of the moulds 2.

As can better be seen in the view from below of Figure 2, the moulds 2 (which, as already stated, are preferably formed by the moulding of plastics material) have a generally ribbed structure with stiffening ribs 13 which extend both in the direction in which the moulds are intended to advance and in a perpendicular direction.

In particular, two of the ribs which extend in the direction of advance are arranged in positions such that, when the mould 2 is mounted on the belts 4 they are aligned with the stop units 10 and, in particular, with the paths of movement (vertical) of the pins 11. The ribs in question (only one of which is visible in Figure 2 where it is indicated 13a) are generally recessed, in the sense that, measured perpendicular to the general plane of the mould, they are shorter than the other corresponding ribs 13a. The formations 12 occupy positions approximately in the middle of the ribs in question. In particular, each of the formations 12 is generally H-shaped with two approximately semi-circular or U-shaped end recesses 14 which are intended (see Figure 1 in particular) to constitute seats for housing and acting against the pins 11 in their raised positions.

Consequently, when a mould 2 is to be stopped in a certain position on the conveyor line, it suffices to provide one or preferably - for the reasons of operational equilibrium and symmetry seen above - two stop units 10, 11 in that position, the pins 11 being moved from their lowered, rest positions, towards their



raised positions when the mould 2 approaches this position. When the mould 2 passes over the stop units 10, 11, the fingers 11 are inserted in the holes 14 in the formations 12, preventing the mould 2 from advancing further and the mould starts to slide on the belts 4 which are kept continually in motion.

These conditions can be maintained without problems throughout the period of time necessary for the envisaged operation on the mould 2 (including any raising and turning-over of the mould), or the following thereof by a handling station.

Once the envisaged operation is completed, the stop units 10, 11 can be returned to the rest positions, by the lowering of the pins 11. The mould 2 is thus released from the restraining effect exerted as a result of the action of the fingers 11 against the formations 12 and can continue to advance on the upper passes of the belts 4.

This operation can be repeated selectively for each mould 2 which advances on the conveyor line without the need simultaneously to stop the movement of the adjacent moulds in the flow. Moreover, the stopping operation is extremely easy to carry out and does not require the provision of particularly complex devices. Furthermore, the stopping - at least momentarily - of the movement of the moulds can also be used to accumulate moulds along the line of advance in order to release them in a selective and metered manner so as to create a regular flow of precisely equally-spaced moulds advancing in a precise space and time relationship with subsequent work stations downstream of the accumulation position.



Naturally, the generally H-like shape of the formations 12 with two opposed cavities 14 is intended to enable the moulds 2 to be disposed on the belts 4 in two opposite orientations.

The formations 12 can thus be formed either on the measured centreline (relative to the lengths of the moulds in the direction of advance thereof) or offset from the centreline.

In the first case, if the units 10, 11 are mounted in fixed positions, the position in which the moulds 2 stop in correspondence with the units will be identical regardless of the orientation of the mould 2 on the belts 4. In the second case, however, it will be possible to achieve two different stopping positions of the mould 2 according to the orientation in which it is mounted on the belts.

Naturally, the principle of the invention remaining the same, the details of construction and forms of embodiment may be varied widely with respect to those described and illustrated, without thereby departing from the scope of the present invention. For example, although the use of two, paired, belt formations 4 is preferable, it is not essential. It would be possible, for example, either to use a larger number of belts (for example, three or more) whilst retaining the ability to stop the movement of the moulds by causing them to slide on the belts, or to use a single belt entrainment formation, the movement of the moulds being regulated, however, by means of passive sliding formations (e.g. guides or rollers) which do not actively entrain the moulds 2. In any case, the ability to stop the movement of the moulds by causing



THIS SHEET HAS BEEN
REPLACED

12
them to slide on the entrainment formation or
formations is retained.

This Sheet Has Been Replaced





13
CLAIMS

THIS SHEET HAS BEEN
REPLACED

1. A conveyor line for moulds (2) characterized in that it comprises:

- at least one entrainment formation (4) which is movable in a transportation direction and can receive the moulds (2) which are supported thereon so that the moulds (2) are entrained by the at least one entrainment formation (4) in the direction of transportation, and

- stop means (10, 11) which are located in generally fixed positions and can interfere with the movement of the moulds (2) so as to stop them whilst each stopped mould (2) performs a sliding movement relative to the entrainment formation (4) which is kept in motion.

2. A conveyor line according to Claim 1, characterized in that the at least one entrainment formation (4) is constituted by an endless motor-driven element with an upper pass on which the moulds (2) are supported.

3. A conveyor line according to Claim 1 or Claim 2, characterized in that the at least one entrainment formation (4) is a belt.

4. A conveyor line according to Claim 3, characterized in that the belt (4) has a rectangular profile.

5. A conveyor line according to any one of Claims 1 to 4, characterized in that there are at least two paired entrainment formations (4).

6. A conveyor line according to Claim 5, characterized

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

in that the stop means ¹⁴ (10, 11) act in positions generally between the at least two entrainment formations (4).

7. A conveyor line according to any one of Claims 1 to 6, characterized in that it comprises at least two units (10, 11) for stopping the movement of the moulds (2), the units operating in generally symmetrical positions relative the moulds (2).

8. A conveyor line according to any one of Claims 1 to 7, characterized in that the bottom of each mould (2) has at least one groove (7) for cooperating with and housing the entrainment formation (4).


9. A conveyor line according to Claim 4 and Claim 8, characterized in that the at least one groove (7) has a rectangular cross-section.

10. A conveyor line according to Claim 8, characterized in that the at least one groove (7) has dimensions such as to provide a certain clearance with respect to the at least one entrainment formation (4).

11. A conveyor line according to any one of Claims 1 to 10, characterized in that the stop means (10, 11) act on the undersides of the moulds (2).

12. A conveyor line according to any one of Claims 1 to 11, characterized in that the stop means (10, 11) comprise at least one engagement element (11) which is movable selectively between a rest position in which the engagement element (11) does not interfere with the advance of the moulds (2) and an active position, in which the engagement element (11) extends towards the

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

15

moulds (2) and can stop their movement.

13. A conveyor line according to Claim 11, characterized in that the bottom of each mould (2) has at least one engagement formation (12) which can cooperate with the stop means (10, 11), in engagement therewith.

14. A conveyor line according to Claim 13, characterized in that the at least one engagement formation (12) has at least one C- or U-shaped recess (14) which can house the stop means (11).

15. A conveyor line according to Claim 13, characterized in that the at least one engagement formation (12) is of a generally symmetrical shape and can therefore cooperate with the stop means (10, 11) regardless of the orientation of the respective mould (2) relative to the at least one entrainment formation (4).

16. A conveyor line according to Claim 15, characterized in that the at least one engagement formation (12) is generally H-shaped.

17. A conveyor line according to Claim 15, characterized in that the at least one engagement formation (12) is located symmetrically relative to the respective mould (2) so that it cooperates with the stop means (10, 11) in an identical manner regardless of the direction of advance of the respective mould (2) on the at least one entrainment formation (4).

18. A conveyor line according to Claim 15, characterized in that the at least one engagement

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

16

formation (12) is located asymmetrically relative to the respective mould (2) so that it cooperates with the stop means (10, 11) in a differentiated manner according to the orientation of the respective mould (2) relative to the at least one entrainment formation (4).

19. A line according to any one of Claims 1 to 18, characterized in that the moulds (2) have complementary elements (8, 9) on their upper faces for enabling the moulds to be precisely superposed and joined together in a generally male-and-female arrangement.

20. A conveyor line according to Claim 19, characterized in that at least some of the complementary elements (8) are in the form of appendages projecting from the upper faces of the respective moulds (2) so that the respective moulds (2) can be stacked with the use of the projecting formations (8).

21. A conveyor line according to any one of Claims 1 to 20, characterized in that it is associated in an operatively paired relationship with a substantially identical line in order to achieve two parallel and synchronized flows of moulds (2).

This Sheet Has Been Replaced



ABSTRACT

A conveyor line for moulds, for example, for lines for handling food products

The line comprises one or more movable entrainment formations, for example motor-driven (5, 6) belts (4). Moulds (2) are supported on the belts without restraint and are entrained by the belts (4) as a result of being supported on the upper passes thereof. The advance of the moulds (2) can be stopped selectively by stop means (10, 11) which engage the moulds (2) in a coupling relationship, stopping them, whilst the moulds (2) slide on the upper passes of the belts (4) which are kept in motion.

(Figure 1).

This Sheet Has Been Replaced







FIG. 1

This Sheet Has Been Replaced



FIG. 2



30 SEP 1997

DescriptionTHIS SHEET HAS BEEN
REPLACED

The present invention relates to conveyor lines for moulds and has been developed with particular attention to its possible use in the field of equipment for handling food products.

In this context, the products being processed are frequently located in moulds which have recesses for housing them. For example, European patent application EP-A-0 083 324 describes a mould which can be used to produce food products each constituted by two hemispherical wafer shells which are intended to be joined to each other so as to fit together frontally after a mass of creamy or pasty filling has been placed in the half shells. For this purpose, the two wafer half shells are inserted in respective (half) moulds in order to receive the corresponding portion of filling. The two moulds are then turned over onto one another in a generally hinged arrangement to bring the two filled half shells to the connection position, encouraging them to join together, also as a result of the connection between the respective portions of filling.

The same solution may, of course, also be used for different products. For example, the moulds may have cells which can create chocolate shells or eggs (hollow and/or filled) and other products.

Naturally, in order to obtain a wholly satisfactory result, it is necessary to arrange for the moulds with the products within them to advance in an orderly manner through the various stations of the production line (for example, for the wafer half shells to be inserted in the moulds, for the mass of filling to be poured in, for the moulds to be joined together, for the moulds to be opened, etc., possibly with intermediate cooling and curing stages) at a precisely predetermined and controlled rate and in conditions in which they are reliably aligned with the zones of operation of the various stations.

This Sheet Has Been Replaced



30 SEP 1997

In conventional equipment, it is usual to ensure that these conditions are respected with the use of conveyor lines on which the moulds advance in engagement with positive entrainment members such as chains, grippers or entrainment teeth or dogs, etc., which are intended coercively to locate each mould precisely in space and time within the conveyor line, particularly in correspondence with the processing stations.

However, this solution gives rise to considerable practical difficulties, particularly in the regions where it is necessary to slow down and, in particular, to stop the advance of the moulds (for example, in correspondence with the stations where the masses of filling are poured into the products or where the products are decorated). Clearly, with the use of direct and positive entrainment of the moulds, it is necessary to provide either for a momentary stoppage of the conveyor line (which therefore advances in steps) or for the momentary disengagement of the mould from the conveyor line.

The same requirements also arise, often in an even more critical manner when, instead of being stopped, the moulds are "followed" by the processing stations.

Neither of the solutions described above can be considered wholly satisfactory; the first since it usually involves the need to stop and/or slow down not only the mould which is being processed at the time in question but also other closely adjacent moulds in the flow; the second since it can create considerable practical complications within the equipment.

The object of the present invention is to provide a conveyor line for products housed in moulds which radically overcomes the problems set out above.

30 SEP 1997

According to the present invention, this object is achieved by virtue of a conveyor line having the specific characteristics recited in Claim 1, some of which are known per se, e.g. from US-A-4 231 465. Specifically that prior art document discloses a self-timing automatic conveyor system including a low-friction conveyor belt as well as a holding mechanism actuable to open and close for selectively controlling flow of goods along the conveyor belt. Advantageous developments of the invention form the subject matter of the subclaims which follow.

The invention will now be described, purely by way of non-limiting example, with reference to the appended drawings, in which:

Figure 1 is a schematic, perspective view of a conveyor line formed according to the invention, and

Figure 2 shows, in greater detail the structure of one of the moulds to be used in the conveyor line according to the invention, from a viewpoint corresponding approximately to that indicated by the arrow II in Figure 1.

In Figure 1, a conveyor line for moulds is generally indicated 1.

By way of example, these may be moulds 2 having holes or cells 3 which can house hemispherical wafer shells which, in turn, are intended to house masses of pasty or creamy filling so as to give rise to a generally spherical food product as a result of the frontal connection of the two filled half shells. Moulds of this type are described, for example, in European patent application EP-A-0 083 324 already mentioned above.

As already stated, this indication of a possible use should in no way be interpreted in a limiting sense: the moulds 2 may in fact be configured with a view to use in conjunction with different products such as chocolate shells or eggs (hollow and/or filled).

30 SEP 1997

It should also be noted that the conveyor line 1 shown in Figure 1 is generally a double line, in the sense that it actually comprises two paired conveyor lines which travel parallel and closely adjacent to each other. For simplicity of illustration, the profile of one of the lines is shown in broken outline and the following description will be given with specific reference solely to the line shown in continuous outline: it is nevertheless intended that what is stated for one of the lines also applies almost identically to the line paired therewith.

The presence of two lines side by side, on which the moulds (or, more correctly, the half-moulds) 2 advance in two paired and coordinated rows is advantageous in any situation in which it is necessary to join respective male and female (half) moulds together in order to produce a product.

One of the paired conveyor lines thus carries the male half-moulds and the other carries the female half-moulds. Turning devices (not shown) are disposed along the paired lines for turning the male half-moulds over onto respective female half-moulds and then reopening the moulds by turning the male half-moulds upwardly again. This is all in accordance with criteria which do not need to be described in detail herein, since they are not relevant for the purposes of an understanding of the invention.

30 SEP 1997

The main characteristic of the solution according to the invention is that the moulds 2 do not move along the respective conveyor line as a result of a positive entrainment effect exerted by hooking or engagement members such as grippers, teeth, dogs, etc., but simply because they are supported on movable entrainment formations which, in the embodiment illustrated, are constituted by the upper passes of two endless belts 4 disposed side by side and extending around respective end pulleys 5 with horizontal axes. In particular, at least in correspondence with one end of the loops formed by the belts 4, the pulleys 5 are rotated by a drive device constituted, for example, by a direct-current electric motor 6. Naturally, Figure 1 shows only one of the many portions in cascade which can make up a more complex conveyor line: the profiles of two adjacent portions disposed upstream and downstream respectively are shown schematically in broken outline in the drawings.

It will be noted, in particular, that the belts 4 are preferably belts with rectangular cross-sections. Although this selection is preferred, it should not be considered limiting. In fact, the belts 4 could even be replaced by other equivalent formations for this purpose, for example belts with circular cross-sections (so-called polycords). In general, however, the selection of belts with flattened, rectangular cross-sections is considered preferable in order to ensure that the moulds 2 are supported correctly on the belts 4.

In the solution according to the invention, in fact, the moulds 2 are unrestrained, so to speak, in the sense that they travel simply supported on the upper passes of the belts 4 and are therefore advanced by the belts 4 as a result of the frictional relationship in which the lower faces of the moulds 2 are supported on the upper passes of the belts 4.

For this purpose, the undersides of the moulds 2 have grooves 7 the shapes of which are complementary to the cross-sections of the belts 4 and which extend in the direction in which the moulds 2 are to be advanced. By way of example, the belts 4 may have rectangular cross-sections approximately 15-25 mm x 4-5 mm. The grooves 5 in the undersides of the moulds 2 have corre-

30 SEP 1997

sponding cross-sections (naturally leaving a small clearance).

The fact that the grooves 7 extend in the direction of advance of the moulds 2 ensures that, once the moulds are fitted securely on the belts 4 with the latter extending within their respective grooves 7, each mould 2 is positioned precisely and is safe from any risk of misalignment relative to the direction of advance.

At the same time, the existence of a certain clearance between the belts 4 and the grooves 7 prevents sticking: from this point of view, the use of a rectangular cross-section is preferable to a circular cross-section, since circular belts show a greater tendency to stick against the walls of the grooves 7.

The moulds 2 may advantageously be made of moulded plastics material. Their production by moulding facilitates the provision of the cells 3 and, possibly, of formations 8 for facilitating the exact superposing and joining together of complementary (half) moulds. More precisely these are formations 8 which project upwardly from the upper or front faces of the male moulds (which are transported on the conveyor structure shown in continuous outline) and can engage corresponding holes 9 in the female moulds (which are transported on the line shown in broken outline). This ensures that the moulds are superposed in precise alignment in the condition in which they are joined together frontally when the male moulds are turned over onto the female moulds.

Moreover, the presence of the projecting formations 8 allows for the male moulds to be stacked, possibly with products housed within them, for example, with a view to locating them temporarily on cooling, conditioning or curing lines, or simply in order to store the moulds.

In the first place, the fact that the moulds 2 are simply supported on the upper passes of the belts 4 offers the advantage that the moulds 2 can be loaded onto and unloaded from the conveyor line simply by a lowering or raising movement relative to the upper passes of the belts 4 and hence without the need for complex operations for engaging or disengaging entrainment formations.

30 SEP 1997

Moreover, at least within certain limits, the initial positions in which the moulds 2 are housed on the upper passes of the belts 4 is not particularly critical: the moulds 2 can then be positioned precisely longitudinally of the belts 4 by being made to slide along them.

The fact that the moulds 2 can slide relative to the upper passes of the belts 4 is thus used, in the solution according to the invention, in order to stop the moulds 2 on the conveyor line.

For this purpose, there are one or more stop units 10 along the line, preferably beneath the moulds 2 and in the space between the belts 4. Two stop units are usually disposed adjacent the belts 4 so that they can operate symmetrically on the opposite ends (transverse the direction of advance) of the moulds 2.

The units 10 are preferably constituted by jack-type devices having pins or fingers 11 which are movable selectively (under the action of a fluid or electromagnetic operating member which in turn is controlled by the processing device - for example, a PLC which controls the operation of the conveyor line) between rest positions, in which they are retracted downwardly (shown in broken outline in the drawings), and raised, operative positions (shown in continuous outline).

In the downwardly-retracted position, the pins or fingers 11 do not interfere with the advance of the moulds 2 along the line 1.

In the raised position, however, the pins 11 (which act as engagement elements) can engage corresponding formations 12 on the lower portions of the moulds 2.

As can better be seen in the view from below of Figure 2, the moulds 2 (which, as already stated, are preferably formed by the moulding of plastics-material) have a generally ribbed structure with stiffening ribs 13 which extend both in the direction in which the moulds are intended to advance and in a perpendicular direction.

30 SEP 1997

In particular, two of the ribs which extend in the direction of advance are arranged in positions such that, when the mould 2 is mounted on the belts 4 they are aligned with the stop units 10 and, in particular, with the paths of movement (vertical) of the pins 11. The ribs in question (only one of which is visible in Figure 2 where it is indicated 13a) are generally recessed, in the sense that, measured perpendicular to the general plane of the mould, they are shorter than the other corresponding ribs 13a. The formations 12 occupy positions approximately in the middle of the ribs in question. In particular, each of the formations 12 is generally H-shaped with two approximately semi-circular or U-shaped end recesses 14 which are intended (see Figure 1 in particular) to constitute seats for housing and acting against the pins 11 in their raised positions.

Consequently, when a mould 2 is to be stopped in a certain position on the conveyor line, it suffices to provide one or preferably - for the reasons of operational equilibrium and symmetry seen above - two stop units 10, 11 in that position, the pins 11 being moved from their lowered, rest positions, towards their raised positions when the mould 2 approaches this position. When the mould 2 passes over the stop units 10, 11, the fingers 11 are inserted in the holes 14 in the formations 12, preventing the mould 2 from advancing further and the mould starts to slide on the belts 4 which are kept continually in motion.

These conditions can be maintained without problems throughout the period of time necessary for the envisaged operation on the mould 2 (including any raising and turning-over of the mould), or the following thereof by a handling station.

Once the envisaged operation is completed, the stop units 10, 11 can be returned to the rest positions, by the lowering of the pins 11. The mould 2 is thus released from the restraining effect exerted as a result of the action of the fingers 11 against the formations 12 and can continue to advance on the upper passes of the belts 4.

30 SEP 1997

This operation can be repeated selectively for each mould 2 which advances on the conveyor line without the need simultaneously to stop the movement of the adjacent moulds in the flow. Moreover, the stopping operation is extremely easy to carry out and does not require the provision of particularly complex devices. Furthermore, the stopping - at least momentarily - of the movement of the moulds can also be used to accumulate moulds along the line of advance in order to release them in a selective and metered manner so as to create a regular flow of precisely equally-spaced moulds advancing in a precise space and time relationship with subsequent work stations downstream of the accumulation position.

Naturally, the generally H-like shape of the formations 12 with two opposed cavities 14 is intended to enable the moulds 2 to be disposed on the belts 4 in two opposite orientations.

The formations 12 can thus be formed either on the measured centreline (relative to the lengths of the moulds in the direction of advance thereof) or offset from the centreline.

In the first case, if the units 10, 11 are mounted in fixed positions, the position in which the moulds 2 stop in correspondence with the units will be identical regardless of the orientation of the mould 2 on the belts 4. In the second case, however, it will be possible to achieve two different stopping positions of the mould 2 according to the orientation in which it is mounted on the belts.

30 SEP 1997

Naturally, the principle of the invention remaining the same, the details of construction and forms of embodiment may be varied widely with respect to those described and illustrated, without thereby departing from the scope of the appended claims. For example, although the use of two, paired, belt formations 4 is preferable, it is not essential. It would be possible, for example, either to use a larger number of belts (for example, three or more) whilst retaining the ability to stop the movement of the moulds by causing them to slide on the belts, or to use a single belt entrainment formation, the movement of the moulds being regulated, however, by means of passive sliding formations (e.g. guides or rollers) which do not actively entrain the moulds 2. In any case, the ability to stop the movement of the moulds by causing them to slide on the entrainment formation or formations is retained.



30 SEP 1997

Claims

1. A conveyor line for moulds (2) comprising:
 - at least one entrainment formation (4) which is movable in a transportation direction and can receive the moulds (2) which are supported thereon so that the moulds (2) are entrained by the at least one entrainment formation (4) in the direction of transportation,
 - stop means (10, 11) which are located in generally fixed positions and can interfere with the movement of the moulds (2) so as to stop them whilst each stopped mould (2) performs a sliding movement relative to the entrainment formation (4) which is kept in motion, and wherein the bottom of each mould (2) has at least one groove (7) for cooperating with and housing the entrainment formation (4).
2. A conveyor line according to Claim 1, characterized in that the at least one entrainment formation (4) is constituted by an endless motor-driven element with an upper pass on which the moulds (2) are supported.
3. A conveyor line according to Claim 1 or Claim 2, characterized in that the at least one entrainment formation (4) is a belt.
4. A conveyor line according to Claim 3, characterized in that the belt (4) has a rectangular profile.
5. A conveyor line according to any one of Claims 1 to 4, characterized in that there are at least two paired entrainment formations (4).

30 SEP 1997



6. A conveyor line according to Claim 5, characterized in that the stop means (10, 11) act in positions generally between the at least two entrainment formations (4).
7. A conveyor line according to any one of Claims 1 to 6, characterized in that it comprises at least two units (10, 11) for stopping the movement of the moulds (2), the units operating in generally symmetrical positions relative the moulds (2).
8. A conveyor line according to Claim 1 and Claim 4, characterized in that the at least one groove (7) has a rectangular cross-section.
9. A conveyor line according to Claim 7, characterized in that the at least one groove (7) has dimensions such as to provide a certain clearance with respect to the at least one entrainment formation (4).
10. A conveyor line according to any one of Claims 1 to 9, characterized in that the stop means (10, 11) act on the undersides of the moulds (2).
11. A conveyor line according to any one of Claims 1 to 10, characterized in that the stop means (10, 11) comprise at least one engagement element (11) which is movable selectively between a rest position in which the engagement element (11) does not interfere with the advance of the moulds (2) and an active position, in which the engagement element (11) extends towards the moulds (2) and stops their movement.



30 SEP 1997

12. A conveyor line according to Claim 10, characterized in that the bottom of each mould (2) has at least one engagement formation (12) cooperating with the stop means (10, 11), in engagement therewith.
13. A conveyor line according to Claim 12, characterized in that the at least one engagement formation (12) has at least one C- or U-shaped recess (14) housing the stop means (11).
14. A conveyor line according to Claim 12, characterized in that the at least one engagement formation (12) is of a generally symmetrical shape and can therefore cooperate with the stop means (10, 11) regardless of the orientation of the respective mould (2) relative to the at least one entrainment formation (4).
15. A conveyor line according to Claim 14, characterized in that the at least one engagement formation (12) is generally H-shaped.
16. A conveyor line according to Claim 14, characterized in that the at least one engagement formation (12) is located symmetrically relative to the respective mould (2) so that it cooperates with the stop means (10, 11) in an identical manner regardless of the direction of advance of the respective mould (2) on the at least one entrainment formation (4).
17. A conveyor line according to Claim 14, characterized in that the at least one engagement formation (12) is located asymmetrically relative to the respective mould (2) so that it cooperates with the stop means (10, 11) in a differentiated manner according to the orientation of the respective mould (2) relative to the at least one entrainment formation (4).




30 SEP 1997

17. A conveyor line according to Claim 14, characterized in that the at least one engagement formation (12) is located asymmetrically relative to the respective mould (2) so that it cooperates with the stop means (10, 11) in a differentiated manner according to the orientation of the respective mould (2) relative to the at least one entrainment formation (4).
18. A line according to any one of Claims 1 to 17, characterized in that the moulds (2) have complementary elements (8, 9) on their upper faces for enabling the moulds to be precisely superposed and joined together in a generally male-and-female arrangement.
19. A conveyor line according to Claim 18, characterized in that at least some of the complementary elements (8) are in the form of appendages projecting from the upper faces of the respective moulds (2) so that the respective moulds (2) can be stacked with the use of the projecting formations (8).
20. A conveyor line according to any one of Claims 1 to 19, characterized in that it is associated in an operatively paired relationship with a substantially identical line in order to achieve two parallel and synchronized flows of moulds (2).

30 SEP 1997


1



30 SEP 1997

2

FIG. 2



02 APR 1998


A CONVEYOR LINE FOR MOULDS, FOR EXAMPLE, FOR LINES FOR HANDLING
FOOD PRODUCTS**Description**

The present invention relates to conveyor lines for moulds and has been developed with particular attention to its possible use in the field of equipment for handling food products.

In this context, the products being processed are frequently located in moulds which have recesses for housing them. For example, European patent application EP-A-0 083 324 describes a mould which can be used to produce food products each constituted by two hemispherical wafer shells which are intended to be joined to each other so as to fit together frontally after a mass of creamy or pasty filling has been placed in the half shells. For this purpose, the two wafer half shells are inserted in respective (half) moulds in order to receive the corresponding portion of filling. The two moulds are then turned over onto one another in a generally hinged arrangement to bring the two filled half shells to the connection position, encouraging them to join together, also as a result of the connection between the respective portions of filling.

The same solution may, of course, also be used for different products. For example, the moulds may have cells which can create chocolate shells or eggs (hollow and/or filled) and other products.

Naturally, in order to obtain a wholly satisfactory result, it is necessary to arrange for the moulds with the products within them to advance in an orderly manner through the various stations of the production line (for example, for the wafer half shells to be inserted in the moulds, for the mass of filling to be poured in, for the moulds to be joined together, for the moulds to be opened, etc., possibly with intermediate cooling and curing stages) at a precisely predetermined and controlled rate and in conditions in which they are reliably aligned with the zones of operation of the various stations.

ABSTRACT

A conveyor line for moulds, for example, for lines for handling food products

The line comprises one or more movable entrainment formations, for example motor-driven (5, 6) belts (4). Moulds (2) are supported on the belts without restraint and are entrained by the belts (4) as a result of being supported on the upper passes thereof. The advance of the moulds (2) can be stopped selectively by stop means (10, 11) which engage the moulds (2) in a coupling relationship, stopping them, whilst the moulds (2) slide on the upper passes of the belts (4) which are kept in motion.

(Figure 1).