

GAS TURBINE ENGINE ASSEMBLY METHOD AND SYSTEM

CROSS REFERENCE TO RELATED APPLICATION

This application claims priority to United States Provisional Application No.
5 62/011,894 filed on June 13, 2014.

BACKGROUND

A gas turbine engine typically includes a fan section, a compressor section, a combustor section and a turbine section. Air entering the compressor section is
10 compressed and delivered into the combustion section where it is mixed with fuel and ignited to generate a high-speed exhaust gas flow. The high-speed exhaust gas flow expands through the turbine section to drive the compressor and the fan section. The compressor section typically includes low and high pressure compressors, and the turbine section includes low and high pressure turbines.

15 A gas turbine engine includes several components that are housed in casings that are assembled together through bolted flanges. In some systems, the gas turbine engine is assembled along a vertical axis and can complicate access to structures about the engine. Moreover, during engine assembly not only are specific components assembled to each other along a common axis, but accessory
20 components and devices are attached to outer casing structures. Engine assembly requires assembling specific case structures together and assembly of accessory components to the case structures. Each accessory component may require wiring for electrical communication and tubing to communicate fluids. The quantity of wires and tubing required for each accessory component can complicate the assembly
25 process.

Accordingly, it is desirable to design a system for assembling an engine that provides repeatability while easing access to each component and section to speed and simplify assembly.

30 **SUMMARY**

In one exemplary embodiment, an assembly system for assembling a gas turbine engine including a support beam defining a horizontal plane for assembly of engine components along a horizontal axis substantially parallel with the support beam. A forward arm is supported on the support beam for supporting a forward portion of an engine component. An aft arm is supported on the support beam for supporting an aft portion of the engine component. An aft mounting ring is attachable to an aft end of an engine assembly. A forward mounting ring is attachable to a forward end of the engine assembly. A drive is mounted to the aft arm engageable to the aft mounting ring for rotating the engine assembly about the horizontal axis. A roller is supported on the forward arm and engageable to the forward mounting ring to support the first end of the engine assembly during rotation about the horizontal axis.

In a further embodiment of the above, includes at least one additional arm disposed between the forward arm and the aft arm for supporting a portion of the engine assembly.

In a further embodiment of any of the above, the at least one additional arm includes a first arm and a second arm movable vertically relative to the support beam.

In a further embodiment of any of the above, includes an end assembly supported on one of the at least one additional arm. The end assembly includes a lateral adjustment linkage for aligning an engine component secured thereto in a direction transverse to the horizontal axis.

In a further embodiment of any of the above, the end assembly includes first and second clamps set apart from each other on opposite sides of an engine centerline.

In a further embodiment of any of the above, includes a first mount secured to the engine assembly and engageable with the first arm and a second mount secured to the engine assembly and engageable with second arm.

In a further embodiment of any of the above, each of the forward arm and the aft arm are supported on a sliding support movable along the support beam.

In a further embodiment of any of the above, the aft arm and the forward arm are each movable between a stowed position and a mount position.

In a further embodiment of any of the above, includes a motor corresponding with each of the forward arm and the aft arm for driving a linkage to move the corresponding one of the forward arm and the aft arm between the stowed position and the mount position.

5 In a further embodiment of any of the above, the aft arm is movable about a pivot between the stowed and mount positions.

In a further embodiment of any of the above, the forward arm is movable vertically to adjust spacing between the support beam and the roller.

10 In a further embodiment of any of the above, the aft mounting ring includes locking features engageable to the drive mounted on the aft arm.

In a further embodiment of any of the above, the forward mounting ring includes a groove receiving a roller of the roller assembly for supporting the forward portion of the engine assembly.

15 In a further embodiment of any of the above, includes at least one cart for supporting an engine component relative to the horizontal axis that enables positioning of the supported engine component in at least two directions.

20 In another exemplary embodiment, a method of assembling a gas turbine engine includes attaching an aft mounting ring to an aft portion of an aft engine section, attaching a forward mounting ring to a forward portion of a forward engine section, supporting a first intermediate engine section along a horizontal axis, attaching the aft engine section to the intermediate engine component, supporting a portion of the aft engine section along a horizontal axis with a drive supported on an aft arm by attaching the aft mounting ring to the drive, supporting a portion of the forward engine section along the horizontal axis with a roller assembly supported on

25 a forward arm by coupling the roller assembly to the forward mounting ring, rotating the aft, first intermediate and forward engine sections about the horizontal axis with the drive supported on the aft arm, and performing assemble operations on the aft, first intermediate, and forward engine sections.

30 In a further embodiment of the above, the drive includes a motor driving a gear assembly and the aft mounting ring includes gear teeth engaged by the gear assembly for driving rotation of the aft engine section about the horizontal axis.

In a further embodiment of any of the above, the forward mounting ring includes a track for receiving rollers of the roller assembly and supporting the forward engine section includes inserting the rollers into the track of the forward mounting ring.

5 In a further embodiment of any of the above, supporting the first intermediate engine section along the horizontal axis includes fixing a first arm to a first mount attached to the first intermediate engine and a second arm to a second mount attached to the first intermediate engine section.

10 In a further embodiment of any of the above, includes detaching the first arm and the second arm from the corresponding first mount and second mount prior to rotating the aft, first intermediate, and forward engine sections about the horizontal axis.

15 In a further embodiment of any of the above, includes aligning the aft engine section along the horizontal axis with a cart, wherein the cart enables positioning of the aft engine section in at least two axes.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration of an example gas turbine engine.

20 Figure 2 is a schematic illustration of an example assembly system for assembling a gas turbine engine.

Figure 3 is a schematic view of an initial step for assembling a gas turbine engine.

Figure 4 is a further schematic illustration of the first assembly step.

25 Figure 5 is a perspective view of an example end assembly for supporting a subassembly of a gas turbine engine.

Figure 6 is a schematic illustration of a subsequent step for installing a low pressure turbine section.

Figure 7 is a schematic illustration of a subassembly of a gas turbine engine supported by the example assembly system.

30 Figure 8 is a perspective view of an example mount ring.

(FDC) section 54 and a fan section 62. The core engine section 30 includes combustor 26, a high spool 34 and a mid-turbine frame 44. The high spool 34 includes a high pressure compressor 36 coupled to a high pressure turbine 38 through high spool shaft 40. The components of the core engine section 30 are mounted
5 within an intermediate case 42.

The low pressure turbine section 46 includes low pressure turbine 48 and the low spool shaft 50 supported within a low pressure turbine case 52. The FDC section 54 includes the low pressure compressor 58 and fan drive gear system 56 supported within a FDC case 60. The fan 22 is supported within a fan case of the fan section
10 62. The fan 22 includes a plurality of blades 66 supported for rotation about the engine axis A. Each of the sections 30, 46, 54 and 62 are disposed about the engine axis A.

It should be appreciated, that components of each of the disclosed sections 30, 46, 54 and 62 are described by way of example and different and/or additional
15 components could be included in the various sections. Moreover, although the disclosed non-limiting embodiment depicts a turbofan gas turbine engine, it should be understood that the concepts described herein are not limited to use with turbofans as the teachings may be applied to other types of turbine engines; for example a turbine engine including a three-spool architecture in which three spools
20 concentrically rotate about a common axis and where a low spool enables a low pressure turbine to drive a fan via a gearbox, an intermediate spool that enables an intermediate pressure turbine to drive a first compressor of the compressor section, and a high spool that enables a high pressure turbine to drive a high pressure compressor of the compressor section.

Referring to Figure 2, an example assembly system 68 provides for the
25 horizontal assembly of engine sections 30, 46, 54 and 62. Horizontal assembly enables each of the sections 30, 46, 54 and 62 to be supported and assembled along a horizontal axis such that each section and component about the entire circumference of the engine 20 is easily accessible to a technician during assembly.

The example system 68 includes sliding supports 72 extending from a beam
30 70. Each of the supports 72 is movable horizontally along the beam 70 and includes

a lock 82 for holding the support in place along the beam 70. Each of the supports 72 holds an arm that includes features for attachment to the engine sections. In this example a first arm 74 includes an end 86 attachable to a forward mount 45 attached to the core engine section 30. A second arm 76 includes an end assembly 88 for attachment to an aft mount 85 attached to the core engine section 30. The supports 72 are movable horizontally along the beam 70 prior to attachment to an engine section. Once attached to the engine sections, the supports 72 lock in place to prevent horizontal movement.

A third or aft arm 90 is movable between a stowed position (Figure 3) and a mounting position shown in Figure 2. The third arm 90 supports a motor 92 that drives a gear assembly 138. A fourth or forward arm 102 includes a roller assembly 112 and a sensor 114 for producing signals indicative of a rotational position of engine components and sections during assembly that are communicated to a controller 150.

The example system 68 includes features enabling complete 360 degree rotation of subassemblies of the engine about the horizontal axis A. The horizontal axis A and the engine axis in this disclosed example are the same. Continuous 360 degree rotation about the axis A aids and simplifies assembly and eases access to portions of the engine sections to facilitate assembly of the engine. Rotation is enabled by mount rings 106 and 116 for a forward part of an engine subassembly and the gear assembly 138 and mount ring 100 at the aft end. The mount ring 100 attaches to a geared ring 94 that is driven by the gear assembly 138 driven by the motor 92. The motor 92 drives rotation of the engine during assembly and the roller assembly 114 supports and enables rotation of the forward part of the engine subassembly. In various stages of assembly the roller assembly 114 will be engaged to the mount ring 106 or the mount ring 116.

Referring to Figures 3 and 4, assembly begins by moving the core engine section 30 into position under the first arm 74 and the second arm 76. The core engine section 30 is supported on a first cart 120 that enables movement of the core engine section 30 along all axes for aligning the core engine section 30 with the first and second arms 74, 76.

The core engine section 30 includes a forward flange 122 and a rear flange 124. Once the core engine section 30 is in position, the first arm 74 is moved downward by a ball screw shaft 75 (Figure 4) driven by an electric motor 78. The forward mount 45 and aft mount 85 are attached to the case 42 and are adapted to the configuration of the core case 42. Each of the forward mount 45 and aft mount 85 includes features for attachment to the corresponding one of the first arm 74 and the second arm 76. The first arm 74 attaches to the forward mount 45 and the second arm 76 attaches to the aft mount 85. Attachment between the first and second arms 74, 76 and the forward and aft mounts 45, 85 are fixed and do not enable rotation about the horizontal axis.

Referring to Figure 5 with continued reference to Figure 4, the second arm 76 is moved downward toward the core engine section 30 by way of scissor mechanism 126 of the attachment assembly 88 and is regulated by a gas spring 80. The gas spring 80 relieves weight on the scissor mechanism 126 and controls movement by slowing momentum. The attachment mechanism 126 includes a locking mechanism 125 that holds a vertical position of the arm 76 once it is attached to the core engine section 30, and the core engine section 30 is set at a desired height. It should be understood, that other mechanisms for moving the attachment mechanism 88 into place relative to the core engine section 30 are within the contemplation of this disclosure.

The attachment mechanism 88 further includes a lateral slide 128 that includes first and second clamps 132A and 132B disposed on either circumferential side of a centerline of the engine core section 30. The clamps 132A and 132 B engage the aft mount 85 to support the core engine section 30. The lateral slide 128 centralizes the load and provides for lateral adjustment of the core engine section 30 once suspended from the beam 70.

Referring to Figures 6 and 7, the low pressure turbine (LPT) section 46 is then moved along the horizontal axis for assembly to the core engine section 30. The LPT section 46 is supported on a second cart 136 that provides movement of the LPT section 46 along all axes to enable alignment along the horizontal axis with the core engine section 30. The core engine section 30 is supported on the first and second

arms 74, 76 suspended from the upper support beam 70 and the LPT section 46 is supported on the cart 136 during assembly. Each of the arms 74, 76 is movable vertically to aid in alignment with the LPT section 46. In this example, the LPT section 46 includes the shaft 50 that extends along the horizontal axis and is assembled through the core engine section 30.

Once the LPT section 46 is aligned with the core engine section 30 and the shaft 50 is inserted therethrough, the sections 46 and 30 are attached to each other. Attachment in this example includes attachment of the rear flange 124 of the core engine section 30 to a forward flange 134 of the LPT section 46. The shaft 50 extends out a forward end of the core engine section 30. The aft flange 124 and the forward flange 134 form a connection 140 (Figure 7) between the core engine section 30 and the LPT section 46.

Once the connection 140 is complete, the aft portion of the LPT section 46 is mounted to the aft arm 90. The aft arm 90 is pivoted to the mount position by actuation of a motor 96 that drives ball screw 93 to drive link 95 and move arm 90 into position. The arm 90 includes a geared ring 94 that attaches to the mount ring 100 secured to the LPT section 46. The mount ring 100 (Figure 8) is an adaptor that is not part of the completed engine and is utilized to facilitate assembly on the arm 90.

Referring back to Figures 6 and 7, the arm 90 is pivoted downward to the mount position by the electric motor 96 that drives the ball screw 93 to drive link 95 such that the geared ring 94 engages the mount 100 ring. An electric motor 92 is supported on the arm 90 and drives the gear assembly 138 in driving engagement with the geared ring 94. The gear assembly 138 enables rotation of the engine subassembly about the engine axis A.

However, in the state illustrated in Figure 7, it should be appreciated that although the LPT section 46 is mounted for rotation, the subassembly is not yet rotatable because the first and second arms 74, 76 are attached to fixed points on the core engine section 30. The motor 92 is therefore locked from rotation until a further rotational support link is provided.

Referring to Figure 9 once the LPT section 46 is attached to the core section 30, the FDC section 54 is installed. A mounting ring 106 (Figure 11) is attached to the FDC section 54 for engagement with a roller assembly 114 (Figure 13) to support rotation of the front portion of the engine subassembly. The mounting ring 106 is engageable with the roller assembly 114 that facilitates rotational movement.

The FDC section 54 is supported on a third cart 142 that also provides for movement in all axes to facilitate alignment with the core section 30, and the shaft 50 of the LPT section 46. In this step, the FDC section 54 is aligned with the core engine section 30 and the shaft 50. An aft flange 146 of the FDC section is attached to the forward flange 122 of the core engine section 30. The shaft 50 is coupled to the fan drive gear system 56 (not shown here) disposed within the FDC case 60.

Referring to Figures 10, and 12, once the FDC section 60 is attached to the core section 30, the forward arm 102 is engaged to the ring 106. The forward arm 102 supports the roller assembly 114. The roller assembly 114 is rotated into position utilizing motor 110 to lower forward arm 102 into position. Motor 108 is utilized to move the arm 102 vertically once the motor 110 has rotated the arm 102 into a vertical orientation. Rollers 112 of the roller assembly 114 are inserted into a groove 105 of the ring 106 to support the engine subassembly and rotation.

Referring to Figure 13, with continued attention to Figures 10 and 12, the roller assembly 114 includes two rollers 112 that are received within the groove 105 of the ring 106. The rollers 112 are spaced apart horizontally to provide stability in support of the engine subassembly. A sensor 104 is provided that senses a rotary position of the ring 106 and thereby the engine subassembly. The sensor 104 provides information to a controller 150 that is in communication and control over the actuators and various sensors of the assembly system 68.

Once the roller assembly 114 is engaged with the ring 106, the first and second arms 74, 76 can be disconnected from the core engine section 30. Once the first and second arms 74, 76 are disconnected the entire engine subassembly is supported between the forward arm 102 and the third arm 90. Accordingly, full 360 degree rotation around the horizontal axis of the engine subassembly is enabled. Rotation of the subassembly is provided by actuating the motor 92 to drive the gear

assembly 138 to rotate the gear ring 94. The gear assembly 138 includes gear teeth that engage gear teeth defined on an inner surface of the gear ring 94.

Referring to Figure 15, once assembly operations on the subassembly are complete including operations on the core section 30, LPT section 46 and FDC section 54 the subassembly is prepared for installation of the fan section 62. Installation of the fan section includes coupling to the FDC section 54 and to the core section 30 and attachment of the fan case 64 to the FDC case 60.

In preparation for assembly of the fan section, the first arm 74 is reattached to the core section 30. The first arm 74 is rigidly attached meaning that rotation is not possible. Accordingly, the subassembly is supported by the first arm 74 and by the aft arm 90. Once the subassembly is supported by the first arm, the arm 102 can be disconnected by removing the roller assemblies 112 from the ring 106 and pivoting the arm 102 upward. Each of the arms 74 and 90 are raised to place the subassembly in a position that enables alignment with the fan case 64. The mount ring 103 is removed and subassembly is ready for assembly of the fan case section 62.

Referring to Figures 15 and 16, the fan case 64 is moved along the horizontal axis into alignment with the FDC section 30 on cart 148. The cart 148 includes features that enable movement of the fan case 64 for alignment along the horizontal axis with the other subassembly components supported by arms extending from the upper beam 70. The fan case 64 includes a mounting ring 116 configured to receive the rollers 112 of the roller assembly 114.

Once the fan case 62 is attached to the FDC case 54, the roller assembly 114 is lowered into position and the rollers 112 (Figures 12 and 13) are inserted into grooves defined within the mounting ring 116. The mounting ring 116 includes a configuration similar to that of the mount ring 106, except that the mounting ring 116 is a size appropriate for the fan case 64 and features compatible with attachment to the fan case 64. The engine subassembly is therefore supported at the forward end by the roller assembly 114 and at the aft end by the gear assembly 138 and ring gear 94. In this supported condition, the engine subassembly may then be rotated around the horizontal axis a full 360 degrees to enable access to all portions of the outer engine

assembly for mounting the accessory components to each of the outer case portions and surfaces.

Accordingly, the example assembly system enables efficient assembly operation in a reduced vertical space that simplifies access to components.

- 5 Although an example embodiment has been disclosed, a worker of ordinary skill in this art would recognize that certain modifications would come within the scope of this disclosure. For that reason, the following claims should be studied to determine the scope and content of this disclosure.

CLAIMS

What is claimed is:

1. An assembly system for assembling a gas turbine engine comprising:
 - a support beam defining a horizontal plane for assembly of engine
 - 5 components along a horizontal axis substantially parallel with the support beam;
 - a forward arm supported on the support beam for supporting a forward portion of an engine component;
 - an aft arm supported on the support beam for supporting an aft portion of the engine component;
 - 10 an aft mounting ring attachable to an aft end of an engine assembly;
 - a forward mounting ring attachable to a forward end of the engine assembly;
 - a drive mounted to the aft arm engageable to the aft mounting ring for rotating the engine assembly about the horizontal axis; and
 - a roller supported on the forward arm and engageable to the forward
 - 15 mounting ring to support the first end of the engine assembly during rotation about the horizontal axis.
2. The assembly system as recited in claim 1, including at least one additional arm disposed between the forward arm and the aft arm for supporting a portion of the
- 20 engine assembly.
3. The assembly system as recited in claim 2, wherein the at least one additional arm includes a first arm and a second arm movable vertically relative to the support beam.
- 25 4. The assembly system as recited in claim 2, including an end assembly supported on one of the at least one additional arm, the end assembly including a lateral adjustment linkage for aligning an engine component secured thereto in a direction transverse to the horizontal axis.

30

5. The assembly system as recited in claim 4, wherein the end assembly includes first and second clamps set apart from each other on opposite sides of an engine centerline.
6. The assembly system as recited in claim 2, including a first mount secured to the engine assembly and engageable with the first arm and a second mount secured to the engine assembly and engageable with second arm.
7. The assembly system as recited in claim 1, wherein each of the forward arm and the aft arm are supported on a sliding support movable along the support beam.
8. The assembly system as recited in claim 1, wherein the aft arm and the forward arm are each movable between a stowed position and a mount position.
9. The assembly system as recited in claim 4, including a motor corresponding with each of the forward arm and the aft arm for driving a linkage to move the corresponding one of the forward arm and the aft arm between the stowed position and the mount position.
10. The assembly system as recited in claim 4, wherein the aft arm is movable about a pivot between the stowed and mount positions.
11. The assembly system as recited in claim 6, wherein the forward arm is movable vertically to adjust spacing between the support beam and the roller.
12. The assembly as recited in claim 1, wherein the aft mounting ring includes locking features engageable to the drive mounted on the aft arm.
13. The assembly as recited in claim 1, wherein the forward mounting ring includes a groove receiving a roller of the roller assembly for supporting the forward portion of the engine assembly.

14. The assembly system as recited in claim 1, including at least one cart for supporting an engine component relative to the horizontal axis that enables positioning of the supported engine component in at least two directions.
- 5 15. A method of assembling a gas turbine engine comprising:
attaching an aft mounting ring to an aft portion of an aft engine section;
attaching a forward mounting ring to a forward portion of a forward engine
section;
supporting a first intermediate engine section along a horizontal axis;
10 attaching the aft engine section to the intermediate engine component;
supporting a portion of the aft engine section along a horizontal axis with a
drive supported on an aft arm by attaching the aft mounting ring to the drive;
supporting a portion of the forward engine section along the horizontal axis
with a roller assembly supported on a forward arm by coupling the roller assembly to
15 the forward mounting ring;
rotating the aft, first intermediate and forward engine sections about the
horizontal axis with the drive supported on the aft arm; and
performing assemble operations on the aft, first intermediate, and forward
engine sections.
20
16. The method as recited in claim 15, wherein the drive comprises a motor
driving a gear assembly and the aft mounting ring includes gear teeth engaged by the
gear assembly for driving rotation of the aft engine section about the horizontal axis.
- 25 17. The method as recited in claim 15, wherein the forward mounting ring
includes a track for receiving rollers of the roller assembly and supporting the
forward engine section includes inserting the rollers into the track of the forward
mounting ring.
- 30 18. The method as recited in claim 16, wherein supporting the first intermediate
engine section along the horizontal axis includes fixing a first arm to a first mount

attached to the first intermediate engine and a second arm to a second mount attached to the first intermediate engine section.

19. The method as recited in claim 18, including detaching the first arm and the
5 second arm from the corresponding first mount and second mount prior to rotating the aft, first intermediate, and forward engine sections about the horizontal axis.

20. The method as recited in claim 15, including aligning the aft engine section along the horizontal axis with a cart, wherein the cart enables positioning of the aft
10 engine section in at least two axes.