

METHOD AND APPARATUS FOR IMPLEMENTING ACCESSIBILITY FUNCTION IN APPLICATIONS

TECHNICAL FIELD

[0001] The present application relates to the field of computer technologies, and
5 in particular, to a method and an apparatus for implementing an accessibility function
in applications.

BACKGROUND

[0002] Currently, to make a device such as a mobile phone or a computer
accessible to a user, the system provides the user with many accessibility functions.
10 For example, a text-to-speech function enables a visually impaired user to better
interact with the device.

[0003] In the existing technology, a specific method for implementing an
accessibility function in applications is shown in FIG. 1.

[0004] Step 101: A user sends a request for invoking an input control unit to
15 application A installed in a device; after receiving the invocation request, application
A invokes the input control unit configured in a system; and when the user triggers an
event corresponding to an accessibility function by performing an operation on the
input control unit, the input control unit sends the event to a system accessibility
manager.

20 [0005] Step 102: After receiving the event, the system accessibility manager
determines an accessibility service corresponding to a type of the event based on
configuration of each accessibility service in the system, and sends the event to the
accessibility service.

[0006] Step 103: After receiving the event, the accessibility service determines a
25 service feedback instruction corresponding to the event, invokes an accessibility
function engine on the device, and finally implements the accessibility function by
using the accessibility function engine based on the service feedback instruction.

[0007] In actual applications, the accessibility service in the system is usually

provided by third-party application software. It can be seen from step 102 that the third-party application software that provides the accessibility service can obtain operation information of the user and information in a device interface, and can also obtain privacy information of the user on application A. For example, in the previous step, the privacy information is an account and a password that are of the user on application A. As such, a threat is posed to information security of the user.

[0008] Currently, there are two methods for alleviating the previous problem: In one method, reliable third-party application software that provides an accessibility service is selected in advance. Apparently, this method cannot completely eliminate security risks brought by the third-party application software to user information. In the other method, the system prohibits enabling of an accessibility service, so information of a user does not need to pass through third-party application software. This method can completely eliminate security risks caused by the third-party application software to the user information, but the user cannot obtain the accessibility service when the method is used. As such, currently, there is no method that can not only secure user information, but also ensure that the user obtains the accessibility service.

SUMMARY

[0009] Implementations of the present application provide a method and an apparatus for implementing an accessibility function in applications, to alleviate a problem in the existing technology that security risks are caused to user information when third-party application software provides an accessibility function for a user.

[0010] The present disclosure provides a method for implementing an accessibility function in applications, where the method includes the following: receiving, by an application, a request for invoking an input control unit, and invoking the input control unit; when detecting an event corresponding to an accessibility function and triggered by using the input control unit, determining a service feedback instruction corresponding to the event; and invoking an accessibility function engine of a device that includes the application, and implementing the accessibility function by using the accessibility function engine based on the service feedback instruction.

[0011] Correspondingly, the present disclosure further provides an apparatus for implementing an accessibility function in applications, where the apparatus includes

the following: a receiving unit, a determining unit, and an implementing unit, where the receiving unit receives a request for invoking an input control unit, and invokes the input control unit; when detecting an event corresponding to an accessibility function and triggered by using the input control unit, the determining unit determines
5 a service feedback instruction corresponding to the event; and the implementing unit invokes an accessibility function engine of a device that includes the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction.

[0012] According to the methods for implementing an accessibility function in applications provided in the present application, when detecting the event
10 corresponding to the accessibility function and triggered by the input control unit, the application directly invokes the accessibility function engine of the device that includes the application based on the service feedback instruction corresponding to the event, to implement the accessibility function. That is, in a process of
15 implementing an accessibility service in the present application, third-party application software does not need to be used. It alleviates a problem that security risks are caused to user information when the third-party application software obtains operation information of a user in the application and information in a device interface.

BRIEF DESCRIPTION OF DRAWINGS

[0013] The accompanying drawings described here are intended to provide a further understanding of the present application, and constitute a part of the present application. The illustrative implementations of the present application and descriptions thereof are intended to describe the present application, and do not
25 constitute limitations on the present application. In the accompanying drawings:

[0014] FIG. 1 is a specific schematic flowchart illustrating a method for implementing an accessibility function in applications in the existing technology;

[0015] FIG. 2 is a specific schematic flowchart illustrating a method for implementing an accessibility function in applications, according to an
30 implementation of the present application; and

[0016] FIG. 3 is a specific schematic structural diagram illustrating an apparatus for implementing an accessibility function in applications, according to an

implementation of the present application.

DESCRIPTION OF IMPLEMENTATIONS

[0017] Currently, in actual applications, in order to facilitate better interaction between a user and a device (for example, a mobile phone or a tablet computer), the device provides some accessibility functions for the user. For example, a "Talk Back" application in an Android system can provide a text-to-speech function for the user. This function enables a relatively weak-sighted user to correct an input error of the user on the mobile phone in time and facilitates the user.

[0018] The technical solutions provided in the present application are also applicable to a text-to-speech function in a mobile phone. To clearly describe the present application, the following uses the text-to-speech function as an example to describe a process that a user uses the text-to-speech function in a mobile phone application in the existing technology.

[0019] First, the user taps an input box in the current interface of application A, and an on-screen keyboard (that is, a native keyboard) configured in the operating system is displayed in the current interface of application A. Then, the user enters information in the input box by using the on-screen keyboard. Finally, text-to-speech is performed on the input information in real time based on the information entered by the user in the input box. For example, each time the user taps a key on the on-screen keyboard, the mobile phone performs text-to-speech on information corresponding to the key.

[0020] In the previous step, after the user enters information in the input box by using the on-screen keyboard, an event corresponding to the text-to-speech function in the mobile phone is triggered. In this case, the on-screen keyboard first sends the event to an accessibility manager (as described in step 101 in FIG. 1). Then, the accessibility manager sends the event to an accessibility service corresponding to the event (as described in step 102 in FIG. 1). Next, the accessibility service determines a service feedback instruction corresponding to the event, and invokes a text-to-speech engine. Finally, the text-to-speech function is implemented by using the text-to-speech engine based on the service feedback instruction (as described in step 103 in FIG. 1).

[0021] As described in the background, the accessibility service is usually provided by third-party application software. In the previous process of implementing

text-to-speech, the third-party application software can obtain privacy information of the user on application A, causing security risks to the information of the user.

[0022] To alleviate the previous problem, the present application provides a method and an apparatus for implementing an accessibility function in applications.

5 To make the objectives, technical solutions, and advantages of the present application clearer, the following clearly and comprehensively describes the technical solutions of the present application with reference to specific implementations and accompanying drawings of the present application. Apparently, the described implementations are merely some rather than all of the implementations of the present application. Other
10 implementations obtained by a person of ordinary skill in the art based on the implementations of the present application without creative efforts shall fall within the protection scope of the present application.

[0023] The technical solutions provided in the implementations of the present application are described in detail below with reference to the accompanying
15 drawings.

[0024] The present application provides a method for implementing an accessibility function in applications, to alleviate a problem in the existing technology that security risks are caused to user information when third-party application software provides an accessibility function for a user. FIG. 2 shows a schematic
20 flowchart of the method. The method includes the following steps.

[0025] Step 201: An application receives a request for invoking an input control unit, and invokes the input control unit.

[0026] In the present step, the application receives the request for invoking the input control unit, where the request for invoking the input control unit can be
25 triggered by that "the user taps an input box in the current application interface" in the previous example, or can be triggered by other predetermined operations.

[0027] After receiving the request for invoking the input control unit, the application displays the input control unit in the current application interface. The input control unit can be an on-screen keyboard. The input control unit can be an
30 on-screen keyboard interface including some on-screen keys. The input control unit can also be another input control unit, and the input control unit can be configured in an operating system or can be preconfigured by the application. Implementations are not specifically limited here.

[0028] Step 202: When detecting an event corresponding to an accessibility

function and triggered by using the input control unit, determine a service feedback instruction corresponding to the event.

[0029] After invoking the input control unit, the application detects an event corresponding to the accessibility function and triggered by using the input control unit. There are many detection methods. For example, the application can detect an event triggered by using the input control unit, determine a type of the triggered event, and determine whether the triggered event is an event corresponding to the accessibility function based on the type of the triggered type.

[0030] For example, event types corresponding to a predetermined accessibility function are "tap", "double tap", and "focus change". If the user "taps" an object on an input control unit, the application detects that the type of the triggered event is an event type corresponding to the accessibility function, that is, the triggered event is an event corresponding to the accessibility function. If the user "drags" an object in the application interface, the application detects that the triggered event is not of an event type corresponding to the accessibility function, that is, the triggered event is not an event corresponding to the accessibility function.

[0031] The previous method for detecting an event corresponding to an accessibility function by the application can further be the following: detecting an event triggered by using the input control unit, determining an operation object of the user in the triggered event, and determining whether the triggered event is an event corresponding to the accessibility function based on the operation object.

[0032] For example, if the input control unit is an on-screen keyboard, and operation objects corresponding to a predetermined accessibility function are "a", "b", and "c" on the on-screen keyboard, and if the user taps "a" on the on-screen keyboard, the application detects that the operation object of the triggered event is an operation object corresponding to the accessibility function, that is, the triggered event is an event corresponding to the accessibility function.

[0033] The previous two examples of methods for detecting an event corresponding to an accessibility function are merely for illustrative description. In actual applications, a detection method can be set by a user based on the user's demands. Implementations are not specifically limited here.

[0034] When detecting the event corresponding to the accessibility function and triggered by the input control unit, the application determines the service feedback instruction corresponding to the event. The method for determining the service

feedback instruction can be determining a service feedback instruction corresponding to a type of the event based on a predetermined mapping relationship between a type of an event corresponding to the accessibility function and each service feedback instruction.

5 **[0035]** Referring back to the previous example, event types corresponding to a predetermined accessibility function are "tap", "double tap", and "focus change". A mapping relationship between each service feedback instruction and each of the three event types is established. For example, if the accessibility function is a text-to-speech function, a mapping relationship can be established between a type "tap" and a service
10 feedback instruction "performing text-to-speech on a tapped object". When a user "taps" an object in an application interface, the application determines that the service feedback instruction corresponding to the triggered event is "performing text-to-speech on a tapped object" based on the type of the triggered event and the previous mapping relationship.

15 **[0036]** The type of the event corresponding to the accessibility function and the service feedback instruction are merely for illustrative description. In actual applications, the type of the event corresponding to the accessibility function and the service feedback instruction are sometimes more complex. For example, the service feedback instruction can further limit an operation object. Assume that text-to-speech
20 is performed only when a user taps "W", or when a user taps "W", text-to-speech volume is higher than that generated when another letter is tapped. These can be set based on the user's demands.

[0037] When the application detects that the event triggered by using the input control unit is not an event corresponding to the accessibility function, to save
25 resources, the application may not need to perform an operation on the triggered event, that is, the application only needs to "pay attention" to an event type corresponding to the accessibility function.

[0038] Step 203: Invoke an accessibility function engine of a device that includes the application, and implement the accessibility function by using the accessibility
30 function engine based on the service feedback instruction.

[0039] In the present step, the accessibility function engine of the device that includes the application is invoked. A specific invocation method can be as follows: The application first establishes a connection relationship to an engine that provides the accessibility function; after successfully establishing the connection relationship,

the application can invoke the accessibility function engine; otherwise, the application cannot invoke the accessibility function engine.

[0040] A specific method for establishing the connection relationship to the accessibility function engine by the application is as follows: The application sends a request for invoking an interface to the accessibility function engine, and after the accessibility function engine receives the request, the application successfully invokes the interface of the accessibility function engine, that is, the application successfully establishes the connection relationship to the accessibility function engine.

[0041] In actual applications, interfaces of some accessibility function engines are open, that is, the accessibility function engine allows an application to invoke an interface as long as the application sends a request for invoking the interface. Some accessibility function engines set permission on objects that invoke interfaces. When an application sends a request for invoking an interface to the accessibility function engine, first, the accessibility function engine needs to verify whether the application has the permission to invoke the interface. After the verification succeeds, the application is allowed to invoke the interface.

[0042] The step of establishing the connection relationship to the accessibility function engine by the application can be performed before the application invokes the accessibility function engine. For example, the application can establish the connection relationship after invoking the input control unit or can establish the connection relationship after determining the service feedback instruction that corresponds to the triggered event.

[0043] If the connection relationship is established after the application invokes the input control unit, a specific process of establishing the connection relationship can be as follows: After invoking the input control unit, the application sends a connection request to the accessibility function engine; if the connection is successfully established, the application performs step 202; if the connection fails to be established, the application does not need to perform step 202. Compared with a method that the connection relationship is established after the application determines the service feedback instruction that corresponds to the triggered event, the connection method can reduce resource consumption.

[0044] After the application invokes the accessibility function engine, the accessibility function engine implements the accessibility function based on the service feedback instruction determined in step 202.

[0045] For example, Table 1 is a predetermined mapping relationship between an event type and each service feedback instruction.

Table 1

Event type	Service feedback instruction
Tap	Performing text-to-speech on a tapped object
Double tap	Broadcasting a specific voice
...	

5 [0046] If the user "taps" an object on the input control unit, the application determines that a service feedback instruction corresponding to the triggered event is "performing text-to-speech on a tapped object". In this case, the application invokes a text-to-speech engine of the device that includes the application, and the text-to-speech engine performs text-to-speech on the object tapped by the user based
 10 on the service feedback instruction "performing text-to-speech on a tapped object". When the user determines that the tapped object is an object that the user wants to enter, the user can "double-tap" the object to indicate that the object is selected as an input object, and the application determines that the service feedback instruction corresponding to the triggered event is "broadcasting a specific voice". For example,
 15 the predetermined specific voice is "jingling". In this case, after the user double-taps the object, the text-to-speech engine broadcasts a "jingling" sound.

[0047] It can be seen from content of the background that, in the method for implementing an accessibility function in applications in the existing technology, when an application detects an event corresponding to an accessibility function and
 20 triggered by an input control unit, the input control unit first sends the event to a system accessibility manager, then the system accessibility manager sends the event and information in an interface to third-party application software, and finally the accessibility function is implemented by invoking an accessibility function engine by using the third-party application software. In the present application, when detecting
 25 an event corresponding to the accessibility function and triggered by the input control unit, the application directly invokes an accessibility function engine of the device that includes the application based on a service feedback instruction corresponding to

the event, to implement the accessibility function. That is, in the present application, an operating system including a system accessibility manager and an accessibility service can be directly bypassed in a process of implementing an accessibility service, that is, the third-party application software is bypassed, and the accessibility function engine is directly invoked to implement the accessibility function. It alleviates a problem that the third-party application software causes security risks to user information after obtaining operation information of the user in the application and information in a device interface.

[0048] It is worthwhile to note that, in step 202 and/or step 203 can be executed by an input control unit or another execution module in the application. Implementations are not limited in the present application.

[0049] As recorded in the previous content, the input control unit can be configured in the operating system or can be preconfigured by the application.

[0050] When the input control unit is configured in the operating system, in the present application, the operating system can be improved. An input control unit configured in an operating system in the existing technology needs to send an event corresponding to an accessibility function to an accessibility manager. However, an input control unit configured in the improved operating system in the present application intercepts an event corresponding to the accessibility function, and directly invokes the accessibility function engine of the device to implement the accessibility function. In a process of implementing the accessibility function, third-party application software does not need to be used. As such, security of user information is improved.

[0051] When the input control unit is configured by the application, after the user sends a request for invoking the input control unit to the application, the application shields an input control unit configured in the operating system, and displays the input control unit configured by the application in an application interface. When the user triggers an event corresponding to the accessibility function by using the input control unit configured by the application, the input control unit configured by the application directly invokes the accessibility function engine of the device to implement the accessibility function. Likewise, in a process of implementing the accessibility function, third-party application software does not need to be used. As such, security of user information is improved.

[0052] Correspondingly, the present disclosure further provides an apparatus for

implementing an accessibility function in applications, to alleviate a problem in the existing technology that security risks are caused to user information when third-party application software provides an accessibility function for a user. FIG. 3 shows a schematic structural diagram of the apparatus. The apparatus includes the following: a receiving unit 301, a determining unit 302, and an implementing unit 303.

[0053] The receiving unit 301 receives a request for invoking an input control unit, and invokes the input control unit.

[0054] When detecting an event corresponding to an accessibility function and triggered by using the input control unit, the determining unit 302 determines a service feedback instruction corresponding to the event.

[0055] The implementing unit 303 invokes an accessibility function engine of a device that includes the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction.

[0056] A working procedure of this apparatus implementation is as follows: First, the receiving unit 301 receives the request for invoking the input control unit, and invokes the input control unit. Then, when detecting the event corresponding to the accessibility function and triggered by using the input control unit, the determining unit 302 determines the service feedback instruction corresponding to the event. Finally, the implementing unit 303 invokes the accessibility function engine of the device that includes the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction.

[0057] There are many methods for implementing an accessibility function in applications in the previous apparatus implementation. For example, in an implementation, the determining unit 302 detects an event corresponding to an accessibility function and triggered by using the input control unit, including the following: detecting an event triggered by using the input control unit; determining a type of the triggered event; and determining whether the triggered event is an event corresponding to the accessibility function based on the type.

[0058] In another implementation, the determining unit 302 determines a service feedback instruction corresponding to the event, includes the following: determining a service feedback instruction corresponding to a type of the event based on a predetermined mapping relationship between a type of an event corresponding to the accessibility function and each service feedback instruction.

[0059] In still another implementation, the implementing unit 303 invokes an

accessibility function engine of a device that includes the application, including the following: establishing a connection relationship to an engine that provides the accessibility function; and invoking the accessibility function engine of the device that includes the application based on the connection relationship.

5 **[0060]** In yet another implementation, the determining unit 302 detects an event corresponding to an accessibility function and triggered by using the input control unit, including the following: detecting an event corresponding to the accessibility function by using the input control unit.

10 **[0061]** The determining unit 302 determines a service feedback instruction corresponding to the event, including the following: determining a service feedback instruction corresponding to the event by using the input control unit.

15 **[0062]** The implementing unit 303 invokes an accessibility function engine of a device that includes the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction, including the following: invoking the accessibility function engine of the device that includes the application by using the input control unit, and implementing the accessibility function by using the accessibility function engine based on the service feedback instruction.

20 **[0063]** Beneficial effects obtained by applying the system implementations provided in the present application are the same as or similar to those obtained by applying the previous method implementations. To avoid repetition, details are omitted here for simplicity.

25 **[0064]** A person skilled in the art should understand that an implementation of the present disclosure can be provided as a method, a system, or a computer program product. Therefore, the present disclosure can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. Moreover, the present disclosure can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

30 **[0065]** The present disclosure is described with reference to the flowcharts and/or block diagrams of the method, the device (system), and the computer program product based on the implementations of the present disclosure. It is worthwhile to note that computer program instructions can be used to implement each process and/or each

block in the flowcharts and/or the block diagrams and a combination of a process and/or a block in the flowcharts and/or the block diagrams. These computer program instructions can be provided for a general-purpose computer, a dedicated computer, an embedded processor, or a processor of another programmable data processing device to generate a machine, so that the instructions executed by the computer or the processor of the another programmable data processing device generate an apparatus for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0066] These computer program instructions can be stored in a computer readable memory that can instruct the computer or the another programmable data processing device to work in a specific way, so that the instructions stored in the computer readable memory generate an artifact that includes an instruction apparatus. The instruction apparatus implements a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0067] These computer program instructions can be loaded onto the computer or another programmable data processing device, so that a series of operations and steps are performed on the computer or the another programmable device, thereby generating computer-implemented processing. Therefore, the instructions executed on the computer or the another programmable device provide steps for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0068] In a typical configuration, a computing device includes one or more processors (CPU), one or more input/output interfaces, one or more network interfaces, and one or more memories.

[0069] The memory can include a non-persistent memory, a random access memory (RAM), a non-volatile memory, and/or another form that are in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

[0070] The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can store information by using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data. Examples of a computer storage medium include but are not limited to a phase-change random access memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), another type

of random access memory (RAM), a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD) or another optical storage, a cassette magnetic tape, a magnetic tape/magnetic disk storage or another magnetic storage device, or any other non-transmission medium. The computer storage medium can be used to store information accessible by the computing device. Based on the definition in the present specification, the computer readable medium does not include transitory computer readable media (transitory media) such as a modulated data signal and carrier.

10 **[0071]** It is worthwhile to further note that, the terms "include", "contain", or their any other variants are intended to cover a non-exclusive inclusion, so a process, a method, a product or a device that includes a list of elements not only includes those elements but also includes other elements which are not expressly listed, or further includes elements inherent to such a process, method, product or device. Without
15 more constraints, an element preceded by "includes a ..." does not preclude the existence of additional identical elements in the process, method, product or device that includes the element.

[0072] The previous implementations are implementations of the present application, and are not intended to limit the present application. A person skilled in
20 the art can make various modifications and changes to the present application. Any modification, equivalent replacement, or improvement made without departing from the spirit and principle of the present application shall fall within the scope of the claims in the present application.

CLAIMS

What is claimed is:

1. A method for implementing an accessibility function in applications, wherein the method comprises:

5 receiving, by an application, a request for invoking an input control unit, and invoking the input control unit;

 when detecting an event corresponding to an accessibility function and triggered by using the input control unit, determining a service feedback instruction corresponding to the event; and

10 invoking an accessibility function engine of a device that comprises the application, and implementing the accessibility function by using the accessibility function engine based on the service feedback instruction.

2. The method according to claim 1, wherein the input control unit is configured in the application.

15 3. The method according to claim 1, wherein the detecting an event corresponding to an accessibility function and triggered by using the input control unit comprises:

 detecting an event triggered by using the input control unit;

 determining a type of the triggered event; and

20 determining whether the triggered event is an event corresponding to the accessibility function based on the type.

4. The method according to claim 3, wherein the determining a service feedback instruction corresponding to the event comprises:

25 determining a service feedback instruction corresponding to a type of the event based on a predetermined mapping relationship between a type of an event corresponding to the accessibility function and each service feedback instruction.

5. The method according to claim 1, wherein the invoking an accessibility function engine of a device that comprises the application comprises:

30 establishing a connection relationship to an engine that provides the accessibility function; and

 invoking the accessibility function engine of the device that comprises the application based on the connection relationship.

6. The method according to claim 1, wherein the detecting an event corresponding to an accessibility function and triggered by using the input control unit comprises:

detecting an event corresponding to the accessibility function by using the input
5 control unit;

the determining a service feedback instruction corresponding to the event comprises:

determining a service feedback instruction corresponding to the event by using
the input control unit; and

10 the invoking an accessibility function engine of a device that comprises the application, and implementing the accessibility function by using the accessibility function engine based on the service feedback instruction comprises:

invoking the accessibility function engine of the device that comprises the application by using the input control unit, and implementing the accessibility
15 function by using the accessibility function engine based on the service feedback instruction.

7. The method according to claim 1, wherein the input control unit is an on-screen keyboard.

8. The method according to any one of claims 1 to 7, wherein the accessibility
20 function is a text-to-speech function.

9. An apparatus for implementing an accessibility function in applications, wherein the apparatus comprises:

a receiving unit, a determining unit, and an implementing unit, wherein

the receiving unit receives a request for invoking an input control unit, and
25 invokes the input control unit;

when detecting an event corresponding to an accessibility function and triggered by using the input control unit, the determining unit determines a service feedback instruction corresponding to the event; and

the implementing unit invokes an accessibility function engine of a device that
30 comprises the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction.

10. The apparatus according to claim 9, wherein that the determining unit detects an event corresponding to an accessibility function and triggered by using the input control unit comprises:

detecting an event triggered by using the input control unit;

determining a type of the triggered event; and

determining whether the triggered event is an event corresponding to the accessibility function based on the type.

5 11. The apparatus according to claim 10, wherein that the determining unit determines a service feedback instruction corresponding to the event comprises:

 determining a service feedback instruction corresponding to a type of the event based on a predetermined mapping relationship between a type of an event corresponding to the accessibility function and each service feedback instruction.

10 12. The apparatus according to claim 9, wherein that the implementing unit invokes an accessibility function engine of a device that comprises the application comprises:

 establishing a connection relationship to an engine that provides the accessibility function; and

15 invoking the accessibility function engine of the device that comprises the application based on the connection relationship.

 13. The apparatus according to claim 9, wherein that the determining unit detects an event corresponding to an accessibility function and triggered by using the input control unit comprises:

20 detecting an event corresponding to the accessibility function by using the input control unit;

 that the determining unit determines a service feedback instruction corresponding to the event comprises:

25 determining a service feedback instruction corresponding to the event by using the input control unit; and

 that the implementing unit invokes an accessibility function engine of a device that comprises the application, and implements the accessibility function by using the accessibility function engine based on the service feedback instruction comprises:

30 invoking the accessibility function engine of the device that comprises the application by using the input control unit, and implementing the accessibility function by using the accessibility function engine based on the service feedback instruction.