

MULTI-STAGE DISTILLATION SYSTEM, METHOD FOR OPERATING SAME

Technical Area

The invention relates to a multistage distillation system, wherein each stage operates in a higher pressure and temperature range than its ensuing stage during operation, wherein each stage comprises an evaporator and condenser with one pressure-tight container each, with an upper spray inlet for introducing and spraying added liquid, as well as with a lower outlet for letting out captured liquid, as well as with a steam space between the spray inlet and the captured liquid, wherein the steam space of each evaporator is compressively bonded with the steam space of the condenser of the same stage by a pressure-tight steam pipe with a cross section large enough that the pressure in the two steam spaces of one stage can always balance itself out during operation, and wherein the outlet of each evaporator is connected with the spray inlet of the next evaporator and the outlet of the last evaporator is connected with the spray inlet of the first evaporator by a respective pressure-tight liquid line to yield an evaporator circuit, and wherein the outlet of each condenser is connected with the spray inlet of the preceding condenser and the outlet of the first condenser is connected with the spray inlet of the last condenser by a pressure-tight liquid line to yield a condenser circuit. In addition, the invention relates to a method for implementing such a distillation system, along with a controller for its operation.

Prior Art

Distillation systems have long been known. For example, they serve to prepare water or separate alcohol from other liquids, and are used in numerous other systems. In principle, the liquid to be distilled is evaporated while exposed to heat, so as to separate it from the residues, for example from salts or other liquids with a higher boiling point. The steam is finally cooled in another chamber, causing it to condense into the distillate.

In recent years, the systems were improved so as to raise the efficiencies and simplify the controllers. WO 2008/122136 describes an advantageous system according to prior art with a high efficiency. It is preferably used in the environment of heat-emitting systems, such as power plants, the released thermal energy of which can be used free of charge or inexpensively. In particular, this type of distillation system can also be given a multistage design, so as to utilize the entire provided differential temperature range, for example 50-100°C.

Available to make optimal use of the provided heat for the intended purpose are heat exchangers and other known auxiliaries, which are sufficiently known. In addition, electrical current is also required for operating such a distillation system, specifically among other things for conveying the liquids by means of pumps or operating vacuum pumps for siphoning incondensable gases. The power required for operating such systems makes up a significant portion of the overall operating costs. Therefore, the power requirement must be lowered to make the distillation system less expensive to operate.

Description of the Invention

Therefore, the object of the present invention is to improve a multistage distillation system of the kind described at the outset in such a way as to lower power consumption during operation. Another object of the present invention is to describe a method that implements such a distillation, as well as controller for its operation.

The object is achieved by the features in the independent claims for the respective categories.

According to the invention, the distillation system described at the outset encompasses a pressure-tight steam line, which at a first end is connected with one of the pressure-tight liquid lines between two adjacent condensers or with the pressure-tight liquid line between the last and first evaporator. In addition, the second end of the pressure-tight steam line is connected with a steam space, which during operation has a higher pressure than the pressure in the steam space into which the liquid flows in the pressure-tight liquid line for pressurizing the liquid with a higher pressure as well as for conveying the liquid.

This pressurization exposes the liquid in the liquid line to a higher pressure, which allows it to evaporate in a stage with a higher temperature. In addition, the pressurization can convey the liquid into a container arranged at a higher potential without having to use electrical current for this purpose. As a result, no pump whatsoever is required during continuous operation.

While pumps are still placed in the evaporator and condenser circuit, they are only necessary to start the process at the outset. The process already runs automatically within several minutes, without pumps having to be operated for circulating the liquids in the circuits. Only a vacuum pump for siphoning incondensable gases at the end of the condensation pathways in the condensers must every so often be made operational, but only for a short time.

Power consumption can be drastically lowered in the distillation system according to the invention. In addition, just a single pump is now required in each of the circuits, which also lowers the investment costs for the distillation system.

The method according to the invention for operating a distillation process with the use of a distillation system according to the invention has an inlet into the evaporator circuit, an outlet from the evaporator circuit, as well as a distillate outlet from the condenser circuit, and is characterized by the following procedural steps:

Monitoring the liquid quantities in both circuits; monitoring the concentration of residues in the evaporator circuit; letting out liquid with a high concentration of residues at the outlet as soon as the liquid in the evaporator circuit has reached a prescribed maximum level and/or the concentration of residues in the evaporator circuit has reached a prescribed maximum value; letting out distillate from the condenser circuit at the distillate outlet as soon as the liquid in the condenser circuit has reached a prescribed maximum level; letting liquid into the condenser circuit at the inlet as soon as the liquid

in the evaporator circuit has reached a prescribed minimum level and/or the concentration of residues in the evaporator circuit has reached a prescribed maximum value. These steps are repeated until the process is to be stopped.

Liquid is preferably only let out from the evaporator circuit once both the maximum concentration and maximum level have been reached, and specifically until such time as the minimum level has been reached. By adding fresh liquid up to the maximum level, the concentration is then lowered. From that point on, the level is again raised to the respective maximum level as soon as the minimum level or maximum concentration has been reached.

A preferred method involves the use of a distillation system that comprises a vacuum pump, which is connected by a gas line with the end of each condensation path of each condenser. The method is characterized by the following procedural steps:

Determining the temperature differences in the steam spaces of the evaporators and condensers of the same stage; removing incondensable gases in the steam space of a condenser through the gas line by means of the vacuum pump as soon as the corresponding temperature difference has reached a prescribed maximum value until it has dropped below a prescribed minimum value. The mentioned steps are repeated until the process is to be stopped.

The controller according to the invention for implementing a method according to the invention encompasses ports for sensors to read in measuring data, a processor for

evaluating the measuring data along with ports for changing the settings of valves and pumps.

Brief Description of the Drawings

The invention will be described in greater detail below drawing reference to the figures. The same reference numbers each refer to the same facts. Shown on:

- Fig. 1 is a multistage distillation system according to prior art;
- Fig. 2 is a multistage distillation system according to the invention;
- Fig. 3 is a distillation system according to Fig. 2 with exemplary temperature and pressure values.

Ways of Implementing the Invention

Fig. 1 shows a multistage distillation system 1 according to prior art. Three stages are depicted, which are each denoted by lower parentheses marked S1, S2 and S3. Stage S1 is also bordered by a dashed line up to a part that is connected with stage S2 by a heat exchanger 14. Each stage S consists of an evaporator (or evaporator) E1, E2, E3, which comprises the respective left chamber of each stage S1, S2, S3, and a condenser (or condenser) C1, C2, C3, which comprises the respective chamber of the stage S shown on the right. The evaporators and condensers all have a steam space, wherein the steam spaces of the evaporators E1, E2, E3 and condensers C1, C2, C3 of the respective

same stage S1, S2, S3 are interconnected by a respective connecting steam space 6, wherein the size of this connecting steam space 6 is dimensioned in such a way that the pressure P inside of the steam spaces of this stage can be balanced out unimpededly. As a consequence, the same pressure P1, P2, P3 prevails in both chambers of each stage S1, S2, S3. In each chamber, liquid 4 is upwardly conveyed out of the chamber to a spray inlet 3, and there sprayed. The sprayed liquids 4a in the evaporators E1, E2, E3 have a slightly higher temperature than the sprayed liquids 4a of the condensers C1, C2, C3 of the respective same stage. The temperatures of the evaporators E1, E2, E3 are correspondingly slightly higher, and the temperatures of the condensers C1, C2, C3 slightly lower, than the temperatures Ts1, Ts2, Ts3 of the saturation curve for the respective steam pressure P1, P2, P3 known for the respective liquid.

For this reason, the liquid 4a sprayed in each evaporator will partially evaporate and flow into the adjacent chamber of the accompanying condenser, where it collides with the cooler drops and itself condenses again. Over time, evaporated liquid thus wanders from each evaporator into the condenser of the same stage. The distillate can there be skimmed, while new liquid can be introduced into the evaporator.

As a consequence, the first stage S1 operates with a temperature T1,1 in the evaporator E1, or with the temperature T1,2 in the condenser C1, in that the liquids 4a are sprayed into the chambers with the indicated temperatures. The adjacent chamber of the condenser C1 is the evaporator E2, which forms the second stage S2 together with the condenser C2. Accordingly, these chambers of stage S2 operate with

temperatures $T_{2,1}$ in the evaporator E2 and $T_{2,2}$ in the condenser C2, wherein the adjoining chambers C1 and E2 are set to the same temperature. Therefore, the following applies: $T_{1,2} = T_{2,1}$. In order to achieve this temperature uniformity, the lower areas of the chambers C1 and E2 are designed as heat exchangers 14. The same holds true for chambers C2 and E3, which are also interconnected with a heat exchanger, so that the temperature $T_{2,2}$ of the condenser C2 and temperature $T_{3,1}$ of the evaporator E3 always keep the same temperatures.

Temperature and pressure measuring devices 26, 27 in each steam space 6 are used for process monitoring. In addition, a vacuum pump V at the end of each condensation path makes it possible to siphon away incondensable gases in the system. This is important for the process to run efficiently.

In prior art, the individual stages are only interconnected with heat exchangers, so that no exchange or flow of liquids or steam can arise between the various stages S. The stages are only connected with each other via heat exchangers. While the individual stages S do operate in different, respectively adjacent temperature ranges, each does so on its own.

Preferred Exemplary Embodiment

Fig. 2 shows an exemplary embodiment according to the invention. The illustration depicts a multistage distillation system 1 with stages S_i where $i=1, \dots, n$, wherein each stage S_i works in a higher pressure and temperature range P_i, T_i than its ensuing stage S_{i+1} during operation. Fig. 3 presents a system according to Fig. 2, which indicates examples of pressure and

temperature values for the individual containers and pressure chambers that might set in according to the invention.

Each stage S_i encompasses an evaporator E_i and a condenser C_i , wherein each evaporator E_i and each condenser C_i comprises a pressure-tight container 2 with an upper spray inlet 3 for introducing and spraying added liquid 4a in the container 2, as well as with a lower outlet 5 for letting out liquid 4b captured in the container 2. In addition, each container 2 encompasses a steam space 6 between the spray inlet 3 and captured liquid 4b, wherein the steam space 6 of each evaporator E_i is connected in terms of pressure with the steam space 6 of the condenser C_i of the same stage S_i by means of a pressure-tight steam pipe 7 having a large enough cross section that the pressure P_i in the two steam spaces 6 of a stage S_i can always balance out during operation. The outlet 5 of each evaporator E_i is connected with the spray inlet 3 of the next evaporator E_{i+1} and the outlet 5 of the last evaporator E_n is connected with the spray inlet 3 of the first evaporator E_1 by way of a pressure-tight liquid line 8 to yield an evaporator circuit. Analogously thereto, the outlet 5 of each condenser C_i is connected with the spray inlet 3 of the preceding condenser C_{i-1} and the outlet 5 of the first condenser C_1 is connected with the spray inlet 3 of the last condenser C_n by means of a pressure-tight liquid line 9 to yield a condenser circuit. According to the invention, the distillation system encompasses at least one pressure-tight steam line 10, which at a first end is connected with one of the pressure-tight liquid lines 9 between the condensers C_{l+1} and C_{i-1} to 3] or with the pressure-tight liquid line 8 between the evaporators E_n and E_1 , and at a second end with a

steam space having a higher pressure P during operation than the pressure P_i in the steam space 6 of the condenser C_i or than the pressure P_1 in the steam space 6 of the evaporator E_1 , so as to pressurize the liquid 4 with a higher pressure and convey the liquid 4.

In particular, the configuration of containers 2 can also be modified in such a way that the circuits of the evaporators and condensers are situated at the same level. For example, the condenser C_n and evaporator E_1 would be at the same or similar level, just as the condenser C_1 and evaporator E_n . This shortens the length of the connecting steam spaces 6. The indicated Fig. 2 and 3 were depicted in this way for reasons of clarity, and must be understood as schematic illustrations.

According to the invention, the evaporators E and condensers C are spatially separated from each other in the distillation system 1 described here, and connected with each other by pipes having a cross section large enough that the pressure difference in the two chambers 2 measures less than 10 mbar. It is important that this pressure compensation always be ensured. This spatial separation of the chambers 2 now opens up options for interconnecting and spatially arranging chambers of the same kind, specifically the respective evaporators and condensers, in such a way that the liquids 4 flow into the next chamber 2 without the assistance of pumps as a result of the potential energy of the individual chambers 2 taking into account the respective steam pressures in the different stages S_i . In particular, this takes place between the evaporators E_1 to E_n , and between the condensers C_1 and C_n . Consequently, support is now

only necessary in the liquid lines between the condensers Cn to C1 as well as between the evaporators En and E1.

This support can be provided either by pumps or steam pressure. When feeding steam into a liquid line at a pressure that exceeds the pressure in the target chamber, the liquid in the line is conveyed into the target chamber. To this end, steam can be taken from a steam space of the distillation chamber 1. However, if steam with suitable pressure and temperature conditions is available in another nearby source, it is naturally also possible to utilize the latter. In addition, a steam chamber 25 in which the liquid flowing through partially changes into steam can be set up in the liquid line before the evaporator E1. This steam is the hottest in the entire distillation system 1, and also has the highest pressure. The pressure in this steam chamber 25 is even higher than the pressure in the evaporator E1. Liquid 4 can be conveyed from this steam chamber 25 and pressurized, and must be brought to a slightly lower pressure. Examples may be gleaned from Fig. 2 and 3. The steam spaces 6 from stage S with lower pressures can convey corresponding liquids, whose target containers 2 are under a lower pressure than the steam spaces 6 from which the steam lines 10 derive their pressure.

The distillation system 1 preferably has one pump 11 each in the liquid line 8 of the evaporator circuit and in the liquid line 9 of the condenser circuit to reach the prescribed pressures of the liquids 4 at the start of the process. However, the latter need only run for a few minutes until the ideal pressure and temperature conditions have been established in all containers 2. The process then runs independently. The pumps 11 are

preferably arranged in the connecting elements 8, 9 between the containers C1 and Cn or between the containers En and E1.

In addition, the distillation system 1 preferably has a heater 12 in the liquid line 8 of the evaporator circuit before the evaporator E1 and a cooling aggregate 13 in the liquid line of the condenser circuit before the condenser Cn for achieving the prescribed temperatures in the evaporator E1 and condenser Cn. This heater 12 and this cooling aggregate 13 are preferably at least partially together configured as a heat exchanger 14. However, since the heat exchanger 14 cannot reach the desired target temperatures of the ensuing containers Cn or E1, the lines 8, 9 must also incorporate a respective separate cooling aggregate 13 in the liquid line of the condenser circuit along with a separate heater 12 in the liquid line 8 of the evaporator circuit.

As has been shown, it is advantageous for initiating the process that enough liquid 4 still be present in the individual sections of the liquid lines 8, 9. In order to ensure the above, siphons 15 can be arranged in the liquid lines 9, 8 between the condensers Cn to C1 and/or between the evaporators E1 to En, so as to prevent individual condensers Ci and/or evaporators Ei from idling given a system shutdown.

In another preferred arrangement, the siphons 15 in the liquid lines 8 between the evaporators E1 and En have a central spout. It has been shown that increased residues accumulate there, which in this way can be easily removed from the circuit in high concentrations.

In order for the process to run optimally and to evaporate as much of the introduced liquid as possible, incondensable gases that accumulate at the end of the condensation path must from time to time be removed from the steam spaces 6. To this end, each condenser C_i has a gas line 17 connected with a vacuum pump 16 at the end of the distillation path. If needed, the vacuum pump 16 is made operational, although this is also only required for a brief time, as a rule for less than 5% of the operating time.

As has been shown, the vacuum pump 16 can also be operated with steam. It must be connected with a pressure-tight steam line 10 in order to be supplied during operation. The vacuum pump 16 is thereby supplied with steam, which has a higher pressure P than the steam spaces 6 in which gases are to be siphoned.

As a result, absolutely no current is used during operation once the process has started and reached a stable state.

In addition, the individual containers 2 are preferably aligned level to each other in such a way as to enable optimal use of the potential energy of the liquid. According to the invention, each evaporator E_{i+1} is arranged on a lower level than the preceding evaporator E_i in such a way that the liquid 4 is made to flow from each evaporator E_i into the respectively ensuing evaporator E_{i+1} solely by pressure and level differences during implementation of the process, without an electrically operated pump being required for this purpose. Since each ensuing stage S_{i+1} operates at a lower pressure than its preceding stage S_i , the ensuing stage S_{i+1} can be arranged

correspondingly higher, so that liquid flows upward due to its elevated pressure.

Accordingly, each condenser C_{i+1} is arranged at such a level by comparison to its ensuing condenser C_i that the liquid is made to flow from the condenser C_{i+1} into the respective ensuing condenser C_i by pressure and level differences and/or the conveying force of a steam line during process implementation, without an electrically operated pump being required for this purpose. Since the direction of flow in the condenser circuit is opposite the direction of flow in the evaporator, the liquid flows from containers 2 with lower pressures to containers 2 with higher pressures. This can be partially supported by arranging the condensers of the higher stages higher than the condensers of the lower stages. For support purposes, the liquid is additionally supplied by feeding steam to steam lines 10 under a higher pressure. This eliminates the need for using pumps that use current.

In addition, the condensers C_1 and C_n are leveled in such a way that the liquid 4 of the condenser C_1 is made to flow from the condenser C_1 to the condenser C_n via the liquid line 9 of the condenser circuit by pressure and level differences during process implementation, without an electrically operated pump being required for this purpose. Since the pressure in C_1 is much higher than in C_n , a great height can be overcome without a pump being required for this purpose.

The evaporators E_n and E_1 are preferably also leveled in such a way that the liquid 4 of the evaporator E_n is made to flow from the evaporator E_n to the evaporator E_1 by pressure and level differences and by the conveying force of one or more steam lines 10 via the

liquid line 8 of the evaporator circuit during process implementation, without an electrically operated pump being required for this purpose. This section of the liquid line 8 requires both that height be overcome and pressure be applied. This is preferably achieved incrementally by introducing several steam lines 10 from varying stages S into the liquid line 8. The different steam lines 10 can also be introduced into the liquid line 8 at the same location or be operated one after the other, so that the respectively best suited steam line 10 is always operational.

The steam lines 10 can optionally also be routed inside of the liquid line 8, 9.

The distillation system 1 according to the invention encompasses a feed 18 into the evaporator circuit for supplying liquid 4 to be distilled, along with an outlet 19 from the evaporator circuit for letting out liquid 4 with a high concentration of residues, as well as a distillate outlet 20 from the condenser circuit for letting out the distillate 21 generated by the system. These are shown on Fig. 2.

In addition, each steam line 10 and/or each gas line 17 encompasses a valve 22 for regulating the flow rate. These valves 17 are preferably controllable and connected with a regulating device.

At least the containers 2 of the first condenser C1 and last evaporator En each encompass a level sensor 23 for determining the levels of the liquid 4b captured in the containers 2. The other containers 2 can also have such level sensors 23. However, in particular the two mentioned level sensors are required for regulating the process. In addition, the preferred

distillation system 1 has a sensor 24 in the evaporation circuit, preferably in the area of the last evaporator E_n , for measuring the concentration of residues. The sensors 23, 24 are also preferably controllable and connected with a regulating device (not shown).

Described below is the method according to the invention for operating a distillation process using a distillation system 1 according to the invention, which comprises a feed 18 in the evaporator circuit for supplying liquid 4 to be distilled, along with an outlet 19 from the evaporator circuit for letting out liquid 4 with a high concentration of residues, as well as a distillate outlet 20 from the condenser circuit for letting out the distillate 21 generated by the distillation system. According to the invention, the following procedural steps are implemented in this method:

Monitoring the liquid level in the evaporator circuit and in the condenser circuit; monitoring the concentration of residues in the evaporator circuit; letting out liquid with a high concentration of residues at the outlet 19 as soon as the liquid level in the evaporator circuit has reached a prescribed maximum level and/or the concentration of residues in the evaporator circuit has reached a prescribed maximum value; letting out distillate from the condenser circuit at the distillate outlet 20 as soon as the liquid level in the condenser circuit has reached a prescribed maximum level; letting liquid 4 into the condenser circuit at the feed 18 as soon as the liquid level in the evaporator circuit has reached a prescribed minimum value and/or the concentration of residues in the evaporator circuit has reached a

prescribed maximum value. The aforementioned steps are repeated until the process is to be stopped.

Remarkable in the above method is the fact that the pressure and temperatures in the individual chambers regulate themselves as soon as the boundary conditions are present. Only the supply and removal of liquid or distillate is regulated. In addition, care must be taken at the beginning of the process that the liquids flowing into the evaporator E1 and condenser Cn correspond to the prescribed pressure and temperature conditions. This is achieved by the heater 15 and cooling aggregate 13.

In order to improve the process, incondensable gases should be removed from the condenser circuit. To this end, each condenser Ci has a gas line 17 connected with a vacuum pump 16 at the end of the distillation path. The method is enhanced by the following procedural steps:

Determining the temperature differences dT_i in the steam spaces 6 of the containers 2 of evaporators Ei and condensers Ci of the same stage Si; removing incondensable gases in the steam space 6 of the condenser Ci through the gas line 17 using the vacuum pump 16 as soon as the temperature difference dT_i has reached a prescribed maximum value, until dT_i has reached a prescribed minimum value; repeating these steps until the process is to be stopped.

A controller according to the invention for implementing a method according to the invention encompasses ports for sensors to read in measuring data, a processor for evaluating the measuring data, along with ports for changing the settings of valves 22 and pumps 11, 16.

As a rule, the valves 22 are open. However, it may be that several valves 22 are closed or throttled at the beginning of the process.

Reference List

- 1 Distillation system
- 2 Container
- 3 Spray inlet
- 4 Liquid; 4a sprayed liquid; 4b captured liquid
- 5 Outlet
- 6 Steam space
- 7 Steam pipe
- 8 Liquid line to an evaporation circuit
- 9 Liquid line to a condenser circuit
- 10 Steam line
- 11 Pump
- 12 Heater
- 13 Cooling aggregate
- 14 Heat exchanger
- 15 Siphons
- 16 Vacuum pump
- 17 Gas line
- 18 Feed
- 19 Letting out liquid with a high concentration of residues
- 20 Distillate outlet
- 21 Distillate
- 22 Valve
- 23 Level sensor
- 24 sensor for measuring the concentration of residues
- 25 Steam chamber
- 26 Temperature sensor
- 27 Pressure sensor

- E Evaporator, E1, ... En
- C Condenser, C1, ... Cn
- S Stage, S1, ... Sn

CLAIMS

1. A multistage distillation system (1) with stages S_i , where $i=1, \dots, n$, wherein each stage S_i works in a higher pressure and temperature range (P_i , T_i) than its ensuing stage S_{i+1} during operation, wherein each stage S_i encompasses an evaporator E_i and a capacitor C_i , wherein each evaporator E_i and each condenser C_i encompasses a pressure-tight container (2) with an upper spray inlet (3) for introducing and spraying added liquid (4a) in the container, (2), as well as with a lower outlet (5) for letting out liquid (4b) captured in the container (2), as well as with a steam space (6) between the spray inlet (3) and the captured liquid (4b), wherein the steam space (6) of each evaporator E_i is compressively bonded with the steam space (6) of the condenser C_i of the same stage S_i by a pressure-tight steam pipe (7) with a cross section large enough that the pressure P_i in the two steam spaces (6) of one stage S_i can always balance itself out during operation, and wherein the outlet (5) of each evaporator E_i is connected with the spray inlet (3) of the next evaporator E_{i+1} and the outlet (5) of the last evaporator E_n is connected with the spray inlet (3) of the first evaporator E_1 by a respective pressure-tight liquid line (8) to yield an evaporator circuit, and wherein the outlet (5) of each condenser C_i is connected with the spray inlet (3) of the preceding condenser C_{i-1} and the outlet (5) of the first condenser C_1 is connected with the spray inlet (3) of the last condenser C_n by a pressure-tight liquid line (9) to yield a condenser circuit, characterized in that at least one pressure-tight steam line (10) is connected at a first end with one of the pressure-tight liquid lines (9) between condensers C_{l+1} and C_i or with the pressure-tight

liquid line (8) between the evaporators E_n and E_1 , and at a second end with a steam space having a higher pressure P during operation than the pressure P_i in the steam space (6) of the condenser C_i or than the pressure P_1 in the steam space (6) of the evaporator E_1 , so as to pressurize the liquid (4) with a higher pressure and convey the liquid (4).

2. The distillation system according to claim 1, characterized in that the steam space with pressure P is a steam space (6) of the distillation system.
3. The distillation system according to claim 1 or 2, characterized by a respective pump (11) in the liquid line (8) of the evaporator circuit, as well as in the liquid line (9) of the condenser circuit, for achieving the prescribed pressures of the liquids (4) at the beginning of the process.
4. The distillation system according to one of the preceding claims, characterized by a heater (12) in the liquid line (8) of the evaporator circuit before the evaporator E_1 and a cooling aggregate (13) in the liquid line of the condenser circuit before the condenser C_n for achieving the prescribed temperatures in the evaporator E_1 and in the condenser C_n .
5. The distillation system according to claim 4, characterized in that the heater (12) and cooling aggregate (13) are together at least partially configured as a heat exchanger (14).
6. The distillation system according to one of the preceding claims, characterized in that siphons (15) are arranged in the liquid lines (9, 8) between the condensers C_n to C_1 and/or between the evaporators E_1

to E_n , so as to prevent individual condensers C_i and/or evaporators E_i from idling given a system shutdown.

7. The distillation system according to one of the preceding claims, characterized in that each condenser C_i has a gas line (17) connected with a vacuum pump (16) at the end of the distillation path to remove incondensable gases from the steam spaces (6).
8. The distillation system according to claim 7, characterized in that the vacuum pump (16) is connected with a pressure-tight steam line (10), which supplies the vacuum pump (16) during operation by feeding steam to the vacuum pump (16) having a higher pressure P than the steam spaces (6) in which gases are to be siphoned.
9. The distillation system according to one of the preceding claims, characterized in that each evaporator E_{i+1} is arranged on a lower level than the preceding evaporator E_i in such a way that the liquid (4) is made to flow from each evaporator E_i into the respectively ensuing evaporator E_{i+1} solely by pressure and level differences during implementation of the process, without an electrically operated pump being required for this purpose.
10. The distillation system according to one of the preceding claims, characterized in that each condenser C_{i+1} is arranged at such a level by comparison to its ensuing condenser C_i that the liquid is made to flow from the condenser C_{i+1} into the respective ensuing condenser C_i by pressure and level differences and/or the conveying force of a steam line during process

implementation, without an electrically operated pump being required for this purpose.

11. The distillation system according to one of the preceding claims, characterized in that the condensers C1 and Cn are leveled in such a way that the liquid (4) of the condenser C1 is made to flow from the condenser C1 to the condenser Cn via the liquid line (9) of the condenser circuit by pressure and level differences during process implementation, without an electrically operated pump being required for this purpose.
12. The distillation system according to one of the preceding claims, characterized in that the evaporators En and E1 are preferably also leveled in such a way that the liquid (4) of the evaporator En is made to flow from the evaporator En to the evaporator E1 by pressure and level differences and by the conveying force of one or more steam lines (10) via the liquid line (8) of the evaporator circuit during process implementation, without an electrically operated pump being required for this purpose.
13. The distillation system according to one of the preceding claims, characterized in that at least one of the liquid lines (8, 9) and/or at least one of the steam lines (10) is arranged inside of a container (2) and/or inside of a steam pipe (6).
14. The distillation system according to one of the preceding claims, comprising a feed (18) in the evaporator circuit for supplying liquid 4 to be distilled, along with an outlet (19) from the evaporator circuit for letting out liquid (4) with a high concentration of residues, as well as a

distillate outlet (20) from the condenser circuit for letting out the distillate (21) generated by the system.

15. The distillation system according to one of the preceding claims, characterized in that each steam line (10) and/or each gas line (17) encompasses a valve (22) for regulating the flow rate.
16. The distillation system according to one of the preceding claims, characterized in that at least the containers (2) of the first condenser C1 and the last evaporator En each encompass a level sensor (23) for determining the level of liquid (4b) captured in the containers (2).
17. The distillation system according to one of the preceding claims, characterized in that a sensor (24) is arranged in the evaporation circuit, preferably in the area of the last evaporator En, for measuring the concentration of residues.
18. A method for implementing a distillation process using a distillation system (1) according to one of the preceding claims, comprising a feed (18) in the evaporator circuit for supplying liquid (4) to be distilled, along with an outlet (19) from the evaporator circuit for letting out liquid with a high concentration of residues, as well as a distillate outlet (20) from the condenser circuit for letting out the distillate (21) generated by the system, characterized by the following procedural steps:
 - a. Monitoring the liquid level in the evaporator circuit and in the condenser circuit;

- b. Monitoring the concentration of residues in the evaporator circuit;
 - c. Letting out liquid with a high concentration of residues at the outlet (19) as soon as the liquid level in the evaporator circuit has reached a prescribed maximum level and/or the concentration of residues in the evaporator circuit has reached a prescribed maximum value;
 - d. Letting out distillate from the condenser circuit at the distillate outlet (20) as soon as the liquid level in the condenser circuit has reached a prescribed maximum level;
 - e. Letting liquid (4) into the condenser circuit at the feed (18) as soon as the liquid level in the evaporator circuit has reached a prescribed minimum value and/or the concentration of residues in the evaporator circuit has reached a prescribed maximum value.
 - f. Repeating steps a. to e. until the process is to be stopped.
19. The method according to claim 18, characterized in that each condenser C_i has a gas line (17) connected with a vacuum pump (16) at the end of the distillation path, characterized by the following procedural steps:
- a. Determining the temperature differences dT_i in the steam spaces (6) of the containers (2) of evaporators E_i and condensers C_i of the same stage S_i ;

- b. Removing incondensable gases in the steam space (6) of the condenser Ci through the gas line (17) using the vacuum pump (16) as soon as the temperature difference dT_i has reached a prescribed maximum value, until dT_i has reached a prescribed minimum value;
 - c. Repeating steps a. and b. until the process is to be stopped.
20. A controller for implementing a method according to claim 18 or 19, comprising ports for sensors to read in measuring data, a processor for evaluating the measuring data, as well as ports for changing the settings of valves (22) and pumps (11, 16).