

DISPERSION METHOD AND DISPERSING APPARATUS**Abstract of the Disclosure:**

For dispersion of a material to be treated by using a dispersing medium, a dispersion method and a dispersing apparatus is provided, by which the dispersing medium can readily be charged, and discharge of the dispersing medium from a dispersing apparatus, and its cleaning is simplified.

In a dispersing chamber (7) in which dispersion treatment is carried out, a disc is disposed to generate a sucking action by rotation of the disc. The dispersing chamber (7) has a sucking inlet (6) and a discharge outlet (14), and at the inner side of the discharge outlet (14), a filter (15) for separating the dispersing medium is detachably disposed. Each of the discharge outlet (14) and the sucking inlet (6) of the dispersing chamber is communicated with a tank (1) by means of a pipeline (29) or (3). The liquid containing a material to be treated and dispersing medium, stored in the tank (1) enter into the dispersing chamber by the sucking action generated by rotation of the disc. The material is dispersed in the liquid and discharged, but the dispersing medium is interrupted by a filter and remains within the dispersing chamber. After completion of the dispersion treatment, when the filter is taken away and then the disc is rotated, the dispersing medium is discharged from the dispersing chamber together with a cleaning liquid, and circulated through the tank and the like, to thereby clean the entire body.

Figure 1