



G00002

30 31 70 31 2 7528

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/24	A1	(11) International Publication Number: WO 99/46944 (43) International Publication Date: 16 September 1999 (16.09.99)
(21) International Application Number: PCT/NL99/00133 (22) International Filing Date: 10 March 1999 (10.03.99) (30) Priority Data: 1008563 11 March 1998 (11.03.98) NL (71) Applicant (for all designated States except US): CONCORD HOLDING B.V. [NL/NL]; Ereprijs 23, NL-6721 ZA Bennekom (NL). (72) Inventor; and (75) Inventor/Applicant (for US only): VERKUIJSSEN, Bartel, Johannes [NL/NL]; Ereprijs 23, NL-6721 Bennekom (NL). (74) Agent: DE BRUIJN, Leendert, C., Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>  *162162*

(54) Title: COMMUNICATION SYSTEM**(57) Abstract**

Communication system comprising one or more exchanges and a number of terminals (telephone sets, facsimile apparatuses, etc.) which each through one of the mentioned exchanges is able to communicate with at least one of the other terminals whereby a) the user of a calling terminal calls the number of its own exchange, transmits signals indicating that the terminal has to be called back by the exchange after which the connection is cut off, b) thereafter the exchange establishes a connection with the calling terminal, c) the user of the terminal transmits the number of a desired other terminal to the exchange, d) the exchange thereafter establishes the connection with the desired terminal, whereby at least the calling terminals can be connected partly through wireless communication paths with their own exchange and to comprise a buffer in which the number of the desired other terminal can be stored, and comprise a circuit which, after said number is keyed in by the user and is stored in the said buffer, performs the above-mentioned steps a) instead of the user, waits until the exchange reports again, retrieves the number from said buffer and transmits this number instead of the user to the exchange which will perform thereafter step d).

