

WIRELESS ENABLED BAGS AND CONTAINERS

This application is a divisional application of Singapore Patent Application No 200904296-1 "WIRELESS ENABLED BAGS AND CONTAINERS" filed on 23.06.2009.

5

Field of the Invention

The present invention relates to a process and device for incorporating wireless enabled devices permanently into disposable bags and containers. More particularly, it relates to the incorporation of a wireless device, such as a RFID tag, into the structure of the bag or container or a component of the bag or container that is permanently attached to the bag or container.

10

Background of the Invention

The use of identification and preferably active or interactive identification devices is becoming a popular item for several businesses. These range from simply bar codes to three dimensional bar codes to more recently wireless devices such as read only or read-write RFID chips (active or interactive systems).

15

In many products, the wireless device is simply attached to the carton in which it is shipped and is useful only during storage and transport.

20

More recently, the wireless devices have begun to be attached to the product itself so that it can be enquired any time during its life.

25

On plastic parts such as tubing and filters, various methods have been suggested for attaching such a tag. These include molding the tag onto a collar on the tubing or to mold the tag as part of the tubing or filter housing. In other applications, the use of an adhesive patch or pouch to bond the tag to the product has been suggested. The use of a spiral wrap of tape to contain the tag has also been suggested. Lastly, the use of straps or "dog tags" containing the tag that are then attached to the device has been suggested.

30

Many of these approaches such as molding as part of the formation of the plastic material will not work for plastic films used to make bags and containers. The film manufacturing process is difficult and the placement of the tag in the film as it is being made is near impossible. Additionally as films are used to make different sized bags, the placement of the tags would have to be far enough apart to accomplish this while providing a tag for each container. This leads to waste of plastic or of the tags themselves in making the different sized bags.

Other means such as the pouch, strap or dog tags all occur as a separate step and there is the risk that they may be forgotten. Additionally, they are an additional processing step and require the use for an additional element (pouch or patch, strap or dog tag).

What is needed is a process for incorporating the tag as part of the manufacture process of the container and a device having such a tag feature.

Summary of Invention

The present invention provides a process for incorporating a wireless device into a plastic container (be it a bag or rigid plastic container) as part of the steps of manufacturing the container.

Most plastic containers are bags and are formed of one or more sheets, generally two or more sheets of plastic film. The bags are formed by sealing together adjacent edge portions of each film layer(s). One embodiment of the present invention is to incorporate a wireless device between the edge portions of the film(s) before sealing so that the device becomes permanently sealed into the film but is isolated from both the bag interior and the outside environment.

The wireless device may be adhered to a film surface if desired.

Another embodiment is to incorporate the wireless device into a plastic component that is sealed to the container, such as a nipple or port, so that the device becomes permanently sealed onto or into the plastic component's material but is isolated from both the bag interior and the outside environment.

5 The wireless device may be adhered to a surface of the plastic component, overmolded onto the plastic component or molded into the component during its manufacture.

10 In either embodiment, the wireless device is incorporated as a standard step of manufacturing and no additional step in making the bag is required in order to incorporate the device into the bag.

15 Optionally, the wireless device is formed of materials that allow it to be gamma compatible, thereby allowing the assembled container to be gamma irradiated for sterility.

The wireless device can be either a read only device, telling the user only that information which has been loaded on to it by the manufacturer , or preferably it is a read/write device allowing the user to add additional trackable events such
20 as date of use, contents added to the container, etc.

In one preferred embodiment the wireless device is always placed in the same relative location from container to container for ease of use by the user. For example by having the wireless device in the same spot, one could attach a
25 reader in a location such as on ancillary equipment or container holders that allows for the automatic interrogation of the device each time a new container is used.

It is an object of the present invention to provide a process for incorporating a
30 wireless device permanently into a disposable container comprising the steps of selecting a wireless device having a memory, an antenna and a communications component, the wireless device being formed as a single entity,

providing plastic components for making a container and incorporating the wireless device into the components such that the wireless device is permanently sealed into the container as it is formed.

5 It is an object of the present invention to provide a process for incorporating a wireless device permanently into a disposable container comprising the steps of selecting a wireless device having a memory, an antenna and a communications component, the wireless device being formed as a single entity, providing plastic components for making a container wherein the plastic
10 components are at least two films of plastic having corresponding and matable edges that are capable of being fluid tightly sealed to each other and the wireless device is placed between the matable edges and retained there before or during the sealing of the matable edges to each other such that the wireless device is permanently sealed into the container as it is formed.

15

It is an object of the present invention to provide a process for incorporating a wireless device permanently into a disposable container comprising the steps of selecting a wireless device having a memory, an antenna and a communications component, the wireless device being formed as a single entity,
20 providing a plastic component to be mated and sealed to the container, incorporating the wireless device into the plastic component, attaching and sealing the plastic component containing the wireless device to the container in a desired location such that the wireless device is permanently sealed to the container.

25

It is a further object to provide one or more holes or openings in the substrate which contains the wireless device so that it is secured or anchored to the component such as a seam or port by the molten plastic of the component flowing through that opening.

30

It is an object to provide a wireless device on a substrate at least a portion of which is made of a like material as the component to which the wireless device

is to be attached. In one embodiment at least a portion of the substrate is formed of a polyolefin as is the component (such as the bag film or port attachment) so as to bond the wireless device to the component by like material welding.

5

It is another object to provide a temperature sensor and/or pressure sensor in the wireless device so that one can determine the characteristics of the seam cycle to verify that a proper seal with the wireless device inside occurs.

10

Brief Description of Drawings

Figure 1 is a planar view of a bag according to the first embodiment of the invention.

15 Figure 2 is a cross sectional view of the embodiment of Figure 1.

Figure 3 shows a typical wireless device useful in the present invention in planar view.

20 Figure 4 is a planar view of a bag according to the second embodiment of the invention.

Figure 5 is a cross sectional view of the embodiment of Figure 4.

25 Figure 6 is close-up planar view of a corner of a container according to one embodiment of the present invention.

Figure 7 is a flow diagram illustrating a first preferred embodiment of the process of this invention.

30

Figures 8A and 8B are flow diagrams illustrating additional preferred embodiments of the process of this invention.

Figure 9 shows an alternative embodiment of the present device in planar view.

Figure 10 shows the device of Figure 9 in partial cutaway view as it is being
5 sealed into a seam of the bag.

Figure 11 shows a further embodiment of the present invention in planar view.

Description of Specific Embodiments

10 Figure 1 shows a disposable container 2, in this embodiment a plastic flexible container or bag, formed of one or pieces of film 4 having open, adjacent edges 6 which are fluid tightly sealed together to form a closed container 2. In the embodiment shown, two pieces of film 4 are used and are in the form of sheets of similar sizes. The two sheets of film 4 are placed adjacent each other,
15 preferably directly touching each other at least along the respective edges 6 to be sealed.

A wireless device 8 is placed between the edges to be sealed and then the edges are fluid tightly sealed together trapping the wireless device between
20 them. The device 8 may contain information such as date of manufacture, container manufacturer, container type, catalog number, serial number etc. This may either be loaded onto the device 8 before it is inserted between the edges 6 to be sealed or after it is sealed in place. If desired the device may have an adhesive or adhesive pad attached to at least one surface for temporarily
25 securing the device to the film during the sealing of the film. In this way, the device is not lost or moved during assembly.

Figure 2 shows a cross-sectional view of the embodiment of Figure 1. As can be seen the device 8 is contained between the two edges 6 of the film 4 so that
30 the device 8 is permanently sealed into the container 2 but is isolated from both the container interior and the outside environment. This allows the device to be used and yet not be in contact with the contents of the container in case there

may be adverse effect to either the contents or the wireless device by such contact. Additionally, the device is permanently affixed to the container and remains with it throughout its life so that data is never lost or compromised. Likewise by isolating it from the outside environment it is protected from dust,
5 liquids and other effects that might otherwise compromise its integrity.

The wireless device essentially comprises two components as shown in Figure 3, a microchip or other memory type of device 100 and an antenna 102. These are generally attached to a plastic surface or sheet 104 or encapsulated with an
10 epoxy (not shown). The antenna can be a cut or punched metal array, a screen printed design or any other type of antenna common to these devices. The device can be of any frequency although high frequency (HF) and ultrahigh frequency (UHF) are the most popular. Additional elements may be added if desired such as a battery or capacitor to provide the device with its own power
15 source (not shown). Most systems however are passive and rely on the signal from the reader/writer to power up the device as needed. Such passive circuits have been constructed from thermally stable materials such as Tagsys SDM RFID tags or Datalogic RFID tags made with polyimide support film (see WO1999019851 A1). These tags are designed and have been shown to survive
20 thermal molding processes compatible with thermal container assembly techniques.

In many applications, the containers are sterilized and remain sterile at least until use. These containers are often irradiated with beta or gamma radiation to
25 render them sterile. Unfortunately for the large majority of wireless devices the memory and other components are not radiation compatible as they use a stored charge to represent the value of each binary bit of data. Such devices are highly susceptible to corruption caused by the radiation. Often the charge is depleted or enhanced by the radiation, thereby affecting its value and the data
30 that may be contained within it. Such devices include but not limited to Flash memory such as EEPROM, DRAM and SRAM.

There are other memory technologies that use mechanisms other than charge storage to retain data and values of a bit. For example, FRAM or ferro-magnetic RAMs, utilize molecules having a bi-stable structure to store state, wherein the one of the stable molecular configurations represents a high or '1' and the other represents a low or '0'. Several common molecules in a FRAM are PZT (lead-zirconate- titanate), SBT (Strontium-bismuth-tantalate) and BLT (lanthanum-substituted bismuth-tantalate). Each possesses a central atom in a cubic unit cell having a dipole moment. The molecules switch between these two stable states based on the application of an electric field to the molecule. Since these cells rely on electrical fields, rather than storage charge, memories utilizing this mechanism are far less susceptible to gamma and other types of radiation than traditional semiconductor memory structures and are described in US 3,728,694.

Another example of a memory device that does not utilize charge as the storage mechanism is MRAM, also known as magnetoresistive or simply magnetic RAM. These devices use ferromagnetic materials often in the form of Hall sensors to store the state of the bit. See US 6,140,139. Since the magnetic fields are utilized instead of the capacitive charge these devices are also less susceptible to radiation especially gamma radiation.

Any other device that uses a system that is not susceptible to radiation may also be used in such embodiments.

The wireless device(s) 8 can be any such device such as a RFID tag, a Zigbee® device, a Bluetooth® device and the like as is known to the art.

By "fluid tightly", it means the container seals are liquid tightly sealed and are sealed to an extent that air or gas is not detected as leaking through the film seal area. Of course depending upon the film material selected some gas may eventually transfer interstitially either from inside the container to the environment or from the environment into the container and the term is meant to allow for that happen if the film selected is not highly gas impervious. The use of

gas impervious plastics such as EVOH can reduce or eliminate this transport of gas across the container wall and it is meant by the term to cover that aspect as well.

5 Figure 4 shows a second embodiment of the present invention. Such containers (be they bags or rigid containers) need one or more plastic components 10 such as ports, tubing nipples, hanging eyelets, alignment plates and the like molded or sealed to them to allow for other functions such as the entry and exit of various components such as product to be stored, worked on, etc, processing
10 liquids such as water, cell culture media if a bioreactor bag, gases such as oxygen, carbon dioxide, nitrogen, etc and the like or to provide means for hanging or aligning the container in a desired arrangement. These plastic components such as the ports 10 (as shown) are generally formed of a flange portion 12 that is sealed to the container 2. In the case of a port 10 the flange
15 portion 12 is around an opening 18 (Figure 5) in the container wall. In this embodiment, a stem 14 extends away from the flange portion of the port 10 and as shown is attached to a tube 16 or other such element. Other elements can include but are not limited to filters, sterile connectors and the like. Alternatively, the plastic component may be a grommet or rivet-like structure having two
20 essentially similar pieces that are sealed together or it may only have one plastic portion that attaches to the surface.

A wireless device 8 is attached to a portion of the plastic component 10. As shown in Figures 4 and 5 the device 8 is attached to the flange portion 12 of the
25 plastic component 10. This may be by being molded into the flange portion or by heat sealing it to a portion of the port or by adhering it to the desired portion of the port as desired. Preferably, it is molded into a portion of the port itself so as to isolate it from the contents of the container and protect it from the environment and accidental damage during storage, shipping or use.
30 Alternatively, it may be located on a portion of the port where it is isolated from the container contents simply by its location. Such positions include but are not limited to the interface between the flange 12 and the inner surface of the

container 2 to which the flange 12 is attached and the outer surface of the stem 14 (preferably in the area covered by the tube 16 to further isolate and protect it from the environment.

5 It is desirable in some applications to have the wireless device mounted in the same relative location from container to container so that a user does not need to search for the device. Additionally, this is particularly useful in applications where the scanner is mounted on an ancillary piece of equipment. In one embodiment, it is mounted to the inlet port of the container. In another, it is
10 located at the left, right or center of the uppermost seam. Some containers use eyelets 20 and other devices to hold them upright or to align them during installation or use (Figure 6). Such structures are another good location for the wireless devices 8 as they also can help orient the container to the user ensuring it always goes in the correct way and in the proper alignment. In a
15 further embodiment, the wireless device may be highly colored or the plastic component to which it is attached is highly colored (not shown) so that it is easily found. Other similar locations may also be used.

The disposable container of this invention is formed of a polymeric composition
20 such as polyethylene, including ultrahigh molecular weight polyethylene, linear low density polyethylene, low density or medium density polyethylene; polypropylene; ethylene vinyl acetate (EVOH); polyvinyl chloride (PVC); polyvinyl acetate (PVA); ethylene vinyl acetate copolymers (EVA copolymers); blends of various thermoplastics; coextrusions of different thermoplastics;
25 multilayered laminates of different thermoplastics; or the like (by different it is meant to include different polymer types such as polyethylene layers with one or more layers of EVOH as well as the same polymer type but of different characteristics such as molecule weight, linear or branched polymer or fillers and the like). Typically medical grade and preferably animal-free plastics are
30 used. The container maybe a flexible plastic container such as a bag or a rigid plastic container such as a bin, box, tote, barrel and the like. They may be sterilized such as by steam, ethylene oxide or radiation, such as beta or gamma

radiation. Most have good tensile strength, low gas transfer and are either transparent or at least translucent.

In use, the wireless devices 8 are read by a scanner (not shown) which may be a fixed station such as a desktop reader like the AccuSmart™ reader available from Millipore Corporation of Billerica, Massachusetts or a scanner mounted to either a holder for the container, such as bin or tote, if used, or an ancillary piece of equipment such as a pump or the like (not shown), or a hand held device such as the Hose Tracker™ reader available from Advantapure of South Hamilton, Pennsylvania.

The wireless device may be a read only device so that it contains only information loaded by the manufacturer at its facility. In use, the wireless device 8 arrives at a user's facility with manufacturer name, container type or use restrictions and sterilization data, etc. already loaded on to it or contained on a secure website of the manufacturer which can be accessed by providing the website with the identification number contained on the wireless device. Also with read only wireless devices one can use a computer, local or wide area network or internet site to track what happens to the container in the hands of the user by listing one or more trackable events (type of use, date of use, contents, etc) on the computer, network or internet site using the identity code assigned to the wireless device.

Preferably, the device 8 is a read/write device capable of adding additional information by the user. This information may be an identity (unique user code or specific user use) or location of the bag or optionally, at least one trackable event such as its date of installation, installer, contents, etc. This information may be entered by the scanner and also read by the scanner. The information may be stored on the wireless device itself and it may be downloaded to a computer or network connection or the internet if desired.

The device 8 may be a passive device being active only when being scanned or interrogated by the reader. Alternatively, it may be an active device and either contain a battery for power or be coupled such as by a magnetic inductive system to a power source.

5

For storage applications, the device 8 or the computer network or internet site may contain specific storage instructions such as temperature to be maintained at, length for storage and the like.

- 10 To make a product containing a wireless device as claimed in this invention, for a plastic bag, one takes one or more pieces of plastic film, preferably two or more pieces, as shown as step 30 in Figure 7, places the wireless device on a portion of the film(s) to be sealed as in step 32 and seals the desired edges of the film(s) together such as by heat sealing or glue or adhesives, or sonic
15 vibration, as in step 34.

In incorporating the wireless device to a plastic component 10, such as a port one follows the procedure of Figure 8A or Figure 8B.

- 20 In Figure 8A the wireless device is incorporated into the plastic component in step 40. This may be done such as by molding the device 8 into the component as it is made. In step 42 the component containing the wireless device 8 is then sealed to the container 2.

- 25 In Figure 8B, the component is made and then the wireless device is associated with it. This can be done by overmolding the device to the component or by adhering it to the component. Alternatively, the device can be placed on the container surface and covered by the component as it is sealed to the container.

- 30 In Figure 9 is shown an alternative embodiment of the present invention. The wireless device 200 is a microchip or other memory type of device 202 and an antenna 204. These are generally attached to a plastic surface or sheet 206

such as polyimide, polyester, a polyolefin such as polyethylene or polypropylene or encapsulated with an epoxy (not shown). As discussed above, the antenna 204 can be a cut or punched metal array, a screen printed design or any other type of antenna common to these devices. The device can be of
5 any frequency although high frequency (HF) and ultrahigh frequency (UHF) are the most popular. Additional elements may be added if desired such as a battery or capacitor to provide the device with its own power source (not shown). Most systems however are passive and rely on the signal from the reader/writer to power up the device as needed. Such passive circuits have been constructed
10 from thermally stable materials such as Tagsys SDM RFID tags or Datalogic RFID tags made with polyimide support film (see WO1999019851 A1). These tags are designed and have been shown to survive thermal molding processes compatible with thermal container assembly techniques.

15 The substrate 206 can have one or more through holes, cutouts or the like formed in non-critical areas such areas inside or outside the antenna design. When the wireless device 200 is either placed into a seam or molded into a component such as a port flange, the molten plastic not only flows around the device 200 but also through the holes 208 to anchor or secure the device 200 in
20 place. The hole(s) 208 can be formed by punching out material, pre-forming the tag substrate 206 with the holes 208 in it such as by molding, or by drilling and the like. The method by which they are made is not important so long as they provide a way for the molten plastic to flow through the hole(s) 208 and secure the device 200 in place while not interfering with the function or design of the
25 device 200 or its components such as the antenna 204. The number of holes 208 and their arrangement is determined by the design of the wireless device 200 and the level of mechanical advantage desired by the user. Typically the holes 208 are from 1 to 5 per device. While shown as being arranged in a row in the Figures they can be randomly arranged or arranged in other desired
30 patterns such as near each corner of the substrate 206, and the like.

Figure 10 shows the device of Figure 9 as it is formed in a seam 300 of bag 302 formed of at least two layers of film 304 and 306. As shown, the molten plastic of the films 304 and 306 fill in the holes 208 of the device 200 to secure it in place.

5

In a further embodiment, at least a portion of the substrate of the wireless device is formed of a material that is compatible with the material into which it is to be bonded so that one can achieve a like-material attachment. For example, the substrate can be chosen from thermoplastics that are the same as the bag
10 sheet material. Such an example is polyethylene which is sufficiently durable to withstand the rigors of circuit fabrication. During the process of seaming, the circuit can be placed within the outer and inner edge and welded to the sheet material at such conditions to form like material welding.

15 In a further embodiment of the present invention a wireless device 400 may include the above described circuit or memory 402 as well as other sensors such as a temperature sensor 410 that may be used to determine the characteristics of the thermal seam cycle and verify that it meets the process requirements. In addition, a pressure sensor 412, such as a piezo electric
20 pressure transducer, on the exposed surface of the circuit of the device 400 may be used to measure the compression pressure during the seaming cycle and verify that it meets the process requirements. The temperature sensor may also be used with the component molding operation to ensure that a proper temperature has been achieved during the bonding operation of the component
25 to the film.

A system according to any of the embodiments allows one to electronically collect and/or store one or more trackable events such as data relating to the container, its installation, use and if done, testing results.

30

The wireless device enabled system of the present invention eliminates any error as to location, date, time, user and the like and allows one to use good

manufacturing practices(GMP) and good laboratory practices(GLP) in sampling systems.

5

Example 1

A wireless device, in this example a RFID tag formed of read/write chip and an antenna, available from Tagsys S.A. of France as catalog item Ario™ SM-ISO RFID tag was selected for this example. The wireless device had dimensions of
10 14 mm wide by 14 mm long and 2 mm high.

Two sheets of a polyethylene based plastic film (Pureflex™ film available from Millipore Corporation) were selected.

15 The wireless device was tested before insertion between the sheets by reading the device with a handheld reader available from Tagsys.

The device was centered between the two sheets and the edges of the sheets around the device were heated sealed using a hot iron at 180° C with hand
20 pressure to simulate a seam in a biobag.

The sheets were allowed to cool and the wireless device was then tested and found to be capable of both reading and writing information.

Example 2

25 A wireless device, in this example a RFID tag formed of read/write chip and an antenna, available from Tagsys S.A. of France as catalog item Ario™ SM-ISO RFID tag was selected for this example. The wireless device had dimensions of
30 14 mm wide by 14 mm long and 2 mm high.

The wireless device was tested before insertion into the housing by reading the device with a handheld reader available from Tagsys.

A circular piece of polypropylene was injection molded to encapsulate the wireless device within the polypropylene. An outer surface of the piece was placed against a polyethylene based film (Pureflex™ film from Millipore Corporation) and bonded to the outer surface of the film by heating the film and circular piece with standard vibration thermal welder at about 200° C for a period of approximately 1 minute while applying pressure between the two. The vibration was then stopped, the film and piece allowed to cool and the wireless device was then tested and found to be capable of both reading and writing information.

Claims

1. A process for incorporating a wireless device (200;300;400) permanently into a disposable container (2) comprising the steps of
 - a. providing plastic components (4) for making a container (2),
 - 5 b. selecting a wireless device (200;300;400) having a memory (202;402), an antenna (204;404) and a communications component, the wireless device (200;300;400) being formed as a single entity on a substrate (206;406) and the substrate (206;406) is elected from the group consisting of a substrate having one or
10 more holes (208;408) formed through it and a substrate made of like materials to the plastic components (4) for the container (2), and
 - c. incorporating the wireless device (200;300;400) into the components (4) such that the wireless device (200;300;400) is
15 permanently sealed into the container (2) as it is formed.
2. The process of claim 1 wherein the wireless device (200;300;400) is sealed into a seam formed in the container (2).
- 20 3. The process of claim 1 or 2 wherein the plastic components are at least two films (4) of plastic having corresponding and matable edges (6) that are capable of being fluid tightly sealed to each other and the wireless device (200;300;400) is placed between the matable edges (6) and retained there before or during the sealing of the matable edges (6) to
25 each other.
4. The process of any one of claims 1 to 3 wherein the wireless device (200;300;400) is incorporated into a plastic component that is sealed to the container and the plastic component is selected from the group
30 consisting of ports, eyelets and alignment plates.

5. A process for incorporating a wireless device (200;300;400) permanently into a disposable container (2) comprising the steps of
- a. providing a plastic component to be mated and sealed to the container (2),
 - 5 b. selecting a wireless device (200;300;400) having a memory (202;402), an antenna (204;404) and a communications component, the wireless device (200;300;400) being formed as a single entity on a substrate (206;406) and the substrate (206;406) is elected from the group consisting of a substrate having one or
10 more holes (208;408) formed through it and a substrate made of like materials to the plastic components for the container (2),
 - c. incorporating the wireless device (200;300;400) into the plastic component,
 - 15 d. attaching and sealing the plastic component containing the wireless device (200;300;400) to the container (2) in a desired location such that the wireless device (200;300;400) is permanently sealed to the container.
6. The process of claim 4 or 5 wherein the plastic component is selected
20 from the group consisting of ports, eyelets and alignment plates.
7. The process of claim 6 wherein the plastic component is a port having a flange portion surrounding an opening in the container and the wireless device is attached to the flange portion of the port.
- 25 8. The process of claim 6 wherein the plastic component is an alignment plate and the wireless device is molded to the alignment plate.
9. The process of claim 6 wherein the plastic component is an eyelet and
30 the wireless device is attached to the eyelet or is molded to the eyelet or is molded into the eyelet.

10. The process of any one of claims 1 to 9 wherein the wireless device (200;300;400) is a read only device and has data selected from the group consisting of manufacturer, lot number, manufacturing date, sterilization data and combinations thereof.

5

11. The process of any one of claims 1 to 10 wherein the wireless device (200;300;400) is a read/write device capable of having data written to it.

10

12. The process of claim 11 wherein one or more trackable events are loaded onto the wireless device.

13. The process of any one of claims 1 to 12 further comprising a second wireless memory/communication device attached to a holder for the container (2).

15

14. The process of any one of claims 1 to 13 wherein the wireless device (200;300;400) contains one or more sensors selected from the group consisting of pressure and temperature sensors and the one or more sensors are used to verify the sealing process conditions