



(51) International Patent Classification:

H02M 1/14 (2006.01) *H02M* 7/10 (2006.01)
H02M 3/07 (2006.01)

(21) International Application Number:

PCT/US2010/043582

(22) International Filing Date:

28 July 2010 (28.07.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/229,217 28 July 2009 (28.07.2009) US
12/845,631 28 July 2010 (28.07.2010) US

(71) Applicant (for all designated States except US): **THX LTD.** [US/US]; 1600 Los Gatos Drive, Suite 130, San Rafael, CA 94903 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JONES, Owen** [GB/GB]; 1600 Los Gatos Drive, Suite 130, San Rafael, CA 94903 (US). **FINCHAM, Lawrence, R.** [GB/US]; 1600 Los Gatos Drive, Suite 130, San Rafael, CA 94903 (US).(74) Agent: **VANDERLAAN, Christopher, A.**; Irell & Manella LLP, 1800 Avenue of the Stars, Los Angeles, CA 90067 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: POWER SUPPLY




FIG. 1

(57) Abstract: A power supply includes two or more input waveforms being shaped or selected so that after being separately level-shifted and rectified, their additive combination results in a DC output waveform with substantially no ripple. The power supply may comprise a waveform generator, a level conversion stage for step up or down conversion, a rectification stage, and a combiner. The waveform generator may generate complementary waveforms, preferably identical but phase offset from each other, such that after the complementary waveforms are level-converted, rectified and additively combined their sum will be constant, thus requiring no or minimal smoothing for generation of a DC output waveform. The level conversion may be carried out using transformers or switched capacitor circuits. Feedback from the DC output waveform may be used to adjust the characteristics of the input waveforms.