



166166

19 JUN 2002



SHIELDED CABLE AND METHOD OF MAKING SAME

G00002

Field of the Invention

The invention relates to a shielded cable and more particularly, to a non-braided drop cable for the transmission of RF signals.

5

Background of the Invention

In the transmission of RF signals such as cable television signals, a drop cable is generally used as the final link in bringing the signals from a trunk and distribution cable directly into a subscriber's home. Conventional drop cables include an insulated center conductor that carries the signal and a conductive shield surrounding the center conductor to prevent signal leakage and interference from outside signals. In addition, the drop cable generally includes a protective outer jacket to prevent moisture from entering the cable. One common construction for drop cable includes an insulated center conductor, a laminated tape formed of metal and polymer layers surrounding the center conductor, a layer of braided metallic wires, and an outer protective jacket.

One problem with conventional braided drop cable is that it is difficult to attach to standard connectors. In particular, the braided shield is difficult to cut and attach to a standard connector and normally must be folded back over the cable jacket during connectorization of the cable. As a result, the metal braid increases installation time and costs. Furthermore, forming the metal braid is generally a time intensive process and limits the rate at which the cable can be produced. Therefore, there have been attempts in the industry to eliminate the braid from conventional drop cable.

For example, U.S Patent Nos. 5,321,202; 5,414,213; and 5,521,331 to Hillburn teach replacing the outer braided shield of the conventional construction with a metallic foil shield or laminated metallic tape shield and adding a plastic layer between this shield and the inner shielding tape. Although this construction eliminates metal braids, it creates other connectorization problems. Specifically, when connectors are attached to these cables, a special coring or trimming tool is required to prepare the cable for the connector to be attached to the cable. This requires additional time during the connectorization of these cables. Furthermore, the connector pull-off force of the braidless cable, i.e., the force needed to pull the connector off of the cable, is undesirably reduced as compared to braided cables.

German applications DE 3931741A and DE 3141636A describe alternative cable constructions. In particular, DE 3931741A describes a cable that includes an inner conductive core, insulation surrounding the inner conductive core, and an outer conductor surrounding the insulation. The outer conductor comprises two unilaterally metallized films with conductive wires arranged therebetween. DE 3141636A describes a cable that includes a copper conductor, a plastic covering surrounding the copper conductor, a copper mesh surrounding the plastic as an inner shield, side-by-side arranged wires that surround the inner shield, a metal foil that surrounds the wires, and a second copper mesh surrounding the metal foil as an outer shield.

Summary of the Invention

The present invention provides a non-braided drop cable that can be easily attached to a connector

and that can properly anchor a connector to prevent connector pull-off once the cable is connectorized. Furthermore, the present invention provides a drop cable with sufficient shielding to prevent signal
5 leakage and interference from extraneous signals.

These features are provided by a non-braided shielded cable that includes a cable core comprising a center conductor and a dielectric layer surrounding the center conductor, a first electrically conductive
10 shield surrounding the cable core and bonded thereto, a second electrically conductive shield surrounding the first shield, and a cable jacket surrounding the second shield and bonded thereto. According to the invention, an interstitial layer is located between the first and
15 second shields and is composed of elongate strands disposed between said first and second shields so as to be freely displaceable axially while also serving to space the first and second shields apart from one another.

In a preferred embodiment of the invention, the first and second shields used in the cable are bonded metal-polymer-metal laminate tapes extending longitudinally of the cable and having overlapping longitudinal edges to produce 100% shielding coverage
20 of the center conductor. Preferably, the first shielding tape is an aluminum-polyolefin-aluminum laminate tape and the second shielding tape is an aluminum-polyester-aluminum laminate tape. The strands of the interstitial layer are typically helically wound
25 around the first shielding tape and are formed of metal wires and/or textile yarns. Preferably, these strands are metal wires covering less than 30 percent of the surface of the underlying first shielding tape. The metal wires can be provided as more than one layer
30 having different orientations such as two layers have opposite helical orientations (e.g., counterclockwise
35

and clockwise). The yarns for the interstitial layer typically cover less than 50 percent of the surface of the first shielding tape and are selected from the group consisting of polyester, cotton and aramid yarns and blends thereof. The interstitial layer can include both yarns and metal wires disposed alongside the yarns, and can also include a water blocking material.

The present invention also provides a method of making a shielded cable. In the manufacture of these cables, a cable core comprising a center conductor and a dielectric layer surrounding the center conductor is advanced and a first electrically conductive shielding tape is longitudinally wrapped or "cigarette-wrapped" around the cable core. The interstitial layer is applied to the first shielding cable typically by helically wrapping the strands around the first shielding tape. A second shielding tape is then longitudinally wrapped over the interstitial layer and a cable jacket extruded over the second shielding tape to produce the cable. Preferably, the method further comprises bonding the first shielding tape to the cable core and bonding the second shielding tape to the jacket. The shielding tapes are preferably bonded metal-polymer-metal laminate tapes having longitudinal edges that are positioned in an overlapping relationship. These laminate tapes also preferably include an adhesive on one surface thereof, with the first shielding tape including an adhesive on the inwardly facing surface adjacent the cable core and the second shielding tape including an adhesive on the outwardly facing surface over which the outer jacket is extruded to provide the desired bonds in the shielded cable.

The shielded cables of the invention are easy to attach to standard connectors. Specifically, because the shielded cable is not braided, the problems

19 JUN 2002

associated with braids are not experienced during connectorization of the shielded cable of the invention. In addition, the interstitial layer in the cable of the invention is composed of strands that are axially displaceable and thus do not require trimming prior to connectorization. Furthermore, these axially displaceable strands assist in anchoring the connector to the cable, thus increasing the pull-off resistance of the cable.

10

Brief Description of the Drawings

Other features and advantages of the present invention will become apparent from the following detailed description of the invention taken in conjunction with the drawings, in which:

15

Figure 1 is a perspective view of a shielded cable according to the invention having portions thereof partially removed for purposes of illustration;

20

Figure 2 is a partial cross-sectional view of the shielded cable of Figure 1 taken along line 2-2;

Figure 3 is a schematic illustration of a method of making a shielded cable according to the invention;

25

Figure 4 is a perspective view of a shielded cable according to the invention attached to a standard one-piece connector and with portions broken away for purposes of illustration; and

30

Figure 5 is a longitudinal cross-sectional view of the connectorized cable of Figure 4 taken along line 5-5.

Detailed Description of the Preferred Embodiments

Referring now to Figures 1 and 2, there is shown a shielded cable **10** in accordance with the present invention. The shielded cable **10** is generally

35

known as a drop cable and is used in the transmission of RF signals such as cable television signals.

Typically, the over-the-jacket diameter of the cable **10** is between about 0.24 inches (0.61 cm) and 0.41 inches (1.04 cm).

The cable **10** includes a cable core **12** comprising an elongate center conductor **14** and a dielectric layer **16** surrounding the center conductor. A first shield preferably formed of a first shielding tape **18** surrounds the cable core **12** and is bonded thereto. A second shield preferably formed of a second shielding tape **20** surrounds the first shielding tape. The first and second shielding tapes **18** and **20** prevent leakage of the signals being transmitted by the center conductor **14** and interference from outside signals. An interstitial layer **22** is located between the shielding tapes **18** and **20** and spaces the shielding tapes apart from one another. A cable jacket **24** surrounds the second shielding tape **20** to protect the cable from moisture and other environmental effects and is bonded to the second shielding tape.

As mentioned above, the center conductor **14** in the shielded cable **10** of the invention is generally used in the transmission of RF signals such as cable television signals. The center conductor **14** is preferably formed of copper clad steel wire but other conductive wire (e.g. copper) can also be used. The dielectric layer **16** can be formed of either a foamed or a solid dielectric material. Preferably, the dielectric layer **16** is a material that reduces attenuation and maximizes signal propagation such as a foamed polyethylene. In addition, solid polyethylene may be used.

The cable **10** further includes a first or inner shielding tape **18** surrounding the cable core **12**

and bonded to the cable core by an adhesive layer **25**. The longitudinal edges of the first shielding tape **18** are typically overlapped so that 100% shielding coverage is provided by the first shielding tape. The first shielding tape **18** includes at least one conductive layer such as a thin metallic foil layer. Preferably, the first shielding tape **18** is a bonded laminate tape including a polymer layer **26** with metal layers **28** and **30** bonded to opposite sides of the polymer layer. The polymer layer **26** is typically a polyolefin (e.g. polypropylene) or a polyester film. The metal layers **28** and **30** are typically thin aluminum foil layers. To prevent cracking of the aluminum in bending, the aluminum foil layers can be formed of an aluminum alloy having generally the same tensile and elongation properties as the polymer layer. Tapes having this construction are available under the HYDRA® trademark from Neptco. In addition, the first shielding tape **18** preferably also includes an adhesive on one surface thereof to provide the adhesive layer **25** between the first shielding tape and the cable core **12**. The adhesive is typically formed of an ethylene-acrylic acid (EAA), ethylene-vinyl acetate (EVA), or ethylene methylacrylate (EMA) copolymer or other suitable adhesive. Preferably, the first shielding tape **18** is formed of a bonded aluminum-polypropylene-aluminum laminate tape with an EAA copolymer adhesive.

A second or outer shielding tape **20** surrounds the first shielding tape **18** and also provides shielding of the center conductor **14**. The longitudinal edges of the second shielding tape **20** are typically overlapped and the second shielding tape is preferably bonded to the cable jacket **24**. The second shielding tape **20** includes at least one conductive layer such as a thin metallic foil layer and is preferably a bonded laminate

tape including a polymer layer **34** with metal layers **36** and **38** bonded to opposite sides of the polymer layer as described above. However, to provide added strength and connector retention to the shielded cable **10**, the
5 second shielding tape **20** is preferably a bonded aluminum-polyester-aluminum laminated tape. In addition, to prevent cracking of the aluminum in bending, the second shielding tape **20** can include aluminum alloy foil layers having generally the same
10 tensile and elongation properties as the polyester such as described above with respect to the first shielding tape **18**. The second shielding tape **20** typically also includes an adhesive on one surface thereof that forms an adhesive layer **40** to provide a bond between the
15 second shielding tape and the cable jacket **24**. Preferably, the adhesive is an EAA copolymer for polyethylene jackets and an EVA copolymer for polyvinyl chloride jackets.

In between the first shielding tape **18** and
20 the second shielding tape **20** is provided an interstitial layer **22** that spaces the shielding tapes apart from one another. The interstitial layer **22** is composed of elongate strands **42** disposed between the first shielding tape **18** and the second shielding tape
25 **20**. The elongate strands **42** are positioned and arranged between the tapes **18** and **20** in such a way that they are freely displaceable axially. As described in more detail below, this allows the strands **42** to be displaced when the cable **10** is attached to a standard
30 connector. In the illustrated embodiment, this is achieved by the strands being loosely arranged between the tapes **18** and **20** without any bonding to one another or to the tapes. Alternatively, a binding agent or adhesive could be utilized to stabilize the strands
35 during manufacture, so long as the bond is relatively

weak and permits axial displacement of the strands during connectorization.

The strands **42** forming the interstitial layer **22** are preferably helically arranged about the first shielding tape **20**. Preferably, the strands **42** are
5 metal wires or textile yarns. Metal wires are especially preferred because they impart more strength, provide a conductive bridge between the shielding layers, and increase the strength of the attachment
10 between the cable and connector. Exemplary wires include copper or aluminum wires having a generally circular cross-section and a diameter of up to about 0.01 inch (0.025 cm). The metal wires can be applied in one layer having a predetermined helical orientation
15 or in more than one layer (e.g. two layers) with each layer having alternating opposite helical orientations. For example, a first layer of wires can be applied in a clockwise orientation and a second layer of wires applied in a counterclockwise orientation. In any
20 event, the metal wires are applied such that they are freely displaceable axially and thus are not interlaced in the manner used to make braided wires. To that end, the metal wires preferably cover less than 30 percent of the surface of the underlying shielding tape **18**, and
25 more preferably between about 10 and 20 percent of the surface of the underlying shielding tape.

As mentioned above, the strands **42** can also be composed of textile yarns. Exemplary yarns include polyester, aramid and cotton yarns, and blends thereof.
30 Preferably, the yarns are continuous multifilament polyester yarns. The yarns can also be semiconductive or contain conductive filaments or fibers to provide a conductive bridge between the shielding tapes **18** and **20**. The yarns can suitably provide less than 50
35 percent coverage of the underlying shielding tape **18** and, for example, may cover between 20 and 40 percent

of the surface of the first shielding tape. The yarns are preferably helically arranged about the first shielding tape **18** and can be used alone to form the interstitial layer **22** or can be combined with metal
5 wires. For example, the yarns and metal wires can be disposed alongside one another to form the interstitial layer **22** or in separate layers as described above.

The interstitial layer **22** can also include a water blocking material to trap any moisture that may
10 enter the cable **10** and prevent corrosion of the metal layers in the cable. The water blocking material can, for example, include a water swellable powder such as a polyacrylate salt (e.g. sodium polyacrylate). This water blocking powder can be provided in the yarns used
15 as strands **42** in the interstitial layer **22**, applied to the strands in the interstitial layer, or provided on the surface of the first or second shielding tape **18** or **20** adjacent the interstitial layer.

As shown in Figures 1 and 2, the cable **10**
20 generally also includes a protective jacket **24** surrounding the second shielding tape **20**. The jacket **24** is preferably formed of a non-conductive material such as polyethylene or polyvinyl chloride. Alternatively, a low smoke insulation such as a
25 fluorinated polymer can be used if the cable **10** is to be installed in air plenums requiring compliance with the requirements of UL910.

Figure 3 illustrates a preferred method of making the shielded cable **10** of the invention. As
30 shown in Figure 3, the cable core **12** comprising a center conductor **14** and surrounding dielectric layer **16** is advanced from a reel **50**. As the cable core **12** is advanced, a first shielding tape **18** is supplied from a reel **52** and longitudinally wrapped or "cigarette-
35 wrapped" around the cable core. As mentioned above,

the first shielding tape **18** is preferably a bonded metal-polymer-metal laminate tape having an adhesive on one surface thereof. The first shielding tape **18** is applied with the adhesive surface positioned adjacent the underlying cable core **12**. If an adhesive layer is not already included on the first shielding tape **18**, an adhesive layer can be applied by suitable means such as extrusion prior to longitudinally wrapping the first shielding tape around the core **12**. One or more guiding rolls **54** direct the first shielding tape **18** around the cable core with longitudinal edges of the first shielding tape overlapping to provide 100% shielding coverage of the cable core **12**.

The wrapped cable core is next advanced to a creel **56** that helically winds or "serves" the strands **42** around the first shielding tape **18** to form the interstitial layer **22**. The creel **56** preferably includes only as many spools **58** as are necessary to provide the desired coverage of the first shielding tape **18** described above. The creel **56** rotates in either a clockwise or counterclockwise direction to provide helical winding of the strands **42**. Additional creels (not shown) can also be included to produce more than one layer of strands **42** in the interstitial layer **22**. In addition, if a water blocking material is not provided in the strands **42** or on the surface of the first or second shielding tapes **18** or **20**, a water swellable powder can be applied to the interstitial layer **22** by suitable means (not shown) to prevent the migration of moisture in the cable **10**.

Once the interstitial layer **22** has been applied, a second shielding tape **20** is provided from a reel **60** and longitudinally wrapped around the interstitial layer. As mentioned above, the second shielding tape **20** is preferably a bonded metal-polymer-

-12-

metal laminate tape having an adhesive layer on one surface thereof. The second shielding tape **20** is applied with the adhesive layer facing outwardly away from the interstitial layer **22**, i.e., adjacent the cable jacket **24**. One or more guiding rolls **62** direct the second shielding tape **20** around the interstitial layer **22** with longitudinal edges of the second shielding tape overlapping to provide 100% shielding coverage.

The cable is then advanced to an extruder apparatus **64** and a polymer melt is extruded at an elevated temperature around the second shielding tape **20** to form the cable jacket **24**. If the second shielding tape **20** does not already include an adhesive, an adhesive layer **40** can be applied to the second shielding tape by suitable means such as coating or extrusion, or it can be coextruded with the cable jacket **24**. The heat from the extruded melt generally activates the adhesive layers **25** and **40** to provide a bond between the cable core **12** and first shielding tape **18**, and between the second shielding tape **20** and the jacket **24**. Once the protective jacket **24** has been applied, the cable is quenched in a cooling trough **66** to harden the jacket and the cable is taken up on a reel **68**.

Figures 4 and 5 illustrate the shielded cable **10** of the invention attached to a standard connector **70**. The connector **70** shown in Figures 4 and 5 is a threaded one-piece connector of the type conventionally used in the cable television industry. However, other types of connectors such as two-piece compression connectors could also be used in accordance with the invention.

The standard one-piece connector **70** typically includes an inner sleeve or bushing **72** and an outer sleeve **74**. As shown in Figure 5, to attach the

shielded cable **10** of the invention to the connector **70**, the shielded cable is typically prepared by cutting away a portion of the dielectric **16** and first shielding tape **18** to expose a short length (e.g. 1/4 of an inch (0.64 cm)) of the center conductor **14** protruding from the dielectric. The second shielding tape **20** and jacket **24** are stripped away an additional short length (e.g. 1/4 of an inch (0.64 cm)) exposing the dielectric **16** and first shielding tape **18**. The connector **70** is then attached to the cable **10** by inserting the bushing **72** between the shielding tapes **18** and **20** and inserting the outer sleeve **74** around the jacket **24**. The outer sleeve **74** is then crimped down onto the cable **10** using a suitable crimping tool to complete connectorization of the cable. Because the strands **42** forming the interstitial layer **22** are freely moveable between the two shielding tapes **18** and **20**, the strands are pushed back axially as the connector bushing **72** is inserted. Insertion of the connector does not require special preparation or use of a coring tool. As best shown in Figure 5, a portion of the axially displaced strands **42** become lodged or tucked between the connector bushing **72** and the second shielding tape **20**. These strands **42** serve to help anchor the connector bushing **72** in the cable **10** and thus increase the pull-off resistance of the cable, i.e., the force necessary to pull the connector **70** off of the cable.

The benefits of the invention can be demonstrated by determining the pull-off force between cables and standard connectors using the test method described in Society of Cable Telecommunications Engineers (SCTE) Document IPS-TP-401, issued January 17, 1994 and entitled "Test Method for Axial Pull Connector/Cable." Using this method, RG6 cables having an over the jacket diameter of 0.272 inch (0.691 cm)

19 JUN 2002

were compared. Cable A was constructed using metal wires according to the invention and Cable B was constructed using a foamed polyvinyl chloride layer between shielding tapes. The results are provided in Table 1 and demonstrate the increased pull-off resistance of the cables according to the invention.

TABLE 1

Connector/Cable	Connector Pull-Off Force
One Piece Crimp Connector:	
Cable A	64 lb _f (280 N)
Cable B	30 lb _f (130 N)
Two Piece Compression Connector:	
Cable A	61 lb _f (270 N)
Cable B	37 lb _f (160 N)

10

In addition to providing ease of connectorization and enhanced connector pull-off resistance, the shielded cable **10** of the invention can be produced at a better rate than conventional braided cables and at lower cost. Furthermore, the shielded cable sufficiently shields the RF signals carried by the center conductor. Accordingly, the shielded cable **10** of the invention overcomes many of the problems associated with prior art cables.

15

19 JUN 2002

THAT WHICH IS CLAIMED:

1. A shielded cable (10) comprising:
a cable core (12) comprising a center
conductor (14) and a dielectric layer (16) surrounding
the center conductor (14);
5 a first electrically conductive shield (18)
surrounding said cable core (12) and bonded thereto,
said shield (18) comprising a bonded metal-polymer-metal
laminate tape extending longitudinally of the cable (10)
and having overlapping longitudinal edges;
10 a second electrically conductive shield (20)
surrounding said first shield (18) comprising a bonded
metal-polymer-metal laminate tape extending
longitudinally of the cable (10) and having overlapping
longitudinal edges;
15 a cable jacket (24) surrounding said second
shield (20) and bonded thereto; and
an interstitial layer (22) located between
said first and second shields (18, 20), said
interstitial layer (22) being composed of elongate
20 strands (42) disposed between said first and second
shields (18, 20) so as to be freely displaceable
axially while also serving to space said first and
second shields (18, 20) apart from one another.
2. The shielded cable according to Claim 1,
wherein said first shield (18) comprises an aluminum-
polyolefin-aluminum laminate tape and said second
shield (20) comprises an aluminum-polyester-aluminum
5 laminate tape.
3. The shielded cable (10) according to any
of Claims 1-2, wherein said interstitial layer (22) is
formed from a first plurality of metal wires helically
arranged about the first shield.

4. The shielded cable (10) according to Claim 3, wherein said interstitial layer (22) further comprises a second plurality of metal wires helically arranged about the first plurality of metal wires and
5 having a helical orientation opposite the orientation of the first plurality of metal wires.

5. The shielded cable (10) according to Claim 3, wherein the first plurality of metal wires covers less than 30 percent of the surface of the underlying first shield (18).

6. The shielded cable (10) according to any of Claims 1-2, wherein said interstitial layer (22) is formed from yarns helically arranged about the first shield (18).

7. The shielded cable (10) according to Claim 6, wherein yarns are arranged in a single layer and cover less than 50 percent of the surface of the underlying first shield (18).

8. The shielded cable (10) according to Claim 6, wherein said yarns are selected from the group consisting of polyester, cotton and aramid yarns and blends thereof.

9. The shielded cable (10) according to Claim 6, wherein said interstitial layer (22) additionally includes metal wires disposed alongside said yarns.

10. The shielded cable (10) according to any of Claims 1-9, wherein said interstitial layer (22) further comprises a water blocking material.

11. A method of making a shielded cable (10) comprising the steps of:

5 advancing a cable core (12) comprising a center conductor (14) and a dielectric layer (16) surrounding the center conductor (14);

 longitudinally wrapping a first bonded metal-polymer-metal laminate shielding tape (18) around the cable core (12) and overlapping longitudinal edges of the shielding tape (18);

10 bonding the first shielding tape (18) to the cable core (12);

 applying an interstitial layer (22) composed of axially displaceable elongate strands (42) around the first shielding tape (18);

15 longitudinally wrapping a second bonded metal-polymer-metal laminate shielding tape (20) around the interstitial layer (22) and overlapping longitudinal edges of the shielding tape (20);

20 extruding a cable jacket (24) around the second shielding tape (20); and

 bonding the cable jacket (24) to the second shielding tape (20).

12. The method according to Claim 12, wherein said step of applying an interstitial layer (22) comprises helically wrapping elongate strands (42) around the first shielding tape (18).

13. The method according to Claim 12, wherein said helically wrapping step comprises helically wrapping a first plurality of metal wires around the first shielding tape (18).

14. The method according to Claim 13,
wherein said helically wrapping step further comprises
helically wrapping a second plurality of metal wires
about the first plurality of metal wires in a helical
orientation opposite the orientation of the first
5 plurality of metal wires.

15. The method according to Claim 13,
wherein said helically wrapping step comprises
helically wrapping the first plurality of metal wires
over less than 30 percent of the surface of the
5 underlying first shielding tape (18).

16. The method according to Claim 12,
wherein said helically wrapping step comprises
helically wrapping a first plurality of yarns around
the first shielding tape (18).

17. The method according to Claim 16,
wherein said helically wrapping step comprises
helically wrapping the first plurality of yarns over
less than 50 percent of the surface of the underlying
first shielding tape (18).

18. The method according to Claim 16,
wherein said helically wrapping step comprises
helically wrapping a first plurality of yarns selected
from the group consisting of polyester, cotton and
5 aramid yarns and blends thereof.

19. The method according to Claim 16,
wherein said helically wrapping step further comprises
helically wrapping metal wires about the underlying
5 first shielding tape (18) and disposed along the first
plurality of yarns.