

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020295 A2

- (51) International Patent Classification⁷: **B65D**
- (21) International Application Number:
PCT/US2003/026861
- (22) International Filing Date: 28 August 2003 (28.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/406,636 29 August 2002 (29.08.2002) US
Not furnished 27 August 2003 (27.08.2003) US
- (71) Applicant: **EMSAR, INC.** [US/US]; 125 Access Road,
Stratford, CT 06615 (US).
- (72) Inventor: **CATER, Miro, S.**; 1777 Mitchell Court, Day-
tona Beach, FL 32124 (US).
- (74) Agents: **SALEHI, Dianoosh et al.**; Kenyon & Kenyon,
1500 K Street, NW, Washington, DC 20015-1257 (US).


- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

[Continued on next page]

(54) Title: PLUG STYLE PUMP



(57) Abstract: A dispenser is mounted on a bottle which has a body, with a neck atop the body forming an inlet passage terminating in an opening. Thin walls are formed around the opening and a relatively thick section is spaced some distance below the opening forming an undercut. The dispenser includes a body having an open outer end with a plug inserted and retained in and projecting from the outer open end of said body. The housing is inserted in and engages the inside of the neck below the undercut, with the projecting portion of the plug engaging the outer portion of the inside of the neck. The dispenser may be a pump with a pump body with an inner end and an open outer end. The pump body forms a cylinder and a piston is disposed for reciprocal movement in the cylinder. A spring biases the piston toward open outer end and an inlet valve is disposed at the inner end of the cylinder. The pump also includes a stem having a central bore for dispensing a fluid from the cylinder with an outlet valve

coupling the cylinder to the bore of the stem. An actuator is disposed on the stem in fluid communication therewith. The plug is inserted and retained in and projects from the outer open end of the pump body, the plug restraining outward movement of the piston.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.