

NON-LINEAR CUSTOMER CONTRAST CONTROL FOR A COLOR TELEVISION WITH AUTOPIX

5 This invention relates to an arrangement for
controlling the contrast of a television receiver or monitor and, in
particular, to circuitry for extending the range of customer
contrast control of a television receiver, or monitor, having
automatic contrast control capability.

10 In modern television systems it is known to
automatically control the contrast and brightness of a reproduced
image. For example, a TV system with automatic contrast control
to inhibit "white spot blooming" is described in USP 5,003,394
entitled DYNAMIC VIDEO SYSTEM INCLUDING AUTOMATIC
CONTRAST AND "WHITE STRETCH" PROCESSING SECTIONS.

15 Automatic contrast control (which is also referred to as "autopix"
where "pix" is an abbreviation for "picture") prevents loss of detail
sharpness in highlight (white) areas due to blooming, while
permitting high contrast (and therefore subjectively bright)
images when the signal peaks remain below the blooming
20 threshold.

Automatic contrast control circuitry used in modern
TV systems is shown in FIG. 1. For ease of illustration, only those
portions of a TV system deemed pertinent to a discussion of the
invention are shown in FIGURE 1.

25 Referring to FIGURE 1, there is shown main and
auxiliary video inputs 1 and 3, respectively, coupled to a picture-
in-picture (PIP) processor 5 which is also controlled by a receiver
control 7. PIP processor 5 provides signals (C and Y) to luminance
circuit 9 and to chrominance circuit 11. The outputs of luminance
30 and chrominance circuits 9 and 11, respectively, are applied to a
matrix 10 whose outputs are red (r), blue (b), and green (g) color
signals which are applied to respective inputs of a contrast control
section 13r, 13b, and 13g. The contrast control section (e.g., 13r,
13b and 13g) is responsive to the red (r), blue (b) and green (g)
35 color signals and its outputs are applied to a brightness control
section (e.g., 15r, 15b and 15g) whose outputs are coupled via
drivers (e.g., 17r, 17b and 17g) to a picture tube (e.g. 19).



The automatic contrast control arrangement includes a combiner circuit 47 for deriving a "combined" signal (e.g., SUMY) from the outputs of the brightness section. The combined signal (i.e., SUMY) as used herein and in the claims appended hereto is representative of the luminance component of the displayed image. The combined signal (SUMY) is then processed via an autopix circuit 41 comprised of a peak detector 49 and a comparator 50 whose output is fed back via a buffer 51 to the control input terminal 13 of the contrast control section (13r, 13b, 13g) of the TV system. The autopix loop 41 comprising peak detector 49, comparator 50, and buffer 51 defines a feedback loop coupled between the output (terminal 14) of the combiner circuit 47 and the input control (terminal 13) of the contrast control section which determines the closed loop gain of the contrast control section. The open loop gain of the contrast control section (13r, 13g and 13b) is determined, in part, by a customer contrast control unit 60 which is driven by receiver control 7.

Contrast control unit 60 includes a common control microprocessor 63, a buffer amplifier 65 and a low pass filter 67. The microprocessor 63 is used to control various functions such as peaking, contrast and brightness. Under the control of microprocessor 63 and a switching element represented by N63, a pulse signal (PS) and its logical complement PSN are generated. The pulse signals PS and PSN include pulses which are pulse width modulated (PWM) to represent the customer's contrast control settings, also defined and referred to herein as customer control steps. The signal PSN (which is the logical complement of PS) is produced at node 29 of microprocessor 63 and is applied to the input of the buffer amplifier 65.

Amplifier 65 is responsive to the pulse width modulated pulse signal (PSN) and produces at its output node 75 amplified and buffered pulse width modulated output pulses (in phase with the PS signal) which are then applied to the input of a low pass filter 67. Filter 67 represented by a series-connected resistor R7 and a shunt-connected capacitor C1, filters the pulse width modulated signals produced by amplifier 65 to produce a DC user contrast control voltage (Vc) at node 670 which is applied to terminal 13.

This Sheet Has Been Replaced



In the arrangement shown in FIGURE 1, an automatic beam current limiter 52 is also coupled to terminal 13.

Consequently, capacitor C1 of low pass filter 67 is shared by circuits 60, 52 and 41 to filter and store the respective control voltages generated by user contrast control unit 60, automatic beam current limiter 52 and automatic contrast control unit 41. The control voltage (V_c) developed across capacitor C1 is thus a combination of the individual control voltages generated by control units 60, 52 and 41.

For the embodiment shown, it is assumed that increasing the direct current (DC) contrast control voltage (V_c) corresponds to increasing gain, and therefore increasing contrast, and that decreasing the DC contrast control voltage (V_c) corresponds to decreasing gain and contrast. [This corresponds to the further assumption that white-going portions of the processed luminance output signal (SUMY) are positive going.]

As shown in FIGURE 1, automatic contrast control unit (autopix) 41 includes a peak detector 49 which detects the peaks of the white-going portion of the processed luminance output signal SUMY. The output voltage of white peak detector 49 is coupled to comparator 50. Peak detector 49 and comparator 50 are arranged to decrease the contrast control voltage as a function of the peak amplitude of the luminance output signal when the peak exceeds a predetermined reference voltage.

A problem with the TV system of FIGURE 1 is that, for some signals, the autopix feedback loop limits the range over which the contrast control may vary. A drawback of this limitation is that since autopix is a relatively new feature, a customer/user trying to adjust the contrast may believe the TV set is defective because the contrast cannot be made to vary in the accustomed manner.

The extent of the limitation may be better appreciated by reference to curve A of FIGURE 2, which shows the SUMY output at terminal 14. In FIGURE 2, the ordinate (y axis) represents the amplitude (in volts) of the video output voltage (SUMY) produced at terminal 14 of FIGURE 1, and the abscissa (x axis) represents the 63 control steps (or settings) available to the customer/user to increase (going from step zero to step 63) the



contrast. Curve A shows the VIDEO or SUMY output for the condition when the autopix loop 41 is closed; i.e., there is feedback via the feedback loop 41 from terminal 14 to contrast terminal 13.

It is seen that the VIDEO output varies linearly in response to the customer's control steps in the range from zero to 21. However, for customer control steps above 21, the response is flat. That is, the operation of the autopix feedback loop limits the user's ability to alter the contrast above control step 21 with the video output voltage being held at approximately 3.5 volts. Thus, in a system which theoretically provides for 63 control steps, only the first 21 may be effectively used.

Applicants' invention resides, in part, in the recognition of the problem discussed above and, in part, in the circuitry to extend the range over which the customer can exercise contrast control.

In TV systems embodying the invention, user responsive contrast control voltage generating circuitry is intentionally rendered non-linear to produce a non-linear control voltage which is applied to the contrast control section in a manner to extend the range over which the user can control the contrast of the TV receiver.

In a particular embodiment, the TV system includes a contrast control section and a brightness control section with each one of the contrast and brightness control sections having inputs and outputs and with the outputs of the contrast control section being coupled to the inputs of the brightness control section. Color signals are applied to the inputs of the contrast control section for processing the color signals via the contrast and brightness control sections. The outputs of the brightness control section are combined for producing a combined signal. A feedback loop (autopix) responsive to the combined signal is coupled between the outputs of the brightness control section and the inputs of the contrast control section. The feedback loop functions to limit the range over which the contrast can vary. User responsive contrast control voltage circuitry is coupled to the input of the contrast control section and applies to it a contrast control voltage which is a non-linear function of the customer control signals for extending the range over which the user can vary the contrast.

This Sheet Has Been Replaced



In the accompanying drawing like reference characteristics denote like components; and

FIGURE 1 is a semi-schematic semi-block diagram of a known TV system;

FIGURE 2 is a drawing of the Video Output Voltage (SUMY) as a function of customer control steps for a closed loop linear (uncompensated) and non-linear (compensated) conditions;

FIGURE 3 is a schematic diagram of a contrast control circuit embodying the invention for use with the circuit of FIGURE 1;

FIGURE 3A is a drawing of a typical pulse width modulated pulse signal corresponding to several customer control steps;

FIGURE 4 is a drawing of the contrast control voltage as a function of customer control step for the open loop linear (uncompensated) and non-linear (compensated) conditions; and

FIGURE 5 is a drawing of the contrast control voltage as a function of customer control steps for the closed loop linear (uncompensated) and non-linear (compensated) conditions.

FIGURE 3 shows a user contrast control voltage generating circuit embodying the invention and, in particular, to an amplifier/filter 81 which may be substituted for the buffer amplifier 65 of FIGURE 1.

Referring to FIGURE 3, there is shown the application of a pulse width modulated customer contrast control pulse signal (PS) to the gate of a switch N63 for controlling its turn-on and turn-off and the logical complement signal (PSN) generated at output terminal 29 of microprocessor 63 which is connected via a pull-up resistor R1 to a source of +5 volts. PSN is applied via resistor R2 to the base of an NPN bipolar transistor Q1 whose emitter is grounded. A resistor R4 is connected between the collector of Q1 and a node 71 and a resistor R3 is connected between node 71 and a power terminal 17 to which is applied Vcc volts which may be, for example, a positive 12 volts.

A nonlinear low pass filter 73 is connected between node 71 and the base of an NPN bipolar transistor Q2 operated as an emitter follower. The filter 73 includes a resistor R8 connected between node 71 and the base of Q2, a diode D1 having its



cathode connected to node 71 and its anode connected to the base of Q2, and a capacitor C2 connected between the base of Q2 and ground.

5 The collector of Q2 is connected to terminal 17 and its emitter is connected to an output node 75. A ground return emitter resistor R5 is connected between node 75 and ground. A low pass filter 671 which may be of the same type as filter 67 of FIGURE 1 is connected between node 75 and contrast control terminal 13 of the RGB IC. As in FIGURE 1, a resistor R7 is
10 connected between node 75 and contrast control terminal 13 and a filter capacitor C1 is connected between terminal 13 and ground. As in FIGURE 1, an output of the autopix network 41 and an output of the beam limiter circuit 52 are connected back to terminal 13.

15 The operation of the circuit of FIGURE 3 and, in particular, the role of the nonlinear network 73 will now be discussed.

Referring to network 73, the combination of R8, D1 and C2 functions to produce a non-linear direct current (DC) contrast control voltage (Vc). In the circuit of FIGURE 3, capacitor C2 is isolated from C1 (and terminal 13), whereby C2 can be charged and/or discharged at different rates. When Q1 is fully turned-off, C2 is charged by the series combination of R3 and R8. When Q1 is turned-on, C2 discharges via D1 (poled to conduct in
25 the forward direction) which shunts R8, and the parallel combination of R3 and R4. Therefore, the charging time constant (Tc) is approximately $(R3+R8)(C2)$ while the discharge time constant (Td) is approximately (R3 in parallel with R4) multiplied by (C2). For R3 = 1.8K ohms, R8 = 10K ohms, and R4 = 4.7K ohms,
30 the series resistance of R3 + R8 is approximately 12K ohms and the parallel combination of R3 and R4 is approximately 1.3K ohms. Consequently, it is evident that the charging time constant (Tc) is more than nine (9) times greater than the discharge time constant (Td). The unequal charge and discharge times of network 73 in
35 FIGURE 3 produces the various curves shown in curves B of FIGURES 2, 4 and 5.

To better understand the role played by filter 73, note that in the circuit of FIGURE 3 (as in FIGURE 1) the user can vary



(increase or decrease) the contrast in 63 steps. The user's control is manifested by the production of a pulse width modulated pulse signal (PS) of the type shown in FIGURE 3A. The PSN signals produced at terminal 29 of the microprocessor are the logical complement of the PS signals and are applied to the input of the buffer amplifier 81. As shown in FIGURE 3A, the period (T_p) of the pulse signal may be divided into 64 steps (63 increments). The first step is a zero dc voltage level to ensure the full turn-off of N63 and the 64th step is a direct current (dc) level of sufficient amplitude to ensure that N63 is fully turned-on. The pulse period T_p is divided into 63 equal increments with each succeeding higher step having a pulse width which is greater than the lower previous step by $T_p/63$. Thus, the "high" level pulse width (TH) duration of any step (N_i) between step 1 and step 63, may be expressed as $(N_i/63)(T_p)$; where T_p is the pulse width duration which is equal to TH plus TL where TH is the length of time the pulse is high and TL is the length of time the pulse is low. Varying the length of time a pulse is high (e.g., TH) versus the pulse duration (T_p) is a means of varying the duty cycle [i.e., $(TH/T_p)(100\%)$] of the pulse train applied to the amplifier/filter combination. As further detailed below, the direct current (d.c.) level of the contrast control voltage is varied by varying the duty cycle of the pulse train.

For ease of explanation, we shall first examine the response of the circuit of FIGURE 3 for two end point conditions. In the discussion to follow, it is assumed that when PS is "low" or "0", PSN is "high" and of sufficient amplitude to fully turn-on Q1 and that when PS is "high" or logic "1", PSN is "low" or "0" and of such an amplitude to fully turn-off Q1.

1. First, at step 0, PS is "low" or "0", PSN is "high" and Q1 is on hard. For this condition, the voltage divider network of R3 and R4 causes the voltage at node 71 to be approximately equal to 8.6 volts. The base of Q2 will be less than, but close to, that voltage and the voltage at the emitter of Q2 (node 75) will be approximately 0.7 volt below the Q2 base voltage. This condition defines the minimum voltage produced at the emitter of Q2 and the minimum voltage (vc) produced at output node 670 and



applied to terminal 13 which is approximately equal to 7.9 volts as shown in FIGURES 4 and 5.

2. At step 63, PS is at a "high" dc level and PSN is at a "low" level whereby Q1 is fully turned-off. Since Q1 is non-conducting, the base of Q2 is coupled via the series combination of R3 and R8 to Vcc volts. Due to the emitter follower action of Q2, the voltage drop across R3 and R8 will be relatively small, being a function of the base current into Q2. For Vcc equal to 12 volts, the voltage drop across R3 and R8 may be assumed to be approximately 0.4 volt, whereby the voltage at the base of Q2 is approximately 11.6 volts. Assuming a VBE drop of approximately 0.7 volt, the voltage (V4) at the emitter of Q2 is then approximately 10.9 volts as shown in FIGURE 4. Thus the maximum voltage (VMAX or VcMAX) produced at the emitter of Q2 and hence at node 670 and applied to terminal 13, is approximately 10.9 volts, while the minimum voltage (VMIN or VcMIN) is approximately 7.9 volts. Consequently, the customer control steps may be used to vary the dc contrast control voltage (Vc) between a minimum value (e.g., 7.9 volts) and a maximum value (e.g., 10.9 volts). As noted above, for the embodiment shown, it is assumed that increasing the direct current (DC) contrast control voltage (Vc) corresponds to increasing gain, and therefore increasing contrast, and that decreasing the DC contrast control voltage (Vc) corresponds to decreasing gain and contrast. Also, in contrast to the known circuit of FIGURE 1, in circuits embodying the invention, the dc contrast control (Vc) is not increased (decreased) linearly as a function of increasing (decreasing) steps (settings).

To better appreciate the effect of the non-linear compensation provided by the invention, reference is made to the circuits of FIGURES 1 and 3 and to the curves shown in FIGURE 4. Referring back to the circuit of FIGURE 1, the amplifier 65 functions to charge capacitor C1 with a charging time constant (Tc) which is nearly equal to the discharging time constant (Td). As a result, in the circuit of FIGURE 1, the pulse signal causes the contrast control voltage produced at the emitter of Q2 and across capacitor C1 to increase linearly as the control settings are



increased from 0 to 63. The result of the open loop operation of the circuit of FIGURE 1 is shown in curve A of FIGURE 4.

Note that in the circuit of FIGURE 1, for the open loop condition (when the output of autopix 41 is not connected to node 13) the contrast control voltage V_c , rises linearly from a V_{cMIN} value of approximately 7.9 volts dc for the zero customer control step (setting) to a value of approximately 11.4 volts dc at the 63rd customer control step.

Referring back to FIGURE 3, recall that in network 73 the charging time constant (T_c) is made much greater than the discharge time constant (T_d). Consequently, the open loop dc voltage produced at the emitter of Q2 (node 75) and at node 670 tends to increase slowly for the low values of customer control steps (settings) where the pulse width of the pulse signal is small and to increase more quickly for the higher valued customer control settings where the pulse width of the pulse signal is larger. This is illustrated by curve B of FIGURE 4. Comparing curve B with curve A, it is evident that the compensated (nonlinear) curve B increases more slowly than the non-compensated (linear) curve A as a function of increasing customer control steps (settings). Therefore, by making the charging time constant greater than the discharging time constant ($T_c > T_d$) the contrast control voltage (V_c) produced at the output of the filter 671 and applied to terminal 13 of the contrast control section tends to be less than the value of V_c produced when T_c is approximately equal to T_d . The end points of curve A and curve B are different because of the additional voltage drop across R8. However, if Q2 were a much higher gain device, the two end points would be much closer.

The smaller increments of control voltage (V_c) for the lower valued control steps generated by the circuit of FIGURE 3 (as compared to the circuit of FIGURE 1) effectively reduces the drive and the gain of the contrast control section 13b, 13g, 13r for the lower valued customer control steps. Consequently, when the control voltage V_c of curve B of FIGURE 4 is applied to terminal 13 and the feedback loop is closed (i.e., autopix 41 is connected in circuit) the response of the system is as shown in curve B of FIGURE 5.

This Sheet Has Been Replaced



FIGURE 5 shows how the open loop voltage V_c of FIGURE 4 applied to terminal 13 of the contrast control section varies when the autopix loop 41 is closed and operable. That is, FIGURE 5 corresponds to the condition for which node 670 is
5 connected to terminal 13 of the RGB IC and the autopix feedback loop 41 is closed between terminals 14 and 13 of the RGB IC.

Curve A of FIGURE 5 illustrates the operation when the amplifier/filter circuit 60 of FIGURE 1 is connected in circuit. The control voltage increases linearly from step 0 to step 21 and then
10 remains flat over the rest of the customer control settings (steps 21 - 63). In contrast thereto, curve B of FIGURE 5 illustrates the closed loop response of the circuit when the amplifier/filter 81 of FIGURE 3 is substituted for amplifier 65 of FIGURE 1. With the amplifier/filter of FIGURE 3 connected in circuit, the control
15 voltage varies over a range extending from step 0 to step 49. Thus, it is evident from an examination of curve B of FIGURE 5 that the contrast control voltage is now responsive to customer control steps over a range which extends from step 0 to at least step 49.

Refer back to FIGURE 2 which shows the response of the video output voltage (the SUMY signal at terminal 14), which is indicative of the video output, as a function of the customer control steps (settings). As discussed above, for the known combination of amplifier 65 and filter 67, the customer control is
20 limited to the first 21 steps (settings). In contrast, for the amplifier/filter 81 of the invention in combination with filter 67 producing the responses shown in curve B of FIGURES 4 and 5, customer control exists over a range extending from step 0 to step 42. Thus, non-linearizing the control voltage applied to terminal
25 13 as a function of customer control steps as shown in curves B of FIGURES 4 and 5, results in the SUMY output response shown in curve B of FIGURE 2. Consequently, in circuits and systems embodying the invention, the luminance is made to be controlled over a range of 42 customer control steps, whereby the contrast
30 control has been expanded over a much wider range than that available with the linear contrast control circuit of FIGURE 1.

In FIGURE 3, the non-linearization of the contrast control voltage (V_c) was achieved by inserting a network 81



comprised of an amplifier and non-linear low pass filter. It should be appreciated that a similar result could be obtained by non-linearizing the pulse width of the pulse signal as a function of customer control steps and applying the "non-linearized" pulse width signals to a linear amplifier filter combination.

In the circuit of FIGURE 3, the duty cycle of the pulse train is varied by using pulse width modulation. However, it should be appreciated that the duty cycle of the pulse train may be varied by using a bit rate multiplier scheme or other known arrangement. In all instances, the teaching of the invention is the production of a direct current (d.c.) contrast control voltage (V_c) which is a non-linear function of the duty cycle of the pulse train.

This Sheet Has Been Replaced





86,756
CLAIMS

1. A video signal processing system comprising:
a video signal processing channel (9,10,11) for
5 processing a video signal (c,y);
a contrast control section (13r;13g;13b) coupled to said
video signal processing channel for controlling a contrast
parameter of said video signal; and
a peak detector (41) coupled to said video signal
10 processing channel for detecting peak video signal levels that
exceed a threshold level, and coupled to said contrast control
section for modifying said contrast parameter in response to said
detected peak signal levels; characterized by
means (63,81,671) coupled to said contrast control
15 section for receiving a user-generated contrast control signal (PS)
and for modifying said contrast parameter non-linearly in
response to said user-generated control signal.

2. The video signal processing system of Claim 1,
20 further characterized in that said non-linear modifying means
includes a low pass filter (73) whose charging time constant is not
equal to its discharging time constant.


3. The video signal processing system of Claim 2,
25 further characterized in that the charging time constant is greater
than the discharging time constant.

4. The video signal processing system of Claim 2,
further characterized in that said non-linear modifying means
30 includes:

a first amplifier (N63) having an input for receiving
said user-generated contrast control signal and having an output;
a second amplifier (Q2) having an input and an output;
and

35 wherein said low pass filter is connected between the
output of said first amplifying means and the input of said second
amplifying means.

This Sheet Has Been Replaced



5. The video signal processing system of Claim 4, further characterized in that said low pass filter includes an RC network (R8,C2).

6. The video signal processing system of Claim 5, further characterized in that said RC network includes a resistor (R8) and a capacitor (C2) and a diode (D1) connected across at least part of the resistor whereby said diode functions as a relatively low impedance shunt for one polarity of signals.

7. The video signal processing system of Claim 1, further characterized in that said non-linear modifying means produces a control voltage (V4) applied to said contrast control section in response to said user-generated contrast control signal (PS).

8. The video signal processing system of Claim 7, further characterized in that said user-generated contrast control signal (PS) includes pulse width modulated rectangular pulses whose duty cycle is defined as TH/TP where TH is the length of time the pulse is relatively positive, TL is the length of time the pulse is relatively negative, and TP is equal to TH plus TL; and wherein the amplitude of said control voltage is a non-linear function of TH/TP .



This Sheet Has Been Replaced

