

OPTIMIZING FLOW CONTROL DEVICE PROPERTIES ON INJECTOR WELLS IN LIQUID FLOODING SYSTEMS

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

[0001] The present disclosure relates generally to the recovery of subterranean deposits and more specifically to methods and systems for optimizing the placement and other properties of one or more flow control devices along a liquid injection well for the purpose of improving recovery from a reservoir.

10 2. Discussion of the Related Art

[0002] Liquid injection refers to the method in the oil industry where fluid (usually water) is injected into the reservoir, to increase pressure and stimulate production. For example, in certain instances, the water replaces the oil which has been taken, thus, maintaining the production rate and the pressure over the long term. In addition, in certain situations, the
15 water displaces or sweeps oil from the reservoir and pushes it towards a well. Liquid injection wells can be found both on and off shore to increase oil recovery from an existing reservoir.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Illustrative embodiments of the present invention are described in detail below with
20 reference to the attached drawing figures, which are incorporated by reference herein and wherein:

[0004] Figure 1 is a diagram depicting a liquid injection method that uses flow control devices on an injector well in accordance with the disclosed embodiments;

[0005] Figure 2 is a schematic diagram indicating a cross-section of the reservoir area next to
25 a pair of injection and production wells in accordance with a disclosed embodiment;

[0006] Figure 3 is a flowchart depicting an example of computer-implemented method for determining the optimum properties for flow control devices on an injector well that yields a uniform displacement front towards the production well in accordance with a disclosed embodiment;

[0007] Figure 4 is a diagram that illustrates an example of a graph that depicts the convergence of the disclosed process in the case of a formation having uniform properties in accordance with the disclosed embodiments;

[0008] Figure 5 is a diagram that illustrates an example of a graph that depicts the flow control device distribution function for a formation having uniform properties and for a formation having a step-wise change in permeability in accordance with the disclosed embodiments;

[0009] Figure 6 is a diagram that illustrates an example of a graph that depicts the optimized distribution of the flow control device diameter for formation having uniform properties and for a formation having a step-wise change in permeability in accordance with the disclosed embodiments;

[0010] Figure 7 is a diagram that illustrates an example of a graph that depicts a profile of porosity with a step-wise change in accordance with the disclosed embodiments; and

[0011] Figure 8 is a block diagram illustrating one embodiment of a system for implementing the disclosed embodiments.

DETAILED DESCRIPTION

[0012] As stated above, water injection is a widely used method of providing reservoir pressure support that significantly increases the amount of oil recovered from a reservoir. Water injection is used in both vertical and horizontal wells. The injected water, sometimes with chemical additives, helps to increase depleted pressure in reservoir and move the oil in the direction of the production well. However, due to the frictional pressure drop and reservoir permeability variations along the well, there is usually a non-uniform fluid flux along the well length. For instance, typically, higher injection and production flow rates occur at the heel of the well that increases the possibility of breakthrough of injected liquid in this area.

[0013] In accordance with the disclosed embodiments, one method to counter this imbalance is to use one or more flow control devices (FCDs) 102 along the injection well 100 to balance or equalize flow rates the fluid injected into the formation 104 as illustrated in Figure 1. As referenced herein, a flow control device (FCD) is any device including an inflow control device (ICD) that is coupled to a wellbore that causes a pressure drop between the wellbore and a reservoir to reduce flow between the wellbore and the reservoir at the location of the flow control device. Non-limiting real examples of FCDs in accordance with the disclosed

embodiments include the EquiFlow® Inject system and the EquiFlow® inflow control device (ICD) both available from Halliburton®.

[0014] To optimize production from wells assisted by liquid flooding, the FCD design must account for high drawdown from heel to toe and reservoir heterogeneity. For optimal injection, the FCD placement needs to be linked to detailed physical characteristics of the reservoir and wellbore. However, to date, no easy methods for determining the proper placement or other properties of FCDs have been developed. Instead, current methods rely on a manual trial and error process in which various sizing/types and placement of FCDs are simulated along a horizontal well using simulation software such as NETool™ available from Landmark Graphics Corporation.

[0015] Therefore, the disclosed embodiments present a numerical algorithm and simulation approach for calculating the optimal FCD placement and other parameters (e.g., number of holes and hole sizes, and/or number and types of FCDs) for an injection well that yields a uniform flooding front along the wellbore for maximizing the overall recovery of oil.

[0016] The disclosed embodiments will be illustrated by several examples utilizing a simplified coupled reservoir-wellbore hydrodynamic model which accounts for FCD effects on the flow in the injection and production wellbore and flooding dynamics. However, the disclosed embodiments and methodology can be applied to coupled reservoir-wellbore models of varying levels of complexity.

[0017] The disclosed embodiments and advantages thereof are best understood by referring to Figures 1-8 of the drawings, like numerals being used for like and corresponding parts of the various drawings. Other features and advantages of the disclosed embodiments will be or will become apparent to one of ordinary skill in the art upon examination of the following figures and detailed description. It is intended that all such additional features and advantages be included within the scope of the disclosed embodiments. Further, the illustrated figures are only exemplary and are not intended to assert or imply any limitation with regard to the environment, architecture, design, or process in which different embodiments may be implemented.

[0018] As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprise" and/or "comprising," when used in this specification and/or the claims, specify the presence of stated features, integers, steps, operations, elements, and/or

components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. The embodiments were chosen and described to explain the principles of the invention and the practical application, and to enable others of ordinary skill in the art to understand the claimed inventions.

[0019] With reference now to Figure 2, a diagram depicting a schematic of the cross-section of the reservoir area next to a pair of injection and production wells is presented. The injection zone 110 near the injection well 100 is filled with injected fluid, while the liquid occupying the production zone 210 near the production well 200 is mostly oil. The injection zone 110 and the production zone 210 are separated by the displacement front 150, slowly moving away from the injection well 100 to the production well 200. In one embodiment, the pressure distributions in both the injection zone 110 and the production zone 210 are determined using the Laplace equations, which are postulated to have the following simple form:

$$[0020] \quad p_{in} = a_{in} \ln \left(\frac{|r-r_{in}|}{r_0} \right) + b_{in} \ln \left(\frac{|r-r_{pr}|}{r_0} \right) + c_{in} \quad (\text{Equation 1})$$

$$[0021] \quad p_{pr} = a_{pr} \ln \left(\frac{|r-r_{pr}|}{r_0} \right) + b_{pr} \ln \left(\frac{|r-r_{in}|}{r_0} \right) + c_{pr} \quad (\text{Equation 1.1})$$

[0022] where r_{in} and r_{pr} are the radius-vectors of the centers of the injection and production well, respectively, and r_0 is the well radius, assumed to be the same for both wells. Significant differences of physical properties of the injection liquid and oil are accounted by the fact that the coefficients a_{in} , b_{in} and c_{in} for the injection zone are different from the corresponding coefficients for the expansion coefficients in the production zone a_{pr} , b_{pr} and c_{pr} . These coefficients are found from the continuity conditions at the front and the reservoir boundary:

[0023] In one embodiment, pressures at the well-reservoir boundary (sandface) p_i^e and p_p^e are found from solving the fluid dynamics problems in the wells and used to determine constants in Equations 1 and 1.1 according to the following equations:

$$[0024] \quad |r - r_{in}| = r_0, \quad |r - r_{pr}| = d : \quad p_{in} = p_i^e \quad (\text{Equation 2})$$

$$[0025] \quad |r - r_{pr}| = r_0, \quad |r - r_{in}| = d : \quad p_{pr} = p_p^e \quad (\text{Equation 2.1})$$

$$[0026] \quad p_p^e = b_{pr} \ln\left(\frac{d}{r_0}\right) + c_{pr}; \quad p_i^e = b_{in} \ln\left(\frac{d}{r_0}\right) + c_{in} \quad (\text{Equation 2.2})$$

[0027] where d is the distance between the wells, which is assumed to be much larger than their radii. In addition, in certain embodiments, a pressure value at the reservoir boundary p_B is used to determine constants in Equations 1 and 1.1 according to the following equations:

$$[0028] \quad |r - r_{pr}| = r_B : \quad p_{pr} = p_B \quad (\text{Equation 3})$$

$$[0029] \quad p_B = a_{pr} \ln\left(\frac{r_B}{r_0}\right) + b_{pr} \ln\left(\frac{r_B}{r_0}\right) + c_{pr} \quad (\text{Equation 3.1})$$

[0030] In one embodiment, the pressure is set to be continuous across the displacement front based on the following set of equations:

$$[0031] \quad |r - r_{in}| = y, \quad |r - r_{pr}| = d - y : \quad p_{in} = p_{pr} \quad (\text{Equation 4})$$

$$[0032] \quad a_{in} \ln\left(\frac{y}{r_0}\right) + b_{in} \ln\left(\frac{d-y}{r_0}\right) + c_{in} = a_{pr} \ln\left(\frac{d-y}{r_0}\right) + b_{pr} \ln\left(\frac{y}{r_0}\right) + c_{pr} \quad (\text{Equation 4.1})$$

[0033] where y is the distance between the front and the center injection well along the line connecting the centers of the wells. In one embodiment, the front velocity written in terms of each of the expressions for pressure (as expressed in Equations 1 and 1.1) is assumed to be the same and is determined based on the following set of equations:

$$[0034] \quad V_f = V_{fi} = V_{fp} \quad (\text{Equation 5})$$

$$[0035] \quad V_{fi} = -\frac{k_0 k'_{in}}{\phi \Delta S_{in} \mu_{in}} n \cdot \nabla p_{in}; \quad V_{fp} = -\frac{k_0 k'_{pr}}{\phi \Delta S_0 \mu_{pr}} n \cdot \nabla p_{in} \quad (\text{Equation 5.1})$$

$$[0036] \quad \frac{a_{in}}{y} - \frac{b_{in}}{d-y} = \gamma \left(\frac{b_{pr}}{y} - \frac{a_{pr}}{d-y} \right); \quad \gamma = \frac{k'_{pr} \mu_{in} \Delta S_{in}}{k'_{in} \mu_{pr} \Delta S_{pr}} \quad (\text{Equation 5.2})$$

$$[0037] \quad a_{in} = \gamma b_{pr} \Rightarrow b_{in} = \gamma a_{pr} \quad (\text{Equation 5.3})$$

[0038] where V_f is the front speed, k_0 and ϕ are the absolute permeability and porosity of the formation, k'_{in} and k'_{pr} are the relative permeabilities of injected liquid and oil, μ_{in} and μ_{pr} are the viscosities of these liquids, and ΔS_{in} and ΔS_{pr} are the saturation changes at the front for the injected liquid and oil. In one embodiment, the proportionality of coefficients a_{in} and b_{pr} is obtained by integrating Equation 5.1 along the contour representing the displacement front. Accounting for Equation 5.2, representing the equality of velocities V_{fi} and V_{fp} at the

intersection of the front and the line connecting producer and injector, results in the proportionality between the coefficients b_{in} and a_{pr} .

[0039] In one embodiment, the linear system of Equations 2-5 can be solved to find the coefficients a_{in} , b_{in} , c_{in} , a_{pr} , b_{pr} and c_{pr} , provided that the pressure distributions at the sandface
 5 $(r = r_0)$ of the injector and producer wells $p_i^e(z)$ and $p_p^e(z)$ are known. These distributions can be found by solving the following system of fluid dynamics equations for the flows in wells:

$$[0040] \frac{dq_i}{dz} = J_i; \quad q_i = \rho_i V_i A_i; \quad i = in, pr \quad (\text{Equation 6})$$

$$[0041] \frac{dp_i}{dz} = - \frac{1}{2D_i} f_{id} \rho_i V_i^2 \quad (\text{Equation 6.1})$$

$$[0042] J_{in} = \frac{cs_{or}^0}{L_{or}} \sqrt{2\rho_i f(z)(p_{in} - p_{in}^e)}; \quad p_{pr} = p_{pr}^e \quad (\text{Equation 6.2})$$

$$10 \quad [0043] f(z) = \left(\frac{s_{or} L_{or}}{s_{or}^0 L_{or}^0} \right)^2 \quad (\text{Equation 6.3})$$

[0044] where i is the index equal to in and pr for the injector and production well, respectively, ρ_i and V_i are the fluid density and average flow velocity, A_i and D_i are the wellbore cross-section area and diameter, q_i is the mass flow rate, f_{id} is the Darcy friction factor, s_{or} and L_{or} are the FCD orifice cross-section and spacing, respectively, with some
 15 default values s_{or}^0 and L_{or}^0 , and C is the orifice flow coefficient. Equations 6-6.3 describe a pair of horizontal injector and producer well. Due to the incompressibility of the liquids, the vertical case can be also considered within the frame of this model using a substitute

$$[0045] p_i \rightarrow p_i + \rho_i g z \quad (\text{Equation 7})$$

[0046] where g is the gravity acceleration.

20 [0047] In accordance with the disclosed embodiments, the FCD devices are installed only on the injection well, so the pressure inside the production well p_{pr} is the same as the sandface pressure p_{pr}^e in the formation immediately next to it. Function $f(z)$ characterizes the longitudinal variation of hole diameter or linear density of FCD devices. Increase of $f(z)$ results in reduction the pressure drop across the FCD and therefore increase of the local
 25 injection rates J_{in} at point z that can be determined, in one embodiment, using the below equation. These rates are related to the coefficients a_{in} and a_{pr} in Equations 1-1.1:

$$[0048] J_i = - \frac{2\pi k_0 k_i'}{\mu_{in}} a_i; \quad i = in, pr \quad (\text{Equation 8})$$

[0049] The disclosed process can then solve Equations 1-7 to find flow distribution inside and outside the wells for any given profile of the front $y(z)$ in the plane containing axes of both wells. However, in order to find the evolution of the front in time, in one embodiment, the disclosed process simultaneously solves the following equation with Equations 1-7:

$$5 \quad [0050] \quad \frac{dy}{dt} = -\frac{k_0 k'_{in}}{\varphi \Delta S_{in} \mu_{in}} \left(\frac{a_{in}}{y} - \frac{b_{in}}{d-y} \right) \quad (\text{Equation 9})$$

[0051] Equation 8 follows from the set of equations 5 for the front velocity V_f . Initially, the front coincides with the injector well surface in accordance with the below conditions:

$$[0052] \quad t = 0; \quad 0 \leq z \leq L; \quad y = r_0 \quad (\text{Equation 10})$$

[0053] where L is the well length, assumed to be the same for both the injection and the
10 production well. At a moment t_m , the front reaches the production well at some location z_1 :

$$[0054] \quad y(z_1, t_m) = d - r_0 \quad (\text{Equation 11})$$

[0055] Equation 11 is the condition of breakthrough at point z_1 . Due to pressure variations along the wells and inhomogeneity of the reservoir properties, the front does not reach the production well at other locations:

$$15 \quad [0056] \quad z \neq z_1: y(z, t_m) < d - r_0 \quad (\text{Equation 12})$$

[0057] In accordance with the disclosed embodiments, one goal of the optimized FCD placement is to find a such FCD distribution, characterized by the function $f(z)$, that the FCDs compensate the pressure drop and formation properties' variation, so that the displacement front approaches the production well uniformly:

$$20 \quad [0058] \quad t = t_m; \quad 0 \leq z \leq L: \quad y(z, t) = d - r_0 \quad (\text{Equation 13})$$

[0059] In one embodiment, the disclosed optimization algorithm uses the solution of the initial-boundary value problem (Equations 1-10) for finding the FCD distribution function $f(z)$ such, that the displacement front approaches the production well uniformly and condition/Equation 13 is fulfilled at a certain moment t_m .

25 [0060] For example, Figure 3 illustrates a flowchart depicting an example of computer-implemented method 300 for determining the optimum flow control device properties for an injection well that yields a uniform flooding front along the wellbore for maximizing the overall recovery of oil in accordance with the disclosed embodiments. The process 300 begins

at step 302 by using an initial uniform FCD placement $f(z) = 1$ (e.g., assume all FCDs are fully open) in accordance with Equation 14.

$$[0061] \quad f(z) = f_0(z) = 1; \quad 0 \leq z \leq L \quad (\text{Equation 14})$$

[0062] At step 304, the process determines the distribution of flow in the wellbore and front propagation until the injected volume reaches the production well. For instance, in one embodiment, the disclosed process determines the evolution of the displacement front $y(z, t)$ by integrating Equation 8 (e.g., using the Runge-Kutta integration method or other suitable integrations methods), while the distributions of pressure and flow rate in the wellbore are calculated at each time step using Equations 1-7. In one embodiment, the disclosed process stops the time integration at time $t = t_m$ when the below condition (Equation 15) is reached, where n is the iteration number.

$$[0063] \quad y^n(z, t_m) = d - r_0 \quad (\text{Equation 15})$$

[0064] The process at step 306 determines a point/location z_0 along the horizontal production length of the wellbore having the least front advance in accordance with the following condition/equation:

$$[0065] \quad y^1(z_0, t_m) = \min[y^1(z, t_m)]; \quad 0 \leq z \leq L \quad (\text{Equation 16})$$

[0066] In one embodiment, the point z_0 and the corresponding value of the FCD distribution function $f(z_0)$ remains fixed for all of the following iterations:

$$[0067] \quad f_n(z_0) = 1; \quad n = 1, 2, \dots \quad (\text{Equation 17})$$

[0068] where n is the iteration number.

[0069] At step 308, based on the results of step 304, the process modifies the FCD distribution function. For instance, in one embodiment, the disclosed process decreases values of the FCD distribution function at points where the front has advanced compared to position $z = z_0$. For example, in one embodiment, the process uses the following equation for performing the adjustment:

$$[0070] \quad f^{n+1}(z) = \left[\frac{y^n(z_0, t_m)}{y^n(z, t_m)} \right] f^n(z) \quad (\text{Equation 18})$$

[0071] The process at step 310, determines the axial variation Δ between the obtained final injected front shape and the target profile. For example, in one embodiment, the process uses the following equation for determining the axial variation Δ :

[0072] $\Delta = \max[y^{n+1}(z, t_m)] - \min[y^{n+1}(z, t_m)]; 0 \leq z \leq L$

(Equation 19)

[0073] At step 312, the process determines whether the axial variation Δ is within a predetermined convergence value (i.e., $\Delta < \varepsilon d$). For example, in one embodiment, the ε is of order 10^{-5} . In certain embodiments, the value of ε may vary or be determined by a user. If the deviation is not within the predetermined convergence value, the process returns to step 302 and repeats the disclosed process. However, if the deviation is within the predetermined convergence value, then process determines the corresponding function $f^{n+1}(z)$ that yields the optimized FCD properties, with process 300 terminating thereafter. In certain embodiments, if the wells are not parallel to each other, d (the distance between the wells) will depend on coordinate z , but the disclosed process remains applicable.

[0074] To help further describe the disclosed embodiments, Figures 4-7 illustrate a set of examples that demonstrate how the disclosed embodiments can be applied in various practical situations. In the given examples, the algorithm is configured to assume that the both injection and production horizontal wells have a diameter 0.114 m and a length 2500 m. A gap of $d = 100$ m separates the horizontal injector and producer wells. Water is chosen as the injection fluid with viscosity 10^{-3} Pa s, while the oil viscosity is equal to 0.15 Pa s. The reservoir absolute permeability is set to 0.1 Darcy and porosity to 0.07. The FCD default hole diameter D_{or}^0 is 3 mm with spacing L_{or}^0 equal to 12 m. The reservoir boundary pressure p_B is set as a constant value 5.4 bar, while the pressures at the toe of injector and producer are equal to 33.3 bar and 5.3 bar, respectively. One of ordinary skill in the art would recognize that the disclosed embodiments are not limited to the above example parameters and may vary depending on the actual parameters of a particular well.

[0075] The convergence of the disclosed process is illustrated by Figure 4, which depicts the final shape of the displacement front at maximum time $t = t_m$. The position $z = 0$ corresponds to the toe end of the wells. As described above, calculations at the first iteration are performed assuming uniform placement of FCD, which results in breakthrough at the heel ($z = L$). In the simulated example, the disclosed process/algorithm converges fast and at iteration 12, the flat shape of the front is achieved, indicating that the optimization is successful.

[0076] Figure 5 illustrates the corresponding FCD distribution function as indicated by line 1 in the graph. The depicted result, based the set of Equations 5-5.3, yields the optimized distribution of the FCD orifice diameter along the injection well, as indicated by line 1 in

Figure 6. The FCD diameter reduction at heel increases the hydrodynamic pressure drop across the FCD, which in turn reduces the injection rate in the area so that the resulting final displacement front shape is uniform.

[0077] Very often, the material properties of the formation change along the direction of the wells. Thus, in accordance with a second example of the disclosed embodiments, the disclosed process/algorithm is configured to assume that all parameters of the injection and production wells, as well as the liquid properties are the same as in Example 1, but the formation porosity ϕ changes stepwise as shown in Figure 7. The absolute permeability k_0 of reservoir is assumed to be proportional to the porosity and changes correspondingly, while all other parameters remain constant.

[0078] The increase of the reservoir permeability in the center of the domain results in the reduction of the pressure gradient in the area, which reduces the velocity of the displacement front according to Equation 5, while the ratio k_0/ϕ remains constant everywhere:

$$[0079] \quad V_f = - \frac{k_0 k'_{in}}{\phi \Delta S_{in} \mu_{in}} \frac{\partial p}{\partial y} \quad (\text{Equation 20})$$

[0080] Placement of FCDs with equal properties in such a situation would result in higher breakthrough risk in the beginning and end parts of the injection well. To compensate for this effect, the diameters of the FCDs in the middle part need to be increased compared to the side areas, as shown by line 2 in Figure 6. Accordingly, the FCD placement with this distribution of nozzle diameters, calculated by the disclosed process/algorithm, would result in uniform displacement front and least risk of water breakthrough.

[0081] Referring now to Figure 8, a block diagram illustrating one embodiment of a system 800 for implementing the features and functions of the disclosed embodiments is presented. The system 800 may be any type of computing device including, but not limited to, a desktop computer, a laptop, a server, a mainframe, a tablet, and a mobile device. The system 800 includes, among other components, a processor 802, memory 804, secondary storage unit 806, an input/output interface module 808, and a communication interface module 810.

[0082] The processor 802 may be any type microprocessor including single core and multi-core processors capable of executing instructions for performing the features and functions of the disclosed embodiments. The input/output interface module 808 enables the system 800 to receive user input (e.g., from a keyboard and mouse) and output information to one or more devices such as, but not limited to, printers, external data storage devices, and audio speakers.

The system 800 may optionally include a separate display module 812 to enable information to be displayed on an integrated or external display device. For instance, the display module 812 may include instructions or hardware (e.g., a graphics card or chip) for providing enhanced graphics, touchscreen, and/or multi-touch functionalities associated with one or
5 more display devices.

[0083] Memory 804 is volatile memory that stores currently executing instructions/data or instructions/data that are prefetched for execution. The secondary storage unit 806 is non-volatile memory for storing persistent data. The secondary storage unit 806 may be or include any type of data storage component such as a hard drive, a flash drive, or a memory card. In
10 one embodiment, the secondary storage unit 806 stores the computer executable code/instructions and other relevant data for enabling a user to perform the features and functions of the disclosed embodiments.

[0084] For example, in accordance with the disclosed embodiments, the secondary storage unit 806 may permanently store executable code/instructions 820 for performing the above-described flow control device optimization process. The instructions 820 associated with the
15 flow control device optimization process are then loaded from the secondary storage unit 806 to memory 804 during execution by the processor 802 for performing the disclosed embodiments. In addition, the secondary storage unit 806 may store other executable code/instructions and data 822 such as, but not limited to, a wellbore simulator application and/or a reservoir simulation application for use with the disclosed embodiments.
20

[0085] The communication interface module 810 enables the system 800 to communicate with the communications network 830. For example, the network interface module 808 may include a network interface card and/or a wireless transceiver for enabling the system 800 to send and receive data through the communications network 830 and/or directly with other
25 devices.

[0086] The communications network 830 may be any type of network including a combination of one or more of the following networks: a wide area network, a local area network, one or more private networks, the Internet, a telephone network such as the public switched telephone network (PSTN), one or more cellular networks, and wireless data
30 networks. The communications network 830 may include a plurality of network nodes (not depicted) such as routers, network access points/gateways, switches, DNS servers, proxy

servers, and other network nodes for assisting in routing of data/communications between devices.

[0087] For example, in one embodiment, the system 800 may interact with one or more servers 834 or databases 832 for performing the features of the disclosed embodiments. For instance, the system 800 may query the database 832 for well log information for creating a coupled wellbore-reservoir model in accordance with the disclosed embodiments. Further, in certain embodiments, the system 800 may act as a server system for one or more client devices or a peer system for peer to peer communications or parallel processing with one or more devices/computing systems (e.g., clusters, grids).

[0088] Accordingly, the disclosed embodiments provide a system and computer implemented method that is able to determine, using a numerical algorithm and simulation process, the optimum FCD placements or other properties such as, but not limited to, hole diameter, for FCDs on an injection well that yields a uniform flooding front along the wellbore to prevent the premature breakthrough of injection fluid.

[0089] One advantage of the disclosed embodiments is that it can be applied to coupled wellbore-reservoir simulations of various complexity levels. Another advantage is that the disclosed process is computationally efficient as it is optimized for a specific set of problems and is much simpler than a universal optimization method. In addition, the disclosed process exhibits an excellent convergence as it does not involve the Lagrange multipliers.

[0090] As stated above, a traditional approach for flow control device placement/optimization involves running multiple reservoir models and choosing the best design (which is usually good, but not optimal) from a set of simulations with different completion placements. In contrast, application of the disclosed embodiments would not only yield to the best placement/optimization design, but also substantially reduce the total computational effort.

[0091] In certain embodiments, the disclosed embodiments may be used to provide a very good initial guess for CPU-expensive simulations involving detailed 3D models (for example field reservoir simulations), thus saving days of simulation time. In one embodiment, the disclosed processes may be integrated into production simulation software package (e.g., NETool™). Moreover, the disclosed process is flexible enough to account for many physical phenomena and reservoir conditions that might be not captured by the reservoir simulator model but be seen in the formation from the log measurements. Additionally, in certain

embodiments, vertical-horizontal anisotropy of permeabilities can be accounted for by using effective permeabilities.

[0092] While specific details about the above embodiments have been described, the above hardware and software descriptions are intended merely as example embodiments and are not intended to limit the structure or implementation of the disclosed embodiments. For instance, although many other internal components of the system 800 are not shown, those of ordinary skill in the art will appreciate that such components and their interconnection are well known.

[0093] In addition, certain aspects of the disclosed embodiments, as outlined above, may be embodied in software that is executed using one or more processing units/components.

Program aspects of the technology may be thought of as “products” or “articles of manufacture” typically in the form of executable code and/or associated data that is carried on or embodied in a type of machine readable medium. Tangible non-transitory “storage” type media include any or all of the memory or other storage for the computers, processors or the like, or associated modules thereof, such as various semiconductor memories, tape drives, disk drives, optical or magnetic disks, and the like, which may provide storage at any time for the software programming.

[0094] Additionally, the flowchart and block diagrams in the figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods and computer program products according to various embodiments of the present invention. It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

[0095] In addition to the embodiments described above, many examples of specific combinations are within the scope of the disclosure, some of which are detailed below.

[0096] Example 1 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution

profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0097] Example 2 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0098] Example 3 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining

whether the axial variation is within a predetermined convergence value, wherein the predetermined convergence value is 10-5 of the distance between the injection well and the production well; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0099] Example 4 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0100] Example 5 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the

predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.

5 [0101] Example 6 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining
10 distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a
15 determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

20 [0102] Example 7 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining
25 distribution of flow in the injection well and front propagation until an injected volume reaches the production well, wherein the injection well and the production well are nonparallel; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between
30 obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0103] Example 8 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining
5 distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a
10 determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; determining the FCD properties for the injection well that yields the uniform flooding front along the production well; and wherein the axial variation is within the predetermined convergence value prior to fifteen iterations of
15 the loop.

[0104] Example 9 is a computer implemented method for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the method comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining
20 distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location; determining an axial variation between obtained final
25 injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a determination that the axial variation is within the predetermined
30 convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

[0105] Example 10 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0106] Example 11 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0107] Example 12 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value, wherein the predetermined convergence value is 10^{-5} of the distance between the injection well and the production well; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0108] Example 13 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and

determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0109] Example 14 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.

[0110] Example 15 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for

the injection well that yields the uniform flooding front along the production well determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

[0111] Example 16 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well, wherein the injection well and the production well are nonparallel; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0112] Example 17 is a system, comprising: at least one processor; and at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; determining the FCD properties for the

injection well that yields the uniform flooding front along the production well; and wherein the axial variation is within the predetermined convergence value prior to fifteen iterations of the loop.

[0113] Example 18 is a system, comprising: at least one processor; and at least one memory
5 coupled to the at least one processor, the at least one memory storing computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining
10 distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location; determining an axial variation between obtained final
15 injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a determination that the axial variation is within the predetermined
20 convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

[0114] Example 19 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a
25 uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well;
30 determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial

variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

5 [0115] Example 20 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of
10 instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location;
15 determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD
20 properties for the injection well that yields the uniform flooding front along the production well.

[0116] Example 21 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when
25 executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front
30 advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value, wherein the predetermined convergence value is 10-5 of the distance between the injection well and the production well; responsive to a

determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

5 [0117] Example 22 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of
10 instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is
15 within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for
20 the injection well that yields the uniform flooding front along the production well.

[0118] Example 23 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD
25 distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between
30 obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting

the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.

[0119] Example 24 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

[0120] Example 25 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well, wherein the injection well and the production well are nonparallel; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and

determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

[0121] Example 26 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop; responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; determining the FCD properties for the injection well that yields the uniform flooding front along the production well; and wherein the axial variation is within the predetermined convergence value prior to fifteen iterations of the loop.

[0122] Example 27 is non-transitory computer readable medium comprising computer executable instructions for determining FCD properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising: initializing a FCD distribution function to have a uniform FCD distribution profile; executing a loop of instructions that perform operations comprising: determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well; determining a reference location along a length of the injection well having a least front advance; adjusting the FCD distribution function by decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location; determining an axial variation between obtained final injected front shape and target profile; determining whether the axial variation is within a predetermined convergence value; responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop; responsive to a

determination that the axial variation is within the predetermined convergence value, exiting the loop; and determining the FCD properties for the injection well that yields the uniform flooding front along the production well, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.

- 5 [0123] While many specific example embodiments are described above, the above examples are not intended to be exhaustive or limit the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention. The scope of the claims is intended to broadly cover the disclosed embodiments and any such modification.

CLAIMS

- Claim 1. A computer implemented method for determining flow control device (FCD) properties for an injection well that yields a uniform flooding front along a production well, the method comprising:
- initializing a FCD distribution function to have a uniform FCD distribution profile;
 - executing a loop of instructions that perform operations comprising:
 - determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well;
 - determining a reference location along a length of the injection well having a least front advance;
 - adjusting the FCD distribution function;
 - determining an axial variation between obtained final injected front shape and target profile;
 - determining whether the axial variation is within a predetermined convergence value;
 - responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop;
 - responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and
 - determining the FCD properties for the injection well that yields the uniform flooding front along the production well.
- Claim 2. The computer implemented method of Claim 1, wherein adjusting the FCD distribution function comprises:
- decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location.
- Claim 3. The computer implemented method of Claim 1, wherein the predetermined convergence value is 10^{-5} of the distance between the injection well and the production well.

- Claim 4. The computer implemented method of Claim 1, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop.
- Claim 5. The computer implemented method of Claim 1, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.
- Claim 6. The computer implemented method of Claim 1, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.
- Claim 7. The computer implemented method of Claim 1, wherein the injection well and the production well are nonparallel.
- Claim 8. The computer implemented method of Claim 1, wherein the axial variation is within the predetermined convergence value prior to fifteen iterations of the loop.
- Claim 9. A system, comprising:
- at least one processor; and
 - at least one memory coupled to the at least one processor, the at least one memory storing computer executable instructions for determining flow control device (FCD) properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions comprises instructions for:
 - initializing a FCD distribution function to have a uniform FCD distribution profile;
 - executing a loop of instructions that perform operations comprising:
 - determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well;
 - determining a reference location along a length of the injection well having a least front advance;
 - adjusting the FCD distribution function;

determining an axial variation between obtained final injected front shape and target profile;
determining whether the axial variation is within a predetermined convergence value;
responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop;
responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and
determining the FCD properties for the injection well that yields the uniform flooding front along the production well.

- Claim 10. The system of Claim 9, wherein adjusting the FCD distribution function comprises decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location.
- Claim 11. The system of Claim 9, wherein the predetermined convergence value is 10^{-5} of the distance between the injection well and the production well.
- Claim 12. The system of Claim 9, wherein the reference location along the length of the injection well does not change during subsequent iterations of the loop.
- Claim 13. The system of Claim 9, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.
- Claim 14. The system of Claim 9, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.
- Claim 15. The system of Claim 9, wherein the injection well and the production well are nonparallel.
- Claim 16. The system of Claim 9, wherein the axial variation is within the predetermined convergence value prior to fifteen iterations of the loop.

- Claim 17. A non-transitory computer readable medium comprising computer executable instructions for determining flow control device (FCD) properties for an injection well that yields a uniform flooding front along a production well, the computer executable instructions when executed causes one or more machines to perform operations comprising:
- initializing a FCD distribution function to have a uniform FCD distribution profile;
 - executing a loop of instructions that perform operations comprising:
 - determining distribution of flow in the injection well and front propagation until an injected volume reaches the production well;
 - determining a reference location along a length of the injection well having a least front advance;
 - adjusting the FCD distribution function;
 - determining an axial variation between obtained final injected front shape and target profile;
 - determining whether the axial variation is within a predetermined convergence value;
 - responsive to a determination that the axial variation is not within the predetermined convergence value, repeating the loop;
 - responsive to a determination that the axial variation is within the predetermined convergence value, exiting the loop; and
 - determining the FCD properties for the injection well that yields the uniform flooding front along the production well.
- Claim 18. The non-transitory computer readable medium of Claim 17, wherein adjusting the FCD distribution function comprises decreasing values of the FCD distribution function at points where the front has advanced compared to the front at the reference location.
- Claim 19. The non-transitory computer readable medium of Claim 17, wherein determining the FCD properties includes determining various hole diameters of the FCDs along the length of the injection well.

Claim 20. The non-transitory computer readable medium of Claim 17, wherein determining the FCD properties includes determining placement of the FCDs along the length of the injection well.