

DESCRIPTION

A lightweight six-axis robotic arm (2 in Figure 1) is adopted to wash and clean the external walls of a building with a high pressure water spray nozzle (1 in Figure 1) mounted on the robotic arm's end-effector to spray the water onto the wall. The robotic arm is mounted on a mini-gondola (10 in Diagram) and hoisted by a pulley system with the controlling motor (9 in Figure 1) located within the mini-gondola, while another set of motor located on the pulley system (11 in Figure 1) at the roof-top end drives the mini-gondola to traverse laterally on a set of twin-rails on the roof-top of the building. The pulley system raises and lowers the mini-gondola in parallel to the external wall of the building to be cleaned, spraying water onto the wall in a vertical manner from top to bottom, column by column.

1. The lightweight six-axis robotic arm (2 in Figure 1)

The six-axis robotic arm is to be lightweight, and is coupled with a 3D camera and a spray nozzle (high pressure water spray) on its end effector. The 3D camera mounted on the robotic arm scans the wall area (approximately 1.2m by 1.2m) to be cleaned; a software program will then calculate the trajectory of the water spraying motion for the robotic-arm to carrying out the water spraying action.

The robotic arm is controlled (through a RS422 cable, TCP/IP) by an industrial PC (personal computer) (5 in Figure 1) mounted within the mini-gondola.

2. Adoption of mini-gondola (10 in Figure 1)

A specially designed mini-gondola, hoisted by a motor-driven pulley system with the controlling motor of the pulley system within the mini-gondola, is used to seat/house the robotic arm to carry out the cleaning of the external wall of a building. Four vacuum suction cups (7 in Figure 1) mounted on the mini-gondola helps to secure the mini-gondola to the wall when the mini-gondola/robotic arm makes a 'stop' for the cleaning process to be conducted. To have further securing of the mini-gondola - prevention of swaying motion - a tow line attached to the mini-gondola is used to secure the mini-gondola to the ground.

An onboard controller (4 in Figure 1) mounted on the mini-gondola manages and controls the distance between the mini-gondola and the wall to be cleaned. The measured distance is fed from the onboard controller to the Industrial PC (personal computer located within the mini-gondola), which then activates the robotic arm to start the cleaning process.

3. Motor-driven pulley system with controlling motor within the mini-gondola, and Industrial PC for roof-top controller

The controlling motor (9 in Figure 1) of the pulley system that hoists and lowers the mini-gondola in parallel to the external wall of the building to be cleaned is located within the mini-gondola. An Industrial PC (personal computer) located within the mini-gondola controls this controlling motor, hoisting and lowering the mini-gondola in the vertical height position (y-axis) to locate the position of the robotic arm (seated on the mini-gondola) for the cleaning process to be carried out. The Industrial PC also controls another motor (11 in Figure 1) that drives the mini-gondola to travel along the linear distance (x-axis), traversing along a set of twin-rails located on the roof-top of the building.

Water weight (12 in Figure 1) is used to counter balance the pulley system on the twin-rails.

4. The control (monitoring of water container level) and discharge of the water sprayed from the nozzle.

The water will be sprayed onto the wall with a high pressure water sprayer mounted on the end-effector of the robotic arm. An Industrial PC (personal computer) is used to monitor the water level within the water container (that supplies the water to the water sprayer) to ensure that water availability is maintained.

5. The building facade cleaning sequence

The cleaning sequence will be from left of the building and moving towards the right as the motor-driven pulley system transverses itself in that direction. The water spray cleaning on the wall will be in a vertical manner from top to bottom, column by column ; once each column is being cleaned, the motor-driven pulley system will traverse to the right and make another 'stop' to clean the next following column.

6. Ground Controller

Through RS422 or RS485 (long distance serial communication), the industrial PC is also controlled by a remote electronic controller to allow the control of the motor-driven pulley system at the ground level.

CLAIMS (10)

(1) A lightweight six-axis robotic arm, coupled with a 3D camera and a spray nozzle on its end effector, is seated on a mini-gondola to carry out water spraying onto the external walls of a building to clean the walls.

(2) The use of an industrial PC (personal computer) located within the mini-gondola to control a motor-driven pulley system to hoist and lower the mini-gondola to locate the vertical location of the robotic arm (seated on the mini-gondola) for the cleaning process to be carried out.

(3) The controlling motor of the pulley system that hoists and lowers the mini-gondola in parallel to the external wall of the building to be cleaned, is located within the mini-gondola.

(4) The mini-gondola hangs on a motor-driven pulley system that traverses along a pair of rails, guiding the mini-gondola/robotic arm to travel along the linear distance (x-axis) for the cleaning process to be carried out.

(5) The use of four vacuum suction cups mounted respectively on each linear actuator to secure the mini-gondola to the wall when the robotic arm makes a 'stop' for the cleaning process to be conducted ; the suction cups are controlled by an industrial PC (personal computer) located within the mini-gondola.

(6) The use of three ultrasonic distance sensors mounted on each linear actuator on the mini-gondola to measure and manage the distance between the mini-gondola and the wall that is to be cleaned ; the distance measured will then be fed back to an industrial PC (personal computer located on the pulley system that hoists the mini-gondola) which controls the distance between the mini-gondola and the wall to be cleaned ; four vacuum suction cups on the mini-gondola will then be activated to secure the mini-gondola to the wall.

(7) Once the mini-gondola is 'secured' to the wall, a 3D camera mounted on the robotic arm will be activated to scan the wall area to be cleaned ; a software program will calculate the trajectory path of the water spraying motion for the robotic-arm to carrying out the water spraying cleaning action.

(8) The use of a pair of facade protection wheel (6 in Figure 1) on the mini-gondola to cushion any impact of the mini-gondola made on the facade of the wall to be cleaned.

(9) The use of an Industrial PC (personal computer) to control a controller located on the roof-top to monitor the water level within the water container to ensure that water availability is maintained.

(10) The use of water weight for counter balancing on the motor-driven pulley system.