

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/024423 A2

(51) International Patent Classification⁷: **B29C 65/44**

(21) International Application Number:
PCT/EP2003/050605

(22) International Filing Date:
2 September 2003 (02.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0211394 13 September 2002 (13.09.2002) FR

(71) Applicant (for all designated States except US): **ITT
MANUFACTURING ENTERPRISES, INC.** [US/US];
1105 North Market Street, Wilmington 19801 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BRICAUD, Hervé**
[FR/FR]; 166, avenue Eisenhower, F-39100 DOLE (FR).
FERRATON, David [FR/FR]; 6, rue des Vergers, F-39100
CRISSEY (FR). **PIZARD, Yves** [FR/FR]; 106, avenue
Georges Pompidou, F-39100 DOLE (FR).

(74) Agent: **KOHN, Philippe**; CABINET PHILIPPE KOHN,
30, rue Hoche, F-93500 PANTIN (FR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii)) for all designations

Published:

— without international search report and to be republished
upon receipt of that report

[Continued on next page]

(54) Title: TRACKBALL DEVICE FOR CONTROLLING AN ELECTRONIC APPARATUS, AND PRODUCTION PROCESS



(57) Abstract: The invention proposes a device (20) of the type comprising a generator of control signals which comprises a mobile contact rod (70T) which is elastically restored by a spiral torsion spring (50T) whose cylindrical body (48T) is accommodated in the housing and whose second axial end (54T) is immobilized, characterized in that the span of second axial end of the spring is accommodated in a duct (46L, 46T) of the housing with at least one turn of this span which is thermowelded into the concave wall (47L, 47T) of the duct so as to immobilize it in rotation. According to the process, the thermowelding is carried out by heating by Joule effect of the turns by means of two electrodes (E1, E2).

WO 2004/024423 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.