

DESCRIPTION

Title of Invention: FLUSH WATER TANK APPARATUS AND FLUSH
TOILET APPARATUS PROVIDED WITH THE SAME

5 Technical Field

[0001]

The present invention relates to a flush water tank
apparatus and, in particular, to a flush water tank apparatus
that supplies flush water to a flush toilet, and a flush
10 toilet apparatus provided with the flush water tank apparatus.

Background Art

[0002]

In Japanese Patent Laid-Open No. 2009-257061 (PTL 1),
a low tank apparatus is described. In this low tank
15 apparatus, a hydraulic cylinder device having a piston and
a drain unit is arranged inside a low tank provided with a
discharge valve, and the piston and the discharge valve are
coupled via a coupling unit. At the time of discharging
flush water in the low tank, water is supplied to the
20 hydraulic cylinder device by opening a solenoid valve, and
the piston is pushed up. Since the piston is connected to
the discharge valve via the coupling unit, the discharge
valve is pulled up by movement of the piston, the discharge
valve is opened, and the flush water in the low tank is
25 discharged. The water supplied to the hydraulic cylinder
device flows out from the drain unit and flows into the low
tank.

[0003]

Furthermore, in the case of causing the discharge valve
30 to be closed, supply of water to the hydraulic cylinder

device is stopped by causing the solenoid valve to be closed. Thereby, the pushed-up piston descends, and, accompanying this, the solenoid valve returns to a valve closed position due to its own weight. At this time, since the water in the hydraulic cylinder device flows out from the drain unit little by little, the piston slowly descends, and the discharge valve gradually returns to the valve closed position. Further, in the low tank apparatus described in PTL 1, a time during which the discharge valve is opened is changed by adjusting a time during which the solenoid valve is open, and, thereby, washings with different amounts of flush water, such as large washing and small washing, are realized.

Citation List

15 Patent Literature

[0004]

PTL 1: Japanese Patent Laid-Open No. 2009-257061

Summary of Invention

20 Technical Problem

[0005]

The low tank apparatus described in PTL 1, however, has a problem that it is difficult to accurately set the amount of flush water to be discharged. In other words, since water in the hydraulic cylinder device flows out from the drain unit little by little after the solenoid valve is closed to cause the discharge valve to be closed, in the low tank apparatus described in PTL 1, descent of the piston is gradual, and it is difficult to set the time during which the discharge valve is open short. Further, since the

descent speed of the piston is dependent on the outflow rate of the water from the drain unit and sliding resistance of the piston, there is a possibility that variation occurs, and there is a possibility that change over time occurs.

5 Therefore, it is difficult to accurately set the amount of flush water to be discharged, in the low tank apparatus described in PTL 1.

[0006]

Therefore, an object of the present invention is to
10 provide a flush water tank apparatus capable of accurately setting the amount of flush water to be discharged while opening the discharge valve using water pressure of supplied water, and a flush toilet apparatus provided with the flush water tank apparatus.

15 Solution to Problem

[0007]

In order to solve the problem described above, the present invention is a flush water tank apparatus for supplying flush water to a flush toilet, the flush water
20 tank apparatus including: a storage tank storing flush water to be supplied to the flush toilet, with a drain port for discharging the stored flush water to the flush toilet formed therein; a discharge valve opening/closing the drain port and performing supply/stop of the flush water to the flush
25 toilet; a discharge valve hydraulic drive unit driving the discharge valve using water supply pressure of supplied tap water; a clutch mechanism coupling the discharge valve and the discharge valve hydraulic drive unit to pull up the discharge valve by driving force of the discharge valve
30 hydraulic drive unit, and being disconnected at a

predetermined timing to cause the discharge valve to descend;
flush water amount selection means capable of selecting
between a first amount of flush water for washing the flush
toilet and a second amount of flush water smaller than the
5 first amount of flush water; a first float device including
a first float moved according to a water level in the storage
tank and a first engaging member capable of moving to an
engaging position of engaging with the discharge valve to
hold the discharge valve and a non-engaging position of not
10 engaging with the discharge valve in conjunction with
movement of the first float; a second float device including
a second float moved according to the water level in the
storage tank and a second engaging member capable of moving
to an engaging position of engaging with the discharge valve
15 and a non-discharging position of not engaging with the
discharge valve in conjunction with movement of the second
float and causing the second engaging member to move to the
non-engaging position at a height different from a height at
which the first float causes the first engaging member to
20 move to the non-engaging position; and a float driving
mechanism driving the first float to cause the first engaging
member to move to the non-engaging position when the second
amount of flush water is selected by the flush water amount
selection means; wherein

25 by the first engaging member of the first float device
being moved to the non-engaging position, the discharge valve
engages with the second engaging member of the second float
device.

[0008]

30 In the present invention configured as described above,

flush water to be supplied to the flush toilet is stored in the storage tank with the drain port formed thereon. The discharge valve hydraulic drive unit drives the discharge valve using water supply pressure of supplied tap water, and performs supply/stop of flush water to the flush toilet. The clutch mechanism couples the discharge valve and the discharge valve hydraulic drive unit to pull up the discharge valve by driving force of the discharge valve hydraulic drive unit. Further, the clutch mechanism is disconnected at a predetermined timing, and, thereby, the discharge valve is caused to descend. As for an amount of flush water to wash the flush toilet, the first amount of flush water or the second amount of flush water smaller than the first amount of flush water is selected by the flush water amount selection means. Furthermore, the first engaging member of the first float device is moved to the engaging position or the non-engaging position. At the engaging position, the first engaging member engages with the discharge valve and holds the discharge valve. The second engaging member of the second float device is configured to hold the discharge valve at a height different from a height by the first float device. When the second amount of flush water is selected, the float driving mechanism drives the first float to cause the first engaging member to move to the non-engaging position. As a result, the discharge valve is engaged with the second engaging member of the second float device.

[0009]

According to the present invention configured as described above, since the discharge valve and the discharge valve hydraulic drive unit are coupled by the clutch

mechanism and disconnected at a predetermined timing, it becomes possible to cause the discharge valve to move irrespective of the operation speed of the discharge valve hydraulic drive unit and cause the discharge valve to be closed. Thereby, it becomes possible to, even if the operation speed of the discharge valve hydraulic drive unit varies at the time of causing the discharge valve to descend, control the timing of causing the discharge valve to be closed without being influenced by the variation. Further, since the float driving mechanism drives the first float to cause the first engaging member to move to the non-engaging position, it is possible to selectively cause the first float device or the second float device to operate according to a selected amount of flush water. Thereby, it is possible to set the first or second amount of flush water using the clutch mechanism.

[0010]

In the present invention, preferably, the first float device is configured to hold the discharge valve at a position higher than a position at which the second float device holds the discharge valve, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-engaging position before the second engaging member is moved to the non-engaging position in conjunction with the second float.

[0011]

According to the present invention configured as described above, the first float device is configured to hold the discharge valve at a position higher than a position by the second float device, and the float driving mechanism

drives the first float to cause the first engaging member to move to the non-engaging position. Therefore, when the float driving mechanism does not normally operate, the discharge valve is held by the first float device, and the first amount of flush water larger than the second amount of flush water is discharged. As a result, even if a malfunction occurs in the float driving mechanism, it does not happen that the flush toilet lacks the amount of flush water, and the flush toilet can be washed.

10 [0012]

In the present invention, preferably, the clutch mechanism is configured to be disconnected at a position higher than a height at which the first engaging member of the first float device and the discharge valve engage with each other, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-engaging position before the discharge valve descends to the height at which the first engaging member and the discharge valve engage with each other.

20 [0013]

According to the present invention configured as described above, the float driving mechanism causes the first engaging member to move to the non-engaging position before the discharge valve descends to the height at which the first engaging member and the discharge valve engage with each other. Therefore, the discharge valve disconnected by the clutch mechanism descends to the second float device without engaging with the first float device and is held by the second float device. Thereby, it is possible to, when the second amount of flush water is selected, cause the discharge

valve to be held by the second float device smoothly and more certainly.

[0014]

5 In the present invention, preferably, the clutch mechanism is configured to pull up the discharge valve from the drain port, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-engaging position before the discharge valve is pulled up to the height at which the first engaging member of the first float and the discharge valve engage with each other.

[0015]

15 According to the present invention configured as described above, the first engaging member is moved to the non-engaging position before the discharge valve is pulled up to the height at which the first engaging member of the first float device and the discharge valve engage with each other. Therefore, it does not happen that the discharge valve and the first engaging member come into contact with each other even when the discharge valve is pulled up from the drain port by the clutch mechanism, and it is possible to cause the discharge valve to be held by the second float device more certainly.

[0016]

25 In the present invention, preferably, the float driving mechanism is configured to, after the clutch mechanism is disconnected, keep the first engaging member at the non-engaging position until the discharge valve descends below the height at which the first engaging member of the first float device and the discharge valve engage with each other.

other.

[0017]

According to the present invention configured as described above, the first engaging member is kept at the non-engaging position until the discharge valve descends below the height at which the first engaging member of the first float device and the discharge valve engage with each other. Therefore, after the clutch mechanism is disconnected, the discharge valve can descend below the first float device without engaging with the first engaging member, and it is possible to cause the discharge valve to be held by the second float device smoothly and more certainly.

[0018]

In the present invention, preferably, the float driving mechanism is configured to drive the first float using the supplied tap water.

According to the present invention configured as described above, since the float driving mechanism drives the first float using supplied tap water, it is possible to cause the float driving mechanism to operate, without separately providing a power source for driving the first float.

[0019]

In the present invention, preferably, the float driving mechanism includes a control jet unit jetting, when the second amount of flush water is selected by the flush water amount selection means, flush water from a jet port to a water receiving surface provided on the first float device, which is a timing control mechanism, so that a timing of the drain port being blocked is earlier than a case of the first

amount of flush water being selected.

[0020]

In the present invention configured as described above, flush water to be supplied to the flush toilet is stored in the storage tank with the drain port formed thereon. The
5 discharge valve hydraulic drive unit drives the discharge valve using water supply pressure of supplied tap water, and performs supply/stop of flush water to the flush toilet. The clutch mechanism couples the discharge valve and the
10 discharge valve hydraulic drive unit to pull up the discharge valve by driving force of the discharge valve hydraulic drive unit. Further, the clutch mechanism is disconnected at a predetermined timing, and, thereby, the discharge valve is caused to descend. As for an amount of flush water to wash
15 the flush toilet, the first amount of flush water or the second amount of flush water smaller than the first amount of flush water is selected by the flush water amount selection means. The control jet unit jets flush water to the water receiving surface provided on the first float
20 device and, when the second amount of flush water is selected, causes the drain port to be blocked earlier than the case of the first amount of flush water being selected.

[0021]

According to the present invention configured as
25 described above, since the discharge valve and the discharge valve hydraulic drive unit are coupled by the clutch mechanism and disconnected at a predetermined timing, it becomes possible to cause the discharge valve to move irrespective of the operation speed of the discharge valve
30 hydraulic drive unit and cause the discharge valve to be

closed. Thereby, it becomes possible to, even if the operation speed of the discharge valve hydraulic drive unit varies at the time of causing the discharge valve to descend, control the timing of causing the discharge valve to be
5 closed without being influenced by the variation. Further, since, by the control jet unit jetting flush water to the water receiving surface of the first float device, the discharge valve is caused to descend early to block the drain port, it is possible to set the first or second amount of
10 flush water using the clutch mechanism.

[0022]

In the present invention, preferably, the jet port of the control jet unit is provided being oriented to face the water receiving surface of the timing control mechanism.

15 According to the present invention configured as described above, since the jet port of the control jet unit is oriented to face the water receiving surface of the first float device, it is possible to effectively give kinetic energy of water jetted from the jet port of the control jet
20 unit to the water receiving surface. Therefore, in comparison with a case where the jet port is not oriented to face the water receiving surface of the first float device, it is possible to cause the first float device to operate by jetting a smaller amount of water from the jet port of the
25 control jet unit.

[0023]

In the present invention, preferably, the jet port of the control jet unit is formed with an area smaller than an area of the water receiving surface of the first float device.

30 According to the present invention configured as

described above, since the area of the jet port of the control jet unit is smaller than the area of the water receiving surface of the first float device, it is possible to receive water by the water receiving surface while
5 suppressing dissipation of kinetic energy of water jetted from the jet port. Thereby, it is possible to cause the first float device to efficiently operate.

[0024]

In the present invention, preferably, the control jet
10 unit is provided with a straight pipe portion connected to the jet port, and turbulence of flush water jetted through the jet port is suppressed by the straight pipe portion.

According to the present invention configured as described above, since the straight pipe portion connected
15 to the jet port is provided, turbulence of flush water jetted from the jet port is suppressed. Thereby, directivity of flush water jetted from the control jet unit is improved; the jetted flush water does not easily splash; and it is possible to cause the first float device to efficiently
20 operate.

[0025]

In the present invention, preferably, the jet port of the control jet unit is arranged to jet flush water downward.

According to the present invention configured as
25 described above, since the control jet unit jets flush water downward, the flow velocity of flush water jetted from the jet port is increased by the gravity, and greater energy can be given to the water receiving surface of the first float device. Thereby, it is possible to cause the first float
30 device to operate more certainly.

[0026]

In the present invention, preferably, the water receiving surface of the first float device is arranged to be submerged in flush water stored in the storage tank, and
5 the control jet unit jets flush water to the submerged water receiving surface.

[0027]

According to the present invention configured as described above, since the water receiving surface of the
10 first float device is submerged in flush water, it is possible to suppress splash of flush water that is jetted from the control jet unit and hits the water receiving surface. When a large amount of flush water jetted from the control jet unit splashes, equipment in the storage tank,
15 such as the clutch mechanism, may malfunction, or a strange sound may be caused. According to the present invention configured as described above, it is possible to prevent malfunction of the equipment in the storage tank and occurrence of a strange sound.

20 [0028]

In the present invention, preferably, the jet port of the control jet unit is arranged to be submerged in flush water stored in the storage tank and jets flush water to the submerged water receiving surface of the first float device.

25 [0029]

According to the present invention configured as described above, since the jet port of the control jet unit is arranged to be submerged, and flush water hits the submerged water receiving surface, it is possible to suppress
30 a sound caused at the time of flush water being jetted from

the jet port and a sound at the time of the jetted flush water hitting the water receiving surface.

[0030]

5 In the present invention, preferably, the water receiving surface of the first float device is provided with a wall surface surrounding a collision point at which flush water jetted from the control jet unit hits.

10 According to the present invention configured as described above, since the wall surface is provided on the water receiving surface surrounding the collision point at which flush water hits, it becomes difficult for the flush water hitting the water receiving surface to escape from the water receiving surface, and it is possible to transmit kinetic energy of the flush water to the water receiving
15 surface more effectively.

[0031]

In the present invention, preferably, the first float device includes a first holding mechanism switchable between a holding state and a non-holding state in conjunction with
20 the movement of the first float; the first holding mechanism includes an arm member rotatably supported by a support shaft, one end of the arm member being coupled with the first float; and the control jet unit jets flush water toward the water receiving surface formed on an upper surface of the first
25 float, and the jetted flush water collides against a side away from the support shaft relative to a center line of the first float in a plan view.

[0032]

In the present invention configured as described above,
30 the arm member coupled with the first float is rotatably

supported by the support shaft. Further, flush water jetted from the control jet unit hits the water receiving surface formed on the upper surface of the first float. According to the present invention configured as described above, since
5 jetted flush water collides against the side away from the support shaft relative to the center line of the first float in a plan view, it is possible to increase the moment of force around the support shaft, which acts by the flush water colliding. Thereby, even when the force of flush water
10 jetted from the control jet unit toward the water receiving surface is relatively weak, the first holding mechanism can be switched to the non-holding state.

[0033]

Further, the present invention is a flush toilet
15 apparatus provided with a plurality of washing modes with different amounts of flush water, the flush toilet apparatus including a flush toilet and a flush water tank apparatus of the present invention performing supply of flush water to the flush toilet.

20 Advantageous Effects of Invention

[0034]

According to the present invention, it is possible to provide a flush water tank apparatus capable of accurately setting the amount of flush water to be discharged while
25 opening a discharge valve by a discharge valve hydraulic drive unit, and a flush toilet apparatus provided with the flush water tank apparatus.

Brief Description of Drawings

[0035]

30 FIG. 1 is a perspective view showing an overall flush

toilet apparatus provided with a flush water tank apparatus according to an embodiment of the present invention;

FIG. 2 is a sectional view showing a schematic configuration of the flush water tank apparatus according to the embodiment of the present invention;

FIG. 3 is a diagram schematically showing a configuration and operation of a clutch mechanism provided in the flush water tank apparatus according to the embodiment of the present invention;

FIG. 4 is a diagram showing enlargingly a portion of a discharge valve, a first float device and a second float device provided for the flush water tank apparatus according to the embodiment of the present invention;

FIG. 5 is a diagram showing operation in a large washing mode of the flush water tank apparatus according to the embodiment of the present invention;

FIG. 6 is a diagram showing the operation in the large washing mode of the flush water tank apparatus according to the embodiment of the present invention;

FIG. 7 is a diagram showing the operation in the large washing mode of the flush water tank apparatus according to the embodiment of the present invention;

FIG. 8 is a diagram showing the operation in the small washing mode of the flush water tank apparatus according to the embodiment of the present invention; and

FIG. 9 is a diagram showing the operation in the small washing mode of the flush water tank apparatus according to the embodiment of the present invention.

Description of Embodiments

[0036]

Next, a flush toilet apparatus according to an embodiment will be described with reference to accompanying drawings.

5 FIG. 1 is a perspective view showing an overall flush toilet apparatus provided with a flush water tank apparatus according to an embodiment of the present invention. FIG. 2 is a sectional view showing a schematic configuration of the flush water tank apparatus according to the embodiment
10 of the present invention.

[0037]

As shown in FIG. 1, a flush toilet apparatus 1 according to the embodiment of the present invention is configured with a flush toilet main body 2, which is a flush
15 toilet, and a flush water tank apparatus 4 according to the embodiment of the present invention, which is placed at the back of the flush toilet main body 2. The flush toilet apparatus 1 of the present embodiment is configured so that washing of a bowl 2a of the flush toilet main body 2 is
20 performed by a remote controller 6 attached to a wall surface being operated after use or by a predetermined time having passed after a human sensor 8 provided on a toilet seat detecting a user leaving the toilet seat. The flush water tank apparatus 4 according to the present embodiment is
25 configured to discharge flush water stored inside to the flush toilet main body 2 based on an instruction signal from the remote controller 6 or the human sensor 8 and wash the bowl 2a by the flush water.

[0038]

30 Further, "large washing" or "small washing" for

washing the bowl 2a is executed by the user pressing a push button 6a on the remote controller 6. Therefore, in the present embodiment, the remote controller 6 functions as flush water amount selection means capable of selecting
5 between a first amount of flush water for washing the flush toilet main body 2 and a second amount of flush water smaller than the first amount of flush water. Note that, though the human sensor 8 is provided on the toilet seat in the present embodiment, the present invention is not limited to this
10 form. The human sensor 8 is only required to be provided at a position where it is possible to detect the user's motions of sitting on, standing from, approach to and leaving from the toilet seat, and holding his hand. For example, the human sensor 8 may be provided on the flush toilet main body
15 2 or the flush water tank apparatus 4. Further, the human sensor 8 may be anything that can detect the user's motions of sitting on, standing from, approach to and leaving from the toilet seat, and holding his hand, and, for example, an infrared sensor or a microwave sensor can be used as the
20 human sensor 8.

[0039]

As shown in FIG. 2, the flush water tank apparatus 4 has a storage tank 10 for storing flush water to be supplied to the flush toilet main body 2, a discharge valve 12 for
25 opening/closing a drain port 10a provided on the storage tank 10, and a discharge valve hydraulic drive unit 14 that drives the discharge valve 12. Further, the flush water tank apparatus 4 has a water supply control valve 16 that controls water supply into the discharge valve hydraulic
30 drive unit 14 and the storage tank 10, a solenoid valve 18

attached to the water supply control valve 16 inside the storage tank 10. Furthermore, the flush water tank apparatus 4 has a control jet unit 20 that jets flush water to control the amount of flush water, a flush water amount control valve 22 for supplying flush water to the control jet unit 20, and a solenoid valve 24 attached to the flush water amount control valve 22 inside the storage tank 10. Further, the flush water tank apparatus 4 has a first float device 26 for holding the pulled-up discharge valve 12 at a first position, and a second float device 28 for holding the discharge valve 12 at a second position lower than the first position. Furthermore, the flush water tank apparatus 4 has a clutch mechanism 30, and the clutch mechanism 30 couples the discharge valve 12 and the discharge valve hydraulic drive unit 14 to pull up the discharge valve 12 by driving force of the discharge valve hydraulic drive unit 14.

[0040]

The storage tank 10 is a tank configured to store flush water to be supplied to the flush toilet main body 2, and the drain port 10a for discharging the stored flush water to the flush toilet main body 2 is formed on a bottom portion of the storage tank 10. Inside the storage tank 10, an overflow pipe 10b is connected to the downstream side of the drain port 10a. The overflow pipe 10b vertically rises from near the drain port 10a and extends above a stopped water level WL of the flush water stored in the storage tank 10. Therefore, flush water that has flowed in from the upper end of the overflow pipe 10b bypasses the drain port 10a and flows out directly to the flush toilet main body 2.

[0041]

The discharge valve 12 is a valve body arranged so as to open/close the drain port 10a. The discharge valve 12 is opened by being pulled upward, and flush water in the storage tank 10 is discharged to the flush toilet main body 2, so that the bowl 2a is washed. The discharge valve 12 is pulled up by driving force of the discharge valve hydraulic drive unit 14. When the discharge valve 12 is pulled up to a predetermined height, the clutch mechanism 30 is disconnected, and the discharge valve 12 descends due to its own weight. When the discharge valve 12 descends, the discharge valve 12 is held for a predetermined time by the first float device 26 or the second float device 28 so that a time required for the discharge valve 12 to seat on the drain port 10a is adjusted.

15 [0042]

The discharge valve hydraulic drive unit 14 is configured to utilize water supply pressure of flush water supplied from a tap water pipe to drive the discharge valve 12. Specifically, the discharge valve hydraulic drive unit 14 has a cylinder 14a into which water supplied from the water supply control valve 16 flows, a piston 14b slidably arranged in the cylinder 14a, and a rod 32 that projects from the lower end of the cylinder 14a to drive the discharge valve 12.

25 [0043]

Furthermore, a spring 14c is arranged inside the cylinder 14a and energizes the piston 14b downward. A packing 14e is attached to the piston 14b so that watertightness between the inner wall surface of the cylinder 14a and the piston 14b is ensured. Furthermore, the clutch

mechanism 30 is provided at the lower end of the rod 32, and the rod 32 and a valve stem 12a of the discharge valve 12 are coupled/released by the clutch mechanism 30.

[0044]

5 The cylinder 14a is a cylindrical-shaped member, which is arranged with its axis in the vertical direction and accepts the piston 14b inside in a slidable state. A drive unit water supply passage 34a is connected to a lower end portion of the cylinder 14a so that water flowing out of the
10 water supply control valve 16 flows into the cylinder 14a. Therefore, the piston 14b in the cylinder 14a is pushed up against energizing force of the spring 14c by the water flowing into the cylinder 14a.

[0045]

15 On an upper part of the cylinder 14a, an outflow hole is provided, and a drive unit discharge passage 34b communicates with the inside of the cylinder 14a via the outflow hole. Therefore, when water flows into the cylinder 14a from the drive unit water supply passage 34a connected
20 to a lower part of the cylinder 14a, the piston 14b is pushed upward from the lower part of the cylinder 14a which is a first position. Then, when the piston 14b is pushed up to a second position above the outflow hole, the water that flowed into the cylinder 14a flows through the drive unit
25 discharge passage 34b from the outflow hole. In other words, when the piston 14b is moved to the second position, the drive unit water supply passage 34a and the drive unit discharge passage 34b are caused to communicate with each other via the inside of the cylinder 14a. At a distal end
30 portion of the drive unit discharge passage 34b extending

from the cylinder 14a, a discharge passage branch portion 34c is provided. The drive unit discharge passages 34b branched at the discharge passage branch portion 34c are configured so that one of them causes water to flow out into the storage tank 10 and the other causes water to flow out into the overflow pipe 10b. Therefore, a part of flush water flowing out from the cylinder 14a is discharged to the flush toilet main body 2 through the overflow pipe 10b, and the remaining flush water is stored in the storage tank 10.

10 [0046]

The rod 32 is a rod-shaped member connected to the lower surface of the piston 14b. The rod 32 passes through a through hole 14f formed in the bottom surface of the cylinder 14a and extends in a manner of projecting downward from inside the cylinder 14a. Between the rod 32 projecting downward from the cylinder 14a and the inner wall of the through hole 14f of the cylinder 14a, a gap 14d is provided, and a part of water flowing into the cylinder 14a flows out from the gap 14d. The water flowing out from the gap 14d flows into the storage tank 10. Note that, since the gap 14d is relatively narrow, and flow channel resistance is large, pressure inside the cylinder 14a increases due to the water flowing into the cylinder 14a from the drive unit water supply passage 34a even in the state of water flowing out from the gap 14d, and the piston 14b is pushed up, being against the energizing force of the spring 14c.

[0047]

The water supply control valve 16 is configured to control water supply to the discharge valve hydraulic drive unit 14 based on operation of the solenoid valve 18 and

control supply/stop of water to the storage tank 10. That is to say, the water supply control valve 16 is provided with a main valve body 16a, a main valve port 16b opened/closed by the main valve body 16a, a pressure chamber
5 16c for causing the main valve body 16a to move, and two pilot valves 16d, 16e for switching pressure in the pressure chamber 16c.

[0048]

The main valve body 16a is configured so as to
10 open/close the main valve port 16b of the water supply control valve 16. When the main valve port 16b is opened, tap water supplied from a water supply pipe 38 flows into the discharge valve hydraulic drive unit 14. The pressure chamber 16c is provided adjacent to the main valve body 16a
15 in a case of the water supply control valve 16. The pressure chamber 16c is configured so that a part of the tap water supplied from the water supply pipe 38 flows in so that internal pressure increases. When the pressure in the pressure chamber 16c increases, the main valve body 16a is
20 moved toward the main valve port 16b, and the main valve port 16b is closed.

[0049]

The pilot valves 16d, 16e are configured to open/close pilot valve ports (not shown) provided for the pressure
25 chamber 16c. When the pilot valve ports (not shown) are opened by the pilot valves 16d, 16e, water in the pressure chamber 16c flows out, and the internal pressure decreases. When the pressure in the pressure chamber 16c decreases, the main valve body 16a leaves from the main valve port 16b, and
30 the water supply control valve 16 is opened. Since the two

pilot valves 16d and 16e are provided for the pressure chamber 16c, the pressure in the pressure chamber 16c rises when both of the pilot valves 16d and 16e are opened, and the water supply control valve 16 is closed.

5 [0050]

The pilot valve 16d is moved by the solenoid valve 18 attached to the pilot valve 16d to open/close the pilot valve port (not shown). The solenoid valve 18 is connected to a controller 40 and causes the pilot valve 16d to move, based
10 on a command signal from the controller 40. Specifically, the controller 40 receives a signal from the remote controller 6 or the human sensor 8 and sends an electrical signal to the solenoid valve 18 to cause the solenoid valve 18 to operate.

15 [0051]

To the pilot valve 16e, a float switch 42 is connected. The float switch 42 is configured to control the pilot valve 16e based on a water level in the storage tank 10 to open/close a pilot valve port (not shown). In other words,
20 when the water level in the storage tank 10 reaches a predetermined water level, the float switch 42 sends a signal to the pilot valve 16e to cause the pilot valve port (not shown) to be closed. In other words, the float switch 42 is configured to set the water storage level in the storage
25 tank 10 to the predetermined stopped water level WL. The float switch 42 is arranged in the storage tank 10 and is configured to, when the water level in the storage tank 10 increases to the stopped water level WL, stop water supply from the water supply control valve 16 to the discharge valve
30 hydraulic drive unit 14.

[0052]

Further, the drive unit water supply passage 34a between the water supply control valve 16 and the discharge valve hydraulic drive unit 14 is provided with a vacuum
5 breaker 36. When negative pressure occurs on the water supply control valve 16 side, backflow of water to the water supply control valve 16 side is prevented by the vacuum breaker 36.

[0053]

10 The flush water amount control valve 22 is configured to control water supply to the control jet unit 20 based on operation of the solenoid valve 24. Though the flush water amount control valve 22 is connected to the water supply pipe 38 via the water supply control valve 16, tap water
15 supplied from the water supply pipe 38 always flows into the flush water amount control valve 22 irrespective of whether the water supply control valve 16 is open or closed. The flush water amount control valve 22 is provided with a main valve body 22a, a pressure chamber 22b and a pilot valve 22c,
20 and the pilot valve 22c is opened/closed by the solenoid valve 24. When the pilot valve 22c is opened by the solenoid valve 24, the main valve body 22a of the flush water amount control valve 22 is opened, and tap water flowing in from the water supply pipe 38 is supplied to the control jet unit
25 20 and jetted downward into the storage tank 10. Further, the solenoid valve 24 is connected to the controller 40 and causes the pilot valve 22c to move, based on a command signal from the controller 40. Specifically, the controller 40 sends an electrical signal to the solenoid valve 24 based on
30 an operation of the remote controller 6 to cause the solenoid

valve 24 to operate.

[0054]

Further, a duct between the flush water amount control valve 22 and the control jet unit 20 is provided with a vacuum breaker 44. When negative pressure is generated on the flush water amount control valve 22 side, backflow of water to the flush water amount control valve 22 side is prevented by the vacuum breaker 44.

[0055]

Water supplied from the tap water pipe is supplied to each of the water supply control valve 16 and the flush water amount control valve 22 via a stop cock 38a arranged outside the storage tank 10 and a fixed flow valve 38b arranged on the downstream side of the stop cock 38a in the storage tank 10. The stop cock 38a is provided to stop supply of water to the flush water tank apparatus 4 at the time of maintenance and the like, and is usually used in an open state. The fixed flow valve 38b is provided to cause water supplied from the tap water pipe to flow into the water supply control valve 16 and the flush water amount control valve 22 at a predetermined flow rate, and is configured so that water at a certain flow rate is supplied irrespective of the installation environment of the flush toilet apparatus 1.

[0056]

Next, a configuration and operation of the clutch mechanism 30 will be described, newly referring to FIG. 3.

FIG. 3 schematically shows the configuration of the clutch mechanism 30 and shows operation at the time of being pulled up by the discharge valve hydraulic drive unit 14.

[0057]

First, as shown in FIG. 3(a), the clutch mechanism 30 is provided at the lower end of the rod 32 extending downward from the discharge valve hydraulic drive unit 14, and is
5 configured so as to couple/release the lower end of the rod 32 and the upper end of the valve stem 12a of the discharge valve 12. The clutch mechanism 30 has a rotary shaft 30a attached to the lower end of the rod 32, a hook member 30b supported by the rotary shaft 30a, and an engaging claw 30c
10 provided at the upper end of the valve stem 12a.

[0058]

The rotary shaft 30a is attached at the lower end of the rod 32 in the horizontal direction and supports the hook member 30b in a rotatable state. The hook member 30b is a
15 plate-shaped member, and an intermediate part of the hook member 30b is rotatably supported by the rotary shaft 30a. The lower end of the hook member 30b is bent in a hook shape to form a hook portion. The engaging claw 30c provided on the upper end of the valve stem 12a of the discharge valve
20 12 is a claw in a right-angle triangular shape. The base of the engaging claw 30c is almost in the horizontal direction, and the side face is formed to be sloped downward.

[0059]

In the state shown in FIG. 3(a), the discharge valve
25 12 seats on the drain port 10a, and the drain port 10a is blocked. In this state, the discharge valve hydraulic drive unit 14 and the discharge valve 12 are coupled. In this coupled state, the claw portion of the hook member 30b is engaged with the base of the engaging claw 30c, and the
30 discharge valve 12 can be pulled up by the rod 32.

[0060]

Next, as shown in FIG. 3(b), when flush water is supplied to the discharge valve hydraulic drive unit 14, the piston 14b moves upward, and, accordingly, the discharge valve 12 is pulled up by the rod 32. Furthermore, as shown in FIG. 3(c), when the discharge valve 12 is pulled up to a predetermined position, the upper end of the hook member 30b comes into contact with the bottom surface of the discharge valve hydraulic drive unit 14, and the hook member 30b is rotated around the rotary shaft 30a. By this rotation, the claw portion at the lower end of the hook member 30b is moved in a direction of disengaging from the engaging claw 30c, and engagement between the hook member 30b and the engaging claw 30c is released. When the engagement between the hook member 30b and the engaging claw 30c is released, the discharge valve 12 descends toward the drain port 10a in flush water stored in the storage tank 10 as shown in FIG. 3(d). (Note that, as described later, the descended discharge valve 12 is temporarily held at a predetermined height by the first float device 26 or the second float device 28 before seating on the drain port 10a.)

[0061]

Furthermore, as shown in FIG. 3(e), when flush water supplied to the discharge valve hydraulic drive unit 14 is stopped, the rod 32 descends due to the energizing force of the spring 14c. When the rod 32 descends, the distal end of the hook member 30b attached to the lower end of the rod 32 comes into contact with the engaging claw 30c as shown in FIG. 3(f). When the rod 32 descends more, the claw portion of the hook member 30b is pushed by the sloped surface of

the engaging claw 30c as shown in FIG. 3(g), and the hook member 30b is rotated. When the rod 32 descends more, the claw portion of the hook member 30b gets over the engaging claw 30c, the hook member 30b is rotated to the original position by the gravity, and the claw portion of the hook member 30b and the engaging claw 30c engage with each other again as shown in FIG. 3(h) and return to the state shown in FIG. 3(a).

[0062]

Next, configurations and operations of the first float device 26 and the second float device 28 will be described, newly referring to FIG. 4. FIG. 4 is a diagram enlargingly showing the portion of the discharge valve 12, the first float device 26 and the second float device 28 in FIG. 2. A state in which the discharge valve 12 is closed is shown in FIG. 4(a), and a state in which the discharge valve 12 is open and held by the first float device 26 is shown in FIG. 4(b).

[0063]

As shown in FIG. 4, the first float device 26 has a first float 26a and a first holding mechanism 46 that supports the first float 26a in a rotatable state.

The first float 26a is a hollow rectangular parallelepiped member and is configured to receive buoyancy from flush water stored in the storage tank 10. When the water level in the storage tank 10 is a predetermined water level or above, the first float 26a is in the state shown by solid lines in FIG. 4(a) due to the buoyancy.

[0064]

The first holding mechanism 46 is a mechanism that

supports the first float 26a in a rotatable state and has a support shaft 46a, and an arm member 46b and a first engaging member 46c supported by the support shaft 46a. The support shaft 46a is a rotary shaft fixed to the storage tank 10 by an arbitrary member (not shown) and supports the arm member 46b and the first engaging member 46c in a rotatable state. At a proximal end portion of the valve stem 12a of the discharge valve 12, a holding claw 12b formed to be engageable with the first engaging member 46c is formed.

The holding claw 12b is a projection in a right-angle triangular shape, which extends toward the first engaging member 46c from the proximal end portion of the valve stem 12a. Its base is in the horizontal direction, and its side face is formed to be sloped downward.

[0065]

The support shaft 46a is a shaft extending in a direction orthogonal to the surface of FIG. 4. Both of its end portions are fixed to the storage tank 10 by an arbitrary member (not shown), and an intermediate part is formed being curved to be away from the valve stem 12a. The arm member 46b is a beam-shaped member that is bent, and its lower end portion is configured to branch into two. These branched lower ends of the arm member 46b are rotatably supported by both end portions of the support shaft 46a, respectively. Therefore, even when the discharge valve 12 is moved in the vertical direction, it does not happen that the support shaft 46a and the arm member 46b interfere with the holding claw 12b provided on the valve stem 12a of the discharge valve 12.

[0066]

An upper end portion of the arm member 46b is fixed to the bottom surface of the first float 26a. Therefore, in a state of receiving buoyancy, the first float 26a is held in the state shown by the solid lines in FIG. 4(a). When the water level in the storage tank 10 drops, the first float 26a and the arm member 46b are rotated around the support shaft 46a due to their own weights up to a state shown by imaginary lines in FIG. 4(a). Note that the rotation of the first float 26a and the arm member 46b is restricted to a range between the holding state of the first holding mechanism 46 shown by the solid lines in FIG. 4(a) and the non-holding state shown by the imaginary lines.

[0067]

Furthermore, the first engaging member 46c is a member rotatably attached to the support shaft 46a, and its proximal end portion is rotatably supported by both end portions of the support shaft 46a. A distal end portion of the first engaging member 46c curvedly extends towards the valve stem 12a of the discharge valve 12. Therefore, in the state in which the first float 26a has been rotated to the position shown by the solid lines in FIG. 4(a), the first engaging member 46c is positioned at an engaging position. In comparison, in the state in which the first float 26a has been rotated to the position shown by the imaginary lines in FIG. 4(a), the first engaging member 46c is positioned at a non-engaging position.

[0068]

The first engaging member 46c is configured to be rotated around the support shaft 46a in conjunction with the arm member 46b. In other words, when the first float 26a

and the arm member 46b rotate from the state shown by the solid lines in FIG. 4(a) to the state shown by the imaginary lines, the first engaging member 46c is also rotated from the engaging position shown by the solid lines to the non-engaging position shown by the imaginary lines in conjunction with the arm member 46b. However, if the distal end of the first engaging member 46c is pushed upward by the holding claw 12b of the discharge valve 12 in the state shown by the solid lines in FIG. (a) of FIG. 4, only the first engaging member 46c can rotate idle. In other words, when the distal end portion of the first engaging member 46c is pushed upward by the holding claw 12b, only the first engaging member 46c can rotate to the position shown by the imaginary lines of FIG. 4 while the first float 26a and the arm member 46b keep holding the position shown by the solid lines.

[0069]

In the state in which the discharge valve 12 is pulled upward, and the holding claw 12b is positioned above the first engaging member 46c as shown by solid lines in FIG. 4(b), the first engaging member 46c existing at the engaging position and the holding claw 12b engage with each other, so that descent of the discharge valve 12 is hindered, and the discharge valve 12 is held. In other words, the first engaging member 46c constituting the first holding mechanism 46 engages with the discharge valve 12 and holds the discharge valve 12 at a predetermined height. Therefore, the discharge valve 12 is pulled up by the rod 32 (FIG. 3) connected to the discharge valve hydraulic drive unit 14, and, after that, the discharge valve 12 descends when the clutch mechanism 30 is disconnected. During the descent,

the holding claw 12b of the discharge valve 12 and the first engaging member 46c existing at the engaging position engage with each other, and the discharge valve 12 is held at the predetermined height.

5 [0070]

Then, when the water level in the storage tank 10 drops, the position of the first float 26a descends, and the first float 26a and the arm member 46b rotate to the position shown by imaginary lines in FIG. 4(b) (in this state, the second
10 float device 28 has also been rotated to the position shown by the imaginary lines as described later). Since the first engaging member 46c is also rotated to the non-engaging position shown by the imaginary lines in FIG. 4(b) in conjunction with this rotation, engagement between the
15 holding claw 12b and the first engaging member 46c is released. Thereby, the discharge valve 12 descends and seats on the drain port 10a, and the drain port 10a is blocked.

[0071]

Further, as shown in FIG. 4(a), the control jet unit
20 20 is provided above the first float 26a. The control jet unit 20 is a nozzle configured to jet flush water vertically downward to the first float 26a, and a jet port 20a for jetting flush water is provided on the lower end. Further, a straight pipe portion 20b in a cylindrical shape is
25 provided at a lower end portion of the control jet unit 20, and the straight pipe portion 20b communicates with the jet port 20a. Disturbance of flush water jetted from the control jet unit 20 is suppressed by the flush water flowing in the straight pipe portion 20b with a circular cross section the
30 cross-sectional area of which is constant. Note that, when

water is still in the storage tank 10, distal end portions of the first float 26a and the control jet unit 20 are in a state of being submerged in the flush water. Therefore, flush water is jetted from the jet port 20a of the submerged control jet unit 20 toward the submerged first float 26a. [0072]

Furthermore, the flush water jetted from the control jet unit 20 hits an upper surface 26b of the first float 26a oriented to face the jet port 20a and acts to push down the first float 26a. Therefore, the upper surface 26b of the first float 26a functions as a water receiving surface where the flush water jetted from the control jet unit 20 hits. By causing flush water to be jetted from the control jet unit 20 and causing the flush water to hit the water receiving surface of the first float 26a, the first engaging member 46c of the first float device 26 is moved to the non-engaging position shown by the imaginary lines in FIG. 4 irrespective of the water level in the storage tank 10. Therefore, the control jet unit 20 functions as a float driving mechanism that causes the first engaging member 46c to move to the non-engaging position. Furthermore, in the present embodiment, the first float device 26 functions as a timing control mechanism for controlling a timing of the discharge valve 12 descending and the drain port 10a being blocked, and it is possible to control the timing of the drain port 10a being blocked by jetting flush water to the water receiving of the timing control mechanism. Further, since the area of the jet port 20a is formed smaller than the area of the upper surface 26b of the first float 26a, which is a water receiving surface, kinetic energy of water

jetted from the jet port 20a is received by the upper surface 26b without dissipation.

[0073]

Further, a wall surface 26c is provided on an outer
5 periphery of the upper surface 26b of the first float 26a. The wall surface 26c is provided surrounding a collision point P at which flush water jetted from the control jet unit 20 hits the upper surface 26b. Thereby, it becomes difficult for flush water hitting the upper surface 26b of
10 the first float 26a to escape from the upper surface 26b, and it is possible to transmit kinetic energy of the flush water to the upper surface 26b more effectively. The collision point P at which flush water hits the upper surface 26b is positioned on a side away from the support shaft 46a,
15 relative to a center line C of the first float 26a. Since flush water jetted from the control jet unit 20 collides against the side away from the support shaft 46a relative to the center line C of the first float 26a as described above, it is possible to increase the moment of force around the
20 support shaft 46a, which acts by the flush water colliding.

[0074]

Next, the second float device 28 will be described with reference to FIG. 4.

As shown in FIG. 4, the second float device 28 has a
25 second float 28a and a second holding mechanism 48 that supports the second float 28a in a rotatable state, and is arranged on an opposite side of the first float device 26, with the valve stem 12a of the discharge valve 12 between the second float device 28 and the first float device 26.

30 The second float 28a is a hollow rectangular

parallelepiped member and is configured to receive buoyancy from water stored in the storage tank 10. When the water level in the storage tank 10 is a predetermined water level or above, the second float 28a is in the holding state shown by the solid lines in FIG. 4(a) due to the buoyancy.

[0075]

The second holding mechanism 48 is a mechanism that supports the second float 28a in a rotatable state and has a support shaft 48a, and an arm member 48b and a second engaging member 48c supported by the support shaft 48a. The configuration and operation of the second holding mechanism 48 is similar to those of the first holding mechanism 46. The second engaging member 48c constituting the second holding mechanism 48 is arranged to engage with a holding claw 12c provided on the valve stem 12a of the discharge valve 12. The holding claw 12c is also a projection in a right-angle triangular shape similarly to the holding claw 12b with which the first engaging member 46c of the first holding mechanism 46 engages, and is formed on the valve stem 12a of the discharge valve 12 at the same height as the holding claw 12b. The second engaging member 48c is positioned at the engaging position when the second float 28a and the arm member 48b are in the state shown by the solid lines in FIG. 4, and is positioned at the non-engaging position when they are in the state shown by the imaginary lines.

[0076]

The support shaft 48a of the second holding mechanism 48 is arranged at a position lower than the support shaft 46a of the first holding mechanism 46. Therefore, the second

float device 28 holds the discharge valve 12 at a position different from a position by the first float device 26, a position lower than the position by the first float device 26. Furthermore, since the arm member 48b of the second holding mechanism 48 is formed longer than the arm member 46b of the first holding mechanism 46, the second float 28a is supported at a position higher than the first float 26a. Thereby, when the water level in the water storage tank 10 is low, the second float 28a is rotated to the position of the non-holding state shown by the imaginary lines in FIG. 4 earlier than the first float 26a.

[0077]

Next, a description will be made on operation of the flush water tank apparatus 4 according to the embodiment of the present invention and operation of the flush toilet apparatus 1 provided with the flush water tank apparatus 4, newly referring to FIGS. 5 to 9.

First, in the toilet washing standby state shown in FIG. 2, the water level in the storage tank 10 is at the predetermined stopped water level WL. In this state, both of the water supply control valve 16 and the flush water amount control valve 22 are closed. The first float device 26 and the second float device 28 are in the holding state shown by the solid lines in FIG. 4(a). Next, when the user pushes a large washing button on the remote controller 6 (FIG. 1), the remote controller 6 transmits an instruction signal for executing the large washing mode to the controller 40 (FIG. 2). When a small washing button is pushed, an instruction signal for executing the small washing mode is transmitted to the controller 40. Thus, in the present

embodiment, the flush toilet apparatus 1 is provided with the two washing modes, the large washing mode and the small washing mode with different amounts of flush water, and the remote controller 6 functions as the flush water amount selection means for selecting the amount of flush water.

[0078]

Note that, in the flush toilet apparatus 1 of the present embodiment, if a predetermined time passes without the washing button on the remote controller 6 not being pressed after it is detected by the human sensor 8 (FIG. 1) that the user has left the toilet seat, an instruction signal for toilet washing is also transmitted to the controller 40. Further, if a time from the user sitting on the toilet seat until leaving the toilet seat is shorter than a predetermined time, the controller 40 judges that the user has urinated and executes the small washing mode. On the other hand, if the time from sitting on the toilet seat until leaving the toilet seat is longer than the predetermined time, the controller 40 executes the large washing mode. Therefore, in this case, since the large washing for performing washing with the first amount of flush water or the small washing for performing washing with the second amount of flush water is selected by the controller 40, the controller 40 functions as the flush water amount selection means.

[0079]

Next, operation of the large washing mode will be described with reference to FIGS. 5 to 7.

When receiving an instruction signal to perform large washing, the controller 40 causes the solenoid valve 18 (FIG. 2) provided for the water supply control valve 16 to operate

to cause the pilot valve 16d on the solenoid valve side to leave from the pilot valve port. Thereby, the pressure in the pressure chamber 16c drops; the main valve body 16a leaves from the main valve port 16b; and the main valve port 16b is opened. Note that, when large washing is selected, the flush water amount control valve 22 is continuously in the closed state, and flush water is not jetted from the control jet unit 20. In other words, when large washing is selected, the first float 26a is not driven by the control jet unit 20 which is a float driving mechanism. When the water supply control valve 16 is opened, flush water flowing in from the water supply pipe 38 is supplied to the discharge valve hydraulic drive unit 14 via the water supply control valve 16 as shown in FIG. 5(a). Thereby, the piston 14b of the discharge valve hydraulic drive unit 14 is pushed up; the discharge valve 12 is pulled up via the rod 32; and flush water in the storage tank 10 is discharged from the drain port 10a to the flush toilet main body 2.

[0080]

When the discharge valve 12 is pulled up, the holding claw 12c provided on the valve stem 12a of the discharge valve 12 pushes up and rotates the second engaging member 48c of the second holding mechanism 48, and the holding claw 12c gets over the second engaging member 48c. When the discharge valve 12 is further pulled up, the holding claw 12b pushes up and rotates the first engaging member 46c of the first holding mechanism 46, and the holding claw 12b gets over the first engaging member 46c (FIG. 4(a)→FIG. 4(b)). Next, when the discharge valve 12 is further pulled up, the clutch mechanism 30 is disconnected as shown in FIG.

5(b). In other words, when the discharge valve 12 reaches a predetermined height, the upper end of the hook member 30b of the clutch mechanism 30 hits the bottom surface of the discharge valve hydraulic drive unit 14, and the clutch
5 mechanism 30 is disconnected (FIG. 3(b)→FIG. 3(c)).

[0081]

When the clutch mechanism 30 is disconnected, the discharge valve 12 starts to descend toward the drain port 10a due to its own weight. Here, since the water level in
10 the storage tank 10 is high immediately after the discharge valve 12 is opened, both of the first engaging member 46c of the first float device 26 and the second engaging member 48c of the second float device 28 are at the engaging positions shown by the solid lines in FIG. 4(b). Therefore, the
15 holding claw 12b of the discharge valve 12 that has descended engages with the first engaging member 46c of the first holding mechanism 46, and the discharge valve 12 is held at a predetermined height by the first float device 26. By the discharge valve 12 being held by the first float device 26,
20 the drain port 10a is kept in the open state, and discharge of flush water in the storage tank 10 to the flush toilet main body 2 is kept.

[0082]

Then, when the water level in the storage tank 10 drops
25 as shown in FIG. 6(a), the float switch 42 that detects the water level in the storage tank 10 is turned off. When the float switch 42 is turned off, the pilot valve 16e (FIG. 2) on the float switch side, which is provided for the water supply control valve 16, is opened. When the pilot valve
30 16e is opened, the controller 40 causes the solenoid valve

18 to operate to close the pilot valve 16d on the solenoid valve side. As described above, the main valve body 16a of the water supply control valve 16 is configured to be closed when both of the pilot valve 16e on the float switch side and the pilot valve 16d on the solenoid valve side are closed. Therefore, even after the pilot valve 16d on the solenoid valve side is closed, the open state of the water supply control valve 16 is kept, and water supply to the storage tank 10 is continued.

[0083]

Note that, though the pilot valve 16e is opened/closed based on a detection signal of the float switch 42 in the present embodiment, the present invention can be configured so that the pilot valve 16e is mechanically opened/closed by a ball tap instead of the float switch 42, as a modification. In this modification, the pilot valve 16e is opened/closed in conjunction with a float that moves up and down according to the water level in the storage tank 10. Meanwhile, in this modification, the pilot valve 16d on the solenoid valve side is closed after the water level in the water storage tank 10 drops after start of washing, and enough time for the pilot valve 16e to be opened passes.

[0084]

As shown in FIG. 6(a), when the water level in the storage tank 10 drops to a predetermined water level WL2, the position of the second float 28a supported by the second holding mechanism 48 descends. Thereby, the second engaging member 48c of the second float device 28 moves to the non-engaging position shown by the imaginary lines in FIG. 4(b).

Even in this state, the first engaging member 46c of the

first float device 26 is kept at the engaging position because the first float 26a is supported at a position lower than the second float 28a, and flush water in the storage tank 10 continues to be discharged.

5 [0085]

When the water level in the storage tank 10 further drops and reaches a predetermined water level WL1 lower than the predetermined water level WL2, the position of the first float 26a supported by the first holding mechanism 46 also drops as shown in FIG. 6(b). Thereby, the first engaging member 46c of the first float device 26 also moves to the non-engaging position shown by the imaginary lines in FIG. 4(b), and engagement between the first engaging member 46c and the holding claw 12b of the discharge valve 12 is released. By the first engaging member 46c moving to the non-engaging position, the discharge valve 12 starts to descend again.

[0086]

Thereby, the discharge valve 12 seats on the drain port 10a, and the drain port 10a is blocked as shown in FIG. 7(a). Thus, when the large washing mode is executed, the discharge valve 12 is held until the water level in the storage tank 10 drops from the stopped water level WL to the predetermined water level WL1, and the first amount of flush water is discharged to the flush toilet main body 2.

[0087]

Since the float switch 42 is still in the off state, the open state of the water supply control valve 16 is kept, and water supply to the storage tank 10 is continued. Flush water supplied to the storage tank 10 passes through the

discharge valve hydraulic drive unit 14 and reaches the discharge passage branch portion 34c (FIG. 2), and a part of the flush water branched at the discharge passage branch portion 34c flows into the overflow pipe 10b, and the remaining flush water is stored in the storage tank 10. The flush water flowing into the overflow pipe 10b flows into the flush toilet main body 2 and is used to refill the bowl 2a. By flush water flowing into the storage tank 10 in the state of the discharge valve 12 being closed, the water level in the storage tank 10 rises.

[0088]

When the water level in the storage tank 10 rises to the predetermined stopped water level WL as shown in FIG. 7(b), the float switch 42 is turned on. When the float switch 42 is turned on, the pilot valve 16e (FIG. 2) on the float switch side is closed. Thereby, both of the pilot valve 16e on the float switch side and the pilot valve 16d on the solenoid valve side enter the closed state. Therefore, the pressure in the pressure chamber 16c rises, the main valve body 16a of the water supply control valve 16 is closed, and water supply is stopped. When water supply to the discharge valve hydraulic drive unit 14 is stopped, the piston 14b of the discharge valve hydraulic drive unit 14 is pushed down by the energizing force of the spring 14c, and, simultaneously, the rod 32 descends. Thereby, the clutch mechanism 30 is connected (FIG. 3(e) to FIG. 3(h)), and the standby state before starting toilet washing is returned to.

[0089]

Next, operation of the small washing mode will be described with reference to FIG. 8, and FIG. 9.

When receiving an instruction signal to perform small washing, the controller 40 causes the solenoid valve 18 provided for the water supply control valve 16 to operate to open the water supply control valve 16. Furthermore, the controller 40 causes the solenoid valve 24 (FIG. 2) provided for the flush water amount control valve 22 to operate to also open the flush water amount control valve 22. When the water supply control valve 16 is opened, flush water flowing in from the water supply pipe 38 is supplied to the discharge valve hydraulic drive unit 14 via the water supply control valve 16 as shown in FIG. 8(a). Thereby, the piston 14b of the discharge valve hydraulic drive unit 14 is pushed up; the discharge valve 12 is pulled up via the rod 32; and flush water in the storage tank 10 is discharged from the drain port 10a to the flush toilet main body 2. Note that, when the discharge valve 12 is pulled up, the holding claw 12c (FIG. 4(a)) provided on the valve stem 12a of the discharge valve 12 pushes up and rotates the second engaging member 48c of the second holding mechanism 48, and the holding claw 12c gets over the second engaging member 48c.

[0090]

When the flush water amount control valve 22 is opened, flush water flowing in from the water supply pipe 38 passes through the flush water amount control valve 22 and is jetted downward from the control jet unit 20. Note that, since the distal end (the lower end) of the control jet unit 20 is positioned below the stopped water level WL of the storage tank 10, the control jet unit 20 jets flush water from the jet port 20a that is submerged (FIG. 4). The flush water jetted from the jet port 20a hits the upper surface 26b of

the first float 26a, which is a water receiving surface and is arranged to face the jet port 20a, and drives the first float 26a downward. Therefore, while flush water is jetted from the jet port 20a of the control jet unit 20, the first
5 float 26a is pushed down to the position shown by the imaginary lines in FIG. 4(a) irrespective of the water level in the water storage tank 10. As described above, the control jet unit 20, which is a float driving mechanism, drives the first float 26a using supplied tap water.

10 [0091]

In other words, as shown in FIG. 8(a), the first engaging member 46c of the first float device 26 is moved to the non-engaging position irrespective of the water level in the water storage tank 10, by flush water jetted from the
15 control jet unit 20. Note that, before the discharge valve 12 is pulled up to the height at which the first engaging member 46c of the first float device 26 and the holding claw 12b of the discharge valve 12 engage with each other, the first float 26a is driven by jet of flush water from the
20 control jet unit 20, and the first engaging member 46c is moved to the non-engaging position.

[0092]

Next, as shown in FIG. 8(b), when the discharge valve 12 is pulled up to a predetermined position, the clutch
25 mechanism 30 is disconnected. In other words, the clutch mechanism 30 is disconnected at a position higher than the height at which the first engaging member 46c of the first float device 26 and the discharge valve 12 engage with each other. Further, as described above, the first float 26a has
30 already been moved (pushed down) by flush water jetted from

the control jet unit 20, and the first engaging member 46c has been moved to the non-engaging position before the discharge valve 12 descends to the height at which the first engaging member 46c and the holding claw 12b of the discharge valve 12 engage with each other.

[0093]

When the clutch mechanism 30 is disconnected, the discharge valve 12 starts to descend toward the drain port 10a due to its own weight. Here, since the water level in the storage tank 10 is high immediately after the discharge valve 12 is opened, the second engaging member 48c of the second float device 28 is at the engaging position shown by the solid lines in FIG. 4(b). Meanwhile, the first engaging member 46c of the first float device 26 has been moved to the non-engaging position shown by the imaginary lines in FIG. 4(b) by jet of flush water from the control jet unit 20 as described above, and the state is kept. In other words, after the clutch mechanism 30 is disconnected, the first engaging member 46c is kept at the non-engaging position by jet of flush water from the control jet unit 20 until the discharge valve 12 descends below the height at which the first engaging member 46c of the first float device 26 and the holding claw 12b of the discharge valve 12 engage with each other. Therefore, the holding claw 12c of the discharge valve 12 that has descended engages with the second engaging member 48c of the second holding mechanism 48, and the discharge valve 12 is held at a predetermined height by the second holding mechanism 48.

[0094]

Here, when being held by the second holding mechanism

48, the discharge valve 12 is held at a position lower than the case of being held by the first holding mechanism 46. By the discharge valve 12 being held by the second holding mechanism 48, the drain port 10a is kept in the open state, and discharge of flush water in the storage tank 10 to the flush toilet main body 2 is kept. After the discharge valve 12 descends, and the holding claw 12b of the discharge valve 12 passes the first engaging member 46c of the first holding mechanism 46, the controller 40 sends a signal to the solenoid valve 24 (FIG. 2) at a predetermined timing to cause the flush water amount control valve 22 to be closed. Thereby, jet of flush water from the control jet unit 20 is stopped.

[0095]

Then, when the water level in the storage tank 10 drops as shown in FIG. 9(a), the float switch 42 that detects the water level in the storage tank 10 is turned off. When the float switch 42 is turned off, the pilot valve 16e (FIG. 2) on the float switch side, which is provided for the water supply control valve 16, is opened. When the pilot valve 16e is opened, the controller 40 causes the solenoid valve 18 to operate to cause the pilot valve 16d on the solenoid valve side to be closed. Thereby, even after the pilot valve 16d on the solenoid valve side is closed, the open state of the water supply control valve 16 is kept, and water supply to the storage tank 10 is continued.

[0096]

As shown in FIG. 9(a), when the water level in the storage tank 10 drops, the position of the second float 28a supported by the second holding mechanism 48 drops. Thereby,

the second engaging member 48c of the second float device 28 moves to the non-engaging position shown by the imaginary lines in FIG. 4(b). Thereby, engagement between the second engaging member 48c and the holding claw 12c of the discharge valve 12 is released. In other words, before the second engaging member 48c is moved to the non-engaging position in conjunction with the second float 28a, the first float 26a has been driven by flush water jetted from the control jet unit 20, and the first engaging member 46c has been moved to the non-engaging position. Therefore, the discharge valve 12 does not engage with the first engaging member 46c but engages with the second engaging member 48c below the first engaging member 46c. Then, by the second engaging member 48c of the second float device 28 moving to the non-engaging position, the discharge valve 12 starts to descend again.

[0097]

Then, the discharge valve 12 seats on the drain port 10a, and the drain port 10a is blocked as shown in FIG. 9(b). Thus, when the small washing mode is executed, the discharge valve 12 is held until the water level in the storage tank 10 drops from the stopped water level WL to the predetermined water level WL2, and the second amount of flush water is discharged to the flush toilet main body 2. In the large washing mode, the discharge valve 12 is held until the water level in the water storage tank 10 descends to the predetermined water level WL1 lower than the predetermined water level WL2. Therefore, the second amount of flush water discharged from the storage tank 10 in the small washing mode is smaller than the first amount of flush water discharged in the large washing mode. In other words, in

the small washing mode, the first holding mechanism 46 is caused to be in the non-holding state by the control jet unit 20 jetting flush water to the first float 26a, and the discharge valve 12 is not held by the first holding mechanism 46 but held by the second holding mechanism 48. As a result, in the small washing mode, the discharge valve 12 is caused to descend earlier than the case of the large washing mode, and the amount of flush water is smaller.

[0098]

In the state of FIG. 9(b), since the float switch 42 is still in the off state, the open state of the water supply control valve 16 is kept, and water supply to the storage tank 10 is continued. By flush water flowing into the storage tank 10 in the state of the discharge valve 12 being closed, the water level in the storage tank 10 rises.

[0099]

Furthermore, when the water level in the storage tank 10 rises to the predetermined stopped water level WL, the float switch 42 is turned on, and the pilot valve 16e (FIG. 2) on the float switch side is closed. Thereby, both of the pilot valve 16e on the float switch side and the pilot valve 16d on the solenoid valve side enter the closed state. Therefore, the main valve body 16a of the water supply control valve 16 is closed, and water supply is stopped.

When water supply to the discharge valve hydraulic drive unit 14 is stopped, the piston 14b of the discharge valve hydraulic drive unit 14 is pushed down, and, at the same time, the rod 32 descends. Thereby, the clutch mechanism 30 is connected (FIG. 3(e) to FIG. 3(h)); the standby state before starting toilet washing is returned to (the state in

FIG. 7(b) is returned to); and the small washing mode is ended.

[0100]

According to the flush water tank apparatus 4 of the embodiment of the present invention, since the discharge valve 12 and the discharge valve hydraulic drive unit 14 are coupled by the clutch mechanism 30 and disconnected at a predetermined timing (FIG. 3), it becomes possible to cause the discharge valve 12 to move irrespective of the operation speed of the discharge valve hydraulic drive unit 14 and cause the discharge valve 12 to be closed. Further, since the control jet unit 20, which is a float driving mechanism, drives the first float 26a to cause the first engaging member 46c to move to the non-engaging position, it is possible to selectively cause the first float device 26 (in the case of large washing) or the second float device 28 (in the case of small washing) according to a selected amount of flush water. Thereby, it is possible to set the first or second amount of flush water using the clutch mechanism 30.

[0101]

Further, according to the flush water tank apparatus 4 of the present embodiment, the first float device 26 is configured to hold the discharge valve 12 at a position higher than a position by the second float device 28 (FIG. 4), and the float driving mechanism 20 drives the first float 26a to cause the first engaging member 46c to move to the non-engaging position (FIG. 8(a)). Therefore, when the control jet unit 20 does not normally operate, and the first float 26a cannot be pushed down, the discharge valve 12 is held by the first float device 26 similarly to the case of

large washing (Fig. 6(a)). As a result, when the control jet unit 20 does not normally operate, the first amount of flush water larger than the second amount of flush water is discharged. Thereby, even if a malfunction occurs in the control jet unit 20, it does not happen that the flush toilet main body 2 lacks the amount of flush water, and the flush toilet main body 2 can be certainly washed.

[0102]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, flush water from the control jet unit 20 causes the first engaging member 46c to move to the non-engaging position (FIG. 8(a)) before the discharge valve 12 descends to the height at which the first engaging member 46c and the discharge valve 12 engage with each other. Therefore, the discharge valve 12 disconnected by the clutch mechanism 30 descends to the second float device 28 without engaging with the first float device 26 and is held by the second float device 28 (FIG. 8(b)). Thereby, it is possible to, when the second amount of flush water is selected, cause the discharge valve 12 to be smoothly and certainly held by the second float device 28.

[0103]

Further, according to the flush water tank apparatus 4 of the present embodiment, the first engaging member 46c is moved to the non-engaging position (FIG. 8(a)) before the discharge valve 12 is pulled up to the height at which the first engaging member 46c of the first float device 26 and the discharge valve 12 engage with each other. Therefore, the discharge valve 12 and the first engaging member 46c do not come into contact with each other when the discharge

valve 12 is pulled up from the drain port 10a by the clutch mechanism 30, and it is possible to cause the discharge valve 12 to be held by the second float device 28 more certainly. [0104]

5 Furthermore, according to the flush water tank apparatus 4 of the present embodiment, the first engaging member 46c is kept at the non-engaging position (FIG. 8(b)) until the discharge valve 12 descends below the height at which the first engaging member 46c of the first float device
10 26 and the discharge valve 12 engage with each other. Therefore, after the clutch mechanism 30 is disconnected, the discharge valve 12 can descend below the first float device 26 without engaging with the first engaging member 46c, and it is possible to cause the discharge valve 12 to
15 be held by the second float device 28 smoothly and certainly. [0105]

 According to the flush water tank apparatus 4 of the present embodiment, since the control jet unit 20, which is a float driving mechanism, drives the first float 26a using
20 supplied tap water, it is possible to cause the control jet unit 20 to operate as a float driving mechanism, without separately providing a power source for driving the first float 26a. [0106]

25 According to the flush water tank apparatus 4 of the embodiment of the present invention, since the discharge valve 12 and the discharge valve hydraulic drive unit 14 are coupled by the clutch mechanism 30 and disconnected (FIG. 3) at a predetermined timing, it becomes possible to cause the
30 discharge valve 12 to move irrespective of the operation

speed of the discharge valve hydraulic drive unit 14 and cause the discharge valve 12 to be closed. Further, since, by the control jet unit 20 jetting flush water to the upper surface 26b (the water receiving surface) of the first float device 26 (FIG. 8(a)), the discharge valve 12 is caused to descend early to block the drain port 10a, it is possible to set the first or second amount of flush water using the clutch mechanism 30.

[0107]

According to the flush water tank apparatus 4 of the present embodiment, since the jet port 20a of the control jet unit 20 is oriented to face the upper surface 26b of the first float device 26 (FIG. 4), it is possible to effectively give kinetic energy of water jetted from the jet port 20a of the control jet unit 20 to the upper surface 26b of the first float 26a. Therefore, it is possible to, only by causing a small amount of water to be jetted from the jet port 20a of the control jet unit 20, cause the first float device 26 to certainly operate.

[0108]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, since the area of the jet port 20a of the control jet unit 20 is smaller than the area of the upper surface 26b of the first float 26a, kinetic energy of water jetted from the jet port 20a is received by the upper surface 26b without dissipation. Thereby, it is possible to cause the first float device 26 to efficiently operate.

[0109]

According to the flush water tank apparatus 4 of the

present embodiment, since the straight pipe portion 20b connected to the jet port 20a (FIG. 4) is provided, disturbance of flush water jetted from the jet port 20a is suppressed. Thereby, directivity of flush water jetted from the control jet unit 20 is improved, and it is possible to cause the first float device 26 to efficiently operate without the jetted flush water easily splashing.

[0110]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, since the control jet unit 20 jets flush water downward (FIG. 4), the flow velocity of flush water jetted from the jet port 20a is increased by the gravity, and greater energy can be given to the upper surface 26b of the first float device 26. Thereby, it is possible to cause the first float device 26 to certainly operate.

[0111]

According to the flush water tank apparatus 4 of the present embodiment, since the upper surface 26b of the first float device 26 is submerged in flush water (FIG. 8), it is possible to suppress splashing of flush water that is jetted from the control jet unit 20 and hits the upper surface 26b.

[0112]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, since the jet port 20a of the control jet unit 20 is arranged to be submerged, and flush water hits the submerged upper surface 26b, it is possible to suppress a sound at the time of flush water being jetted from the jet port 20a and a sound at the time of the jetted flush water hitting the upper surface 26b.

[0113]

According to the flush water tank apparatus 4 of the present embodiment, since the wall surface 26c (FIG. 4) is provided on the upper surface 26b of the first float device 5 26 to surround the collision point P at which flush water hits, it becomes difficult for the flush water hitting the upper surface 26b to escape from the upper surface 26b, and it is possible to transmit kinetic energy of the flush water to the upper surface 26b more effectively.

10 [0114]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, it is possible to switch between engagement (FIG. 5(b)) and non-engagement (FIG. 8(b)) between the first holding mechanism 46 and the 15 discharge valve 12 to switch the operation of the first float 26a. Thereby, it becomes possible to set a plurality of times during which the discharge valve 12 is open, using a float, and it becomes possible to accurately set the plurality of times during which the discharge valve 12 is 20 open, by a simple mechanism.

[0115]

According to the flush water tank apparatus 4 of the present embodiment, the second float 28a and the second holding mechanism 48 are provided which are configured to 25 hold the discharge valve 12 at a position lower than a position by the first float 26a and the first holding mechanism 46. In other words, when the first amount of flush water (large washing) is selected, the discharge valve 12 is held at a predetermined height by the first float 26a and 30 the first holding mechanism 46 (FIG. 5(b)). When the second

amount of flush water (small washing) is selected, the discharge valve 12 is held at a lower position by the second float 28a and the second holding mechanism 48 (FIG. 8(b)). Thereby, it is possible to accurately set the first or second amount of flush water using the first float 26a or the second float 28a.

[0116]

Furthermore, according to the flush water tank apparatus 4 of the present embodiment, the arm member 46b coupled with the first float 26a is rotatably supported by the support shaft 46a. Further, flush water jetted from the control jet unit 20 hits the water receiving surface formed on the upper surface 26b of the first float 26a. Since the flush water jetted from the control jet unit 20 collides against the side away from the support shaft 46a relative to the center line C of the first float 26a (FIG. 4(a)), it is possible to increase the moment of force around the support shaft 46a, which acts by the flush water colliding. Thereby, even when the force of flush water jetted from the control jet unit 20 toward the upper surface 26b is relatively weak, the first holding mechanism 46 can be switched to the non-holding state.

[0117]

The embodiment of the present invention has been described above. Various changes can be added to the embodiment described above.

In the embodiment described above, the first float device 26 and the second float device 28 are provided; and, when the small washing mode is executed, the control jet unit 20 jets flush water toward the first float 26a to cause

the first engaging member 46c of the first float device 26 to be forcedly moved to the non-engaging position. In comparison, as a first modification, a float driving member driven by pressure of supplied flush water, for example, a piston is provided above the first float 26a, and a rod is attached to the piston. The present invention can be configured so that the first float 26a is pushed down by this rod.

[0118]

In other words, when the small washing mode is executed, the float driving piston is caused to move, and the first float 26a is pushed down via the rod thereby to cause the first engaging member 46c to be forcedly moved to the non-engaging position. Thereby, the clutch mechanism 30 is disconnected, and the holding claw 12b of the descending discharge valve 12 does not engage with the first engaging member 46c of the first float device 26, but the holding claw 12c and the second engaging member 48c of the second float device 28 engage with each other. When the large washing mode is executed, the float driving piston is not caused to move, and the holding claw 12b of the discharge valve 12 is caused to engage with the first engaging member 46c of the first float device 26. Thereby, an amount of flush water is set by the second float device 28 when the small washing mode is selected, and an amount of flush water is set by the first float device 26 when the large washing mode is selected. In this modification, the float driving piston and the rod attached thereto function as a float driving mechanism.

[0119]

As a second modification, a water weight can be used instead of the float driving piston in the first modification. In other words, a small tank that is movable in the vertical direction is arranged in the storage tank 10, and a rod
5 extending downward is provided on the bottom surface of the small tank. Furthermore, the lower end of the rod extending from the small tank is caused to be in contact with the upper surface 26b of the first float 26a.

[0120]

10 When the small washing mode is selected, flush water is caused to flow into the small tank to make a water weight, and the first float 26a is forcibly pushed down by the weight of the water weight to cause the first engaging member 46c of the first float device 26 to move to the non-engaging
15 position. The clutch mechanism 30 is disconnected thereby, and the holding claw 12b of the descending discharge valve 12 does not engage with the first engaging member 46c of the first float device 26, but the holding claw 12c and the second engaging member 48c of the second float device 28
20 engage with each other. Note that a small hole is provided in a lower part of the small tank so that all flush water in the small tank flows out when a predetermined time has passed. On the other hand, when the large washing mode is executed, flush water is not caused to flow into the small tank, and
25 the holding claw 12b of the discharge valve 12 is caused to engage with the first engaging member 46c of the first float device 26. Thereby, an amount of flush water is set by the second float device 28 when the small washing mode is selected, and an amount of flush water is set by the first
30 float device 26 when the large washing mode is selected. In

this modification, the small tank and the rod attached thereto function as a float driving mechanism.

[0121]

Furthermore, as a third modification, a small tank and
5 a third float that receives buoyancy therein can be used instead of the float driving piston in the first modification. In other words, the small tank is fixed in the storage tank 10, and the third float that is movable in the vertical direction is arranged in the small tank. Furthermore, a
10 link mechanism is connected to the third float, and the link mechanism is configured so that the first float 26a is pushed downward when the third float floats in the small tank.

[0122]

When the small washing mode is selected, flush water
15 is caused to flow into the small tank to cause the third float to float, and the first float 26a is forcedly pushed down via the link mechanism by the buoyancy to cause the first engaging member 46c of the first float device 26 to move to the non-engaging position. Thereby, the clutch
20 mechanism 30 is disconnected, and the holding claw 12b of the descending discharge valve 12 does not engage with the first engaging member 46c of the first float device 26, but the holding claw 12c and the second engaging member 48c of the second float device 28 engage with each other. Note
25 that a small hole is provided in a lower part of the small tank so that all flush water in the small tank flows out when a predetermined time has passed, and the third float descends. On the other hand, when the large washing mode is executed, flush water is not caused to flow into the small
30 tank, and the holding claw 12b of the discharge valve 12 is

caused to engage with the first engaging member 46c of the first float device 26. Thereby, an amount of flush water is set by the second float device 28 when the small washing mode is selected, and an amount of flush water is set by the first float device 26 when the large washing mode is selected. In this modification, the small tank, the third float and the link mechanism connected to the third float function as a float driving mechanism.

[0123]

10 In the embodiment described above, the first float device 26 and the second float device 28 are provided; and, when the small washing mode is executed, the control jet unit 20 jets flush water toward the first float 26a to cause the first float 26a to be forcedly switched to the non-
15 holding state. In comparison, as a fourth modification, the present invention can be configured so that the control jet unit 20 jets flush water toward the clutch mechanism 30 to release the clutch mechanism 30. In other words, when the small washing mode is executed, by jetting flush water from
20 the control jet unit 20 toward the clutch mechanism 30 at a timing when the holding claw 12b of the discharge valve 12 is pulled up to a height between the height of the first engaging member 46c of the first float device 26 and the height of the second engaging member 48c of the second float
25 device 28, the clutch mechanism 30 is released. A configuration is made in which, when the large washing mode is executed, the clutch mechanism 30 is released at a timing when the holding claw 12b of the discharge valve 12 is pulled up above the first engaging member 46c of the first float
30 device 26. Thereby, when the small washing mode is selected,

the timing of the drain port 10a being blocked can be earlier than the case of the large washing mode being selected. In this modification, the clutch mechanism 30 also functions as a timing control mechanism, and a surface of the clutch mechanism 30 that receives jet of flush water from the control jet unit 20 functions as a water receiving surface. [0124]

As a fifth modification, the present invention can be configured so that only one float device is provided as a timing control mechanism. In other words, the flush water tank apparatus 4 is configured so that the discharge valve 12 is held by one float device no matter which of the large washing mode and the small washing mode is selected. Then, by jetting flush water from the control jet unit 20 toward a float at a predetermined timing, the float device is switched to the non-holding state. Furthermore, by, when the small washing mode is selected, jetting flush water from the control jet unit 20 earlier than the case of the large washing mode being selected, the timing of the drain port 10a being blocked when the small washing mode is selected can be earlier. In this modification, the single float device functions as a timing control mechanism, and a surface of the float device that receives jet of flush water from the control jet unit 20 functions as a water receiving surface. [0125]

Or alternatively, as a fifth modification, a configuration can be made in which a single float device is energized to be in the non-holding state, using a spring mechanism or the like. Then, by jetting flush water from

the control jet unit 20 to the spring mechanism, the float device is forcedly switched to the holding state against the energizing force of the spring mechanism. In this modification, by stopping jet of flush water from the control
5 jet unit 20, the float device can be switched to the non-holding state. Therefore, by, when the small washing mode is selected, stopping jet of flush water from the control jet unit 20 earlier than the case of the large washing mode being selected, the timing of the drain port 10a being
10 blocked can be earlier when the small washing mode is selected. In this modification, the spring mechanism functions as a timing control mechanism, and a surface of the spring mechanism that receives jet of flush water from the control jet unit 20 functions as a water receiving
15 surface.

[0126]

Furthermore, as a sixth modification, the present invention can be configured so that the clutch mechanism 30 is released at a predetermined timing by jet of flush water
20 from the control jet unit 20, without using a float mechanism. The control jet unit 20 is arranged to jet flush water toward the clutch mechanism 30. Furthermore, the clutch mechanism 30 is configured so that it is not released even when the discharge valve 12 is pulled up to the upper end but is
25 released when flush water from the control jet unit 20 hits. In this configuration, by, when the small washing mode is selected, jetting flush water from the control jet unit 20 earlier than the case of the large washing mode being selected, the timing of the drain port 10a being blocked
30 when the small washing mode is selected can be earlier. In

this modification, the clutch mechanism 30 also functions as a timing control mechanism, and a surface of the clutch mechanism 30 that receives jet of flush water from the control jet unit 20 functions as a water receiving surface.

5 [0127]

Or alternatively, as a sixth modification, a spring mechanism or the like configured to cause the clutch mechanism 30 to be forcedly released is provided, and the spring mechanism is configured not to be able to release the clutch mechanism 30 when flush water from the control jet unit 20 hits. In this modification, by stopping jet of flush water from the control jet unit 20, the spring mechanism can be switched to a state of being able to release the clutch mechanism 30. Therefore, by, when the small washing mode is selected, stopping jet of flush water from the control jet unit 20 earlier than the case of the large washing mode being selected, the timing of the drain port 10a being blocked can be earlier when the small washing mode is selected. In this modification, the spring mechanism functions as a timing control mechanism, and a surface of the spring mechanism that receives jet of flush water from the control jet unit 20 functions as a water receiving surface.

Reference Signs List

25 [0128]

- 1 flush toilet apparatus
- 2 flush toilet main body (flush toilet)
- 2a bowl
- 4 flush water tank apparatus
- 30 6 remote controller (flush water amount selection means)

6a push button
 8 human sensor
 10 storage tank
 10a drain port
 5 10b overflow pipe
 12 discharge valve
 12a valve stem
 12b holding claw
 12c holding claw
 10 14 discharge valve hydraulic drive unit
 14a cylinder
 14b piston
 14c spring
 14d gap
 15 14e packing
 14f through hole
 16 water supply control valve
 16a main valve body
 16b main valve port
 20 16c pressure chamber
 16d pilot valve
 16e pilot valve
 18 solenoid valve
 20 control jet unit (float driving mechanism)
 25 20a jet port
 20b straight pipe portion
 22 flush water amount control valve
 22a main valve body
 22b pressure chamber
 30 22c pilot valve

- 24 solenoid valve
- 26 first float device (timing control mechanism)
- 26a first float
- 26b upper surface (water receiving surface)
- 5 28 second float device
- 28a second float
- 30 clutch mechanism
- 30a rotary shaft
- 30b hook member
- 10 30c engaging claw
- 32 rod
- 34a drive unit water supply passage
- 34b drive unit discharge passage
- 34c discharge passage branch portion
- 15 36 vacuum breaker
- 38 water supply pipe
- 38a stop cock
- 40 controller (flush water amount selection means)
- 42 float switch
- 20 44 vacuum breaker
- 46 first holding mechanism
- 46a support shaft
- 46b arm member
- 46c first engaging member
- 25 48 second holding mechanism
- 48a support shaft
- 48b arm member
- 48c second engaging member

CLAIMS

1. A flush water tank apparatus for supplying flush water to a flush toilet, the flush water tank apparatus comprising:

5 a storage tank storing flush water to be supplied to the flush toilet, with a drain port for discharging the stored flush water to the flush toilet formed therein;

a discharge valve opening/closing the drain port and performing supply/stop of the flush water to the flush
10 toilet;

a discharge valve hydraulic drive unit driving the discharge valve using water supply pressure of supplied tap water;

a clutch mechanism coupling the discharge valve and
15 the discharge valve hydraulic drive unit to pull up the discharge valve by driving force of the discharge valve hydraulic drive unit, and being disconnected at a predetermined timing to cause the discharge valve to descend;

flush water amount selection means capable of
20 selecting between a first amount of flush water for washing the flush toilet and a second amount of flush water smaller than the first amount of flush water;

a first float device comprising a first float moved according to a water level in the storage tank and a first
25 engaging member capable of moving to an engaging position of engaging with the discharge valve to hold the discharge valve and a non-engaging position of not engaging with the discharge valve in conjunction with movement of the first float;

30 a second float device comprising a second float moved

according to the water level in the storage tank and a second engaging member capable of moving to an engaging position of engaging with the discharge valve and a non-discharging position of not engaging with the discharge valve in
5 conjunction with movement of the second float and causing the second engaging member to move to the non-engaging position at a height different from a height at which the first float causes the first engaging member to move to the non-engaging position; and

10 a float driving mechanism driving the first float to cause the first engaging member to move to the non-engaging position when the second amount of flush water is selected by the flush water amount selection means;

wherein by the first engaging member of the first float
15 device being moved to the non-engaging position, the discharge valve engages with the second engaging member of the second float device.

2. The flush water tank apparatus according to claim 1,
20 wherein the first float device is configured to hold the discharge valve at a position higher than a position at which the second float device holds the discharge valve, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-
25 engaging position before the second engaging member is moved to the non-engaging position in conjunction with the second float.

3. The flush water tank apparatus according to claim 2,
30 wherein the clutch mechanism is configured to be disconnected

at a position higher than a height at which the first engaging member of the first float device and the discharge valve engage with each other, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-engaging position before the discharge valve descends to the height at which the first engaging member and the discharge valve engage with each other.

4. The flush water tank apparatus according to claim 3, wherein the clutch mechanism is configured to pull up the discharge valve from the drain port, and the float driving mechanism is configured to drive the first float to cause the first engaging member to move to the non-engaging position before the discharge valve is pulled up to the height at which the first engaging member of the first float device and the discharge valve engage with each other.

5. The flush water tank apparatus according to claim 4, wherein the float driving mechanism is configured to, after the clutch mechanism is disconnected, keep the first engaging member at the non-engaging position until the discharge valve descends below the height at which the first engaging member of the first float device and the discharge valve engage with each other.

6. The flush water tank apparatus according to any one of claims 1 to 5, wherein the float driving mechanism is configured to drive the first float using the supplied tap water.

7. The flush water tank apparatus according to claim 1, wherein the float driving mechanism comprises a control jet unit jetting, when the second amount of flush water is selected by the flush water amount selection means, flush water from a jet port to a water receiving surface provided on the first float device so that a timing of the drain port being blocked is earlier than a case of the first amount of flush water being selected.

10

8. The flush water tank apparatus according to claim 7, wherein the jet port of the control jet unit is provided being oriented to face the water receiving surface of the first float device.

15

9. The flush water tank apparatus according to claim 8, wherein the jet port of the control jet unit is formed with an area smaller than an area of the water receiving surface of the first float device.

20

10. The flush water tank apparatus according to any one of claims 7 to 9, wherein the control jet unit is provided with a straight pipe portion connected to the jet port, and turbulence of flush water jetted through the jet port is suppressed by the straight pipe portion.

25

11. The flush water tank apparatus according to any one of claims 7 to 10, wherein the jet port of the control jet unit is arranged to jet flush water downward.

30

12. The flush water tank apparatus according to any one of claims 7 to 11, wherein the water receiving surface of the first float device is arranged to be submerged in flush water stored in the storage tank, and the control jet unit jets
5 flush water to the submerged water receiving surface.

13. The flush water tank apparatus according to any one of claims 7 to 12, wherein the jet port of the control jet unit is arranged to be submerged in flush water stored in the
10 storage tank and jets flush water to the submerged water receiving surface of the first float device.

14. The flush water tank apparatus according to any one of claims 7 to 13, wherein the water receiving surface of the
15 first float device is provided with a wall surface surrounding a collision point at which flush water jetted from the control jet unit hits.

15. The flush water tank apparatus according to any one of
20 claims 7 to 14, wherein

the first float device comprises a first holding mechanism switchable between a holding state and a non-holding state in conjunction with the movement of the first float;

25 the first holding mechanism comprises an arm member rotatably supported by a support shaft, one end of the arm member being coupled with the first float; and

the control jet unit jets flush water toward the water receiving surface formed on an upper surface of the first
30 float, and the jetted flush water collides against a side

away from the support shaft relative to a center line of the first float in a plan view.

16. A flush toilet apparatus comprising a plurality of
5 washing modes with different amounts of flush water, the flush toilet apparatus comprising:

a flush toilet; and

the flush water tank apparatus according to any one of claims 1 to 15 supplying flush water to the flush toilet.