

APPARATUS AND METHOD FOR MARKING A RUBBER ARTICLE WITH
A MESSAGE READABLE BY A LIGHT SCANNING DEVICE

Technical Field

5 The invention herein resides in the art of
marking cured substrate, such as a rubber tire, with a
code, preferably a bar code, marking readable with a
light or laser scanning device, said marking being
capable when properly marked to furnish a history of
10 the article from its so-called "birth to grave".
Also, the message on the label or insignia cured to
the plastic or rubber substrate can serve to identify
the cured plastic or rubber and afford a logo such as
may be used with the article alone or with the message
15 or insignia.

Background - Art

Heretofore indicia or decorations, including
logos, have been applied to the sidewall of tires.
20 For example, white sidewalls have been applied to
tires, special identifying or grading codes have been
placed on the sidewall of a tire for purpose of
indicating grade, uniformity, identification of
source, as well as decorations and the like have been
25 used.

Generally, tires are marked using inks and paints
that are commercially available. These marks are
applied by stamping, stenciling, labeling or painting
onto the tire with or without curing. Unfortunately,
30 these markings on the tire may be washed off or
smeared by abrasion. Also, the methods used
heretofore were costly and were subjected to producing
identifying indicia subjects to being disturbed,
damaged or marred in use.

35 There is need in the art for simpler, inexpensive
methods for imparting indicia to tires, especially

REPLACED SHEETS		SG
☒	Description : paged ...2.... to paged ...3....	
☒	Claim(s) : paged ...4.... to paged ...5....	
☐	Drawing(s) : paged to paged	
☒	Abstract : paged ...4.... to paged ...5....	
DATE OF RECEIPT		

with said indicia exhibiting high clarity, resolution,
and preferably the indicia can be coded at the point
of manufacture to carry its history from birth to
grave as desired in the art with improved resistance
5 to destruction, distortion and higher clarity.

Summary of the Invention

An apparatus and method for supplying a graphic
label that is readable with a light scanning device
10 with such label placed on a rubber or plastic article.
The graphic bar code label is optically interpreted
with a bar code reader. The bar code reader consists
of a scanning device and decoder logic. The scanner
emits a light beam and detects light reflection. The
15 dark bars absorbs the light and, thus, the absence of
electrical signal, the light spaces reflects lights
and generates an electrical signal. The electrical
signal duration determines the width of the bars and
spaces. The decoder logic subjects the signal to a
20 comprehensive decoding algorithm which determines code
type accuracy and validity. The scanned data can then
be transmitted and/or stored. There is also two types
of bar code readers, a visible laser scanner that
detects a bar code based on light reflectance and an
25 infrared scanner that reads a bar code based on the
detection of carbon black or a similar pigment. The
graphic label is adhered to an uncured or cured
substrate such as a tire, a building bladder or other
rubber articles by placing the graphic label on the
30 curable substrate, preferably in a mold and effecting
cure by pressure and heat or other curing conditions
to cause the label to adhere to the cured article such
as a tire.

Thus, the cured substrate with the label with the
35 graphic message is produced by using thermal transfer
techniques. For this purpose, the ribbon in contact



with the substrate are passed between print head and pressure roll. The print head is composed of a grid of elements that are computer controlled to precisely heat and cool. The ribbon and label stock passes by
5 the print head and the ink can be selectively heated with this operation being synchronized by computer operation. A combination of heat and pressure is applied to the ribbon in contact with the substrate which causes the ink to liquefy and transfer from the
10 ribbon web to the label structure. When the ribbon is stripped away, the ink is left where heating occurred on the substrate material. The label is placed on a cured or curable article and the label and substrate are subjected to curing conditions to effect transfer
15 of the label to the cured substrate which may now contain the message in solely, alphanumeric, bar codes, human readable characters, and logos or mixtures of them. The bar code message is normally printed as a series of vertical bars and spaces of
20 varying widths to supply the message in readable form with the light reflected from the series of varying width bars and spaces.

The bar code itself is preferably a binary code with information encoded in the relative widths of
25 bars and spaces in a printed pattern which is an optically read language. Bar codes are read by sweeping a small beam of light across the bar code. The light source may be a light pen with on light emitting diode/photo diode or a handheld and fixed
30 laser scanner that uses a mechanically or electronically scanned light beam.



Disclosure of Invention

In light of the foregoing, an aspect of this invention is to furnish a method of applying a plastic
5 or rubber substrate with a label that exhibit a message which can be read by reflective light preferably with a scanner.

It is the objective of this invention to provide for a logo insignia and/or bar code or other code on a
10 tire or similar rubber object which yields a characteristic markings which are cosmetically acceptable in appearance and scannable which are not considered a foreign material to the article such as a paper label or a decal with a non-compatible adhesive.

15 A further aspect of this invention is to furnish an apparatus that allows the label to be generated by the operator at his work station to include a message which may indicate the current history of the specific cured article being formed. Said current history
20 indicating its numerical sequence in the manufacturing process, and in some cases, its individual components. Thus, this invention provides apparatus for making a label from label stock and ribbon which the operator can use a keyboard via a computer to control the
25 printing of the message including logos if desired, and securing or cutting the label in the desired lengths. Then the operator can place the label on the uncured substrate, preferably so the message transfers to the cured article is inverted but still be readable
30 in the normal manner as by a scanner device or visual eye contact on the finished product.

Thermal transfer technology enables the user to print on-site, on-demand, variable information in
human-readable and bar code form in acceptable quality
35 and quantity. If the article to which the message is being transferred to is black, then the ink on the

ribbon should be white or silver or any reflective type color. The thermal transfer equipment can then be programmed for the reverse printing of bar codes such that upon application to a black substrate, the printed white or silver bars would act as the reflective spaces between the non-printed black bars of the substrate backing for appropriate scanning capability.

10 Description of Drawings

For a complete understanding of the objects, techniques, apparatus structure and the method of placing an indicia and cured substrate with said indicia being readable by a scanner device in response to reflective light or electromagnetic radiation, reference should be had to the following detailed description and drawing wherein:

Fig. 1 is a block diagram of my novel method and apparatus.

20 Fig. 1A is a schematic view of the apparatus for preferably performing various steps of the method.

Fig. 1B is a schematic sectional view showing a thermal transfer printing step under heat/pressure.

25 Fig. 1C is a sectional view of the curing station showing the protective substrate being removed.

Fig. 1D is a sectional view of the station where the bar code scanning occurs.

Figs. 2A-2B are plan views showing various forms of the finished messages may take.

30 Fig. 2C is another view of a label showing an opaque message for use on a contrasting object.

Figs. 3A-3E are detail views showing steps required for forming a label and application to a green rubber object.

Figs. 4A-4C are schematics sectional view showing steps required for attaching a label to a cured object.

5 Figs. 5A-5B are detail views similar to Fig. 3C and Fig. 3E showing a label may emboss a green object.

Best Mode For Carrying Out The Invention

Referring now to the drawing Fig. 1A, numerical 11 designated schematically one embodiment of the apparatus for practicing this invention. A thermal transfer printer 13 melts the ink 12B off a ribbon 12 onto the substrate 14. These types of printers produce excellent images and does not require specially treated substrates. The label stock 14 can be paper, plastics such as Mylar or rubber films. The numerical 12 designates a roll of ribbon on a support 12A that feeds to and through the printer assembly 13. The numerical 14 designates a roll of label stock on a support 14A that also feeds to and through the printer assembly. In response to an electronic message generated by the operator's activation of the keyboard 15 of a computer. The activation of the keyboard can be wired to send an electronic signal directly to the motor (not shown) of the printer assembly to cause the ribbon drive to advance the ribbon and substrate. The ribbon is advance due to tension on the ribbon from rotation of the drive wheels on rolls. Preferably, it is constructed so the activation of the keyboard by striking various keys to cause the computer 16 to synchronizely activated via the drive motor and the ribbon drive to advance the ribbon with the substrate through the printer. The computer activates the printer print head to print on the ribbon the indicia of the message typed by the operator. This message can be printed at any stage in manufacture and use of the article with a message thereon. A combination of

heat and pressure is applied to the ribbon in contact with the substrate, which causes the ink 12B to liquefy and transfer from the ribbon web to the label substrate. When the ribbon is stripped away from the label structure, ink is left where heating occurred on the label material. Preferably, as the label substrate with the message thereon exits the print head 13, the computer can then cause the cutting member 17 to contact an anvil to cut the substrate to give a label 18 of the desired length.

In the heat pressure station 19, the label is inverted and placed on a curable substrate 20 and the curable substrate with the label 18 is cured in the customary way in the heat pressure station 19 such as a tire mold or related mold.

The cured substrate with the label cured or adhered thereto as shown by numerical 21 can be read either visually or by use of a scanning device 22. The scanning device 22 preferably emits a light or related electromagnetic radiation which strikes the label and is reflected back to be read by the scanner.

Thermal transfer ribbons consists of at least two major elements, a carrier film and the transfer ink layer. The roll 12 of ribbon is preferably a laminate of desired width and thickness for securing it to the substrate. The laminate usually comprises a carrier or backing sheet of a polyester typically Mylar, Tedlar, High Density Polyolefin or other film or sheet materials about 4.5 microns (0.18 mils) to 5.7 microns (0.22 mils) and the ink layer.

This carrier sheet has an ink face coating of a suitable transfer stock such as any suitable thermoplastic elastomer, for example, a rubber, a hydrogenated styrene-butadiene block copolymer, a carnauba wax, an ester wax, or a suitable dry film ink. The coating usually has a thickness which is

substantially less than that of the backing sheet face.

A method of printing a graphic message on a plastic or rubber substrate comprising activating an electronic system to advance a thermal transfer ribbon to a printer and electronically directing said printer to print a graphic message, severing or cutting said substrate to generate a label with a heat transferable message thereon, placing said label on a curable plastic or rubber substrate, curing said label on the curable plastic or rubber substrate, and later reading said graphic message.

The message on the printed label may consist of various groups of letters, numbers, logos and bars codes. The bar code itself is preferably a binary code with information, numbers, letters and symbols encoded in the widths of bars and spaces in an established pattern. The nature of one message is shown encoded in Fig. 2C. The logo of Goodyear is shown with a series of vertical bars 23 and spaces 24 with the width of the bars and spaces being adjusted to reflect the light so a message may be read. Also, the message of Fig. 2A has the number 03260108 to show other forms the message may take.

In a preferred embodiment of this invention where reverse printing of bar codes and/or mirror printing of other insignia are being used, a silver ink printed transfer ribbon gives unique results with black substrates such as a rubber stock loaded with carbon black. In this case, it is advantageous to have the printed silver ink bars act as the reflective spaces between the non-printed bar formed by the black loaded rubber backing material. Referring to Fig. 2C, the dark inks may be used for reverse printing on light or non-carbon black stocks.

It should be appreciated that the printing inks used in this invention are available commercially including silver colored ink.

Although the silver inks have been disclosed herein; it should be appreciated that the white inks made with white pigments, such as titanium oxide, may be used, too.

The logo can be printed on heat resistant Mylar film whose gauge can range from 1 mil to 20 mils thick using well known thermal transfer printing techniques and subsequently attached to a tire sidewall or position on a green tire prior to curing the article. The inked markings transfers directly to the rubber during heat application by a temperature controlled platen or curing. The label exhibits excellent dimensional uniformity on the finished part while the same Mylar film is protecting the heated platen surface or mold itself from the ink and protects the ink from platen/mold residue. The Mylar film can be removed or left on for surface protection.

An important concept for application is the mirror image printing of any insignia such that in using a white or silver ink thermal transfer ribbon; when transferred to a black surface, the distinguishing marks or logo are human readable.

Thermal printing techniques were successfully employed for label fabrication. For this purpose, the thermal transfer ribbons used are constructed of a polyester film carrier web that is coated on one side with a pigmented wax-based or resin-based ink. At the print head of the equipment, the ribbon is in constant contact with the label stock such as Mylar film. A combination of heat and pressure is applied to the ribbon which causes the ink to liquify and transfer from the polyester web to the label structure.

By design of the equipment, the inks flows from one dot to another resulting in very uniform lines and extremely crisp lines. The ink returns to its harden state immediately upon removal of the heat and
5 pressure. When the ribbon is stripped away, ink is left where heating occurred on the label material or substrate. Thermal transfer printing devices can also be used for text and graphics applications since high density, sharp, crisp imaging is feasible. These
10 units are suitable for centralized label production or on-demand printing in the factor at the operator's work station.

Particularly suitable for this label making is a personal computer having software that includes bit
15 image data transfer. The preparation of graphics for inclusion in the bar code label consists of the following steps: (1) the image is read by an electronic scanner whose electronic signal is transferred to a computer such as a MacIntosh® IIci to
20 store and display the graphics; (2) the scanned image is stored in a TIFF file format for use in an IBM PC computer; (3) PC Paintbrush program is loaded in the IBM® PC computer and the file in TIFF format is saved to a PCX file format; (4) this PCX file is then
25 converted into a hexadecimal format and subsequently transposed a negative image into a positive image.

This transposed hexadecimal graphic file is sent via the IBM® PC computer to the Zebra® 130 thermal transfer printer (having 512K RAM) for MEMORY storage.
30 The equipment has a high resolution printhead preferably 8 dot/mm density which can yield superior graphics and bar code outputs. Finally the ZPL® (Zebra Programming Language) format is sent from the IBM® PC computer that include commands to call up the

graphics and all ZPL® statements for text and bar codes for a unique label.

For several applications, this unique label is printed on Mylar film 5 mils thick using a
5 commercially available white (wax base) ribbon with the characters and/or graphics reproduced mirror images and the bar codes reverse printed such that the white bars act as the reflective spaces when applied to a black object (Fig. 2).

10 This invention may be practiced on so-called green rubber applications or cured rubber applications.

In green rubber application, the steps referring to specific Figures, i.e. Fig. 3A are

15

- 1) printing the label identification on the surface of a heat-resistant label material such as Mylar film with the characters reproduced as
20 mirror images and bar codes reverse printed;

20

- 2) Fig. 3B: positioning the label to an appropriate location on an
25 uncured rubber article such as a green tire of Fig. 3B: or in a mold with the ink surface facing the rubber surface; and

25

- 30 3) curing the green rubber article such as a tire in a heated mold i.e. in Fig. 3C for a specified period of time and temperature such that the bar code ink is
35 selectively transferred and bonded

to the outer surface of the rubber article.

In the cured rubber application, the steps are as
5 shown in Fig. 3A again:

- 10 1) printing the label identification on the surface of a heat-resistant label material such as Mylar film with the characters reproduced as mirror images and bar codes reverse printed;
- 15 2) then as seen in Fig. 3B positioning the label to a cured rubber article such as a cured tire with the ink surface facing the rubber substrate; and now referring to Fig. 4A-4C:
- 20 3) effecting the transfer of the ink by the uniform application of heat (250°F - 300°F) and pressure (300-500 psi) for a short time (15-30
25 seconds) such as by the use of a heated iron.

It is believed that the heat resistant Mylar film stabilizes the insignia information during transfer
30 such that a precise label is obtained on the tire or rubber product. The film also protects the heated platen or mold surface from any contamination. The ink that is used in the thermal printing process is the same ink that is transferred to the tire or rubber
35 product after the application of heat. The same

capability is possible with text, graphics and bar codes.

5 The unique labels can be printed using a
conventional thermal transfer printing techniques and
utilizing a heavy pigmented, light color
(white/silver) thermal transfer ribbon. The use of a
heat resistant substrate such as Mylar film remains
undistorted in processing (printing and transfer) and
its contrast is unchanged during end use application.
10 Labels can be printed at the tire building station or
other areas upon demand which eliminates inventory and
logistics problems with preprinted labels or mix-ups
during transport to the application point. Practicing
this technique result in sharp, crisp well defined
15 logos of distinguishing markings on a rubber surface
with its method of application being relatively simple
and versatile.

20 This invention intends that the label may be
updated at any time during its life, for instance,
when the tires are brought in to be recapped.

25 While certain representative embodiments and
details have been shown for the purpose of
illustrating the invention, it will be apparent to
those skilled in this art that various changes and
modifications may be made therein without departing
from the spirit or scope of the invention.



WHAT IS CLAIMED IS:

1. Apparatus for marking a cured rubber substrate with a graphic message that can be read by a scanning unit characterized by including a means to hold a thermal transfer ribbon and advance said ribbon to a printer on demand from a signal from an electronic means, said printer printing a heat transferable graphics on a substrate, means to sever or cut the substrate to give a label having a graphic message thereon, placing said label on a curable rubber article, means to subject said label on the curable rubber article to curing conditions in a curing means and a means to read light reflected from the graphic label on the cured rubber article.

2. The apparatus of claim 1 characterized in that the ribbon is a heat resistant polyester film whose gauge is usually less than 1 mil with a silver or white pigmented ink coating.

3. The apparatus of claim 1 characterized in that the substrate is a heat resistant polyester film whose gauge is from 1 to 20 mils thick.

4. The apparatus of claim 1 characterized in that the label is placed on the curable rubber article to effect a mirror image transfer of the graphics on the label to the rubber article and reverse transfer of a bar code to the rubber article.

5. The method of labeling an article characterized by comprising the steps of making a label at a work station by advancing a transfer ribbon through a print head, activating a means that controls





the advance of the transfer ribbon to advance the transfer ribbon, advancing said ribbon thereby, and directing an activation means to control the print head to print a message on a substrate and then sever
5 said substrate to give a label, placing said label on an article, curing said label to said article to give an article labeled with a message, then reading the label to discover the message.

10 6. The method of claim 5 characterized in that the label is placed on a curable article to offset a reverse printed bar code label to the rubber article and mirror image transfer of the graphics on the label to the article.

15 7. The method of claim 5 characterized in that the label is placed on a black curable rubber article to offset a reverse printed white/silver bar code label to the rubber article, wherein the printed
20 silver/white bars act as the reflected spaces between the non-printed bar formed by black loaded rubber backing material of the rubber article.

25 8. The method of claim 6 characterized in that the message is readable by a scanner that is activated by reflected electromagnetic radiation.

9. The method of claim 8 characterized in that any reflection of the electromagnetic radiation
30 supplies an electrical input to a computer to store said input and allow said input to be printed in a print form.

