

5

Implantable medical device with temperature sensor

The present invention relates to an implantable medical device for stimulating a human or animal heart according to the preamble of claim 1, to an arrangement comprising such an implantable medical device according to the preamble of claim 7, to a method for
10 calibrating a temperature sensor of an implantable medical device according to the preamble of claim 11, and to a computer program product according to the preamble of claim 13.

15 An increase in body temperature is an early indicator for infection, e.g., for a viral infection such as influenza or COVID-19. In case of COVID-19, the available clinical data shows that patients with heart diseases appear to have a higher mortality rate compared to patients without such diseases.

20 Active cardiac implants are capable of collecting an implant temperature which directly corresponds to the body temperature of a person to whom the implant has been implanted. However, the on-board temperature sensors of such active cardiac implants are not calibrated to the patient body temperature.

25 It would be generally possible to calibrate a temperature sensor of an implantable medical device prior to its implantation. However, such external calibration is not feasible for medical devices that are already implanted in patients. For such implants, an external temperature sensor would be necessary to determine the patient's body temperature. This information could then be used to calibrate the temperature sensor of the implantable
30 medical device. However, an external temperature sensor would be necessary for such procedure.

It is an object of the present invention to provide an implantable medical device with a temperature sensor, wherein the temperature sensor can be calibrated without the need of additional external devices.

- 5 This object is achieved with an implantable medical device having the claim elements of claim 1. Such an implantable medical device serves for stimulating a human or animal heart. It comprises a processor, a memory unit, a stimulation unit, a detection unit, and a temperature sensor. The stimulation unit serves for stimulating a cardiac region of a human or animal heart. The detection unit serves for detecting an electrical signal of the same
- 10 heart. The temperature sensor serves for sensing a body temperature or a temperature of the implantable medical device which directly corresponds to the body temperature of the patient to whom the implantable medical device has been implanted.

According to the presently claimed invention, the memory unit comprises a computer-
15 readable program that causes the processor to perform the steps explained in the following when executed on the processor.

First, the temperature sensor is caused to sense the body temperature of the person to whom the implantable medical device is implanted. In this context, the temperature sensor
20 is caused to sense the body temperature a plurality of times so that a plurality of time-dependent body temperature values is obtained. The obtained body temperature values are stored in the memory unit.

Afterwards, a statistical analysis on at least a subset of the stored body temperature values, in particular on all of the stored body temperature values, is performed. This statistical
25 analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

The calculated statistical parameters are then used to be output, to adjust the previously
30 measured, calculated or determined temperature value or to be compared with an actually measured body temperature value. To be more specific, the computer-readable program causes the processor to perform at least one of the tasks explained the following.

One of the possible tasks is to output the body temperature reference value and/or the variation of the sensed body temperature values and/or the variability of the sensed body temperature values. Then, these values can be used for further analyses or for
5 documentation purposes.

Another possible task is to compare an actual body temperature value with the previously calculated body temperature reference value. In doing so, it is particularly simple to detect an increase in body temperature and thus a potential infection of the patient carrying the
10 medical device in an implanted state. Thus, the calculated body temperature reference value serves as internal calibration of the temperature sensor of the implantable medical device. Even though the determination of the body temperature reference value does not enable an absolute temperature calibration of the temperature sensor, it guarantees a relative calibration so that future discrepancies from the calculated body temperature
15 reference value can be easily and exactly detected.

Another possible task is to compare a predetermined expectancy value of temperature variations with the variation of the sensed body temperature values. By such a comparison, a general body temperature trend can be observed and evaluated with respect to the
20 predetermined expectancy value (e.g., an expected temperature variation of a standard population). In doing so, patient-specific temperature variations, either normal or suspicious with respect to an infection, can be detected.

Another possible task is to compare a predetermined expectancy value of temperature
25 variability with a variability of the sensed body temperature values. Such a comparison serves for the detection of intraday or interday variances of the patient's body temperature and can help identifying future temperature deviations from the body temperature reference value as significant (i.e., being indicative for a possible infection) or as insignificant (lying within an expected range of variability). Furthermore, by evaluating the
30 variability of the sensed body temperature, it is possible to evaluate temperature sensor inaccuracies and to consider such inaccuracies for future body temperature evaluations.

Another possible task is to add an absolute value of the variety or of the variability of the sensed body temperature values to the calculated body temperature reference value or, alternatively, to subtract an absolute value of the variety or of the variability of the sensed body temperature values from the calculated body temperature reference value. In doing
5 so, an adjusted body temperature reference value is obtained. This adjusted body temperature reference value can then be output or can be used to compare an actual body temperature value with the adjusted body temperature reference value. By using such an adjusted body temperature reference value, the sensitivity of the detection of a suspiciously increased body temperature can be increased or decreased, as desired. If an absolute value
10 of the variety or of the variability is added to the body temperature reference value, it is less likely that a slight increase in body temperature will result in exceeding a threshold being indicative for a suspiciously increased body temperature, if the threshold is based on the adjusted body temperature reference value. Likewise, the probability that an actually sensed body temperature exceeds a threshold based on an adjusted body reference
15 temperature value is higher if the adjusted body temperature reference value is calculated by subtracting an absolute value of the variety or of the variability of the sensed body temperature values from the previously calculated body temperature reference value.

In an embodiment, the statistical analysis comprises calculating a mean value or a median
20 value of at least a subset of the stored body temperature values, in particular of all of the stored body temperature values. This mean value or this median value is then used as body temperature reference value.

In an embodiment, the statistical analysis comprises calculating an exponential moving
25 average value of at least a subset of stored temperature values, in particular of all of the stored body temperature values. An exponential moving average is a type of moving average that places a greater weight and significance on the most recent data points or here specifically the most recent temperature values. This exponential moving average value is then used as body temperature reference value.

30

In an embodiment, the statistical analysis comprises calculating an exponential moving median value of at least a subset of stored temperature values, in particular of all of the

stored body temperature values. An exponential moving median is a type of moving median that places a greater weight and significance on the most recent data points or here specifically the most recent temperature values. This exponential moving median value is then used as body temperature reference value.

5

In an embodiment, the statistical analysis comprises calculating a standard deviation of at least a subset of the stored body temperature values, in particular of all of the stored body temperature values. Such a standard deviation can be used as the variety of the sensed body temperature values.

10

In an embodiment, the statistical analysis comprises fitting at least a subset of the stored body temperature values, in particular all stored body temperature values, by a function and calculating a function parameter. In an embodiment, the function is a function describing a line. In such a case, the function parameter is, e.g., the slope of the line. Such a slope is typically indicative for a temperature variation with time. In an embodiment, the function is a first-order exponential function and the function parameter is a coefficient or an exponent of the function.

The subset of the stored body temperature values is, in an embodiment, chosen such that it comprises different body temperature values of a single day. In an embodiment, the subset of the stored body temperature values used for the statistical analysis is chosen such that it comprises body temperature values of different days. In an embodiment, the subset of the body temperature values used for the statistical analysis is chosen such that it comprises body temperature values of at least 2 days, in particular at least 3 days, in particular at least 4 days, in particular at least 5 days, in particular at least 6 days, in particular at least 7 days. In an embodiment, the subset of the stored body temperature values used for the statistical analysis is chosen such that it comprises body temperature values of 1 to 14 days, in particular of 2 to 13 days, in particular of 3 to 12 days, in particular of 4 to 11 days, in particular of 5 to 10 days, in particular of 6 to 9 days, in particular of 7 to 8 days. In an embodiment, the body temperature values used for the statistical analysis originate from consecutive days.

In an embodiment, the computer-readable program causes the processor to sense the body temperature a plurality of times per day. E.g., the body temperature can be sensed 2 to 12 times a day, in particular 3 to 11 times a day, in particular 4 to 10 times a day, in particular 5 to 9 times a day, in particular 6 to 8 times a day. In an embodiment, the body temperature
5 is sensed every hour, i.e., 24 times a day. In an embodiment, the temperature is sensed every 30 minutes, i.e., 48 times a day. In an embodiment, the body temperature is sensed in an interval lying between every 15 minutes and every 2 hours, in particular between every 30 minutes and every 1.5 hours, in particular between every 45 minutes and every hour.

10 In an embodiment, the computer-readable program causes the processor to sense the body temperature for a plurality of days, in particular 2 to 14 days, in particular 3 to 13 days, in particular 4 to 12 days, in particular 5 to 11 days, in particular 6 to 10 days, in particular 7 to 9 days.

15 In an embodiment, the computer-readable program causes the processor to perform the statistical analysis on body temperature values sensed on at least 3 different days, in particular at least 4 days, in particular at least 5 days, in particular at least 6 days, in particular at least 7 days. In an embodiment, the body temperature values used for the statistical analysis are sensed on a number of different days lying in a range of 3 to 14
20 days, in particular of 4 to 13 days, in particular of 5 to 12 days, in particular of 6 to 11 days, in particular of 7 to 10 days, in particular of 8 to 9 days.

In an embodiment, the computer-readable program causes the processor to output an alert if the actual body temperature value exceeds the body temperature reference value or the
25 adjusted body temperature reference value by a predetermined value. In an embodiment, this predetermined value lies in a range from 0.3 to 2.0°C, in particular from 0.4 to 1.9°C, in particular from 0.5 to 1.8°C, in particular from 0.6 to 1.7°C, in particular from 0.7 to 1.6°C, in particular from 0.8 to 1.5°C, in particular from 0.9 to 1.4°C, in particular from 1.0 to 1.3°C, in particular from 1.1 to 1.2°C.

30

Such an alert can be used as indication that a risk of infection of the patient carrying the implantable medical device in an implanted state is given. Medical staff, in particular a

medical doctor, evaluating the patient's data can then inform the patient that he or she might be infected and can take appropriate countermeasures. Alternatively, the alert on a potential infection (e.g., a potential influenza infection or a potential COVID-19 infection) can be automatically processed and communicated to the patient.

5

In an aspect, the present invention relates to an arrangement comprising an implantable medical device for stimulating human or animal heart and an evaluation unit separate from the implantable medical device. The implantable medical device comprises a first processor, a first memory unit, a stimulation unit, a detection unit, a temperature sensor,
10 and a data communication unit. The stimulation unit serves for stimulating a cardiac region of a human or animal heart. The detection unit serves for detecting an electrical signal of the same heart. The temperature sensor serves for sensing a body temperature.

The first memory unit of the arrangement comprises a first computer-readable program that
15 causes the first processor to perform the steps explained the following when executed on the first processor.

First, the processor causes the temperature sensor to repeatedly sense a body temperature of the person to whom the implantable medical device has been implanted. Thus, a
20 plurality of body temperature values is obtained.

These body temperature values are then transmitted via the data communication unit to the evaluation unit located outside body of the person to whom the implantable medical device is implanted.

25

The evaluation unit comprises a second processor and a second memory unit. The second memory unit comprises a second computer-readable program that causes the second processor to perform the steps explained in the following when executed on the second processor.

30

First, the transmitted body temperature values are stored in the second memory unit.

Then, a statistical analysis is performed on at least a subset of the stored body temperature values, in particular on all stored body temperature values. This statistical analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

5

Afterwards, the evaluation unit is caused to perform at least one of the tasks explained in the following.

One of the possible tasks is to output the body temperature reference value and/or the variation of the sensed body temperature values and/or the variability of the sensed body temperature values.

10

Another possible task is to compare an actual body temperature value with the previously calculated body temperature reference value.

15

Another possible task is to compare a predetermined expectancy value of temperature variations with the variation of the sensed body temperature values.

Another possible task is to compare a predetermined expectancy value of temperature variability with a variability of the sensed body temperature values.

20

Another possible task is to add an absolute value of the variety or of the variability of the sensed body temperature values to the calculated body temperature reference value or, alternatively, to subtract an absolute value of the variety or of the variability of the sensed body temperature values from the calculated body temperature reference value. In doing so, an adjusted body temperature reference value is obtained. This adjusted body temperature reference value can then be output or can be used to compare an actual body temperature value with the adjusted body temperature reference value.

25

Thus, the arrangement serves for the same purpose as the implantable medical device described above. However, the data evaluation and further use of the evaluated data is not directly performed within the implantable medical device, but rather outside in an external

30

evaluation unit. This approach requires less energy consumption of the implantable medical device than evaluating the data within the implantable medical device. Since the energy resources of an implantable medical device are very limited (in particular in case of miniaturized implantable medical devices), it is generally favorable to perform energy consuming calculation tasks outside the implantable medical device. In such a case, additional energy is necessary for the data transmission. The data transmission requires, however, typically much less energy than calculations and data manipulation within the implantable medical device.

All embodiments explained above with respect to the evaluation unit of the implantable medical device can be transferred to the first evaluation unit and/or the second evaluation unit of the described arrangement.

In an embodiment, the data communication unit serves for transferring data to the evaluation unit in a wireless manner. All standard data transmission protocols are appropriate for such a wireless data communication.

In an embodiment, the first computer-readable program causes the first processor to transmit the body temperature values at least once a day, in particular exactly once a day, in particular 2 to 12 times a day, in particular 3 to 11 times a day, in particular 4 to 10 times a day, in particular 5 to 9 times a day, in particular 6 to 8 times a day. In an embodiment, the data is transmitted every hour, i.e., 24 times a day. In an embodiment, the data is transmitted every 30 minutes, i.e., 48 times a day. In an embodiment, the data is transmitted in an interval lying between every 15 minutes and every 2 hours, in particular between every 30 minutes and every 1.5 hours, in particular between every 45 minutes and every hour. In an embodiment, each body temperature value is transmitted directly after sensing it.

In an embodiment, the evaluation unit is located remote from the implantable medical device. To give an example, the evaluation unit can be located within a medical center and can be arranged to receive temperature and other medical data from a plurality of implantable medical devices. In such a case, the data communication unit of the

implantable medical device typically transfers the body temperature values to an external local data communication unit which then serves for further data transmission to the evaluation unit.

5 In an aspect, the present invention relates to a method for calibrating a temperature sensor of an implantable medical device. Such an implantable medical device serves for stimulating a human or animal heart. It comprises a processor, a memory unit, a stimulation unit, a detection unit, and a temperature sensor. The stimulation unit serves for stimulating a cardiac region of a human or animal heart. The detection unit serves for
10 detecting an electrical signal of the same heart. The temperature sensor serves for sensing a body temperature or a temperature of the implantable medical device which directly corresponds to the body temperature of the patient to whom the implantable medical device has been implanted.

15 The method comprises the steps explained in the following.

First, body temperature values are stored in the memory unit. The body temperature values are provided by the temperature sensor. They reflect the body temperature of a person carrying the implantable medical device in an implant state at different time points.

20

Afterwards, a statistical analysis on at least a subset of the stored body temperature values, in particular on all of the stored body temperature values, is performed. This statistical analysis serves for calculating a body temperature reference value.

25 This body temperature reference value is then used as expected regular body temperature value for calibrating the temperature sensor.

In an embodiment, the method further comprises performing a statistical analysis on at least a subset of the stored body temperature values, in particular on all of the stored body
30 temperature values, to calculate at least one of a variation of the stored body temperature values and a variability of the stored body temperature values. In this context, an absolute value of the variation or the variability of the sensed body temperature values is added to

or subtracted from the calculated body temperature reference value to obtain an adjusted calculated body temperature reference value. The adjusted calculated body temperature reference value replaces then the calculated body temperature reference value during further data analysis.

5

In an aspect, the present invention relates to a computer program product comprising computer-readable code that causes a processor to perform the steps explained in the following when executed on the processor.

10 In a first step, body temperature values obtained from a temperature sensor of an implantable medical device are stored in a memory unit of the implantable medical device or of an evaluation unit located outside the body of a person to whom the implantable medical device has been implanted.

15 Then, a statistical analysis is performed on at least a subset of the stored body temperature values, in particular on all stored body temperature values. This statistical analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

20 Afterwards, the evaluation unit is caused to perform at least one of the tasks explained in the following.

One of the possible tasks is to output the body temperature reference value and/or the variation of the sensed body temperature values and/or the variability of the sensed body
25 temperature values.

Another possible task is to compare an actual body temperature value with the previously calculated body temperature reference value.

30 Another possible task is to compare a predetermined expectancy value of temperature variations with the variation of the sensed body temperature values.

Another possible task is to compare a predetermined expectancy value of temperature variability with a variability of the sensed body temperature values.

Another possible task is to add an absolute value of the variety or of the variability of the sensed body temperature values to the calculated body temperature reference value or, alternatively, to subtract an absolute value of the variety or of the variability of the sensed body temperature values from the calculated body temperature reference value. In doing so, an adjusted body temperature reference value is obtained. This adjusted body temperature reference value can then be output or can be used to compare an actual body temperature value with the adjusted body temperature reference value.

In an aspect, the present invention relates to a method for sensing a body temperature of a person in need of such sensing, wherein the method comprises the steps explained in the following.

First, the body temperature of a person to whom an implantable medical device has been implanted is repeatedly sensed with a temperature sensor of the implantable medical device. In this context, the implantable medical device serves for stimulating a human or animal heart. It comprises, besides the temperature sensor, a processor, a memory unit, and a stimulation unit, a detection unit. The stimulation unit serves for stimulating a cardiac region of a human or animal heart. The detection unit serves for detecting an electrical signal of the same heart. The temperature sensor serves for sensing a body temperature or a temperature of the implantable medical device which directly corresponds to the body temperature of the patient to whom the implantable medical device has been implanted.

The body temperature is sensed a plurality of times so that a plurality of time-dependent body temperature values is obtained. The obtained body temperature values are stored in the memory unit.

Afterwards, a statistical analysis on at least a subset of the stored body temperature values, in particular on all of the stored body temperature values, is performed. This statistical

analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

The calculated statistical parameters are then used to be output, to adjust the previously
5 measured, calculated or determined temperature value or to be compared with an actually measured body temperature value. To be more specific, at least one of the tasks explained the following is performed.

One of the possible tasks is to output the body temperature reference value and/or the
10 variation of the sensed body temperature values and/or the variability of the sensed body temperature values.

Another possible task is to compare an actual body temperature value with the previously
calculated body temperature reference value.

15 Another possible task is to compare a predetermined expectancy value of temperature variations with the variation of the sensed body temperature values.

Another possible task is to compare a predetermined expectancy value of temperature
20 variability with a variability of the sensed body temperature values.

Another possible task is to add an absolute value of the variety or of the variability of the sensed body temperature values to the calculated body temperature reference value or, alternatively, to subtract an absolute value of the variety or of the variability of the sensed
25 body temperature values from the calculated body temperature reference value. In doing so, an adjusted body temperature reference value is obtained. This adjusted body temperature reference value can then be output or can be used to compare an actual body temperature value with the adjusted body temperature reference value.

30 In an embodiment, the method further comprises a step of indicating a risk of an infection of the person if an actual body temperature value measured with a temperature sensor exceeds the body temperature reference value or the adjusted body temperature reference

value by a predetermined value. In an embodiment, this predetermined value lies in a range from 0.3 to 2.0°C, in particular from 0.4 to 1.9°C, in particular from 0.5 to 1.8°C, in particular from 0.6 to 1.7°C, in particular from 0.7 to 1.6°C, in particular from 0.8 to 1.5°C, in particular from 0.9 to 1.4°C, in particular from 1.0 to 1.3°C, in particular from
5 1.1 to 1.2°C.

In an embodiment, the risk of infection is a risk of an influenza infection or the risk of a COVID-19 infection.

10 All embodiments of the implantable medical device can be combined in any desired way and can be transferred either individually or in any arbitrary combination to the described arrangement, the described methods, and to the described computer program product. Likewise, all embodiments of the described arrangement can be combined in any desired way and can be transferred either individually or in any arbitrary culmination to the
15 described implantable medical device, to the described methods, and to the described computer-readable program. Furthermore, all embodiments of the described methods can be combined in any desired way and can be transferred either individually or in any arbitrary combination to the respective other method, to the implantable medical device, to the arrangement, and to the computer program product. Finally, all embodiments of the
20 described computer program product can be combined in any desired way and can be transferred either individually or in any arbitrary combination to the described implantable medical device, to the described arrangement, and to the described methods.

The idea behind the invention shall subsequently be explained by referring to the
25 embodiments shown in the figures. Herein:

Fig. 1 shows an implantable medical device in accordance with the present invention implanted in a patient and in communication with an external evaluation unit;

30

Fig. 2 shows a schematic view of an implantable medical device in accordance with the present invention; and

Fig. 3 shows a schematic view of an evaluation unit in accordance with the present invention.

5 Fig. 1 illustrates the implantable medical device 10 implanted in a human patient 30 (although it could also be implanted in an animal) and attached to the heart 20. The heart 20 includes a right ventricle 21 and a right atrium 22 (and corresponding left ventricle and atrium – now shown). The implantable medical device 10 communicates with an evaluation unit 40 positioned outside the patient's body.

10

Fig. 2 illustrates the implantable medical device 10 that serves for stimulating a human or animal heart 20. The implantable medical device 10 is connected to the heart 20 at tissue contacts A and B, and comprises a processor 120, a memory unit 122, a stimulation unit 124, a detection unit 126, and a temperature sensor 132. The stimulation unit 124 serves
15 for stimulating a cardiac region of a human or animal heart 20. The detection unit 126 serves for detecting an electrical signal of the same heart 20. The temperature sensor 132 serves for sensing a body temperature or a temperature of the implantable medical device 10 which directly corresponds to the body temperature of the patient 30 to whom the implantable medical device 10 has been implanted.

20

According to the presently claimed invention, the memory unit 122 comprises a computer-readable program 130 that causes the processor 120 to perform the steps explained in the following when executed on the processor 120.

25 First, the temperature sensor 132 is caused to sense the body temperature of the person to whom the implantable medical device 10 is implanted. In this context, the temperature sensor 132 is caused to sense the body temperature a plurality of times so that a plurality of time-dependent body temperature values is obtained. The obtained body temperature values are stored in the memory unit 122.

30

Afterwards, a statistical analysis on at least a subset of the stored body temperature values, in particular on all of the stored body temperature values, is performed. This statistical

analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

The calculated statistical parameters are then used to be output, to adjust the previously
5 measured, calculated or determined temperature value or to be compared with an actually
measured body temperature value. To be more specific, the computer-readable program
130 causes the processor 120 to perform at least one of the tasks explained in the
following.

10 One of the possible tasks is to output the body temperature reference value and/or the
variation of the sensed body temperature values and/or the variability of the sensed body
temperature values. Then, these values can be used for further analyses or for
documentation purposes.

15 Another possible task is to compare an actual body temperature value with the previously
calculated body temperature reference value. In doing so, it is particularly simple to detect
an increase in body temperature and thus a potential infection of the patient carrying the
medical device in an implanted state. Thus, the calculated body temperature reference
value serves as an internal calibration of the temperature sensor 132 of the implantable
20 medical device 10. Even though the determination of the body temperature reference value
does not enable an absolute temperature calibration of the temperature sensor 132, it
guarantees a relative calibration so that future discrepancies from the calculated body
temperature reference value can be easily and exactly detected.

25 Another possible task is to compare a predetermined expectancy value of temperature
variations with the variation of the sensed body temperature values. By such a comparison,
a general body temperature trend can be observed and evaluated with respect to the
predetermined expectancy value (e.g., an expected temperature variation of a standard
population). In doing so, patient-specific temperature variations, either normal or
30 suspicious with respect to an infection, can be detected.

Another possible task is to compare a predetermined expectancy value of temperature variability with a variability of the sensed body temperature values. Such a comparison serves for the detection of intra-day or inter-day variances of the patient's body temperature and can help identifying future temperature deviations from the body temperature reference value as significant (i.e., being indicative for a possible infection) or as insignificant (lying within an expected range of variability). Furthermore, by evaluating the variability of the sensed body temperature, it is possible to evaluate temperature sensor 132 inaccuracies and to consider such inaccuracies for future body temperature evaluations.

10

The evaluation unit 40, as shown in Fig.3, comprises a second processor 420 and a second memory unit 422. The second memory unit 422 comprises a second computer-readable program 430 that causes the second processor 420 to perform the steps explained in the following when executed on the second processor 420.

15

First, the transmitted body temperature values are stored in the second memory unit 422.

Then, a statistical analysis is performed on at least a subset of the stored body temperature values, in particular on all stored body temperature values. This statistical analysis serves for calculating a body temperature reference value and/or a variation of the sensed body temperature values and/or a variability of the sensed body temperature values.

20

Afterwards, the evaluation unit 40 is caused to perform at least one of the tasks explained in the following.

25

One of the possible tasks is to output the body temperature reference value and/or the variation of the sensed body temperature values and/or the variability of the sensed body temperature values.

Another possible task is to compare an actual body temperature value with the previously calculated body temperature reference value.

30

Another possible task is to compare a predetermined expectancy value of temperature variations with the variation of the sensed body temperature values.

Another possible task is to compare a predetermined expectancy value of temperature
5 variability with a variability of the sensed body temperature values.

Another possible task is to add an absolute value of the variety or of the variability of the sensed body temperature values to the calculated body temperature reference value or, alternatively, to subtract an absolute value of the variety or of the variability of the sensed
10 body temperature values from the calculated body temperature reference value. In doing so, an adjusted body temperature reference value is obtained. This adjusted body temperature reference value can then be output or can be used to compare an actual body temperature value with the adjusted body temperature reference value.