What is claimed is:

1. A fishing rod comprising:

a base rod;

a grip and a reel seat adjacent to each other on an outer side of the base rod; and

a ring member between the grip and the reel seat,

wherein an extension portion that protrudes in an axial direction is on an end surface of the reel seat, the end surface being adjacent to the grip;

wherein a part of the grip overlaps the extension portion at an outer position in a radial direction;

wherein the ring member is interposed and fixed between the reel seat and a part of the grip on the extension portion; and

wherein an outer diameter of the ring member is less than an outer diameter of the reel seat at a position directly adjacent to the ring member and an outer diameter of the grip at a position directly adjacent to the ring member.

2. The fishing rod according to claim 1, wherein

an annular recessed portion is on an end surface on the reel seat side of the grip,

the extension portion is fixed to an inner surface of a wall portion forming the annular recessed portion, and

the ring member is interposed between the reel seat and an end surface of the wall portion.

3. The fishing rod according to claim 2, wherein

a step portion is on the reel seat side of the wall portion, and

the ring member is fixed on the step portion.

4. The fishing rod according to claim 1, wherein

a protrusion that extends in an axial direction is on the ring member, and

the protrusion is interposed between the extension portion and a part of the grip.

5. The fishing rod according to claim 1, wherein

the extension portion has an axial length of 4.5 mm or more from a distal end,

and

an axial length from the distal end of the extension portion to a position where the ring member abuts on a part of the grip is equal to or less than the axial length of the extension portion and is equal to or greater than 3.5 mm.

6. The fishing rod according to any one of claims 1 to 5, wherein

a spacer is interposed between the base rod and the reel seat, and

the spacer forms a gap surrounded by an end surface of the spacer, an end surface of the grip, and an inner surface of the extension portion.

7. A fishing rod comprising:

a base rod;

a grip and a reel seat adjacent to each other on an outer side of the base rod; and

a ring member between the grip and the reel seat,

wherein an extension portion that protrudes in an axial direction is on an end surface of the reel seat, the end surface being adjacent to the grip;

wherein a part of the grip overlaps the extension portion at an outer position in a radial direction;

wherein the ring member is interposed and fixed between the reel seat and a part of the grip on the extension portion;

wherein a protrusion that extends in an axial direction is on the ring member; and

wherein the protrusion is interposed between the extension portion and a part of the grip.