

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: C10G 47/16, B01J 29/80	A1	(11) International Publication Number: WO 97/20016 (43) International Publication Date: 5 June 1997 (05.06.97)
(21) International Application Number: PCT/EP96/05352 (22) International Filing Date: 26 November 1996 (26.11.96) (30) Priority Data: 95203269.6 28 November 1995 (28.11.95) EP (34) Countries for which the regional or international application was filed: GB et al. (71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL). (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA). (72) Inventors: KRAUSHAAR-CZARNETZKI, Bettina; Badhuisweg 3, NL-1031 CM Amsterdam (NL). WJNBELT, Johannes; Badhuisweg 3, NL-1031 CM Amsterdam (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: CATALYST COMPOSITIONS AND THEIR USE IN HYDROCARBON CONVERSION PROCESSES (57) Abstract <p>The present invention provides a catalyst composition, and a hydrocarbon conversion process in which it is used, comprising as first cracking component a zeolite beta having a silica to alumina molar ratio of at least (20) which is in the form of crystals less than 100 nm in size; a second cracking component selected from (i) crystalline molecular sieves having pores with diameters greater than 0.6 nm, (ii) crystalline, mesoporous aluminosilicates having pores with diameters of at least 1.3 nm, and (iii) clays; and at least one hydrogenation component.</p>		