

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 May 2002 (02.05.2002)

PCT

(10) International Publication Number
WO 02/35014 A1

(51) International Patent Classification⁷: **E02D 23/00**

(21) International Application Number: PCT/US01/28098

(22) International Filing Date:
7 September 2001 (07.09.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/693,470 20 October 2000 (20.10.2000) US
09/704,998 2 November 2000 (02.11.2000) US
09/727,343 29 November 2000 (29.11.2000) US

(71) Applicant and

(72) Inventor: **KHACHATURIAN, Jon, E.** [US/US]; 5427
Sutton Place, New Orleans, LA 70131 (US).


(74) Agents: **GARVEY, Charles, C.** et al.; Garvey, Smith,
Nehrbass & Doody, L.L.C., 3 Lakeway Center, Suite 3290,
3838 North Causeway Boulevard, Metairie, LA 70002
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE
(utility model), DK, DK (utility model), DM, DZ, EC, EE,
EE (utility model), ES, FI, FI (utility model), GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA,
UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

[Continued on next page]

(54) Title: ARTICULATED MULTIPLE BUOY MARINE PLATFORM APPARATUS AND METHOD OF INSTALLING SAME



(57) Abstract: A marine platform 17 (and method of installation) provides a plurality of buoys 13-16, a platform 17 having a peripheral portion that includes a plurality of attachment positions 27, one attachment position for each buoy, and a connection 24,27 that connects each buoy to the platform at a respective attachment position 27, the connection 24,27 allowing for sea state induced buoy motions while minimizing effect on the platform 17. Each connection 24,27 can provide first and second portions 65,66 (or devices) and a load transfer mechanism that transfers load from the first portion 65 to the second portion 66 so that one of the portions (or devices) can be serviced. In an alternative embodiment a method of installation places the platform 17 (including oil and gas drilling and/or production facility next to the buoys 13-16. Ballasting moves the platform 17 and buoys 13-16 relative to one another until connections 24,27 are perfected between each buoy 13-16 and the platform 17.



CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*