A1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
31 January 2002 (31.01.2002)

PCT

(10) International Publication Number
WO 02/08659 A1

(51) International Patent Classification[7]: F17C 13/00

(21) International Application Number: PCT/NO01/00316

(22) International Filing Date: 23 July 2001 (23 07 2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20003841 26 July 2000 (26 07.2000) NO

(71) Applicant *(for all designated States except US)*: **VENTURIE AS** [NO/NO], Hølleveien 43, N-4640 SØGNE (NO)

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **HALSE, Helge-Ruben** [NO/NO], Odderhei Terrasse 79, N-4638 KRISTIANSAND S. (NO)

(74) Agent: **HÅMSØ, Gunnar**, Håmsø Patentbyrå, Vågsgaten 43, N-4306 Sandnes (NO).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW


(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

[Continued on next page]

(54) Title: GAS CONDENSER

162162

WO 02/08659 A1



(57) Abstract: Gas condenser (2) arranged to condense gas/vapour (4) evaporating from a volatile liquid (6) being stored, for example, in a storage tank. The gas/vapour (4) is conducted into a gas chamber (16) provided with openings, possibly also nozzles (76), the gas chamber (16) being placed in a surrounding housing (36) Thereafter, the gas/vapour (4) is sucked into at least one venturi section (62, 64), wherein the liquid (6), for example, is flowing with a static underpressure relative to the inflowing gas/vapour (4). Via at least one expansion section (88, 90), a mixture (92) of gas/vapour (bubbles) (4) and liquid (6) flows onward to a condensing chamber (98), through which the static pressure of the liquid (6) increases and the gas/vapour (4) is condensed, after which the mixture (92) is conducted back to, for example, the storage tank By means of one or several adjusting devices arranged to the gas condenser (2), the shape of the slot volume of the venturi section(s) (62, 64), possibly also the slot volume of expansion section(s) (80, 90), and thus the course of pressure through it/them, may be optimally adjusted/changed/adapted to the current operating condition and the current gas condensing need

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette