

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 July 2003 (03.07.2003)

PCT

(10) International Publication Number
WO 03/054413 A2

- (51) International Patent Classification⁷: **F16F**
- (21) International Application Number: PCT/US02/39546
- (22) International Filing Date:
11 December 2002 (11.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/025,025 19 December 2001 (19.12.2001) US
- (71) Applicant: **ENERGY ABSORPTION SYSTEMS, INC.**
[US/US]; One East Wacker drive, Chicago, IL 60601 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (72) Inventors: **WELCH, James, B.**; 6703 Long Avenue, Placerville, CA 95667 (US). **COBB, Lincoln, C.**; 12543 Incline Drive, Auburn, CA 95603 (US).
- (74) Agent: **STOVER, Andrew, D.**; BRINKS HOFER GILSON & LIONE, P.O.Box 10087, Chicago, IL 60610 (US).
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: HIGHWAY CRASH ATTENUATOR FRAME

(57) Abstract: A highway crash attenuator frame includes transverse elements that are interconnected by side elements. Each side element is disposed entirely on a respective side of a central longitudinal axis of the frame, and one or more tension elements are secured to the side elements to extend between the side elements across the longitudinal axis. Each tension element includes a mechanical fuse operative to fail in tension when the first and second side elements supply an excessive tensile load to the tension element. When the mechanical fuse fails in tension in an impact, the side elements are simultaneously released to move outwardly, away from the longitudinal axis, and thereby to collapse in a way which is coordinated between the left and the right sides of the frame.



WO 03/054413 A2