

Behind-the-ear hearing aid

The present invention relates to a behind-the-ear hearing aid according to the preamble of claim 1.

In hearing aids of this type, it is customary to provide an on/off switch and, separately from the latter, a further actuating member, for example for adjusting the amplification. This leads, especially when operating the applied hearing aid, to the problem of having to feel around for the particular actuating member required, quite apart from the fact that considerable structural volumes are taken up by the actuating members provided, and the provision of said members leads to considerable complication of the hearing aid with the electrical connections to be provided, and thus also to increased susceptibility to faults.

It is an object of the present invention to eliminate said disadvantages. For this purpose, the hearing aid according to the invention is distinguished according to the characterizing clause of claim 1.

Thus, according to the invention, two categories of switching functions are combined on one and the same actuating member, namely, in said positions, preferably

the ON/OFF switch of the hearing aid and, in a second actuating direction, for example adjustment of the amplification. In this way, the user friendliness is considerably increased as it is easily possible to differentiate by feel between the two different types of actuation provided on the one actuating switch. Furthermore, a single actuating switch provided according to the invention requires less structural volume, and in addition the hearing aid as a whole is made simpler because electrical connections to switching members have to be guided only into the area of the one actuating member provided according to the invention.

By providing only one mechanical actuating member, the susceptibility to faults is also reduced, and, in particular, if faults do occur, they are much simpler to rectify.

As has been mentioned, in a preferred embodiment, one of the positions is used as the ON-position of the hearing aid, while the other is used as the OFF position, and the actuating member acts as a toggle switch when activated in the second direction. In a further preferred embodiment, the actuating member is mounted tiltably on a substantially linearly displaceable slide and has a contact which, by activation in the second direction, can be brought into

contact with a switching contact secured on the hearing aid. This contact is preferably made of rubber-elastic plastic, preferably in the shape of a small hat, as is known from computer keyboard mats or remote-control keyboards. It is also preferred that the first actuating direction of the actuating member lies substantially in the direction of generating lines of the hearing-aid body, preferably along generating lines on the outside curvature, in relation to the flexure of the hearing-aid body, and the second actuating direction is perpendicular to the wall of the hearing-aid body.

The behind-the-ear hearing aid according to the invention is explained in an illustrative manner below with reference to figures which show a presently preferred embodiment of the behind-the-ear hearing aid.

Fig. 1 shows, in a simplified longitudinal section, a behind-the-ear hearing aid according to the invention;

Fig. 2 shows a perspective representation of the hearing aid according to the invention;

Fig. 3 shows a perspective representation of the preferred design of a battery compartment lid on the hearing aid according to the invention;

Fig. 4 shows the top view of the lid according to Fig. 3 with areas for left/right ear coding;

Fig. 5 shows a perspective representation of, on the one hand, the main housing of the hearing aid according to the invention and, on the other hand, an add-on module which is or can preferably be provided;

Fig. 6 shows an enlarged representation of the electric/acoustic transducer unit on the hearing aid according to the invention as per Fig. 1;

Fig. 7 shows a simplified and schematic representation of an actuating member provided in accordance with the invention on the hearing aid according to the invention, and

Fig. 8 shows a schematic representation of the unit according to Fig. 6 in order to illustrate the acoustic couplings.

The behind-the-ear hearing aid according to the invention is represented in its entirety in Fig. 1, in a partially simplified longitudinal section, and its individual operational blocks or operational parts will be described first. The hearing aid 1 comprises a tubular main body which is curved in a horn shape, with a center axis A, and which has, acting as acoustic

output at the thinner, curved end, a connector piece 5 for a coupling tube leading into the ear. The connector piece 5 is exchangeably pushed or screwed onto a tubular piece 9 which sits on a main housing 3.

The inner channel 7 of the connector piece 5 continues through the tubular piece 9 into a transfer channel 11 in the main housing 3. The transfer channel 11 is in turn coupled to an electric/acoustic transducer arrangement 15 in a section 13 of the main housing 3.

As can be seen from Fig. 1, the transfer channel 11 extends along the inner curvature of the main housing 3 in such a way that there is space for a microphone unit 17 on the side of the outer curvature. A lid 19 is formed integrally on the main housing 3 in this area, and it is stopped by means of a pin shaft 21 in the region of the maximum point of the curve of the hearing aid. As can be seen in particular in Fig. 2, the lid 19 extends along generatrices M of the hearing-aid body as far as (Fig. 1) the area of the electric/acoustic transducer unit 15. The microphone unit 17 is accessible on removal of the hinged lid 19 and preferably makes electrical contact only at a flexprint strap (not shown), is closed over the transfer channel 11 and rests against an acoustic input slot 23.

When the lid 19 is closed, at least two microphone

apertures of the microphone unit 17 lie opposite an insert 25 in a slot 23 of the lid 19. The insert 25 is acoustically "transparent" and has a multiplicity of passages between the environment U and a compensating volume V, the latter being left free between the discrete microphone inlet apertures (not shown) and said insert. The insert 25 is preferably made of a sintered material, in particular of sintered polyethylene, and is also preferably provided with a water-repellant coating. It also forms a mesh fineness of between 10 μm and 200 μm , with an open-pore rate of preferably above 70%. Moreover, the microphone unit 17 and the insert 25 in the slot 23 are arranged in the hearing aid 1 in such a way that, when the hearing aid is being worn, they are shielded as far as possible from any dynamic air pressure of the environment U by being positioned, as can be seen from Fig. 1, in the area of the apex of the horn-shaped curved tubular main body. In particular, as regards the embodiment of an acoustic/electric transducer with directional characteristics using the abovementioned at least two mutually spaced microphones, the gap volume V, entailing a common mode suppression, tends to cancel identical acoustic signals differently coupled-in along the insert 25 on account of the compensating effect of the volume V.

The insert 25 also acts as a shield against soiling

and, by virtue of its preferred water-repellant coating, can be easily cleaned.

A further advantage of the insert 25 with its multiplicity of through-openings is, closely linked to the aspect of the aforementioned common mode suppression, that any soiling will affect both microphones equally and, as a result, the directional characteristics will not be adversely affected, something which represents a central problem in conventional directional microphones with two or more discrete apertures.

Regarding this insert 25 and its effects, reference is made to EP-A-0,847,227 of the same Applicant.

In the main housing 3, the electric/acoustic transducer arrangement 15 is followed by an electronics unit 27, then by a battery compartment 29. An actuator switch 31 is provided on the outside of the main housing of the hearing aid, in the area between battery compartment 29 and electronics unit 27. The connector piece 5, the main housing 3, the lid 19 with acoustic input slot 23 and insert 25, and the actuator switch 31 can be seen particular clearly in the perspective representation of Fig. 2.

Battery compartment

In the battery compartment 29 formed in the end of the main housing 3, a cylindrical flat battery or a correspondingly shaped accumulator 33 is inserted in such a way that the axis of the battery cylinder, with its end faces 33_u and 33_o, lies at least substantially coaxial to the longitudinal axis A of the main body.

Provided on the base 30 of the battery compartment 29, and centered on the axis A, there is a first spring-loaded contact 35, and a second one 37 is in resilient contact with the side surface of the battery 33. The battery compartment 29 can be closed by a lid 39 which in the closed position is transverse to the axis A and which is mounted in a pivotable or bayonet-lock manner on the main housing 3, at 41, or on the battery compartment 29.

This transverse arrangement of the battery 33 in the hearing aid affords considerable advantages: The surface closed off by the lid 39 is relatively large, and this can be exploited still further, as will be explained below. Because the battery compartment lid 39 is arranged at the deepest part of the hearing aid and the lid areas abutting the main housing 3 lie transverse to the axis A, penetration of perspiration into the battery compartment is hardly critical.

Moreover, in this design of the battery compartment, the contacts 37 and 35 are protected inside the compartment, and the lid 39 has no electrical contacts. Also, because the substantially cylindrical interior of the main body 3 is fully exploited, there is practically no space left unused.

Fig. 3 shows a perspective representation of a preferred embodiment of the battery compartment lid 39, designed as a hinged lid. With the snap-on hinge part 43, it can be easily released from or snapped into the pivot bearing 41 according to Fig. 1. In a preferred embodiment, it also has a lock 45 and in addition a resilient pawl 46.

Fig. 4 shows an outside view of the lid 39 according to Fig. 1. The lock 45 can be operated from the outside only using a tool, for example a screwdriver, and for this purpose it has an engagement slot 49 on a rotary disk 47. The disk 47, which is integrated in the hinged lid 39 only when the lock 45 is installed, is colored in a specific manner, in two ways, for example red and blue, so that this part at the same time serves as an indicator of whether the particular hearing aid is for the left ear or right ear.

As has been stated, the represented embodiment of the battery compartment 29, in particular the fact that the

flat cylinder of the battery lies coaxial to the axis A of the hearing aid, has a further important advantage. The hearing aid shown in Fig. 1 effectively represents a basic configuration.

It is often desirable to equip this basic configuration with add-on options, for example with an interface unit for wireless signal transmission, a programming plug-in unit, a further audio input, a larger accumulator compartment, a mechanical actuator unit, etc. To this end, the battery compartment shown in Fig. 1 is redesigned as shown in Fig. 5. The battery 33 is removed from the compartment and in its place the plug-in part 34 of a corresponding add-on module 51 is inserted and is made to electrically contact at the contacts 35a and 37a corresponding to the battery contacts.

Regarding the use of such add-on modules, it is readily possible to provide further contacts in the compartment 29.

The compartment 29a now acting as the actual battery compartment, with the battery 33, is now provided on the add-on module 51, and, likewise, the lid 39, which is removed for example from the main housing 3, is snapped onto the add-on module or locked onto it in the manner of a bayonet lock. If appropriate, several such modules 51 can be stacked onto the basic module of the

hearing aid represented in Fig. 1. The add-on modules 51 are in each case fixed preferably with a locking part 43a provided on the modules 51 and analogous to the hinge part 43 on the hinged lid 39, and with a snap-in part 46a designed analogously to the snap-in part 46 on said hinged lid 39, or, in the case of bayonet locking, by appropriate insertion and rotary locking.

In this way, the hearing aid can be built up in modular fashion in an extremely simple way and in the manner desired, and the battery and accumulator 33 are at all times readily accessible from outside.

Electric/acoustic transducer arrangement

Fig. 6 shows, in a simplified manner, the design and the support of the abovementioned arrangement 15 on the main housing 3 and in a view according to Fig. 1. The arrangement 15 comprises, encapsulated in a loudspeaker housing 53, the loudspeaker arrangement (not shown) with a loudspeaker diaphragm. By way of coupling apertures indicated schematically at 55, the acoustic waves generated by the loudspeaker diaphragm are coupled from the diaphragm-side space in the loudspeaker housing 53 into the surrounding space U_{53} of the loudspeaker housing 53. From the space on the front side of the diaphragm, the acoustic signals are

coupled, as indicated by the arrow S, into the transfer channel 11 shown in Fig. 1.

The loudspeaker housing 53 is supported on all sides in a substantially freely vibrating manner in resilient and preferably rubber-elastic bearings 57. The relatively large space U_{53} is defined, by the supports 57, between the outer wall of the loudspeaker housing and a capsule 59, said large space significantly enhancing the bass tones. The resonance chamber on the reverse side of the diaphragm is increased by a multiple by the space U_{53} . To ensure that the space U_{53} is acoustically effective about its entire circumference, the capsule 59 and its support 61 are tightly connected.

In this way, the storage volume for the loudspeaker arrangement is used to the optimum extent acoustically. The capsule 59 also preferably acts as a magnetic shield housing and for this purpose is preferably made of μ -metal. It is beaker-shaped and is hooked sealingly in the form of a plastic bearing part into the support 61. The abovementioned resilient and preferably rubber-elastic bearings 57 are tensioned between capsule 59 and support 61, on the one hand, and the loudspeaker housing 53.

The acoustic coupling discussed above is shown in

purely diagrammatic terms in Fig. 8. The diaphragm 54 of the loudspeaker in the housing 53 defines, in said housing, a first space R_1 , which is coupled to the acoustic output of the hearing aid, as indicated by S, and a second space R_2 which is coupled via one or more openings 55 to the space U_{53} formed between capsule 59 and housing 53.

Actuator switch 31

Fig. 7 shows a preferred embodiment of the actuator switch 31, in a simplified and diagrammatic representation. The actuator switch 31 comprises a toggle key 63 which is mounted in a tilting manner on one side, at 65.

The toggle support 65 is formed integrally on a slide 67 which, as is shown by the double arrow F, is mounted so as to be displaceable linearly with respect to the main housing 3. As is shown diagrammatically by the spring contact 69, ~~fixed in~~ relation to the main housing 3, and the bridging contact 70 on the slide 67, the hearing aid is switched on and off by pushing the slide to and fro via the key 63.

A continuous channel 72 is formed in the slide 67, and a contact pin 73 fixed to the housing 3 protrudes through this channel. This contact pin is covered by a

resilient contact part 75 which is arranged on the slide 67 and which as a keypad element is preferably made of rubber-elastic and at least partially electrically conductive plastic, as is known for example from remote-control keyboards. When toggling the toggle key 63, as is indicated by the double arrow K, the contact part 75 comes into contact with the contact pin 73 and establishes an electrical connection between these elements. Although a number of possible electrical connections suggest themselves to the skilled person, including the switching path S_1 , actuated by the slide motion F, and the switching path S_2 , actuated by the toggle movement K of the toggle key 63, it is preferable, as is indicated by broken lines in Fig. 7, to connect the spring contact 69 to the hearing-aid battery 33, the bridging contact 70 to the contact part 75, and the contact pin 73 then acts as an electrical output of the switch arrangement.

The actuator switch 31 thus acts both as an on/off slide switch and additionally, in the on position, as a toggle switch, as a result of which the electronics unit 27 according to Fig. 1 can be acted on in steps, for example for rapid individual adjustment of amplification.

Accordingly, the actuator switch 31 combines two functions, namely slide switch and toggle switch, which

combination of functions is highly advantageous in particular for the behind-the-ear hearing aid according to the invention. The operational differential ensures that there is no confusion of the functions, which confusion is substantially more critical if two switches are provided for said two functions.

Structure of the housing 3

As can be seen in particular from Fig. 5, the main housing 3 is formed by a curved and correspondingly shaped tubular part. In a preferred embodiment, this part 3 is made in one piece, preferably of plastic, but unlike the conventional structure of such hearing aids it cannot be separated into two shells along generatrices indicated by M in Fig. 5. In this way, the assembling of the individual units into the main housing 3 is also defined: They are simply introduced into the tube, which is much easier than assembling on opened shells. A further advantage of a tubular one-piece embodiment is its much greater stability compared to a divided housing. It is thus possible to reduce the thickness of the housing wall and in so doing to reduce its size, or, for a given outer volume, to increase the useful internal volume.

Advantages of the overall configuration

Referring to Fig. 1, it is clear, particularly from the preferred one-piece design of the main housing 3, that the individual structural units, in particular 11, 15, 27, 29 and/or 51, are assembled by being pushed axially and sequentially into the main housing 3. The shape of the housing 3 with its corresponding guides thereby ensures rapid and exact positioning, the mutual electrical contact between the electrically powered units being solder-free and effected by means of spring-loaded contacts. Thus, the units to be provided can be pre-tested and dimensioned and thereafter assembled without any fear of their being damaged. This assembling can be easily automated. The entire housing including main housing 3 and lid 19, if appropriate 39, fitted with appropriate seals at the contact zones, can be easily sealed off.

The preferred embodiment of the electric/acoustic transducer arrangement 15 ensures optimum magnetic shielding of the loudspeakers and optimum acoustic shielding in respect of hearing-aid acoustics.

Patent Claims:



1. A behind-the-ear hearing aid with a hook-shaped curved hearing-aid body, substantially along a similarly curved longitudinal axis (A) of the hearing aid, in which acoustic/electric transducers (17), electric/acoustic transducers (15) and electronics units (27) are integrated, and with an operating switch member provided on the body, characterized in that the operating switch member (31) can be moved with electrical contact in a first actuating direction (F) into at least a first and second position, and, in at least one of the positions, can be moved with electrical contact in a further actuating direction (K).
2. The behind-the-ear hearing aid as claimed in claim 1, characterized in that at least one of the positions is the ON position of the hearing aid, ~~the first OFF position, and in that~~ the actuating member (31) acts as a toggle switch when actuated in the second direction (K).
3. The behind-the-ear hearing aid as claimed in either of claims 1 and 2, characterized in that the actuating member (31) is mounted tiltably (65) on a substantially linearly displaceable slide



(67) and has a contact (75) which, by activation in the second direction (K), can be brought into contact with a switching contact (73) secured on the hearing aid.

4. The behind-the-ear hearing aid as claimed in claim 3, characterized in that the contact (75) which can be brought into contact with the switching contact secured on the hearing aid is made of rubber-elastic plastic, preferably in the shape of a small hat.
5. The behind-the-ear hearing aid as claimed in one of claims 1 through 4, characterized in that the first actuating direction (F) is substantially in the direction of generating lines (M) of the hearing-aid body, preferably along generating lines on the outside curvature, and the second actuating direction (K) is perpendicular to the wall of the hearing-aid body.