

NEEDLE SHIELD REMOVERS, DRUG DELIVERY DEVICES, AND RELATED METHODS

[0001]

Field of the Disclosure

[0002] The present disclosure relates to drug delivery devices, and, more particularly, devices for automatically injecting a drug into a patient.

Background

[0003] A general aversion to exposed needles, as well as health and safety issues, have led to the development of drug delivery devices which conceal a needle or other insertion member prior to use and which automate various aspects of an injection process. Such devices offer a variety of benefits as compared with traditional forms of drug delivery including, for example, delivery via a conventional syringe.

[0004] A drug delivery device may incorporate various mechanisms to implement various automated features. Such features include automatically covering a needle in a pre-delivery and/or post-delivery state, providing an interface for a user to activate a drive mechanism, indicating to the user that drug delivery is complete, among other features. Typically a drug delivery device will incorporate a separate or independently operable mechanism to realize each of its automated features. As a consequence, with each added feature, the mechanical complexity of the device tends to increase. This, in turn, can increase the size of the device, which can make it cumbersome for the user to handle, as well as increase manufacturing costs and timeframes. As the demand grows for drug delivery devices with greater ease of use and safety, finding a way to incorporate more automated features without adding undue complexity to the drug delivery device presents various design and manufacturing challenges.

[0005] The present disclosure sets forth drug delivery devices embodying advantageous alternatives to existing drug delivery devices, and that may address one or more of the challenges or needs mentioned herein.

Summary

[0006] In accordance with a first aspect, there is provided a needle shield remover comprising: a body having a tubular configuration with first and second ends, the body formed from a sheet of material having opposing first and second longitudinal edges; a closure configured to couple the first and second longitudinal edges together to form the tubular configuration of the body, the closure comprising: a plurality of teeth extending laterally outwardly from the first longitudinal edge; and a plurality of grooves extending laterally inwardly into the sheet of material from the second longitudinal edge, wherein the plurality of teeth extend generally perpendicularly away from the first longitudinal edge; and the plurality of grooves extend along an axis at an angle with respect to the second longitudinal edge, such that the plurality of teeth bend as each respective tooth enters a respective one of the plurality of grooves; a first plurality of barbs arrayed around a circumference of the body adjacent to the first end, the first plurality of barbs configured to grip a removable cap; and a second plurality of barbs arrayed around a circumference of the body adjacent to the second end, the second plurality of barbs configured to grip a needle shield.

[0007] In further forms, each of the first plurality of barbs and the second plurality of barbs can extend within an opening of the body and include a distal end having laterally spaced pointed tips and/or the first plurality of barbs and the second plurality of barbs can extend inwardly into the body.

[0008] In further forms, each of the plurality of teeth can include an associated cut-out portion configured to relieve stress within the material as a result of the plurality of teeth bending. In some examples, the cut-out portion can be disposed in an edge of each of the plurality of teeth or in a corner between each of the plurality of teeth and the first longitudinal edge. In additional forms, the plurality of grooves can extend along an axis at an angle of between 5 degrees and 20 degrees with respect to the second longitudinal edge and/or the axes of the

plurality of grooves can be staggered to extend above or below a horizontal line extending between the first and second longitudinal edges.

[0009] In accordance with a second aspect, there is provided an auto-injector drug delivery device comprising: a housing; a drug container coupled to the housing, the drug container including a needle; a needle shield disposed at least partially over a distal end of the needle of the drug container; a removable cap coupled to the housing; and a needle shield remover defined in the first aspect coupled to the removable cap and the needle shield, such that uncoupling the removable cap from the housing removes the needle shield off the needle of the drug container, wherein the first plurality of barbs grip the removable cap and the second plurality of barbs grip the needle shield.

[0010] In further forms, each of the first plurality of barbs and the second plurality of barbs can extend within an opening of the body and include a distal end having laterally spaced pointed tips and/or the first plurality of barbs and the second plurality of barbs can extend inwardly into the body.

[0011] In some forms, the removable cap can include a central wall configured to be gripped by the first plurality of barbs and, in further forms, an annular wall spaced outwardly from the central wall configured to engage an outer surface of the first end of the body.

[0012] The closure of these forms can have a configuration according to any of the above configurations. Additionally, the needle shield remover of any of the above forms can be symmetrical about a horizontal plane extending through a midpoint of the body perpendicular to a longitudinal axis thereof.

[0013] In accordance with a third aspect, there is provided a method of forming the needle shield remover as defined in the first aspect from a strip of metal, the method comprising: forming a sheet from the strip of metal having first and second longitudinal edges and end edges, where the sheet comprising the closure for the needle shield remover including the plurality of teeth extending laterally outwardly from the first longitudinal edge and the plurality of grooves extending laterally inwardly into the sheet of material from the second longitudinal edge; forming a first plurality of barbs across a width of the strip of metal; forming a second plurality of barbs across the width of the strip of metal; and creating a tubular form from the sheet by forcing the plurality of teeth into the plurality of grooves.

[0014]

[0015] In some forms, the method can include punching guide holes into the strip of metal to form a cutting pattern for the closure, the first plurality of barbs, and the second plurality of barbs.

Brief Description of the Drawings

[0016] Figure 1 is a perspective view of a drug delivery device according to various embodiments of the present disclosure.

[0017] Figure 2 is cross-sectional view of the drug delivery device in Figure 1.