RAMPS copy

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04L 12/26, G04B 17/00, 3/46, G06F — A1

(11) International Publication Number: **WO 97/28626**

(43) International Publication Date: 7 August 1997 (07.08.97)

(21) International Application Number: PCT/AU97/00055

(22) International Filing Date: 31 January 1997 (31.01.97)

(30) Priority Data:
PN 7868 2 February 1996 (02.02.96) AU

(71) Applicant *(for all designated States except US)*: TELSTRA CORPORATION LIMITED [AU/AU]; 242 Exhibition Street, Melbourne, VIC 3000 (AU).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: ROWLES, Christopher, David [AU/AU]; 43 Waratah Avenue, Belgrave, VIC 3160 (AU). SEMBER, Peter, Paul [AU/AU]; 22 Neville Street, Glenhuntly, VIC 3163 (AU). SZYMCZAK, Mark [AU/AU]; 5 Merlyn Avenue, Clayton, VIC 3169 (AU).

(74) Agents: WEBBER, David, Brian et al.; Davies Collison Cave, 1 Little Collins Street, Melbourne, VIC 3000 (AU).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: A NETWORK FAULT SYSTEM

(57) Abstract

A network fault system (2) for mobile telecommunications network which includes a first interface (8, 14) for accessing first fault data representative of faults reported by users of mobile stations of the network a second interface (12, 14) for accessing second fault data representative of faults in the network determined by a network analysis system (10), and pattern matching means (14, 24) for allocating the first and second fault data to fault patterns representative of faults having at least one common characteristic.

