

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/074493 A3

(51) International Patent Classification:

E21B 10/00 (2006.01) *E21B 10/08* (2006.01)

(21) International Application Number:

PCT/US2005/001796

(22) International Filing Date: 13 January 2005 (13.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

10/768,532 30 January 2004 (30.01.2004) US

(71) Applicants and

(72) Inventors: **AARON, Anna, Victorovna** [US/US]; 5117 Presley Drive, Flowery Branch, GA 30542-3728 (US).
LYTVYNENKO, Viktor [UA/UA]; Kosigina Street 7/41, Krivoy Rog 50082 (UA).

(74) Common Representative: **AARON, Anna, Victorovna**; 5117 Presley Drive, Flowery Branch, GA 30542-3728 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv))

Published:

— with international search report

[Continued on next page]

(54) Title: ANTI-TRACKING EARTH BORING BIT WITH SELECTED VARIED PITCH FOR OVERBREAK OPTIMIZATION AND VIBRATION REDUCTION



(57) Abstract: An earth boring drill bit is constructed having rotatable cutter for forming a borehole in earth. At least one circumferential row of cutting elements is optimized to create overbreak of rock and eliminate tracking, wherein selected pitches have mathematically determined pairs and the absolute difference between the selected pitch and its pair is greater than 10 % of the difference between maximum and minimum pitch for that circumferential row. Furthermore, cutting elements are placed along pre-selected generatrices with deviated from said generatrices, which is less than half the maximum pitch of circumferential rows occupied by said cutting element. The present invention eliminates tracking and reduces detrimental axial resonance frequency vibration while reducing cutting element count, including tungsten - carbide inserts, as compared to conventional roller cutter drill bits used for oil, gas and shot hole drilling wells and simultaneously increases footage drilled, drilling speed, and durability.



— *with amended claims*

Date of publication of the amended claims: 3 August 2006

(88) Date of publication of the international search report:
18 May 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.