

92916965.4

IPos Copy

9606221-1

PATENTANWALT G. ZEITLER

POSTFACH 26 02 51
D-8000 MÜNCHEN 26

TELEFON: 089 / 22 18 06
TELEX: 523 535 zeit d
TELEFAX: 089 / 22 26 27

HERRNSTRASSE 15
D-8000 MÜNCHEN 22

3769

TITLE OF THE INVENTION

Capsule

BACKGROUND ART

The present invention relates to a capsule of the
5 kind used to mount the upper parts of the neck of a
bottle the mouth of which has been closed by a cork,
screw-cap, bung or other form of closure, and exposed
parts of the closure to provide a tamper-evidence cover
for the closure, and an ornamental addition.

10 According to the invention there is provided a
bottle having a neck the mouth of which is closed by a
bung, cork, screw-cap or other form of closure, the upper
portions of the neck of the bottle and the exposed por-
tion of the applied closure being covered by a capsule
15 formed from a material of a tin, aluminum or an any of
these materials laminated with a synthetic resin film,
the sides of a capsule being deformed inwardly into close
contact with the surface of the neck of the bottle and
any exposed laterally-facing surface of the closure,
20 whereby the capsule is retained on the closure and
provides a tamper-evidence cover for the closure.

Hitherto, as illustrated in Figure 1, a capsule
comprises a cap portion 1, skirt portion 2, and a tea-
rable guarantee strip 3 connecting the cap portion 1 and
25 the skirt portion 2. And weakening lines 4 and 5 are



provided, respectively, at a boundary between the tearable guarantee strip 3 and the cap portion 1, and at a boundary between the tearable guarantee strip 3 and the skirt portion 2. The weakening lines 4 and 5 are

5 generally formed by compressing a capsule body in the direction of thickness like a perforation. Accordingly, when pulling the tearable guarantee strip 3 outwardly, the tearable guarantee strip 3 is gradually torn and removed along the weakening lines 4 and 5 due to less
10 strength of these lines formed compressively like a perforation. After removing completely the tearable guarantee strip 3 and the cap portion 1, the bottle is unsealed or open.

In this respect, the conventional weakening lines 4
15 and 5 are formed as illustrated in Figure 2. That is, saw-tooth-like compressed sections 6 are formed at the boundary between the tearable guarantee strip 3 and the cap portion 1 as well as at the boundary between the tearable guarantee strip 3 and the skirt portion 2. A
20 problem, however exists in the mentioned removal of the tearable guarantee strip 3 as follows. That is, at the time of pulling the tearable guarantee strip 3 circumferentially and outwardly by picking up a bulge thereof, there arises a disadvantage that a non-compressed parts 7
25 each locating between one tooth and another of the



saw-tooth-like compressed sections 6 protrudes outwardly from the circumference of the bottle.

Notwithstanding, the mentioned disadvantage has not been considered serious because lead is employed as a material for capsule. More specifically, since lead is a relatively soft material, there is almost no possibility of feeling pain in the finger or injuring any finger in such case of touching the protrusions (i.e., burr).

Recently, however, it has been pointed out that lead is disqualified for capsule material because lead is not suitable for the health and poisonous once entering into human body, resulting in lead poisoning and lead injury.

It has been a recent trend to employ tin for a capsule material. Tin is a material harder than lead. Hence, the mentioned disadvantage of feeling pain or injuring finger has become a serious problem. More specifically, in case of tin capsule, there arises a serious problem of feeling pain in the finger or injuring finger when touching burr formed of the non-compressed parts 7. In

particular, the skirt portion 2 is still left on the neck of the bottle after opening the bottle, being different from the tearable guarantee strip 3 and the cap portion 1 which are removed once opening the bottle. As a result, the burr formed on the upper edge of the skirt portion 2 may cause a pain in the finger or injure it when touching



the burr at the time of handling the bottle. The situation is quite the same even when employing a soft aluminium which is also a material harder than lead.

DISCLOSURE OF THE INVENTION

5 The present invention was made to solve the above-discussed problem and has an object of providing an improved capsule of tin or soft aluminium in which burr causing any finger to feel pain or to be injured, i.e., larger and sharp burr, is not formed after tearing and
10 removing the tearable guarantee strip.

 To accomplish the foregoing object, in the capsule according to the invention, each of the weakening lines comprises linear compressed part forming a boundary between a tearable guarantee strip and a skirt portion,
15 and saw-tooth-like compressed parts serrating from the linear compressed part to the tearable guarantee strip side. The saw-tooth-like compressed parts may serrate to the skirt portion side instead of serrating to the
tearable guarantee strip side.

20 More, to accomplish the foregoing object, each of weakening lines comprises circular arc compressed parts each drawing an arc on the tearable guarantee strip side so that the circular arc compressed parts are located at the boundary between the tearable guarantee strip and the
25 skirt portion with a certain distance between one



circular arc and another. Instead of the circular arc compressed parts, the circular arc perforated parts may be located at the boundary between the tearable guarantee strip and the skirt portion.

5 The capsule according to the invention comprises a cap portion 1, a skirt portion 2 and a tearable guarantee strip 3 connecting the cap portion 1 and the skirt portion 2. The capsule is hollow so as to be mounted on the neck of the bottle. Since the neck of the bottle is
10 almost cylindrical in general, the cap portion 1 is a cylinder having a bottom, while the tearable guarantee strip 3 and the skirt portion 2 are cylinders without bottom.

 For opening or unsealing the bottle, a bulge of the
15 tearable guarantee strip 3 is pulled circumferentially and outwardly, and the tearable guarantee strip is torn along the each of the weakening lines. Then, the cap portion 1 is removed to expose the closure which is then opened. Accordingly, the weakening lines 4 and 5 are
20 formed at the boundary between the tearable guarantee strip 3 and the cap portion 1 as well as at the boundary between the tearable guarantee strip 3 and the skirt portion 2 so that the tearable guarantee strip 3 is easy to be removed at the time of pulling it. The invention
25 is principally characterized by the construction



arrangement of the weakening line 5 as described hereinafter.

As illustrated in Figure 3 or 4, the weakening line 5 comprises a linear compressed part 8 disposed at the boundary between the tearable guarantee strip 3 and the skirt portion 2, and saw-tooth-like compressed parts 9 serrating from the linear compressed part 8 to the tearable guarantee strip 3 side. This arrangement of the weakening line 5 is intended to make it difficult to form large and sharp burr on the upper edge of the skirt portion 2. On the other hand, as for the weakening line 4 disposed at the boundary between the cap portion 1 and the tearable guarantee strip 3, any arrangement may be freely employed. However, since it is also desired to make it difficult to form large and sharp burr on the lower edge of the cap portion 1, it is preferable that the weakening line 4 is also arranged in the same manner as the mentioned weakening line 5. In other words, the weakening line 4 is preferably comprised of the linear compressed part 8 disposed at the boundary between the tearable guarantee strip 3 and the cap portion 1, and the saw-tooth-like compressed parts 9 serrating from the linear compressed part 8 to the tearable guarantee strip 3 side. The linear compressed part 8 and the saw-tooth-like compressed parts 9 are both formed by compressing a



region of the tearable guarantee strip 3 in the direction of thickness. In such compression, a wedge-shaped cutting edge with sharp tip end is generally used.

Compressive force to be applied for forming the linear

5 compressed parts 8 may be either the same as or different from that for forming the saw-tooth-like parts 9. It is particularly preferable that compressive force to be

applied for forming the saw-tooth-like compressed parts 9 is higher than that to be applied for forming the linear

10 compressed part 8. Because if a higher compressive force is applied for forming the linear compressed part 8, the linear compressed part 8 is easy to be broken, and there is a possibility of breaking the linear compressed part 8 without cooperation with the saw-tooth-like compressed

15 parts 9, thereby causing the upper edge of the skirt portion 2 to be sharp-edged, eventually resulting in the danger of injuring any finger. It is also capable that, in the process of compressing the saw-tooth-like

compressed parts 9, the saw-tooth-like compressed parts 9

20 are partially perforated by applying a very high pressure thereto. As is obvious from the above description, any desired opening or unsealing characteristic may be

applied to the capsule by adjusting or varying strength of the compressive force applied between the linear

25 compressive part 8 and the saw-tooth-like compressed



parts 9.

It is also capable that, as illustrated in Figure 8, the weakening line 5 comprising a linear compressed part 8 disposed at the boundary between the tearable guarantee strip 3 and the skirt portion 2, and
5 saw-tooth-like compressed parts 9 serrating from the linear compressed part 8 to the skirt portion 2 side. As a result of such arrangement, any burr is difficult to come out on the upper edge of the skirt portion 2. Also
10 in this case, with regard to the weakening line 4 disposed at the tearable guarantee strip 3 and the cap portion 1, any arrangement may be employed. However, since it is desired to make it difficult to form burr on the lower edge of the cap portion 1, it is preferable
15 that the weakening line 4 comprises a linear compressed part 8 disposed at the boundary between the tearable guarantee strip 3 and the cap portion 1, and the saw-tooth-like compressed parts 9.

As for specific examples of the mentioned arrangement of the linear compressed part 8 and the saw-tooth-like compressed parts 9 forming the weakening lines 4 and
20 5, Figure 3 and 8 and Figure 4 respectively show several examples. Each of the weakening lines illustrated in Figures 3 and 8 comprises the linear compressed part 8
25 and the saw-tooth-like compressed parts 9, and a flat



line is formed between one saw tooth and another in the saw-tooth-like parts 9. Each of the weakening lines 4 and 5 illustrated in Figure 4 also comprises linear compressed part 8 and saw-tooth-like compressed parts 9, but the saw-tooth-like compressed parts 9 are closely or densely disposed and no flat line is formed between one saw tooth and another. In addition, width of the linear compressed part 8, serrating length of the saw-tooth-like compressed parts 9, pitch of the saw-tooth-like compressed parts 9, etc. may be selected freely.

In the weakening lines comprising the linear and saw-tooth-like compressed parts as described above, when trying to tear the tearable guarantee strip along the weakening lines by pulling the tearable guarantee strip outwardly, the tearable guarantee strip may be easily torn due to the linear compressed part disposed throughout the saw teeth of the saw-tooth-like compressed parts. If no linear compressed part is disposed, every portion between one saw tooth and another of the saw-tooth-like parts 9 is not easily torn or removed, but some large force will be applied from outside to the portion between one saw tooth and another, resulting in unnecessary formation of large and sharp burr. In this respect, the capsule according to the invention may effectively prevent every non-compressed part from forming conside-



5 rable outward protrusion by the existance of the linear
compressed part, when applying some large force from
outside. In effect, burr formed by the outward protru-
sion of the non-compressed parts are relatively small and
round. Accordingly, when employing the capsule according
to the invention, an advantage is such that there is no
feel of pain in such case of touching the upper edge of
the skirt portion of the capsule left on the bottle after
opening it. This advantage of feeling no pain as
10 mentioned above is also exhibited at the time of throwing
the removed tearable guarantee strip and cap portion, as
a result of arranging the weakening line disposed at the
boundary between the tearable guarantee strip and the cap
portion as described above.

15 The weakening line 5 may comprise a plurality of
circular arc compressed parts 18 each disposed with a
certain distance between one circular arc and another so
that each arc of the circular arc compressed parts 18 is
drawn on the tearable guarantee strip 3 side, as illust-
20 rated in Figure 9. These circular arc compressed parts
18 are formed by compression in the shape of circular arc
without compressing outside 21 and inside 20 thereof.
The weakening line 5 is formed as mentioned above because
even if any burr is formed on the upper edge of the skirt
25 2 portion from the non-compressed part between one



circular arc compressed part 18 and another at the time of tearing along the weakening line 5, a non-compressed circular arc portion 20 located inside the circular arc compressed part 18 will protrude outward more largely than the formed burr. If the inside 20 of the circular arc compressed part 18 should protrude outwardly, no pain will be felt in any finger or no finger will be injured in such case of touching the inside 20 because of its circular arc shape. Distance α between one circular arc compressed part and adjacent another, chord length β of each circular arc compressed part 18, and height γ thereof may be freely selected considering material, etc. of the capsule so as to be easy to tear. It is preferable the chord of every circular arc compressed part 18 is located in a row. It is further preferable to additionally provide dot-like holes or compressed parts each between the circular arc compressed parts adjacent each other so as to be easier to tear the tearable guarantee strip 3.

Arrangement of the weakening line 4 formed between the cap portion 1 and the tearable guarantee strip 3 may be freely selected, in case of forming the weakening line 5 of the circular arc compressed parts 18. It is preferable that this weakening line 4 is arranged in the same manner as the mentioned weakening line 5. More



specifically, as illustrated in Figure 9, the weakening line 4 preferably comprises a plurality of circular arc compressed parts 18 each disposed with a certain distance so that each arc of the circular arc compressed parts 18 is drawn on the tearable guarantee strip 3 side. Because in the weakening line 4 of such arrangement, a non-compressed circular arc portion 20 which is located inside the circular arc compressed part 18 will protrude outward largely than the burr formed at the non-compressed portion between one circular arc compressed part 18 and another. In this regard, the circular arc compressed parts 18 formed between the cap portion 1 and the tearable guarantee strip 3 and the circular arc compressed parts 18 formed between the skirt portion 2 and the tearable guarantee strip 3 may be both formed by compression with a semi-circular cylindrical cutter of which tip end is sharpened like a graver. In compression, it is preferable to apply a strong compressive force so that the circular arc compressed parts 18 are partially formed into through holes. By such formation, the tearable guarantee strip 3 is easy to tear along the weakening lines 4 and 5. It is to be noted that "the circular arc" used herein includes not only perfect circular arc but also U-shape, oval in section.

It is also capable to provide the weakening lines 4



and 5 in the form of circular arc holes instead of the circular arc compressed parts 18. The circular arc compressed parts 18 are formed by compression as mentioned above. On the other hand, the circular arc holes are provided by punching. Accordingly, holes of perfect circular arc are formed on the required portion, being different from the holes formed in the circular arc compressed parts 18 by strong compression.

Since the weakening lines are formed of a large number of circular arc compressed parts or circular arc punched hole parts as illustrated in Figure 9, when tearing along the weakening lines, the non-compressed parts or non-punched parts inside the circular arc compressed or punched hole parts protrude largely outward thereby each forming a circular arc protrusion. Such circular arc protrusions are larger than the sharpened burr formed by protruding the non-compressed parts between one circular arc compressed part and another. Accordingly, when touching the upper edge of the skirt portion with finger, the touched part is a circular arc protrusion having a round end, and there is almost no possibility of touching the dangerous sharpened burr. Thus, an advantage is exhibited such that fingers are effectively prevented from feeling pain or being injured.

As for the material for the capsule, a metallic



foil of 100% by weight of tin or alloy thereof is mainly used. It is also capable to use a foil of 100% by weight of aluminum or alloy thereof. The conventionally used foil of 100% by weight of lead or alloy thereof can be
5 used as a material of capsule as a matter of course. It is also capable to use any of these metallic foils coated with a synthetic resin film. Thickness of the mettalic foil is preferably not more than 200 μ m. If the thickness of metallic foil is more than 200 μ m, the capsule is
10 exces- sively hard, and the tearable guarantee strip 3 tends to be difficult to be torn along the weakening lines 4 and 5.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a front view of a capsule.

15 Figure 2 is an enlarged front view showing a tearable guarantee strip and adjacent portions of the capsule according to the prior art, and in which each weakening line comprises saw-tooth-like compressed parts only.

20 Figure 3 is an enlarged front view showing a tearable guarantee strip and adjacent portions of the capsule according to an example of the present inventon, and in which each weakening line comprises linear com-pressed part and saw-tooth-like compressed parts.

25 Figure 4 is an enlarged front view showing a



tearable guarantee strip and adjacent portions of the capsule according to another example of the invention, and in which each weakening line comprises linear compressed parts and saw-tooth-like compressed part
5 disposed more closely.

Figure 5 is an enlarged front view showing a tearable guarantee strip of the capsule prepared as a comparative exapmle, and in which each weakening line comprises linear compressed part only.

10 Figure 6 is an enlarged view showing a weakening line according to an example of the invention.

Figure 7 is a sectional view of the weakening line taken along the line A-A in Figure 6.

Figure 8 is an enlarged front view of a tearable
15 guarantee strip and adjcent portions of the capsule according to another example of the invention, and in which each weakening line comprises linear compressed part and saw-tooth-like compressed parts.

Figure 9 is an enlarged front view of a tearable
20 guarantee strip and adjacent portions of the capsule according to a further example of the invention, and in which each weakening line comprises circular arc compressed parts.

BEST MODE FOR CARRYING OUT THE INVENTION

25 Examples 1 to 4 and Comparative Examples 1 to 5



Capsules each of 150 μ m in thickness at the
weakening lines were prepared by molding using a tin foil
of 200 μ m in thickness. Every capsule was provided with
the weakening lines 4 and 5 illustrated in Figure 3
5 (Examples 1 to 4). Different capsules each provided with
the weakening lines 4 and 5 illustrated in Figure 2
(Comparative Examples 1 to 4) and Figure 5 (Comparative
Example 5) were also prepared using the same tin foil as
Examples 1 to 4. Tables 1 and 2 respectively show
arrangement of the weakening lines 4 and 5 of the
capsule.

This Sheet Has Been Replaced.



Table 1

	Example	1	2	3	4
5	Width of weakening line	a	1.5mm	1.0mm	1.5mm
	Width of linear compressed part	b	0.3mm	0.3mm	0.3mm
	Serrating length of saw-tooth-like compressed parts	c	1.2mm	0.7mm	1.2mm
	Pitch of saw-tooth-like compressed parts	d	1.4mm	1.4mm	1.4mm
	Max. depth of linear compressed part	e	100 μ m	50 μ m	100 μ m
15	Max. depth of saw-tooth-like compressed parts	f	*	*	130 μ m
	Max. width of saw-tooth-like compressed parts	g	0.7mm	0.7mm	0.7mm
	Angle of tooth of saw-tooth-like compressed parts	h	85°	85°	85°
20	Distance between linear compressed parts		8mm	10mm	8mm
					10mm



Table 2

		Comparative Example	1	2	3	4	5
5	Width of weakening line	a	1.0mm	1.0mm	1.5mm	1.5mm	0.5mm
	Width of linear compressed part	b	-	-	-	-	0.5mm
	Serrating length of saw-tooth-like compressed parts	c	1.0mm	1.0mm	1.5mm	1.5mm	-
10	Pitch of saw-tooth-like compressed parts	d	1.0mm	1.0mm	1.0mm	1.4mm	-
	Max. depth of linear compressed part	e	-	-	-	-	100 μ m
15	Max. depth of saw-tooth-like compressed parts	f	100 μ m	*	*	*	-
	Max. width of saw-tooth-like compressed parts	g	0.5mm	0.5mm	0.5mm	0.7mm	-
	Angle of tooth of saw-tooth-like compressed parts	h	70°	70°	85°	85°	-
20	Distance between linear compressed parts		8mm	8mm	8mm	8mm	8mm

This Sheet Has Been Replaced



Maximum depth of the linear compressed part and that of the saw-tooth-like compressed parts shown in Tables 1 and 2 mean a distance from the deepest point to the surface since the compressed parts are wedge-shaped in the direction of thickness. In the tables, when the applied compressive force was so strong that the linear and saw-tooth-like compressive parts were partially provided with holes, depth was not measured but indicated simply by the mark * in the tables. Maximum width of the saw-tooth-like compressed parts means a distance at the widest point of each tooth. In this respect, Figures 6 and 7 show respectively location of each column item in Tables 1 and 2.

With respect to every capsule obtained as mentioned above, the tearable guarantee strip was torn along the weakening lines, then the tearable guarantee strip was removed, and conditions of burr formed on the upper edge of the skirt portion and the lower edge of the cap portion, feeling and unsealing (or opening) characteristic were evaluated. Table 3 shows the result. In this regard, three-grade evaluation was employed as to feeling, while five-grade evaluation was employed as to the unsealing characteristic, as mentioned below.

(Feeling) 1: No pain was felt at all when touching the cut edge of the skirt or the like. 3: A little pain was



felt when touching the cut edge of the skirt or the like.

5: A strong pain was felt when touching the cut edge of the skirt or the like.

- (Unsealing characteristic) 1: Unsealing was achieved
5 very smoothly. 2: Unsealing was achieved smoothly.
3: Unsealing was achieved with average smoothness.
4: Unsealing was achieved with a little stiffness.
5: Unsealing was acheived with a large stiffness.

This Sheet Has Been Replaced.



Table 3

	Formation of burr	Feeling	Unsealing characteristic
Example	Small round burr		
5 1	were found	1	1
Example	Small round burr		
2	were found	1	2
Example	Small round burr		
3	were found	1	1
10 Example	Small round burr		
4	were found	1	2
Comparative	Large sharp burr		
Example 1	were found	5	5
Comparative	Large sharp burr		
15 Example 2	were found	5	4
Comparative	Large sharp burr		
Example 3	were found	5	4
Comparative	Large sharp burr		
Example 4	were found	5	5
20 Comparative	Sharp edge was		
Example 5	formed without burr	3	3

It is obviously understood from Table 3 that in case of the capsules according to Examples of the invention, though burr were formed, those burr were so



small and round that no pain was felt in such case of touching them. On the other hand, in case of the capsule according to Comparative Examples 1 to 4, large and sharp burr was formed, and pain was felt in such case of touching them. In case of the capsule according to Comparative Example 5, since the weakening lines comprise the linear compressed parts only, no burr was formed, but the upper edge of the skirt portion and the lower edge of the cap portion were sharp-edged, and there was a feeling like injuring finger on the sharp edge in such case of touching them. From the viewpoint of unsealing characteristic, it is understood that the capsules according to Examples 1 to 4 were superior to those according to Comparative Examples 1 to 5.

Examples 5 to 8 and Comparative Examples 6 to 9

Capsules each of 150 μ m in thickness at the weakening lines were prepared by molding using a tin foil of 200 μ m in thickness. Each of these capsules was provided with the weakening lines 4 and 5 illustrated in Figure 8. Arrangement of the weakening lines 4 and 5 was changed as shown in Table 4, thus capsules according to Examples 5 to 8 being obtained. Further, capsules according to Comparative Examples 6 to 9 were also prepared, and in which weakening lines were formed by removing the linear compressed parts from the weakening



lines 4 and 5 illustrated in Figure 8 (i.e., weakening lines formed by changing the weakening line 4 illustrated in Figure 2 so that acute angle of each saw-tooth is facing to the cap portion side, and by changing the
5 weakening line 5 illustrated in Figure 2 so that acute angle of each saw-tooth is facing to the skirt portion side). Dimensions of each weakening line of the capsules according to these Comparative Examples 6 to 9 are as shown in Table 5.

This Sheet Has Been Replaced



Table 4

	Example	5	6	7	8
5	Width of weakening				
	line	a	1.5mm	1.0mm	1.5mm
	Width of linear				
	compressed part	b	0.3mm	0.3mm	0.3mm
	Serrating length of				
10	saw-tooth-like				
	compressed parts	c	1.2mm	0.7mm	1.2mm
	Pitch of saw-tooth-				
	like compressed parts	d	1.4mm	1.4mm	1.4mm
	Max. depth of linear				
15	compressed part	e	100 μ m	50 μ m	100 μ m
	Max. depth of saw-				
	tooth-like compressed				
	parts	f	*	*	130 μ m
	Max. width of saw-				
20	tooth-like				
	compressed parts	g	0.7mm	0.7mm	0.7mm
	Angle of tooth of				
	saw-tooth-like				
	compressed parts	h	85°	85°	85°
	Distance between linear				
	compressed parts		8mm	10mm	8mm



Table 5

Comparative Example		6	7	8	9	
5	Width of weakening line	a	1.0mm	1.0mm	1.5mm	1.5mm
	Width of linear compressed part	b	-	-	-	-
	Serrating length of saw-tooth-like compressed parts	c	1.0mm	1.0mm	1.5mm	1.5mm
	Pitch of saw-tooth-like compressed parts	d	1.0mm	1.0mm	1.0mm	1.4mm
	Max. depth of linear compressed part	e	-	-	-	-
15	Max. depth of saw-tooth-like compressed parts	f	100μm	*	*	*
	Max. width of saw-tooth-like compressed parts	g	0.5mm	0.5mm	0.5mm	0.7mm
	Angle of tooth of saw-tooth-like compressed parts	h	70°	70°	85°	85°
20	Distance between linear compressed parts		8mm	8mm	8mm	8mm



With respect to every capsule obtained as mentioned above, the tearable guarantee strip was torn along the weakening lines, and unsealing characteristic was evaluated. Then, the tearable guarantee strip was removed, and feeling of burr formed on the upper edge of the skirt portion and the lower edge of the cap portion was evaluated. Table 6 shows the result.

This Sheet Has Been Replaced



Table 6

	Formation of burr	Feeling	Unsealing characteristic
Example	Scarcely burr		
5 5	were found	1	1
Example	Scarcely burr		
6	were found	1	2
Example	Scarcely burr		
7	were found	1	1
10 Example	Scarcely burr		
8	were found	1	2
Comparative	Large sharp burr		
Example 6	were found	5	5
Comparative	Large sharp burr		
15 Example 7	were found	5	4
Comparative	Large sharp burr		
Example 8	were found	5	4
Comparative	Large sharp fins		
Example 9	were found	5	5

20

It is obviously understood from Table 6 that in case of the capsules according to Examples 5 to 8, since burr were scarcely formed, no pain was felt in such case of touching them. On the other hand, in case of the capsule according to Comparative Examples 1 to 4, large

25



and sharp burr were formed, and pain was felt in such case of touching them. Concerning the unsealing characteristic, the capsules according to Examples 5 to 8 were smoothly opened or unsealed. On the contrary, the capsules according to Comparative Examples 6 to 9 were stiff and not smoothly unsealed. In addition, every column item shown in Table 4 to 6 has the same meaning as Table 1 to 3.

Example 9 to 12

Capsules each of 150 μ m in thickness at the weakening lines were prepared by molding using a tin foil of 200 μ m in thickness. Each of these capsules was provided with the weakening lines 4 and 5 illustrated in Figure 9. Distance α between one circular arc compressed part and adjacent another, chord length β of each circular arc compressed part, and height γ of each circular arc compressed part were as shown in Table 7.



Table 7

		9	10	11	12
5	Distance between one circular arc compressed part and adjacent another α	0.3mm	0.3mm	0.6mm	0.6mm
	Chord length of circular arc compressed part β	1.0mm	1.0mm	1.0mm	0.8mm
10	Height of circular arc compressed part γ	0.8mm	0.8mm	0.8mm	1.0mm
	Depth of circular arc compressed part	*	130 μ m	**	130 μ m
15	Distance between weakening lines	8mm	10mm	10mm	10mm

In Table 7, the mark ** indicates the circular arc hole provided by punching in place of circular arc compressed part.

20 With respect to the capsules according to Examples 9 to 12, evaluation was carried out on the feeling, formation of burr and unsealing characteristic. Table 8 shows the results.



Table 8

	Formation of burr	Feeling	Unsealing characteristic
Example 9	Burr were found		
5	between one circular arc compressed part and adjacent another	1	1
Example 10	Burr were found		
10	between one circular arc compressed part and adjacent another	1	1
Example 11	Burr were found		
15	between one circular arc compressed part and adjacent another	1	1
Example 12	Burr were found		
20	between one circular arc compressed part and adjacent another	1	2

It is obviously understood from Table 8 that in case of the capsules according to Examples 9 to 12, though burr were formed, circular arc protrusions protruding outwardly were also formed more largely than the burr, and therefore no pain was felt in such case of



touching them. On the other hand, as is obvious from Table 3, in case of the capsules according to Comparative Examples 1 and 2, burr with sharp point were formed, and pain was felt in such case of touching them. Concerning the unsealing characteristic, the capsules according to Examples 9 to 12 were smoothly unsealed. On the contrary, the capsules according to Comparative Examples 1 and 2 were stiff and not smoothly unsealed.





What is claimed is :

1) A capsule comprising a cap portion, a skirt
portion and a tearable guarantee strip connecting said
cap portion and said skirt portion, and weakening lines
5 formed respectively at a boundary between said tearable
guarantee strip and said cap portion and at a boundary
between said tearable guarantee strip and said skirt
portion, characterized in that

10 said weakening line formed at the boundary between
said tearable guarantee strip and said skirt portion
comprises linear compressed part disposed along the
boundary between said tearable guarantee strip and said
skirt portion, and saw-tooth-like compressed parts
serrating from said linear compressed part to said
15 tearable guarantee strip side.

2) A capsule as set forth in claim 1, wherein said
weakening line formed at the boundary between said
tearable guarantee strip and said cap portion comprises
linear compressed part disposed along the boundary
20 between said tearable guarantee strip and said cap
portion, and saw-tooth-like compressed parts serrating
from said linear compressed part to said tearable
guarantee strip side.

3) A capsule comprising a cap portion, a skirt
25 portion and a tearable guarantee strip connecting said





cap portion and said skirt portion, and weakening lines formed respectively at a boundary between said tearable guarantee strip and said cap portion and at a boundary between said tearable guarantee strip and said skirt portion, characterized in that

said weakening line formed at the boundary between said tearable guarantee strip and said skirt portion comprises linear compressed part disposed along the boundary between said tearable guarantee strip and said skirt portion, and saw-tooth-like compressed parts serrating from said linear compressed part to said skirt portion side.

4) A capsule as set forth in claim 3, wherein said weakening line formed at the boundary between said tearable guarantee strip and said cap portion comprises linear compressed part disposed along the boundary between said tearable guarantee strip and said cap portion, and saw-tooth-like compressed parts serrating from said linear compressed part to said cap portion side.

5) A capsule as set forth in any of claim 1, 2, 3, or 4, wherein said saw-tooth-like compressed parts are strongly compressed as compared with said linear compressed part.

6) A capsule as set forth in claim 5, wherein said





saw-tooth-like compressed parts are partially provided with holes.

5 7) A capsule comprising a cap portion, a skirt portion and a tearable guarantee strip connecting said cap portion and said skirt portion, and weakening lines formed respectively at a boundary between said tearable guarantee strip and said cap portion and at a boundary between said tearable guarantee strip and said skirt portion, characterized in that

10 said weakening line formed at the boundary between said tearable guarantee strip and said skirt portion comprises a large number of circular arc compressed parts each drawing an arc on said tearable guarantee strip side and disposed with a certain distance between one circular arc compressed part and another.

15 8) A capsule as set forth in claim 7, wherein said weakening line formed at the boundary between said tearable guarantee strip and said cap portion comprises a large number of circular arc compressed parts each drawing an arc on said tearable guarantee strip side and disposed with a certain distance between one circular arc compressed part and another.

20 9) A capsule as set forth in claim 7 or 8, wherein said circular arc compressed parts are provided with holes.





10) A capsule as set forth in claim 7 or 8, wherein non-compressed parts each located between two circular arc compressed parts adjacent each other are provided with dot-like holes or compressed parts.

5 11) A capsule comprising a cap portion, a skirt portion and a tearable guarantee strip connecting said cap portion and said skirt portion, and weakening lines formed respectively at a boundary between said tearable guarantee strip and said cap portion and at a boundary
10 between said tearable guarantee strip and said skirt portion, characterized in that

said weakening line formed at the boundary between said tearable guarantee strip and said skirt portion comprises a large number of circular arc holes each
15 drawing an arc on said tearable guarantee strip side and disposed with a certain distance between one circular arc and another.

20 12) A capsule as set forth in any of claims 1, 2, 3, 4, 7, 8 or 11, wherein material of the capsule is a metallic foil mainly composed of tin or aluminium.

13) A capsule as set forth in claim 12, wherein thickness of said mettalic foil is not more than 200 μ m.

25 14) A capsule as set forth in any of claim 1, 2, 3, 4, 7, 8 or 11, wherein material of the capsule is a laminated product of a metallic foil mainly composed of



tin or aluminum and a synthetic resin film.

This Sheet Has Been Replaced.



* C L N S *