(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
1 May 2003 (01.05.2003)

PCT

(10) International Publication Number
WO 03/035243 A3

(51) International Patent Classification[7]: B01J 13/00, C09G 1/06, C10M 169/02, C10L 1/16, 1/22 // (C10M 169/02, 101:02, 101:04, 115:08, 119:02)

(21) International Application Number: PCT/US02/33746

(22) International Filing Date: 22 October 2002 (22.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/007,496 22 October 2001 (22.10.2001) US

(71) Applicant: S. C. JOHNSON & SON, INC. [US/US]; 1525 Howe Street, Racine, WI 53403 (US).

(72) Inventor: MOODYCLIFFE, Timothy, I.; 270 East Highland Avenue, Milwaukee, WI 53202 (US).

(74) Agent: MCDONALD, Frank, B.; S. C. Johnson & Son, Inc., 1525 Howe Street, Racine, WI 53403 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

(88) Date of publication of the international search report:
30 October 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 03/035243 A3

(54) Title: VISCOSITY MODIFICATION OF PETROLEUM DISTILLATES

(57) Abstract: A method for the thickening of mineral oil products, wherein the thickened mineral oil product exhibits shear-thinning so as to be applicable to a surface by non-pressurized spray mechanisms. The thickening agent added to the petroleum distillate comprises a thixotropic thickener chosen from the group consisting of mixtures comprising a triblock copolymer and a hydrocarbon oil, and N-Lauroyl glutamic acid di-n-butylamide.