(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 2003/087523 A3

(51) International Patent Classification[7]: E21B 33/04

(21) International Application Number:
PCT/US2003/011418

(22) International Filing Date: 11 April 2003 (11.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/372,399	12 April 2002 (12.04.2002)	US
10/411,543	10 April 2003 (10.04.2003)	US

(71) Applicant: **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Highway, Houston, TX 77040 (US).

(72) Inventors: **REIMERT, Larry, E.**; 6 Winner's Circle, Houston, TX 77024 (US). **MILBERGER, Lionel, J.**; 8911 Rocky Lane, Houston, TX 77040 (US).


(74) Agent: **HELMREICH, G., Loren**; Browning, Bushman, PC, Suite 1800, 5718 Westheimer, Houston, TX 77057 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SPLIT CARRIER ANNULUS SEAL ASSEMBLY FOR WELLHEAD SYSTEMS



(57) Abstract: The seal assembly (10) seal between a subsea wellhead housing (12) and a casing hanger (16). A metal seal body (20) includes fingers (32 and 34) and one or more elastomeric seals (38). An upper seal body (64) may include threads for engagement with the metal seal body. According the method of the invention, an initial elastomeric seal is first formed, and fluid pressure is applied from above to set the high temperature metal seal.

WO 2003/087523 A3

Published:
— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
29 July 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.