

9801679-3
IPOS's copy



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04R 17/00, 7/06, 1/02		A1	(11) International Publication Number: WO 97/09861
			(43) International Publication Date: 13 March 1997 (13.03.97)
(21) International Application Number: PCT/GB96/02160		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, <u>SG</u> , SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 2 September 1996 (02.09.96)			
(30) Priority Data: ① 9517918.0 ✓ 2 September 1995 (02.09.95) ✓ GB ✓ ② 9522281.6 ✓ 31 October 1995 (31.10.95) ✓ GB ✓ ③ 9606836.6 ✓ 30 March 1996 (30.03.96) ✓ GB ✓			
(71) Applicant (for all designated States except US): VERITY GROUP PLC [GB/GB]; Stonehill, Huntingdon, Cambridgeshire PE18 6ED (GB). ASSIGNEE		Published With international search report. ✓ Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(72) Inventors; and (75) Inventors/Applicants (for US only): ① AZIMA, Henry [CA/GB]; 3 Southacre Close, Chaucer Road, Cambridge CB2 2TT (GB); ② COLLOMS, Martin [GB/GB]; 22 Burgess Hill, London NW2 2DA (GB); ③ HARRIS, Neil [GB/GB]; 9 Davey Crescent, Great Shelford, Cambridge CB2 5JF (GB).		3 PDS 1 appl. 3 Invs.	
(74) Agent: MAGUIRE & CO.; 5 Crown Street, St. Ives, Cambridgeshire PE17 4EB (GB).			

(54) Title: INERTIAL VIBRATION TRANSDUCERS ✓

(57) Abstract

An inertial vibration transducer (9) characterised by a plate-like piezo-electric bender (27) and means (20, 93) adapted to mount the bender on a member (2) to be vibrated, the arrangement being such that a substantial part of the bender is spaced from the member for movement relative thereto.

