



(43) International Publication Date
24 September 2009 (24.09.2009)

PCT

(10) International Publication Number
WO 2009/114927 A1

(51) International Patent Classification:
B04C 3/06 (2006.01)

(21) International Application Number:

PCT/CA2008/001059

(22) International Filing Date:

3 June 2008 (03.06.2008)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12/050,882 18 March 2008 (18.03.2008) US

(71) Applicant (for all designated States except US): **UTI LIMITED PARTNERSHIP** [CA/CA]; Suite 130, 3553-31 Street N.W., Calgary, Alberta T2L 2K7 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAN, Zhongchao** [CN/CA]; 7 Citadel Crest Heath N.W., Calgary, Alberta T3G 4W4 (CA). **YU, Zhimin** [CA/CA]; 3749 Springbank Dr. S.W., Calgary, Alberta T3H 4J5 (CA).

(74) Agents: **FRITZ, Joachim, T.** et al.; Borden Ladner Gervais LLP, World Exchange Plaza, 100 Queen Street, Suite 1100, Ottawa, Ontario K1P 1J9 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI

[Continued on next page]

(54) Title: CYCLONE




FIG. 1

(57) Abstract: A cyclone includes a cylindrical housing and has an inner diameter D. An inlet is near a first end of the housing. A deflection member can be positioned within the first end or the second end of the housing, depending on whether the cyclone is uniflow or reverse flow. An outlet tube is positioned within and extends from a second end or the first end of the housing (depending on whether uniflow or reverse flow). A bunker is formed between the outlet tube and an inner wall of the housing in a uniflow design and between the deflection member and the housing in a reverse flow design, and collects particles separated from an inlet gas stream. A gap between the deflection member and the outlet tube has a length in the range of approximately $0.4 \cdot D$ to $0.8 \cdot D$. The length of the bunker is approximately greater than or equal to $1.5 \cdot D$.



(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, **Published:**
NE, SN, TD, TG).

— *with international search report (Art. 21(3))*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii))*