

An identity card and a method for producing an identity card

The present invention relates to an identity card according to the preamble of claim 1 and to a method of producing such an identity card.

Identity cards of the type in question here are, for example, check cards, credit cards, membership cards and the like, the card structure corresponding generally to ISO Standard 7813 (DIN 9781).

Such identity cards are designed for example as multilayer plastic cards. On the front of the card there is general information, such as the name of a credit institute, and user-related information, such as the printed name of the user, his account number, the card number and the like. Furthermore, the user's signature is present on a special signature field. When the card is handed out, the user is usually requested to put his signature in the special signature field.

In order to avoid forgery and falsification, the identity cards are produced and designed in such a way as to rule out imitation and/or fraudulent manipulation of the card.

The safety measures include the card structure itself. For example, a multilayer card structure made of plastic, in which the data are located in the interior of the card between layers welded together using heat and pressure, prevents direct access to the data and thus their falsification.

A further safety feature is a so-called security print, usually a guilloche print but possibly also a logo, a microprint of sequences of letters and numbers and the like. Due to their complicated design, such security prints serve in particular to prevent both total forgeries - i.e. complete reproductions - and falsification.

A frequent object of such unauthorized manipulation is the signature of the authorized user located on the card. In order to rule out falsification, i.e. manipulation, of these signatures, particularly the signature field must thus be equipped with special safety features to prevent the signature of the authorized card user from being removed and replaced by a manipulator's signature. Since the signature is generally written on the surface of the finished card, the signature field must firstly take up the ink permanently, and secondly be designed in such a way that any attempts at erasure will lead to a change in the signature field that can be checked by anyone and is preferably conspicuous.

Various methods and measures have been proposed for protecting signature stripes from forgery, i.e. reproduction and/or manipulation.

DE-C 27 56 692 describes an identity card in which a signature stripe made of paper or plastic and provided with steel intaglio printing is laminated onto the card body.

Since the signature stripe is very difficult to imitate due to the special and complicated steel intaglio print, there is a relatively low risk of the proper stripe being replaced by a forged stripe.

DE-A 16 46 225 shows an identity card having a glued-on signature stripe equipped with a security pattern that is destroyed by any attempt to remove the old signature, and thereby exposes a warning print (void). However, one could fundamentally replace the destroyed signature stripe by a reproduction.

It has also been proposed to make a signature stripe printed onto the card body unforgeable by using special inks, e.g. fluorescent inks (DE-C 28 01 015, EP-A 176 403). An otherwise valid identity card of this type could also be provided with a forged signature stripe. DE-C 34 22 908 describes an identity card in which a hologram additionally provided in the signature field is to protect the signature stripe from forgery that is provided on the card body by the hot embossing technique. However, the production of such cards using the hot embossing technique is elaborate, and the hologram can be replaced by a deceptively similar metallically reflecting image (simulacrum counterfeit).

FR-A 2 449 930 describes an identity card with a signature stripe laminated on separately and protected by a security print located not only on the signature field but on the card body.

Apart from the abovementioned attempts to make the signature stripe unforgeable, there are also proposals according to which the signature is invisible when regarded in daylight or artificial light from usual light sources and can only be made visible using special light sources, e.g. using a UV lamp. This limits the possibilities of checking so as to be unacceptable in many cases.

GB-A 2 040 807 describes an identity card wherein a microcapsule layer located within the card body is discolored by application of pressure from the outside, e.g. using a hard pen, so that the signature can be provided subsequently in the interior of the card. However, the constant use of this card and the unavoidable mechanical stress thereby destroys more and more microcapsules so that the card shows an undesirable coloration.

US-C 2,545,804 describes an identity card having a paper inlay and a plastic coating on both sides, one plastic layer having a window through which the free place in the paper inlay can be written on. However no precautions were taken for protecting the signature from forgery.

The above-described known identity cards have the common feature that the signature must be made personally. Along with identity cards of this kind, there are also those in which the signature is applied by electrophotographic means or by a laser. DE-C 29 33 436 shows an identity card in which not only the user-related information (card number, account number and the like) but also the signature are applied electrophotographically to a security paper inlay

which is then laminated with plastic films on each side. DE-C 29 07 004 describes an identity card in which all user-related information, including the signature, is burned into the paper inlay through a transparent cover film.

However, the invention is based on the problem of providing an identity card which is easy to produce and allows for the signature to be written on the signature field, after completion of the card, visibly and in a form that subsequently cannot be changed, in particular replaced. Another objective is to state a method for producing such an identity card.

This problem is solved by the invention stated in claim 1 and claim 6. Advantageous developments are stated in the subclaims.

In the inventive identity card, the security print provided on the card body anyway for security purposes extends across the signature field applied, for example, by the screen printing technique. The predetermined pattern of the security print is continuous on the boundary between the signature field and the surroundings of the signature field. It is virtually impossible to detach the material of the signature field and replace the detached field by another field, since the security print - if it is imitable at all - can certainly not be adapted continuously to the print in the surrounding area of the signature field. The color coordination of the signature print on the signature field and surroundings also rules out forgery. The signature field, which hitherto had a clearly independent appearance, can be readily included in the overall appearance of the inventive identity card.

In particular, the production of the signature field can be readily included in the production process for the card body. Both the security print and the signature field can be produced e.g. by the screen printing technique. In order to protect the card after the security print has been applied, one provides a transparent protective layer on the security print, the protective layer leaving a window through which the signature can be subsequently provided on the signature field.

A further measure for increasing the protection from forgery is that the security print is aperiodic from card to card. Security prints, e.g. guilloche prints, usually have periodic patterns and according to the invention the card length, for example, is not an integral multiple of the pattern periodicity.

In the inventive method, the signature field is first applied and only then the security print, in such a way that the print at least partly overlaps the signature field. The special advantages of the method are apparent when the signature field is produced e.g. by screen printing and then the security print applied continuously across the signature field from the surroundings existing in the form of a plastic surface. Both method steps are customary printing methods which can be carried out with relatively little effort.

In order to obtain a very fine security print in particular in the signature field and in the area of the boundary between the signature field and the surroundings, one can perform an intermediate lamination between the screen printing operation and the security printing operation. This intermediate lamination smoothes the surface of the card body provided with the signature field, so that the security print can be applied to a homogeneous, flush surface.

To protect the card one preferably provides a transparent cover film, leaving out the area of the signature field. Instead of a cover film, which has a thickness of about 80 μm , one can also apply a substantially thinner layer of varnish consisting of artificial resin, e.g. two-component resin, UV-hardenable resin or the like, again leaving out the signature field. Such a layer of varnish has about the same height as the screen printing of the signature field (about 10 μm). If the card body is varnished with artificial resin the window can be formed by printing technology. After varnishing the card can be completed by another lamination to make the card surface completely smooth.

In the following, exemplary embodiments of the invention shall be explained in more detail with reference to the drawing, in which:

Fig. 1 shows a front view of an inventive identity card,

Fig. 2 shows a partially cross-sectional view of an identity card, and

Fig. 3 shows a partially cross-sectional view of another embodiment of an inventive identity card.

As shown by Fig. 1, signature field 2 is provided approximately in the center of card body 1 designed here as an all-plastic card. The signature field is, for example, a printed layer applied by screen printing using absorbable inks, i.e. a layer which permanently absorbs e.g. ball-point pen ink or other inks used in customary writing utensils. Other printing methods for applying layer materials having the property of subsequent writability are, for example, intaglio printing or tampon printing. The layer forming the signature field can also be transferred to the card surface by the transfer method, in particular by the known hot embossing method. Security print 3 designed as a guilloche print, which is indicated only symbolically in Fig. 1, covers at least part of signature field 2 and adjacent areas of the surface of card body 1. As apparent from Fig. 1, there are no interruptions whatsoever in the pattern of security print 3 on the boundary of signature field 2. This makes the signature field virtually impossible to replace or print over without such manipulation being recognizable by an irregularity in security print 3.

As indicated by Fig. 2, the card body is formed of a thick plastic layer to which signature field 2 is applied by a suitable printing method. After the signature field is applied, the surface of the card can be laminated to smooth the surface, if desired. Security print 3 is then applied

e.g. by the same printing method or by other printing methods suitable for printing fine lines. After a further laminating step transparent plastic film 4 is applied as a smooth transparent cover. Window 5 is punched out of this cover film 4 so that signature field 2 remains free for the card user to sign subsequently.

The size of window 5 can be freely selected in its limits. As indicated in Fig. 1 by broken limiting line 6, the plastic window can somewhat overlap signature field 2. However, a small peripheral gap can also be provided between the printed surface and the plastic cover, as indicated in Fig. 2. After cover film 4 is applied, the card can again be laminated to smooth the surface. Cover film 4 should be as thin as possible so that the signature field is not covered by the softening cover film material. Film thicknesses of about 80 μm thickness meet this requirement.

Instead of a cover film one can provide a layer of varnish consisting of artificial resin. One can easily leave window 5' free above signature field 2 by printing techniques. In Fig. 3, security print 3 is indicated by a dot-dash line; the varnish consisting of transparent artificial resin is represented by a broken line.

Layer of varnish 7 consists for example of UV-hardenable resin. Card body 1' of the identity card of Fig. 3 comprises two plastic layers. Since layer of varnish 7 is approximately as thick as signature field 2 (10 μm), one obtains a virtually uninterrupted, smooth card surface, whose smoothness can even be further improved by a final laminating step.



Claims

1. An identity card having a plastic card inlay bearing information relating to the user of the card and having at least on one side a security print (3) and a signature field (2) in the form of a printed layer of absorbable inks whose surface is thus designed to take up the user's personal signature on the finished identity card, the security print (3) covering at least part of the signature field (2), characterized in that the security print (3) extends continuously from the signature field into the surrounding areas of the card, the security print (3) being covered by a transparent protective layer so that the security print continues from the freely accessible surface of the signature field below the transparent protective layer.

2. The identity card of claim 1, characterized in that the signature field (2) and the protective layer (4) form an uninterrupted smooth card surface.

3. The identity card of claim 1 or 2, characterized in that the security print is designed to be aperiodic from card to card.

4. The identity card of claim 1, characterized in that the protective layer is a transparent cover film.

5. The identity card of claim 1, characterized in that the protective layer is a transparent varnish layer of artificial resin.

6. A method of producing an identity card having a plastic card inlay bearing at least on one side information relating to the user of the card and having at least on one side a security print and a signature field in the form of a printed layer of absorbable inks whose surface is thus designed to take up the user's personal signature on the finished identity card, characterized in that it has the following method steps:

applying the signature field,

applying the security print so as to overlap the signature field at least in part, whereby the security print extends continuously from the signature field into the surroundings existing as a plastic surface,

covering the security print by a transparent protective layer in the card areas surrounding the signature field so that the security print continues from the freely accessible surface of the signature field below the transparent protective layer.

7. The method of claim 6, characterized in that a lamination is performed between application of the signature field and the security printing operation.



8. The method of claim 6, characterized in that the card is subjected to an additional lamination after the protective layer is applied.

9. The method of claim 6, characterized in that a transparent film is applied as the transparent protective layer.

10. The method of claim 6, characterized in that a transparent varnish layer of artificial resin is applied as the transparent protective layer.