



- (51) International Patent Classification:
E21B 33/08 (2006.01) *E21B 33/06* (2006.01)
- (21) International Application Number:
PCT/US2013/076438
- (22) International Filing Date:
19 December 2013 (19.12.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/725,100 21 December 2012 (21.12.2012) US
- (71) Applicant: HYDRIL USA MANUFACTURING LLC
[US/US]; 3300 N. Sam Houston Parkway East, Houston,
TX 77032 (US).
- (72) Inventor: SMITH, Aaron, P.; 3300 N. Sam Houston
Parkway East, Houston, TX 77032 (US).
- (74) Agents: DOMBROWSKI, Joanna, M. et al.; General
Electric Company, Global Patent Operation, 2 Corporate
Drive, Suite 648, Shelton, CT 06484 (US).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.
- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,

[Continued on next page]

(54) Title: ANNULAR BLOWOUT PREVENTER AND LOWER MARINE RISER PACKAGE CONNECTOR UNIT




FIG. 3

(57) Abstract: An annular blowout preventer assembly has annular element housing and a central cavity with an elastomeric annular element in the central cavity. An annular element piston is located within the central cavity in engagement with the annular element. A connector housing has an upper end that abuts a lower end of the annular element housing. Bolts extend upward from the connector housing into threaded blind holes in the annular element housing for securing the connector housing to the annular element housing. A locking element is carried within the connector housing for radial inward movement into engagement with a profile on a mandrel of a blowout preventer stack.



TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

31 December 2014