CLAIMS

What is claimed is:

1. A method implemented by a decoder, the method comprising:

receiving, by a receiver of the decoder, a bitstream comprising a coded picture and a current supplemental enhancement information (SEI) message that comprises a decoding unit (DU) hypothetical reference decoder (HRD) parameters present flag (du_hrd_params_present_flag) that specifies whether DU level HRD parameters are present in the bitstream; and

decoding, by a processor of the decoder, the coded picture to produce a decoded picture.

2. The method of claim 1, wherein the du_hrd_params_present_flag further specifies whether a HRD operates at an access unit (AU) level or a DU level.

3. The method of any of claims 1-2, wherein the du_hrd_params_present_flag is set to one when specifying that DU level HRD parameters are present and the HRD can be operated at the AU level or the DU level, and wherein the du_hrd_params_present_flag is set to zero when specifying that DU level HRD parameters are not present and the HRD operates at the AU level.

4. The method of any of claims 1-3, wherein the current SEI message further comprises a DU coded picture buffer (CPB) parameters in picture timing (PT) SEI flag (du_cpb_params_in_pic_timing_sei_flag) that specifies whether DU level CPB removal delay parameters are present in a PT SEI message.

5. The method of any of claims 1-4, wherein the du_cpb_params_in_pic_timing_sei_flag further specifies whether DU level CPB removal delay parameters are present in a decoding unit information (DUI) SEI message.

6. The method of any of claims 1-5, wherein the du_cpb_params_in_pic_timing_sei_flag is set to one when specifying that that DU level CPB removal delay parameters are present in a PT SEI message and no DUI SEI message is available, and wherein the du_cpb_params_in_pic_timing_sei_flag is set to zero when specifying that DU level CPB removal delay parameters are present in a DUI SEI message and PT SEI messages do not include DU level CPB removal delay parameters.

7. The method of any of claims 1-6, wherein the current SEI message is a Buffering Period (BP) SEI message, a PT SEI message, or a DUI SEI message.

~~8. A method implemented by an encoder, the method comprising:~~

~~encoding, by a processor of the encoder, a coded picture into a bitstream;~~

~~encoding into the bitstream, by the processor, a current supplemental enhancement information (SEI) message that comprises a decoding unit (DU) hypothetical reference decoder (HRD) parameters present flag (du_hrd_params_present_flag) that specifies whether DU level HRD parameters are present in the bitstream;~~

~~performing, by the processor, a set of bitstream conformance tests on the bitstream based on the current SEI message; and~~

~~storing, by a memory coupled to the processor, the bitstream for communication toward a decoder.~~

~~9. The method of claim 8, wherein the du_hrd_params_present_flag further specifies whether a HRD operates at an access unit (AU) level or a DU level.~~

~~10. The method of any of claims 8-9, wherein the du_hrd_params_present_flag is set to one when specifying that DU level HRD parameters are present and the HRD can be operated at the AU level or the DU level, and wherein the du_hrd_params_present_flag is set to zero when specifying that DU level HRD parameters are not present and the HRD operates at the AU level.~~

~~11. The method of any of claims 8-10, wherein the current SEI message further comprises a DU coded picture buffer (CPB) parameters in picture timing (PT) SEI flag (du_cpb_params_in_pic_timing_sei_flag) that specifies whether DU level CPB removal delay parameters are present in a PT SEI message.~~

12. The method of any of claims 8-11, wherein the du_cpb_params_in_pic_timing_sei_flag further specifies whether DU level CPB removal delay parameters are present in a decoding unit information (DUI) SEI message.

13. The method of any of claims 8-12, wherein the du_cpb_params_in_pic_timing_sei_flag is set to one when specifying that that DU level CPB removal delay parameters are present in a PT SEI message and no DUI SEI message is available, and wherein the du_cpb_params_in_pic_timing_sei_flag is set to zero when specifying that DU level CPB removal delay parameters are present in a DUI SEI message and PT SEI messages do not include DU level CPB removal delay parameters.

14. The method of any of claims 8-13, wherein the current SEI message is a Buffering Period (BP) SEI message, a PT SEI message, or a DUI SEI message.

158. A video coding device comprising:

a processor, a receiver coupled to the processor, a memory coupled to the processor, and a transmitter coupled to the processor, wherein the processor, receiver, memory, and transmitter are configured to perform the method of any of claims 1-147.

169. A non-transitory computer readable medium comprising a computer program product for use by a video coding device, the computer program product comprising computer executable instructions stored on the non-transitory computer readable medium such that when executed by a processor cause the video coding device to perform the method of any of claims 1-147.

1710. A decoder comprising:

a receiving means for receiving a bitstream comprising a coded picture and a current supplemental enhancement information (SEI) message that comprises a decoding unit (DU) hypothetical reference decoder (HRD) parameters present flag (du_hrd_params_present_flag) that specifies whether DU level HRD parameters are present in the bitstream;

a decoding means for decoding the coded picture to produce a decoded picture; and

a forwarding means for forwarding the decoded picture for display as part of a decoded video sequence.

~~18~~11. The decoder of claim ~~17~~10, wherein the du_hrd_params_present_flag further specifies whether a HRD operates at an access unit, AU, level or a DU level.~~wherein the decoder is further configured to perform the method of any of claims 1-7.~~

12. The decoder of claim 10 or 11, wherein the du_hrd_params_present_flag is set to one when specifying that DU level HRD parameters are present and the HRD can be operated at the AU level or the DU level, and wherein the du_hrd_params_present_flag is set to zero when specifying that DU level HRD parameters are not present and the HRD operates at the AU level.

13. The decoder of any of claims 10-12, wherein the current SEI message further comprises a DU coded picture buffer, CPB, parameters in picture timing, PT, SEI flag, du_cpb_params_in_pic_timing_sei_flag, that specifies whether DU level CPB removal delay parameters are present in a PT SEI message.

14. The decoder of any of claims 10-13, wherein the du_cpb_params_in_pic_timing_sei_flag further specifies whether DU level CPB removal delay parameters are present in a decoding unit information, DUI, SEI message.

15. The decoder of any of claims 10-14, wherein the du_cpb_params_in_pic_timing_sei_flag is set to one when specifying that that DU level CPB removal delay parameters are present in a PT SEI message and no DUI SEI message is available, and wherein the du_cpb_params_in_pic_timing_sei_flag is set to zero when specifying that DU level CPB removal delay parameters are present in a DUI SEI message and PT SEI messages do not include DU level CPB removal delay parameters.

19. An encoder comprising:

an encoding means for:

encoding a coded picture into a bitstream; and

encoding into the bitstream a current supplemental enhancement information (SEI) message that comprises a decoding unit (DU) hypothetical reference decoder (HRD) parameters present flag (du_hrd_params_present_flag) that specifies whether DU level HRD parameters are present in the bitstream;

a hypothetical reference decoder (HRD) means for performing a set of bitstream conformance tests on the bitstream based on the current SEI message; and

a storing means for storing the bitstream for communication toward a decoder.

20. The encoder of claim 19, wherein the encoder is further configured to perform the method of any of claims 8-14.