

METHOD FOR FORMING ESD PROTECTION CIRCUIT

Field of the Invention

[0001] This invention relates generally to electronic circuits, and in particular to silicon controlled rectifier (SCR) structures for electrostatic discharge protection (ESD). More particularly this invention relates to polycrystalline silicon (polysilicon) bounded SCR structures and to electronic protection circuits employing polycrystalline silicon bounded SCR's.

Description of Related Art

[0002] In ESD protection circuits, the series resistance of the active devices affects the performance of the devices. Higher resistance at the voltage levels of an ESD event may lead to a voltage drop across the active devices that may destroy the device. Fig. 1 shows an ESD protection diode structure of the prior art. In this example, shallow trenches are etched within the region that will become the N-well **10** and filled with an insulating material to form the shallow trench isolation (STI) **15** are formed on the substrate. A semiconductor material that is lightly doped with a p-type impurity is formed on the substrate to construct the P-well **5**. Within the P-well **5**, a lightly doped n-type impurity is diffused into the P-well **5** to form the N-well **10**. Between two of the STI regions **15** a P-type material is diffused into the N-well until a heavily doped P⁺ region **20** is formed. Similarly, between two other STI regions **15** an N-type material is diffused into the N-well until a heavily doped N⁺ region **25** is formed. An insulative layer **40** is formed on the surface of the substrate and opening **32** and **37** are created over the P⁺ region **20** and the N⁺ region **25**. Silicides **30** and **35** are respectively formed on the surfaces of the P⁺ region **20** and N⁺ region **25** to create the necessary contacts to external circuitry. In the case of the ESD protection diodes shown, the contacts will be to the signal input/output interface connection pads and the power supply voltage source connection pads.

[0003] According to U. S. Patent 5,629,544 (Voldman, et al. - 544), diode series resistance is largely determined by the dimensions of the diode features, the resistivity of N-well **10** in which diode is located, the distance current flows in N-well **10** and the depth of the current path, and by the resistance of contacts **30** and **35** to the p⁺ and n⁺ diffusions **20** and

25. Thus, a wider diode with a lower well resistivity, a shorter current path, and silicided films and contacts provide a lower diode series resistance. In the case of the diode as shown, the depth of the current path is determined by the depth of the STI regions 15. Further, it is known in the art that the width of the STI regions 15 have certain achievable minimums that cause the series resistance to be larger than desired.

[0004] Voldman, et al. - 544 and "Semiconductor Process and Structural Optimization of Shallow Trench Isolation-Defined And Polysilicon-Bound Source/Drain Diodes For ESD Networks," Voldman, et al., Proceedings Electrical Overstress/Electrostatic Discharge Symposium, October 1998, pp: 151-160 discusses polysilicon-bounded diode. Refer to Fig. 2 for more discussion of the structure of a polysilicon bounded diode. The structure of the polysilicon bounded diode is constructed in a P-type well 5 that has been created with a substrate has been lightly doped with a p-type impurity. Within the P-well 5 a lightly doped n-type impurity is diffused into the P-well 5 to form the N-well 10. An insulative layer 40 is formed on the surface of the substrate. A gate stack is formed with a gate oxide layer 60 and a polysilicon layer 65. Spacers 70 are added to the sides of the gate oxide layer 60 and the polysilicon layer 65. A P-type material is diffused into the N-well until a heavily doped P⁺ region 75 is formed and an N-type material is diffused into the N-well until a heavily doped N⁺ region 80 is formed on each side of the gate stack. Openings 77 and 82 are created over the P⁺ region 75 and the N⁺ region 80. Silicides 90 and 95 are respectively formed on the surfaces of the P⁺ region 75 and N⁺ region 80 to create the necessary contacts to external circuitry. As described above, the contacts will be to the signal input/output interface connection pads and the power supply voltage source connection pads.

[0005] In the polysilicon bounded diode as shown, the gate stack maybe constructed with smaller dimensions than those permitted in the diode constructed with the STI 15 of Fig. 1. This permits the series resistance of the diode to be lower to and thus improves the operation of the diode during an ESD event.

[0006] Use of silicon controlled rectifiers (SCR) as ESD protection devices are well known in the art. Referring to Fig. 3, the P-well 100 is constructed of a semiconductor material that is lightly doped with a p-type impurity is diffused into a substrate. Within the P-well 100 a lightly doped n-type impurity is diffused into the P-well 100 to form the N-well 105. Shallow trenches are then etched within the region of the N-well 105 and filled with an insulating material to form the shallow trench isolation (STI) 110. Between two of the STI

regions **110** a P-type material is diffused into the N-well until a heavily doped P⁺ regions **125** and **135** are formed. Similarly, between two other STI regions **110** an N-type material is diffused into the N-well until the heavily doped N⁺ regions **120** and **130** are formed. An insulative layer **140** is formed on the surface of the substrate and openings **127** and **137** are created over the P⁺ regions **125** and **135** and openings **122** and **132** are created over the N⁺ regions **120** and **130**. Silicides **145**, **150**, **155**, and **160** are formed on the surfaces of the P⁺ regions **125** and **135** and N⁺ regions **120** and **130** to create the necessary contacts to external circuitry. The contacts will be to the signal input/output interface connection pads and the power supply voltage source connection pads.

[0007] The SCR is formed of the P⁺ regions **125**, the N-well **105**, the P-well **105** and the N⁺ regions **130**. The anode of the SCR being the P⁺ regions **125** and the cathode N⁺ regions **130**. As structured, a positive voltage of an ESD event applied to the anode will cause the SCR to be activated once the snapback voltage is reached. In general the snapback voltage as shown is greater than 50V and may not cause damage to connected integrated circuits. However, as the feature sizes of integrated circuits have become smaller, the voltages at which damage may occur is becoming smaller and the SCR needs to be triggered at lower voltages that are greater than the operating voltages of the integrated circuits.

[0008] "Electrostatic Discharge (ESD) Protection in Silicon-On-Insulator (SOI) CMOS Technology with Aluminum and Copper Interconnects in Advanced Microprocessor Semiconductor Chips," Voldman, et al., Proceedings Electrical Overstress/Electrostatic Discharge Symposium, 1999, pp: 105-115, discusses the electrostatic discharge (ESD) robustness of silicon-on-insulator (SOI) high-pin-count high-performance semiconductor chips. The ESD results demonstrate that sufficient ESD protection levels are achievable in SOI microprocessors using lateral ESD SOI polysilicon-bound gated diodes.

[0009] "An ESD Protection Scheme for Deep Sub-Micron ULSI Circuits," Sharma, et al. Digest of Technical Papers - 1995 Symposium on VLSI Technology, 1995. pp: 85-86, describes a scheme for on-chip protection of sub-micron ULSI circuits against ESD stress using low voltage zener-triggered SCR, and a zener-triggered thin gate oxide MOSFET.

[0010] U. S. Patent 6,610,262 (Peng, et al.) describes an ESD semiconductor protection with reduced input capacitance.

[0011] U. S. Patent 6,605,493 (Yu) teaches about an SCR ESD protection device used with shallow trench isolation structures. The invention incorporates polysilicon gates

bridging SCR diode junction elements and also bridging between SCR elements and neighboring STI structures. The presence of the strategically located polysilicon gates effectively counters the detrimental effects of non-planar STI "pull down" regions as well as compensating for the interaction of silicide structures and the effective junction depth of diode elements bounded by STI elements. Connecting the gates to appropriate voltage sources such as the SCR anode input voltage and the SCR cathode voltage, typically ground, reduces normal operation leakage of the ESD protection device.

[0012] U. S. Patent 6,580,184 (Song) illustrates an ESD protection circuit having a silicon-controlled rectifier structure. A switch circuit is connected between a ground voltage terminal and a well region that is a base of the PNP transistor. The switch circuit is formed of plural diode-coupled MOS transistors, so that a trigger voltage of the SCR is determined by threshold voltages of the MOS transistors.

[0013] U. S. Patent 6,534,834 (Ashton, et al.) teaches about a snapback device that functions as a semiconductor protection circuit to prevent damage to integrated circuits resulting from events such as electrostatic discharge. The snapback device includes a polysilicon film overlapping the active area.

[0014] U. S. Patent 5,453,384 (Chatterjee) describes a silicon controlled rectifier structure that is provided for electrostatic discharge protection. A polysilicon gate layer is formed over a gate insulator region and is electrically coupled to the input pad of an integrated circuit.

[0015] U. S. Patent 5,159,518 (Roy) details an input protection circuit that protects MOS semiconductor circuits from electrostatic discharge voltages and from developing circuit latchup. The input protection circuit includes a low resistance input resistor, and two complementary true gated diodes.

[0016] United States Patent Application 2003/0016479 (Song) describes an ESD protection circuit having silicon-controlled rectifier structure that includes a PNP transistor and an NPN transistor. A switch circuit is connected between a ground voltage terminal and a well region that is a base of the PNP transistor. The switch circuit is formed of plural diode-coupled MOS transistors, so that a trigger voltage of the SCR is determined by threshold voltages of the MOS transistors.

Summary of the Invention

[0017] An object of this invention is to provide an ESD protection circuit that becomes activated at a voltage sufficient to protect integrated circuits connected to the protection circuit.

[0018] Another object of this invention is to provide an ESD protection circuit with a polysilicon bounded SCR that conducts of applied energy resulting from an ESD event to an input/output interface connection pad.

[0019] Still another object of this invention is to provide a bias triggering circuit for an SCR that causes the SCR to turn on at a lower voltage in order to conduct the energy of an ESD event.

[0020] A further object of this invention is to provide a diode bias triggering circuit for an SCR that causes the SCR to turn on at a lower voltage in order to conduct the energy of an ESD event.

[0021] One more object of this invention is to provide a resistor/capacitor triggering circuit for an SCR that causes the SCR to turn on at a lower voltage to conduct the energy of an ESD event.

[0022] To accomplish at least one of these objects, an ESD protection circuit is formed at the input/output interface contact of an integrated circuit to protect the integrated circuit from damage caused by an ESD event. The ESD protection circuit has a polysilicon bounded SCR and a biasing circuit. The polysilicon bounded SCR is connected between a signal input/output interface contact of the integrated circuit and a power supply connection of the integrated circuit. The biasing circuit is connected to the polysilicon bounded SCR to bias the polysilicon bounded SCR to turn on more rapidly during the ESD event.

[0023] The polysilicon bounded SCR includes a first well region lightly doped with impurities of a first conductivity type formed on the substrate and connected to the power supply connection and a second well region formed within the first well region and lightly doped with impurities of a second conductivity type. A first diffusion region is formed within the second well by heavily doping the region with the impurities of the first conductivity type. The first diffusion region is connected to the signal input/output interface contact. A second diffusion region is formed within the first well region at a second distance from the first diffusion region by heavily doping the region with impurities of the second conductivity type. The second diffusion region is connected to the power supply connection.

A first heavily doped polycrystalline layer is formed at the surface of the substrate and placed between the first and second diffusion regions and astride a junction of the first well region and the second well region to form a bounding component to prevent silicide formation at junctions of the first diffusion region and the second well region, the first well region and the second region and the second diffusion region and the first well region during fabrication of the SCR.

[0024] The SCR being the junctions of the first diffusion region and the second well region, the junction of the first and second well regions, and the junction of the first well region and the second diffusion region. The anode of the SCR is the first well region and the cathode of the SCR is the second diffusion region.

[0025] The biasing circuit is formed of at least one polysilicon bounded diode formed on the substrate and connected between the signal input/output interface contact and an anode connection of the polysilicon bounded SCR to increase a holding voltage for the polysilicon bounded SCR when the polysilicon bounded SCR is turned on.

[0026] The polysilicon bounded diode is formed from the first diffusion region and the second well region and has a second heavily doped polysilicon layer formed at the surface of the substrate and placed adjacent to the first diffusion region and astride a junction of the second well region and first diffusion region to form a bounding component to prevent silicide formation at the junction of the first diffusion region and the second well region during fabrication of the polysilicon bounded diode. The junction of the first diffusion region and the second well region forms the polysilicon bounded diode.

[0027] The biasing circuit has a first resistance formed by material from the second well from a first gate of the polysilicon bounded SCR to a third diffusion region formed within the second well, heavily doped with the impurities of the second conductivity type, and connected to the power supply connection to provide a low resistance path to the second well from the power supply connection. The biasing circuit further has a second resistance formed material of the second well from the first gate to the first diffusion region.

[0028] A second embodiment of the biasing circuit includes a first resistor connected from the signal input/output interface contact to the first gate of the polysilicon bounded SCR and a first capacitor connected from the first gate of the polysilicon bounded SCR to the power supply connection. When an ESD event occurs, a top plate of the capacitor connected

to the gate of the polysilicon bounded SCR is a virtual ground and the polysilicon bounded SCR is activated.

[0029] A third embodiment of the biasing circuit has a plurality of serially connected diodes. The first diode of the plurality of serially connected diodes is connected to the signal input/output interface contact and the last diode of the plurality of the serially connected diodes is connected to a second gate of the polysilicon bounded SCR. The biasing circuit further has a second resistor connected from the second gate and the last diode of the plurality of serially connected diodes to the power supply connection. When an ESD event occurs, a current flows through the plurality of serially connected diodes and the second resistor, which triggers the polysilicon bounded SCR to turn on.

[0030] A fourth embodiment of the biasing circuit: includes a resistor/capacitor biasing circuit connected from the first gate of the polysilicon bounded SCR and a diode triggering biasing circuit connected from the second gate of the polysilicon bounded SCR. The resistor/capacitor biasing circuit has a first resistor connected from the signal input/output interface to the first gate of the polysilicon bounded SCR and a first capacitor connected from the first gate of the polysilicon bounded SCR to the power supply connection. The diode triggering biasing circuit has a plurality of serially connected diodes. The first diode of the plurality of serially connected diodes is connected to the signal input/output interface contact and the last diode of the plurality of serially connected diodes is connected to a second gate of the polysilicon bounded SCR. The diode triggering biasing circuit has a second resistor connected from the second gate and the last diode of the plurality of serially connected diodes to the power supply connection.

[0031] When an ESD event occurs, the top plate of the capacitor connected to the gate of the polysilicon bounded SCR is a virtual ground and the polysilicon bounded SCR is activated. Simultaneously, a current flows through the plurality of serially connected diodes and the second resistor to trigger the polysilicon bounded SCR to turn on.

[0032] The heavily doped polycrystalline layer of the polysilicon bounded SCR and the polysilicon bounded diode permits a series resistance of the polysilicon bounded SCR and the polysilicon bound diode to be smaller for a more efficient operation. The heavily doped polycrystalline layer is connected to bias the heavily doped polysilicon layer such that salicide shorting is prevented the first and second diffusion regions and preventing of accidental formation of an inversion region heavily doped polycrystalline layer.

Brief Description of the Drawings

[0033] Fig. 1 is a cross sectional view of a substrate illustrating an ESD protection diode structure of the prior art.

[0034] Fig. 2 is a cross sectional view of a substrate illustrating a polysilicon bounded ESD protection diode structure of the prior art.

[0035] Fig. 3 is a cross sectional view of a substrate illustrating an ESD protection SCR structure of the prior art.

[0036] Fig. 4a is a cross sectional view of a substrate illustrating an ESD protection polysilicon bounded SCR structure of this invention.

[0037] Fig. 4b is a top plan view of a substrate illustrating an ESD protection polysilicon bounded SCR structure of this invention.

[0038] Fig. 4c is a plot of current through an ESD protection polysilicon bounded SCR structure of this invention versus the voltage across the ESD protection polysilicon bounded SCR structure of this invention.

[0039] Fig. 5 is a schematic of a diode triggered ESD protection circuit of this invention incorporating ESD protection polysilicon bounded SCR structure.

[0040] Fig. 6 is a schematic of a resistor/capacitor triggered ESD protection circuit of this invention incorporating ESD protection polysilicon bounded SCR structure.

[0041] Fig. 7 is a schematic of a second diode triggered ESD protection circuit of this invention incorporating ESD protection polysilicon bounded SCR structure.

[0042] Fig. 8 is a schematic of a resistor/capacitor triggered and diode triggered ESD protection circuit of this invention incorporating ESD protection polysilicon bounded SCR structure.

[0043] Fig. 9 is a schematic of a third diode triggered ESD protection circuit of this invention incorporating an ESD protection polysilicon bounded SCR structure.

[0044] Fig. 10 is a schematic of a fourth diode triggered ESD protection circuit of this invention incorporating an ESD protection polysilicon bounded SCR structure.

Detailed Description of the Invention

[0045] The polysilicon bounded SCR of this invention as shown in Figs. 4a and 4b includes a P-well **200** lightly doped with p-type impurities formed on the substrate and

connected to the power supply connection **280** through the P⁺ diffusion **225**. An N-well region **205** is formed within the P-well **200** and lightly doped with N-type impurities and connected through the N⁺ diffusion region **220** to the power supply connection **280**. A P⁺ diffusion region **210** is formed within the N-well **205** by heavily doping the N-well **205** with the P-type impurities. The P⁺ diffusion region **210** is connected to the signal input/output interface contact **275**. An N⁺ diffusion region **215** is formed within the P-well **200** at a second distance from the N⁺ diffusion region **210** by heavily doping the P-well **200** with N-type impurities. The N⁺ diffusion **215** is also connected to the power supply connection **280**.

[0046] An insulative material such as a silicon dioxide is formed on the surface of the substrate between the P⁺ diffusion region **210** and the N⁺ diffusion region **215** and astride a junction of the P-well **200** to form a gate oxide **230**. A polysilicon layer is then formed on the gate oxide **230** to form the gate structure **240**. The gate structure **240** forms a bounding component to prevent silicide formation at junctions of the P⁺ diffusion region **210** and the N-well region **205**, the P-well **200** and the N-well region **205** and the N⁺ diffusion region **215** and the P-well **200** during fabrication of the SCR.

[0047] As is known in the art, an SCR is regarded as a PNP transistor **Q1** connected serially with an NPN transistor **Q2**. Thus, the collector of the PNP transistor **Q1** is the P-well **200**, the base is the N-well **205**, and the emitter is the P⁺ diffusion region **210**. The collector of the NPN transistor **Q2** is the N-well **205**, the base is the P-well **200**, and the emitter is the N⁺ diffusion region **215**. with the junctions being the boundaries between the P⁺ diffusion region **210** and the N-well region **205**, the P-well **200** and the N-well region **205** and the N⁺ diffusion region **215** and the P-well **200**.

[0048] A N⁺ diffusion region **220** is formed within the N-well **205** by heavily doping the N-well **205** with the N-type impurities and the P⁺ diffusion region **225** is formed within the P-well **200** by heavily doping the P-well **200** with the P-type impurities. An insulation layer **270** is formed on the surface of the substrate to protect the surface. Openings **227**, **217**, **212**, and **222** are made in the insulation layer **270** to respectively provide access to the P⁺ diffusion region **225**, N⁺ diffusion region **215**, P⁺ diffusion region **210**, and N⁺ diffusion region **220**. A silicide contact **265**, **255**, **250**, and **260** is formed respectively on the surface of each of the P⁺ diffusion region **225**, N⁺ diffusion region **215**, P⁺ diffusion region **210**, and N⁺ diffusion region **220**. The silicide contacts **255** and **250** are restricted or bounded by the polysilicon gate structure **240**.

[0049] The diode **D₁** is formed as the junction of the P⁺ diffusion region **210** and the N-well **205**. The gate oxide **235** is formed between and slightly overlaps the P⁺ diffusion region **210** and the N⁺ diffusion region **220**. A polysilicon layer is formed on the gate oxide **235** to form the gate structure **245**. The gate structure **245** provides bounding for the silicide contacts **250** and **260**. The polysilicon bounding gate structures **240** and **245** permit the P⁺ diffusion region **210** and N⁺ diffusion region **215** to be placed relatively close by avoiding the necessity for a larger shallow trench isolation, thus minimizing the serial resistance of the diode **D₁** and the SCR formed by the transistors **Q1** and **Q2**.

[0050] The gate structures **240** and **245** are connected to the power supply connection **280** to prevent salicide shorting between the silicide contacts **265** and **250** and silicide contacts **250** and **260** and preventing of accidental formation of an inversion region under said first and second diffusion regions.. The silicide contacts **265**, **255**, and **260** provide low resistivity connections for the P⁺ diffusion region **225**, N⁺ diffusion region **215**, and N⁺ diffusion region **220** to the power supply connection **280**. The silicide contact provides a low resistivity connection for the P⁺ diffusion region **210** to the signal input/output interface pad **275**.

[0051] Refer now additionally to Fig. 5 for a discussion of the circuit structure of the polysilicon bounded SCR having a diode triggering of this invention. As described above, the diode **D₁** is formed as the junction of the P⁺ diffusion region **210** and the N-well **205**. The polysilicon bounded SCR is formed of the P-well **200**, the N-well **205**, the P⁺ diffusion region **210**, the N-well **205**, the P-well **200**, and the N⁺ diffusion region **215**. The resistor **R_{1-SUB}** is the bulk resistance of the N-well **205** to the P⁺ diffusion region **210**. The resistor **R_{2-SUB}** is the bulk resistance of the N-well **205** to the N⁺ diffusion region **220**. And the resistor **R_{3-SUB}** is the bulk resistance of the P-well **200** to the P⁺ diffusion region **225**.

[0052] Upon application of the voltage of an ESD event to the input/output interface pad **275**, the diode **D₁** begins to conduct. The current through the resistance **R_{2-SUB}** develops sufficient voltage to turn on the transistor **Q1**, which in turn provides a current through the resistor **R_{3-SUB}**. This develops a voltage sufficient to turn on the transistor **Q2**, thus completely activating the SCR.

[0053] Referring to Fig. 4c, as the voltage applied between the anode (P⁺ diffusion region **210**) and the cathode (N⁺ diffusion region **215**) of the Polysilicon bounded SCR increases the current rises slowly **290** until the biasing of the diode **D₁** and the resistor **R_{2-SUB}**

turns on the SCR at the snapback point **292**. At the current and voltage level **294** the SCR fundamentally acts as a resistor, with the resistance determined by the internal resistance of the SCR. The internal resistance is then determined by the dimensions of the SCR and the proximity of the P⁺ diffusion region **210** and the N⁺ diffusion region **215**. The polysilicon gate structures **240** and **245** allow current to flow laterally between the P⁺ diffusion region **210** and the N⁺ diffusion region **215** more efficiently with a lower resistance to prevent ohmic heating of the device.

[0054] A second embodiment of the ESD protection circuit, as shown in Fig. 6 is connected between the signal input/output interface pad **275** and the power supply connection pad **280**. The SCR is formed as described in Figs 4a and 4b. The diodes **D₁** and **D₂** are optional diodes placed in series with the SCR between the signal input/output interface pad **275** and the SCR. These diodes are structured as the diode **D₁** of the Fig. 4a and increase the holding voltage of the SCR when it is turned on. The base of the transistor **Q1** and the collector of the transistor **Q2** is the N-well **205** of Fig. 4a and will be referred to as the first gate of the SCR. The base of the transistor **Q2** and the collector of the transistor **Q1** is the P-well **200** of Fig. 4a and is referred to as the second gate of the SCR. The resistor **R₁** is connected between the signal input/output interface pad **275** and the first gate. The capacitor **C₁** is connected from the first gate to the power supply connection pad **280**. In this example the power supply connection pad **280** is the ground reference point for the integrated circuit.

[0055] The resistor **R_{P-WELL}** is the bulk resistance of the P-well **200** of Fig. 4a and is connected from the second gate of the SCR and the power supply connection pad **280**. The resistor **R₁** is constructed using any known technique such as a highly doped diffusion region. The capacitance is constructed using any known technique such as employing a gate to bulk capacitance of a MOSFET as the capacitor **C₁**.

[0056] When an ESD event **285** occurs, the voltage at the signal input/output interface pad **285** increases dramatically. The top plate of the capacitor **C₁** at the first gate is at a virtual ground, thus causing the transistor **Q1** to turn on, which causes the current through the resistor **R_{P-WELL}** to increase and turn on the transistor **Q2**. The SCR then transfers the energy to the power supply connection pad **280**.

[0057] A third embodiment of the ESD protection circuit, as shown in Fig. 7 is connected between the signal input/output interface pad **275** and the power supply connection pad **280**. The SCR is formed as described in Figs 4a and 4b. As described above, the base of

the transistor **Q1** and the collector of the transistor **Q2** is the N-well **205** of Fig. 4a and is referred to as the first gate of the SCR. The base of the transistor **Q2** and the collector of the transistor **Q1** are the P-well **200** of Fig. 4a and is referred to as the second gate of the SCR.

[0058] The diodes **D₁**, **D₂**, and **D₃** are serially connected from cathode to anode and are structured as the diode **D₁** of the Fig. 4a. The anode of the first diode **D₁** is connected to the signal input/output interface pad **275** and the cathode of the last diode **D₃** is connected to the second gate of the SCR. The resistor **R₂** is connected to the second gate of the SCR and the cathode of the last diode **D₃**. It should be noted that while this embodiment is implemented with the three diodes **D₁**, **D₂**, and **D₃**, there may be any number of diodes connected serially. The number being determined by the operational voltages of the integrated circuits connected to the signal input/output interface pad **275**.

[0059] The resistor **R_{P-WELL}** is the bulk resistance of the P-well **200** of Fig. 4a and is connected from the second gate of the SCR and the power supply connection pad **280**. The resistors **R₁** and **R₂** are constructed using any known technique such as a highly doped diffusion region.

[0060] When an ESD event **285** occurs, the voltage at the signal input/output interface pad **285** increases dramatically. The diodes **D₁**, **D₂**, and **D₃** begin to conduct and a voltage is developed across the resistors **R₂** and **R_{P-WELL}**. The transistor **Q2** turns on causing current to flow through the resistor **R₁**. The voltage developed across the resistor **R₁** turns on the transistor **Q2**. The SCR is thus activated to conduct the energy of the ESD event from the integrated circuits connected to the signal input/output interface pad **275** to the power supply connection pad **280**.

[0061] A fourth embodiment of the ESD protection circuit, as shown in Fig. 8 is connected between the signal input/output interface pad **275** and the power supply connection pad **280**. This embodiment incorporates the triggering bias circuits of the second and third embodiments. Further, the optional diodes **D₁** and **D₂** of the second embodiment are included as the diodes **D₄** and **D₅** and placed in series with the SCR between the signal input/output interface pad **275** and the SCR. These diodes are structured as the diode **D₁** of the Fig. 4a and increase the holding voltage of the SCR when it is turned on.

[0062] The SCR is formed as described in Figs 4a and 4b. The base of the transistor **Q1** and the collector of the transistor **Q2** is the N-well **205** of Fig. 4a and will be referred to

as the first gate of the SCR. The base of the transistor **Q2** and the collector of the transistor **Q1** are the P-well **200** of Fig. 4a and are referred to as the second gate of the SCR.

[0063] The resistor/capacitor triggering circuit is formed by the resistor **R1** and capacitor **C1**. The resistor **R1** is connected between the signal input/output interface pad **275** and the first gate and the capacitor **C1** is connected from the first gate to the power supply connection pad **280**. In this example, the power supply connection pad **280** is the ground reference point for the integrated circuit.

[0064] As described above, the resistor **R1** is constructed using any known technique such as a highly doped diffusion region. The capacitance is constructed using any known technique such as employing a gate to bulk capacitance of a MOSFET as the capacitor **C1**.

[0065] The diode triggering circuit includes the serially connected diodes **D1**, **D2**, and **D3** and the resistor **R2**. The diodes **D1**, **D2**, and **D3** are serially connected cathode to anode and are structured as the diode **D1** of the Fig. 4a. The anode of the first diode **D1** is connected to the signal input/output interface pad **275** and the cathode of the last diode **D3** is connected to the second gate of the SCR. The resistor **R2** is connected to the second gate of the SCR and the cathode of the last diode **D3**. As noted above, that while this embodiment is implemented with the three diodes **D1**, **D2**, and **D3**, there may be any number of diodes connected serially. The number is determined by the operational voltages of the integrated circuits connected to the signal input/output interface pad **275**.

[0066] The resistor **R_{P-WELL}** is the bulk resistance of the P-well **200** of Fig. 4a and is connected from the second gate of the SCR and the power supply connection pad **280**. The resistor **R2** is constructed using any known technique such as a highly doped diffusion region.

[0067] When an ESD event **285** occurs, the voltage at the signal input/output interface pad **285** increases dramatically. The diodes **D1**, **D2**, and **D3** begin to conduct and a voltage is developed across the resistors **R1** and **R_{P-WELL}**. The transistor **Q2** turns on. Simultaneously, the top plate of the capacitor **C1** at the first gate is at a virtual ground, thus causing the transistor **Q1** to turn on, thus activating the SCR. The SCR then transfers the energy to the power supply connection pad **280**.

[0068] A fifth embodiment of the ESD protection circuit, as shown in Fig. 9 is connected between the signal input/output interface pad **275** and the power supply connection pad **280**. In this embodiment, the triggering bias circuit is a resistor **R** and capacitor **C** that are formed of a first metal oxide semiconductor (MOS) transistor **M1** biased to act as the

resistor **R** and a second MOS transistor **M₅** connected to form the capacitor **C**. The MOS transistor **M₂** connected to bias the MOS transistor **M₁** to an on condition to act as the resistor **R**. The junction connection between the resistor **R** and capacitor **C** is connected to an input terminal of a first inverter **I₁** of a group of serially connected inverters **I₁**, **I₂**, and **I₃**. In this embodiment the preferred implementation of the group of serially connected inverters **I₁**, **I₂**, and **I₃** is shown as three inverters however, the number of inverters maybe adjusted according to the requirements of the design.

[0069] The SCR is formed as described in Figs 4a and 4b. The base of the transistor **Q1** and the collector of the transistor **Q2** is the N-well **205** of Fig. 4a and will be referred to as the first gate of the SCR. The base of the transistor **Q2** and the collector of the transistor **Q1** are the P-well **200** of Fig. 4a and are referred to as the second gate of the SCR.

[0070] Each of the group of serially connected inverters **I₁**, **I₂**, and **I₃** is formed as shown for the inverter **I₁**. The inverter **I₁** is formed of the PMOS transistor **M₃** serially connected drain to drain with the NMOS transistor **M₄**. The gates of the PMOS transistor **M₃** and the NMOS transistor **M₄** are connected to be the input of the inverter **I₁**. The drains of the PMOS transistor **M₃** and the NMOS transistor **M₄** being the output of the inverter **I₁**. The source of the NMOS transistor **M₄** is connected to the power supply connection pad **280** and the source of the PMOS transistor **M₃** is connected to the diode **D₂**.

[0071] The output of the inverter **I₂** that is in phase with the input of the group of serially connected inverters **I₁**, **I₂**, and **I₃** is connected to the first gate of the SCR. The output of the inverter **I₃** that is out of phase with the input of the group of serially connected inverters **I₁**, **I₂**, and **I₃** is connected to the second gate of the SCR.

[0072] When an ESD event **285** occurs, the voltage at the signal input/output interface pad **285** increases dramatically. The top plate of the capacitor **C₁** at the first gate is at a virtual ground, thus activating the group of serially connected inverters **I₁**, **I₂**, and **I₃**. This causes the transistors **Q1** and **Q2** to turn on, thus activating the SCR. The SCR then transfers the energy to the power supply connection pad **280**. The group of serially connected inverters **I₁**, **I₂**, and **I₃** provide a sharp transition and a clearly defined window when the SCR is turned on.

[0073] The diode **D₂** is connected in series with the inverter **I₁** to provide protection against accidental triggering of the ESD protection circuit during normal operation. The diode **D₁** is placed in series with the SCR to increase the holding voltage of the ESD

protection circuit. The diode **D₁** may optionally be a group of serially connected diodes to adjust the holding voltage.

[0074] A sixth embodiment of the ESD protection circuit, as shown in Fig. 10 is connected between the signal input/output interface pad **275** and the power supply connection pad **280**. In this embodiment, the triggering bias circuit is a resistor **R** and capacitor **C** are formed of a first metal oxide semiconductor (MOS) transistor **M₁** biased to act as the resistor **R** and a second MOS transistor **M₅** connected to form the capacitor **C**. The MOS transistor **M₂** connected to bias the MOS transistor **M₁** to an on condition to act as the resistor **R**.

[0075] The SCR is formed as described in Figs 4a and 4b. The base of the transistor **Q1** and the collector of the transistor **Q2** is the N-well **205** of Fig. 4a and will be referred to as the first gate of the SCR. The base of the transistor **Q2** and the collector of the transistor **Q1** are the P-well **200** of Fig. 4a and are referred to as the second gate of the SCR.

[0076] The junction connection between the resistor **R** and capacitor **C** is connected to an input terminal of a first inverter **I₁** and to the gates of the PMOS transistor **M₇** and the NMOS transistor **M₈** within the inverter **I₃**. The output of the inverter **I₁** is connected to the gate of the NMOS transistor **M₄**.

[0077] The inverter **I₂** is constructed of the PMOS transistor **M₃** and the NMOS transistor **M₄** having their drains connected together. The source of the NMOS transistor **M₄** is connected to the power supply connection pad **280**. The source of the PMOS transistors **M₃** is connected to the anode of the diode **D₂** and the cathode of the diode is connected to the signal input/output interface pad **275**. The output of the inverter **I₂** at the junction of the drains of the PMOS transistor **M₃** and the NMOS transistor **M₄** is connected to the first gate of the SCR and the gate of the PMOS transistor **M₆**.

[0078] The third inverter **I₃** is constructed of the serially connected PMOS transistors **M₆** and **M₇** and the NMOS transistor **M₈**. The junction connection between the resistor **R** and the capacitor **C** is connected to the gates of the PMOS transistors **M₇** and the NMOS transistor **M₈**. The output of the third inverter **I₃** at the junction of the PMOS transistors **M₇** and the NMOS transistor **M₈** is connected to the second gate of the SCR and provide a weak feedback to the gate of the PMOS transistor **M₃**.

[0079] When an ESD event **285** occurs, the voltage at the signal input/output interface pad **275** increases dramatically. The top plate of the capacitor **C₁** at the first gate is at a virtual ground, thus activating the group of serially connected inverters **I₁**, **I₂**, and **I₃**.

This causes the transistors **Q1** and **Q2** to turn on, thus activating the SCR. The SCR then transfers the energy to the power supply connection pad **280**. The weak feedback at the pullup of the PMOS transistor **M3** provides a sharp transition and a clearly defined window when the SCR is turned on.

[0080] The diode **D2** is connected in series with the inverter **I1** to provide protection against accidental triggering of the ESD protection circuit during normal operation. The diode **D1** is placed in series with the SCR to increase the holding voltage of the ESD protection circuit. The diode **D1** may optionally be a group of serially connected diodes to adjust the holding voltage.

[0081] The ESD protection circuit of this invention, as shown in the six embodiments, is preferably a polysilicon bounded SCR of this invention. The polysilicon bounded SCR of this invention provides a more compact device with a lower internal resistance. However, the ESD protection circuit of this invention, as shown in the four embodiments may have a shallow trench isolation bounded SCR as shown in Fig. 3. Further the diodes **D1** and **D2** of Fig. 6, diodes **D1**, **D2**, and **D3** of Fig. 7, and diodes **D1**, **D2**, **D3**, **D4**, and **D5** of Fig. 8 may be the shallow trench isolation bounded diodes as shown in Fig. 1. As is known in the art, the shallow trench isolation does not allow the small feature size achievable with the polysilicon bounded SCR or polysilicon bounded diodes. Further the depth of the shallow trench isolation forces the currents to travel farther through the bulk of the devices, thus increasing the series resistance of the devices and thereby the heating during an ESD event.

[0082] While this invention has been particularly shown and described with reference to the preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made without departing from the spirit and scope of the invention.

The invention claimed is:

1. A method for forming an ESD protection circuit formed at an input/output interface of an integrated circuit formed on a substrate to protect said integrated circuit from damage caused by an ESD event, said ESD protection circuit comprising:
 - forming a polycrystalline silicon bounded SCR on a surface of said substrate by the steps of :
 - forming a first well region lightly doped with impurities of a first conductivity type on a surface of said substrate,
 - forming a second well region within said first well region by lightly doping said second well region with impurities of a second conductivity type, said impurities of the second conductivity type having a polarity opposite from the impurities of the first conductivity type,
 - forming a first diffusion region within said second well by heavily doping said first diffusion region with the impurities of the first conductivity type,
 - forming a second diffusion region within said first well region at a second distance from the first diffusion region by heavily doping said second diffusion region with impurities of the second conductivity type, and
 - forming a heavily doped polycrystalline layer at the surface of said substrate and between the first and second diffusion regions and astride a junction of the first well region and the second well region to form a bounding component to prevent silicide formation at junctions of the first diffusion region and the second well region, the first well region and the second region, and the second diffusion region and the first well region during fabrication of said silicon controlled rectifier;
 - connecting said polycrystalline silicon bounded SCR between a signal input/output interface of said integrated circuit and a power supply connection of said integrated circuit;
 - forming a biasing circuit; and

connecting said biasing circuit to said polycrystalline silicon bounded SCR to bias said polycrystalline silicon bounded SCR to turn on more rapidly during said ESD event.

2. The method of claim 1 further comprising the steps of:
forming at least one diode on said substrate; and
connecting said diode between said signal input/output interface and an anode connection of said polycrystalline silicon bounded SCR to increase a holding voltage for said polycrystalline silicon bounded SCR when said polycrystalline silicon bounded SCR is turned on.
3. The method of claim 1 wherein forming said biasing circuit: comprises the steps of:
forming a polycrystalline silicon bounded diode said polycrystalline silicon bounded diode by the steps of:
forming the first diffusion region,
forming the second well region, and
forming a second heavily doped polycrystalline layer at the surface of said substrate and placed adjacent to the first diffusion region and astride a junction of the second well region and first diffusion region to form a bounding component to prevent silicide formation at said junction of the first diffusion region and the second well region during fabrication of said polycrystalline silicon bounded diode;
wherein said junction of the first diffusion region and the second well region forms said polycrystalline bounded diode; and
connecting said polycrystalline silicon bounded diode to the signal input/output interface,
forming a third diffusion region within said second well by heavily doping said third diffusion region with the impurities of the second conductivity type,
forming a first resistance of material of the second well from a first gate of said polycrystalline silicon bounded SCR to said third diffusion region,
and

connecting said third diffusion region to said power supply connection to provide a low resistance path to said second well from said power supply connection.

4. The method of claim 3 wherein forming said biasing circuit further comprises the steps of:

forming a second resistance of the material of the second well from said first gate to said first diffusion region.

5. The method of claim 1 wherein said biasing circuit: comprises the steps of:
forming a plurality of serially connected diodes;
connecting a first diode of said plurality of serially connected diodes to the signal input/output interface;
connecting a last diode of said plurality of serially connected diodes to a second gate of said polycrystalline silicon bounded SCR; and
forming a second resistor from the second gate and the last diode of the plurality of serially connected diodes to the power supply connection;
wherein an ESD event causes a current to flow through said plurality of serially connected diodes and said second resistor to trigger the polycrystalline silicon bounded SCR to turn on.

6. The method of claim 1 wherein said heavily doped polycrystalline layer of the polycrystalline silicon bounded SCR permits a series resistance of said polycrystalline silicon bounded SCR to be smaller for a more efficient operation.

7. The method of claim 1 further comprising the step of connecting the heavily doped polycrystalline layer to bias said heavily doped polycrystalline silicon layer such that silicide shorting is prevented said first and second diffusion regions and preventing of accidental formation of an inversion region under said heavily doped polycrystalline layer.

8. The method of claim 7 further comprising the step of connecting said heavily doped polycrystalline silicon layer to the second diffusion region.

9. The method of claim 7 further comprising the step of linking the first diffusion region to a voltage source which provides a relatively large voltage during said ESD event which when said relatively large voltage exceeds said snapback voltage, said polycrystalline silicon bounded SCR conducts.

10. The method of claim 8 further comprising the step of linking the first well region, the second well region, said highly doped polycrystalline silicon layer, and the second diffusion to a return of the voltage source.

11. A method for forming an ESD protection circuit formed at an input/output interface of an integrated circuit formed on a substrate to protect said integrated circuit from damage caused by an ESD event, said ESD protection circuit comprising: forming a shallow trench isolation bounded SCR on a surface of said substrate;

connecting said shallow trench isolation bounded SCR between a signal input/output interface of said integrated circuit and a power supply connection of said integrated circuit;

forming a biasing circuit;

connecting said biasing circuit to said shallow trench isolation bounded SCR to bias said shallow trench isolation bounded SCR to turn on more rapidly during said ESD event;

forming at least one diode on said substrate; and

connecting said diode between said signal input/output interface and an anode connection of said shallow trench isolation bounded SCR to increase a holding voltage for said shallow trench isolation bounded SCR when said shallow trench isolation bounded SCR is turned on.