

FRACTIONATION SYSTEM USING BUNDLED COMPACT CO-CURRENT CONTACTING SYSTEMS

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 **[0001]** This application claims the priority benefit of United States Patent Application No. 62/520,274 filed June 15, 2017 entitled FRACTIONATION SYSTEM USING BUNDLED COMPACT CO-CURRENT CONTACTING SYSTEMS, the entirety of which is incorporated by reference herein

RELATED APPLICATIONS

- 10 **[0002]** This application is related to U.S. Provisional Application No. 62/520,213 titled FRACTIONATION SYSTEM USING COMPACT CO-CURRENT CONTACTING SYSTEMS, filed on an even date and having a common assignee herewith, the disclosure of which is incorporated by reference herein in its entirety.

FIELD

- 15 **[0003]** The present techniques provide methods and systems for fractionating one or more components from a gas stream. More specifically, the present techniques provide for methods and systems to remove heavy hydrocarbons from a natural gas stream during a liquefaction process.

BACKGROUND

- 20 **[0004]** This section is intended to introduce various aspects of the art, which can be associated with exemplary examples of the present techniques. This description is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present techniques. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.
- 25 **[0005]** Numerous applications within the upstream and downstream oil and gas industry use absorption and fractionation columns for a variety of processes including, for example, dehydration for water removal from hydrocarbon gas, amine treating for acid gas removal from hydrocarbon gas and fractionation of hydrocarbons. One application of hydrocarbons fractionation is the fractionation column – also known as a scrub column – in a typical LNG
- 30 process. **Figure 1** illustrates a known scrub column **100** that may be used in such an LNG

process. According to known LNG processes, gas fed to the scrub column is first pre-treated and cooled. The scrub column typically operates at high pressure. The main objective of the scrub column is to remove most of the heavy hydrocarbons, such as pentane, from the natural gas stream. The traditional scrub column **100** includes a bottom section, also known as a stripping section **102**, and a top section, also known as a rectification section **104**. A gas stream **108** enters the scrub column **100** at high pressure and at a position adjacent both the stripping section **102** and the rectification section **104**. The vapor and liquid in the gas stream separate from each other, with the vapor moving upward into the rectification section **104** and the liquid moving downward into the stripping section **102**. The stripping section **102** uses trays **110** to separate and direct liquid downward. Trays **110** are typically used instead of packing because of anticipated high liquid flux, which is defined as a volumetric flow per unit area.

[0006] A liquid stream **112** is extracted near the bottom of the scrub column **100** and is reheated in a reboiler **114**. The reheated stream **116** is returned to the stripping section **102**, where vapors in the reheated stream can rise through the stripping section and enter the rectification section **104**. Liquids in the reheated stream **116** combine with other liquids at the bottom of the scrub column **100**. A scrub column liquid bottoms stream **117** may be taken from the bottom of the scrub column.

[0007] Vapors from the gas stream **108** combine with vapors rising from the stripping section **102** and pass into the rectification section **104**, where they contact liquid descending the column. In the rectification section **104**, packing **118** is typically used instead of trays because of the low liquid circulation rate. The rectification section **104** includes several theoretical separation stages (typically two to four) where, based on the different boiling points of the components in the stream going to that separation stage, the fractionation/separation of hydrocarbons takes place. The packing in each section promotes intimate contact and mass transfer between the liquid and vapor. A vapor stream **122** exits the top of the scrub column **100** and is cooled in a reflux cooler system **124**, which may include one or more heat exchangers or other coolers. The cooled vapor stream **126** is sent to a reflux drum **128** where liquids and vapor are separated from each other. A reflux liquid stream **130** is returned to a top portion of the scrub column, while the reflux vapor stream **132** exiting the reflux drum **128** is sent for further processing, which may include the remainder of a natural gas liquefaction process. Vapor rising in the scrub column **100** gets richer in the lighter hydrocarbons components and the liquid descending the column gets richer in the heavier hydrocarbons components. Therefore, the scrub column liquid bottoms stream **117** is proportionally higher

in heavier hydrocarbons components than in lighter hydrocarbons components, and the reflux vapor stream **132** is proportionally higher in lighter hydrocarbons components than in heavier hydrocarbons components.

5 **[0008]** Typically, the diameter of the rectification section **104** of the scrub column **100** is much larger than the diameter of the stripping section **102** because of the high gas flow rate through the rectification section. Therefore, due to its size, pressure, and material selection due to cold temperatures, the rectification section controls the cost and weight of the scrub column, which in some applications may be substantial. The size and weight of the fractionation column may limit its application in populated areas where height must be minimized for visual
10 population reasons. Additionally, applications where size and weight are critical design factors, such as offshore LNG processing, can be limited by the size and weight of such a large fractionation column. What is needed is a method and apparatus for removing heavy hydrocarbons from a natural gas stream that eliminates the large, heavy, and costly rectification section of a fractionation column.

15 **[0009]** Besides height and weight considerations, the theory of operation of a typical fractionation column may itself be a limiting design factor. The fractionation process requires a certain amount of liquid to interact with the incoming gas stream, and in the process shown in **Figure 1** this liquid is designed to come from the fractionation process itself. This can pose difficulties for applications when relatively small amounts of heavy hydrocarbons are present
20 in a natural gas stream to be liquefied. Additionally, it may not be economically feasible to install an additional fractionation column in a pre-existing facility, such as an LNG facility, for de-bottlenecking purposes. What is needed is a method and apparatus for removing heavy hydrocarbons from a natural gas stream that can be used in applications having low liquid circulation rates. What is also needed is a method and apparatus for removing heavy
25 hydrocarbons from a natural gas stream that can be economically used in debottlenecking applications.

SUMMARY

30 **[0010]** The disclosed aspects include a fractionation system for removing heavy hydrocarbons in a gas stream. The fractionation system includes a feed gas inlet through which a feed gas stream is introduced. A stripping section receives a predominantly liquid phase of the feed gas stream. A co-current contacting system receives a predominantly vapor phase of the feed gas stream. The co-current contacting system includes a compact contacting bundle

disposed within a vessel that forms a unitary pressure boundary. The compact contacting bundle includes a plurality of substantially parallel contacting units. Each of the plurality of contacting units includes a droplet generator and a mass transfer section. Each droplet generator generates droplets from a liquid and disperses the droplets into a gas stream. Each mass transfer section provides a mixed, two-phase flow having a vapor phase and a liquid phase. A separation system separates the vapor phase from the liquid phase. An inlet manifold distributes the liquid to each droplet generator of the plurality of contacting units. A concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units.

[0011] The disclosed aspects also include a method of removing heavy hydrocarbons in a gas stream. A feed gas stream is introduced into a feed gas inlet. A predominantly liquid phase of the feed gas stream is received into a stripping section. A predominantly vapor phase of the feed gas stream is received into a co-current contacting system including a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary. The compact contacting bundle includes a plurality of substantially parallel contacting units, each of which having a droplet generator and a mass transfer section, and a separation system arranged in-line within a pipe. The liquid is distributed to each droplet generator of the plurality of contacting units. Using each droplet generator, droplets are generated from a liquid and the droplets are dispersed into a gas stream. In each mass transfer section, a mixed, two-phase flow is provided having a vapor phase and a liquid phase. In each separation system, the vapor phase is separated from the liquid phase. A concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units.

[0012] The disclosed aspects further include a fractionation system for removing heavy hydrocarbons in a gas stream. The fractionation system includes a feed gas inlet through which a feed gas stream is introduced. The feed gas is a natural gas stream. A stripping section receives a predominantly liquid phase of the feed gas stream. A plurality of co-current contacting systems are connected in series and including a first co-current contacting system and additional co-current contacting systems, the first co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, each of the plurality of co-current contacting systems include a compact contacting bundle disposed within a vessel that

forms a unitary pressure boundary. Each compact contacting bundle includes a plurality of substantially parallel contacting units, each of which have a droplet generator and a mass transfer section. The droplet generator generates droplets from a liquid and disperses the droplets into a gas stream, and the mass transfer section provides a mixed, two-phase flow having a vapor phase and a liquid phase. At least one of the droplet generators includes an annular support ring securing the droplet generator in-line within the pipe, a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes, and a gas entry cone supported by the plurality of spokes and configured to allow a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and a second portion of the gas stream to flow around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream. A separation system separates the vapor phase from the liquid phase. The vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems. The liquid phase of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in the first or second co-current contacting systems. An in-line flash separator receives the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the first co-current contacting system. The in-line flash separator separates liquids from the predominantly vapor phase. A flash reflux line is connected to the in-line flash separator and to the stripping section. The flash reflux line conveys liquids separated from the predominantly vapor phase in the in-line flash separator to the stripping section.

DESCRIPTION OF THE DRAWINGS

- [0013] The advantages of the present techniques are better understood by referring to the following detailed description and the attached drawings, in which:
- [0014] Figure 1 is a generalized schematic diagram of a prior art gas fractionation system;
- [0015] Figure 2 is a schematic diagram of a co-current contacting system according to disclosed aspects;
- [0016] Figure 3A is a front view of a contacting device according to disclosed aspects;
- [0017] Figure 3B is a side perspective view of the contacting device of Figure 3A;

[0018] Figure 3C is a cross-sectional side perspective view of the contacting device of Figure 3A according to disclosed aspects;

[0019] Figure 3D is another cross-sectional side perspective view of the contacting device according to disclosed aspects;

5 [0020] Figure 4 is a generalized schematic diagram of a gas fractionation system according to aspects disclosed herein;

[0021] Figure 5 is a process flow diagram of a portion of a gas fractionation system including a number of co-current contacting systems, according to disclosed aspects;

10 [0022] Figures 6A and 6B are side and end views, respectively, of a bundle of parallel co-current contacting systems according to disclosed aspects;

[0023] Figure 7 is a process flow diagram of a method for gas fractionation using co-current contacting systems according to disclosed aspects; and

[0024] Figure 8 is a process flow diagram of a method for gas fractionation using co-current contacting systems according to disclosed aspects.

15 DETAILED DESCRIPTION

[0025] In the following detailed description section, non-limiting examples of the present techniques are described. However, to the extent that the following description is specific to a particular example or a particular use of the present techniques, this is intended to be for exemplary purposes only and simply provides a description of the exemplary examples.
20 Accordingly, the techniques are not limited to the specific examples described below, but rather, include all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

[0026] At the outset, for ease of reference, certain terms used in this application and their meanings as used in this context are set forth. Further, the present techniques are not limited
25 by the usage of the terms shown below, as all equivalents, synonyms, new developments, and terms or techniques that serve the same or a similar purpose are considered to be within the scope of the present claims.

[0027] "Acid gas" refers to any gas that produces an acidic solution when dissolved in water. Non-limiting examples of acid gases include hydrogen sulfide (H₂S), carbon dioxide
30 (CO₂), sulfur dioxide (SO₂), carbon disulfide (CS₂), carbonyl sulfide (COS), mercaptans, or

mixtures thereof.

[0028] “Co-current contactor” refers to a vessel that receives a gas stream and a separate solvent stream in such a manner that the gas stream and the solvent stream contact one another while flowing in generally the same direction.

5 [0029] The term "co-currently" refers to the internal arrangement of process streams within a unit operation that can be divided into several sub-sections by which the process streams flow in the same direction.

[0030] As used herein, a "column" is a separation vessel in which a counter-current flow is used to isolate materials on the basis of differing properties.

10 [0031] As used herein, the term “dehydration” refers to the pre-treatment of a raw feed gas stream to partially or completely remove water and, optionally, some heavy hydrocarbons.

[0032] The term "fractionation" refers to the process of physically separating components of a fluid stream into a vapor phase and a liquid phase based on differences in the components' boiling points and vapor pressures at specified temperatures and pressures. Fractionation is typically performed in a “fractionation column,” which includes a series of vertically spaced plates. In a typical process, a feed stream enters the fractionation column at a mid-point, dividing the fractionation column into two sections. The top section can be referred to as the rectification section, and the bottom section can be referred to as the stripping section. Condensation and vaporization occur on each plate, causing lower boiling point components to rise to the top of the fractionation column and higher boiling point components to fall to the bottom. A reboiler is located at the base of the fractionation column to add thermal energy. The “bottoms” product is removed from the base of the fractionation column. A condenser is located at the top of the fractionation column to condense the product emanating from the top of the fractionation column, which is called the distillate. A reflux pump is used to maintain flow in the rectification section of the fractionation column by pumping a portion of the distillate back into the distillation column.

15
20
25

[0033] As used herein, the term "facility" is used as a general term to encompass oil and gas field gathering systems, processing platform systems, and well platform systems.

[0034] The term "gas" is used interchangeably with "vapor," and is defined as a substance or mixture of substances in the gaseous state as distinguished from the liquid or solid state. Likewise, the term "liquid" means a substance or mixture of substances in the liquid state as

30

distinguished from the gas or solid state.

[0035] A “hydrocarbon” is an organic compound that primarily includes the elements hydrogen and carbon, although nitrogen, sulfur, oxygen, metals, or any number of other elements can be present in small amounts. As used herein, hydrocarbons generally refer to components found in natural gas, oil, or chemical processing facilities.

[0036] A “heavy” hydrocarbon is a hydrocarbon with three or more carbon atoms in each molecule. The precise number of carbon atoms comprising a heavy hydrocarbon molecule may depend on the feed gas and the desired product gas. For example, if methane gas (having one carbon atom per molecule) is the desired product gas, then heavy hydrocarbons may include propane (having three carbon atoms). Examples of heavy hydrocarbons include pentane, hexane, heptane, and the like.

[0037] With respect to fluid processing equipment, the term “in series” means that two or more devices are placed along a flow line such that a fluid stream undergoing fluid separation moves from one item of equipment to the next while maintaining flow in a substantially constant downstream direction. Similarly, the term “in line” means that two or more components of a fluid mixing and separating device are connected sequentially or, more preferably, are integrated into a single tubular device. Similarly, the term “in parallel” means that a stream is divided among two or more devices, with a portion of the stream flowing through each of the devices.

[0038] The term “stream” indicates a material that is flowing from a first point, such as a source, to a second point, such as a device processing the stream. The stream may include any phase or material, but is generally a gas or liquid. The stream may be conveyed in a line or pipe, and used here, reference to the line or pipe also refers to the stream the line is carrying, and vice versa.

[0039] “Natural gas” refers to a multi-component gas obtained from a crude oil well or from a subterranean gas-bearing formation. The composition and pressure of natural gas can vary significantly. A typical natural gas stream contains methane (CH₄) as a major component, i.e., greater than 50 mol % of the natural gas stream is methane. The natural gas stream can also contain ethane (C₂H₆), heavy hydrocarbons (e.g., C₃-C₂₀ hydrocarbons), one or more acid gases (e.g., CO₂ or H₂S), or any combinations thereof. The natural gas can also contain minor amounts of contaminants such as water, nitrogen, iron sulfide, wax, crude oil, or any combinations thereof. The natural gas stream can be substantially purified, so as to remove

compounds that may act as poisons.

[0040] “Solvent” refers to a substance capable at least in part of dissolving or dispersing one or more other substances, such as to provide or form a solution. The solvent can be polar, nonpolar, neutral, protic, aprotic, or the like. The solvent may include any suitable element, molecule, or compound, such as methanol, ethanol, propanol, glycols, ethers, ketones, other
5 alcohols, amines, salt solutions, ionic liquids, or the like. The solvent may include physical solvents, chemical solvents, or the like. The solvent may operate by any suitable mechanism, such as physical absorption, chemical absorption, or the like.

[0041] “Substantial” when used in reference to a quantity or amount of a material, or a
10 specific characteristic thereof, refers to an amount that is sufficient to provide an effect that the material or characteristic was intended to provide. The exact degree of deviation allowable may depend, in some cases, on the specific context.

[0042] The present techniques provide for the fractionation of substances from a gas stream, for example removing heavy hydrocarbons from a natural gas stream, using co-current
15 contacting systems. Alternatively, the present techniques provide for the separation of at least a portion of heavy hydrocarbons from a hydrocarbons stream that includes heavy hydrocarbons and light hydrocarbons. The co-current contacting systems disclosed herein include stages composed primarily of in-line devices, or of bundles of parallel in-line devices, in either case the devices and/or the bundles having smaller diameters than a conventional tower.

[0043] Known counter-current flow schemes, such as the known scrub column **100** of
20 Figure 1, require comparatively low velocities to avoid entrainment of the down-flowing liquid in the natural gas stream. Further, relatively long distances are useful for disengagement of the liquid droplets from the raw natural gas stream. Depending on the flow rate of the natural gas stream, the scrub column **100** may be greater than four meters in diameter and more than 30
25 meters tall. For high-pressure applications, the vessel has thick, metal walls. Consequently, counter-current contactor vessels can be large and very heavy. This is generally undesirable, particularly for offshore liquefaction applications, and may not be feasible for other applications.

[0044] The present technological advancement can use a co-current flow scheme as an
30 alternative to the counter-current flow scheme demonstrated in the scrub column **100** of Figure 1. The co-current flow scheme utilizes one or more co-current contacting systems connected in series within a pipe. A natural gas stream and a liquid reflux stream may move

together, i.e., co-currently, within each co-current contacting system. In general, co-current contactors can operate at much higher fluid velocities than counter-current contacting systems. As a result, co-current contacting systems tend to be smaller than counter-current contactors that utilize standard towers with packing or trays. Further, the co-current contacting systems are smaller than conventional pressure vessels of equivalent processing capacity, and are thus more suited to modular design/construction, offshore deployment, de-bottlenecking applications, and applications where visual pollution may be a factor. In natural gas liquefaction application, two to three co-current contacting systems in series can be used to separate heavy hydrocarbons from a natural gas stream.

10 [0045] Figure 2 is a schematic of a co-current contacting system (CCCS) **200**. The co-current contacting system **200** can provide for the separation of components within a gas stream. The co-current contacting system **200** can include a co-current contactor **202** that is positioned in-line within a pipe **204**. The co-current contactor **202** may include a number of components that provide for the efficient contacting of a liquid droplet stream with a flowing gas stream **206**. The liquid droplet stream may be used for the separation of impurities, such as heavy hydrocarbons, from a gas stream **206**.

[0046] The co-current contactor **202** may include a droplet generator **208** and a mass transfer section **210**. As shown in Figure 2, the gas stream **206** may be flowed through the pipe **204** and into the droplet generator **208**. A liquid stream **212** may also be flowed into the droplet generator **208**, for example, through a hollow space **214** coupled to flow channels **216** in the droplet generator **208**.

[0047] From the flow channels **216**, the liquid stream **212** is released into the gas stream **206** as fine droplets through injection orifices **218**, and is then flowed into the mass transfer section **210**. This can result in the generation of a treated gas stream **220** within the mass transfer section **210**. The treated gas stream **220** may include small liquid droplets dispersed in a gas phase. For fractionation associated with a natural gas liquefaction process, the liquid droplets may include heavy hydrocarbons from the gas stream **206** that were absorbed or dissolved into the liquid stream **212**.

[0048] The treated gas stream **220** may be flowed from the mass transfer section **210** to a separation system **222**, which includes a cyclonic separator **223** and a collector **224**. Alternatively the separation system may include a mesh screen, or a settling vessel. Preferably, in-line cyclonic separators may be used to realize the benefits of compactness and reduced

diameter. The cyclonic separator **223** removes the liquid droplets from the gas phase. The liquid droplets, which as previously stated may include heavy hydrocarbons **206** absorbed or dissolved into the liquid stream **212**, are diverted into collector **224**, which directs the collected liquids stream **226** through a valve **228** and pump **230** to other portions of the disclosed aspects
5 as will be further described herein. A gas purge line **232** extends from the collector **224** and operates to re-inject gas present in the collector into the separation system **222**. In an aspect, this gas is re-injected using a nozzle **233** or eductor situated inside the separation system **222**. A gas stream **234**, from which the heavy hydrocarbons-rich liquid has been separated, exits the separation system **222** in an in-line orientation with the pipe **204**. The proportion of light
10 hydrocarbons to heavy hydrocarbons is higher in gas stream **234** than in gas stream **206**.

[0049] Figure 3A is a front view of a contacting device **300**. The contacting device **300** may be implemented within a co-current contactor, for example, in the co-current contactor **202** described with respect to the co-current contacting system **200** of Figure 2. The contacting device **300** can be an axial, in-line co-current contactor located within a pipe. The front view
15 of the contacting device **300** represents an upstream view of the contacting device **300**.

[0050] The contacting device **300** may include an outer annular support ring **302**, a number of spokes **304** extending from the annular support ring **302**, and a gas entry cone **306**. The annular support ring **302** may secure the contacting device **300** in-line within the pipe. In addition, the spokes **304** may provide support for the gas entry cone **306**.

20 [0051] The annular support ring **302** may be designed as a flanged connection, or as a removable or fixed sleeve inside the pipe. In addition, the annular support ring **302** may include a liquid feed system and a hollow channel described further with respect to Figures 3C and 3D. A liquid stream may be fed to the contacting device **300** via the hollow channel in the annular support ring **302**. The hollow channel may allow equal distribution of the liquid stream along
25 the perimeter of the contacting device **300**.

[0052] Small liquid channels within the annular support ring **302** may provide a flow path for the liquid stream to flow through liquid injection orifices **308** within the spokes **304**. The liquid injection orifices **308** may be located on or near the leading edge of each spoke **304**. Placement of the liquid injection orifices **308** on the spokes **304** may allow the liquid stream to
30 be uniformly distributed in a gas stream that is directed between the spokes **304**. Specifically, the liquid stream may be contacted by the gas stream flowing through the gaps between the spokes **304**, and can be sheared into small droplets and entrained in the gas phase.

[0053] A portion of the feed gas stream flows between the spokes to the mass transfer section while the remainder of the gas stream flows into the gas entry cone **306** through a gas inlet **312**. The gas entry cone **306** may block a cross-sectional portion of the pipe. The spokes **304** include gas exit slots **310** that allow the gas stream to be flowed out of the gas entry cone **306**. This may increase the velocity of the gas stream as it flows through the pipe. The gas entry cone **306** may direct a predetermined amount of the gas stream to the gas exit slots **310** on the spokes **304**.

[0054] Some of the liquid stream injected through the spokes **304** may be deposited on the surface of the spokes **304** as a liquid film. As the gas stream flows through the gas entry cone **306** and is directed out of the gas exit slots **310** on the spokes **304**, the gas stream may sweep, or blow, much of the liquid film off the spokes **304**. This may enhance the dispersion of the liquid stream into the gas phase. Further, the obstruction to the flow of the gas stream and the shearing effect created by the exit of the gas through the gas exit slots may provide a zone with an increased turbulent dissipation rate. The may result in the generation of smaller droplets that enhance the mass transfer rate of the liquid stream and the gas stream.

[0055] The dimensions of various components of the contacting device **300** may be varied such that the gas stream flows at a high velocity. This may be accomplished via either a sudden reduction in the diameter of the annular support ring **302** or a gradual reduction in the diameter of the annular support ring **302**. The outer wall of the contacting device **300** may be slightly converging in shape, terminating at the point where the gas stream and the liquid stream are discharged into the downstream pipe. This can allow for the shearing and re-entrainment of any liquid film that is removed from the contacting device **300**. Further, a radial inward ring, grooved surface, or other suitable equipment may be included on the outer diameter of the contacting device **300** near the point where the gas stream and the liquid stream are discharged into the downstream pipe. This may enhance the degree of liquid entrainment within the gas phase.

[0056] The downstream end of the contacting device **300** may discharge into a section of pipe (not shown). The section of pipe can be a straight section of pipe, or a concentric expansion section of pipe. The gas entry cone **306** may terminate with a blunt ended cone or a tapered ended cone. In other embodiments, the gas entry cone **306** can terminate with a ridged cone, which can include multiple concentric ridges along the cone that provide multiple locations for droplet generation. In addition, any number of gas exit slots **310** may be provided on the cone itself to allow for the removal of the liquid film from the contacting device **300**.

[0057] Figure 3B is a side perspective view of the contacting device **300**. Like numbered items are as described with respect to Figure 3A. As shown in Figure 3B, the upstream portion of the gas entry cone **306** may extend further into the pipe than the annular support ring **302** and the spokes **304** in the upstream direction. The downstream portion of the gas entry cone **306** can also extend further into the pipe than the annular support ring **302** and the spokes **304** in the downstream direction. The length of the gas entry cone **306** in the downstream direction depends on the type of cone at the end of the gas entry cone **306**, as described further with respect to Figures 3C and 3D.

[0058] Figure 3C is a cross-sectional side perspective view of the contacting device **300** according to a disclosed aspect. Like numbered items are as described with respect to Figures 3A and 3B. According to Figure 3C, the gas entry cone **306** of the contacting device **300** terminates with a tapered ended cone **314**. Terminating the gas entry cone **306** with a tapered ended cone **314** may reduce the overall pressure drop in the pipe caused by the contacting device **300**.

[0059] Figure 3D is a cross-sectional side perspective view of the contacting device **300** according to another disclosed aspect. Like numbered items are as described with respect to Figures 3A-3C. According to Figure 3D, the gas entry cone **306** of the contacting device **300** terminates with a blunt ended cone **316**. Terminating the gas entry cone **306** with a blunt ended cone **316** may encourage droplet formation in the center of the pipe.

[0060] Figure 4 depicts a gas fractionation system **400** according to disclosed aspects, which may be used with natural gas liquefaction process. The gas fractionation system **400** includes a bottom section, also known as a scrub stripper column **402**, and a top section or rectification section **404**, which according to disclosed aspects comprises a plurality of co-current contacting systems. The scrub stripper column **402** may be a stand-alone column, and performs an equivalent function to the stripping section **102** of scrub column **100** depicted in Figure 1. As can be seen in Figure 4, the feed gas stream **408**, which typically is a two-phase stream, enters the gas fractionation system **400** at high pressure and at a position adjacent both the scrub stripper column **402** and the rectification section **404**. A predominantly vapor phase and a predominantly liquid phase in the feed gas stream **408** separate from each other, with the predominantly vapor phase moving upward into the rectification section **404** and the predominantly liquid phase moving downward into the scrub stripper column **402**. The scrub stripper column **402** uses trays **410** to separate and direct liquid downward. Trays **410** are typically used instead of packing because of anticipated high liquid flux, which is defined as a

volumetric flow per unit area.

[0061] A liquid stream **412** is extracted near the bottom of the scrub stripper column **402** and is re-heated in a reboiler **414**. The reheated stream **416** is returned to the scrub stripper column **402**, where vapors in the reheated stream may rise through the scrub stripper column and enter the rectification section **404**. Liquids in the reheated stream **416** combine with other liquids at the bottom of the scrub stripper column **402**. A scrub stripper column liquid bottoms stream **417** may be taken from the bottom of the scrub stripper column **402**.

[0062] The vapor phase of the feed gas stream **408** is combined with the vapor rising from the scrub stripper column **402**. The combined vapor stream **420** enters the rectification section **404**, which in an aspect includes a separation system **418** and one or more scrubbing stages, with each scrubbing stage including an in-line co-current contacting system **421a**, **421b**, **421c** similar to the in-line co-current contacting system **200** described in Figure 2. In a preferred aspect the separation system **418** includes a cyclonic separator, and in a more preferred embodiment includes an in-line cyclonic separator **422** and a collector **423** similar to the cyclonic separator **223** and collector **224** used in separation system **222** of Figure 2. The in-line cyclonic separator **422** serves as a flash zone to cause some of the liquids entrained in the combined vapor stream **420** to be separated therefrom. If the gas fractionation system **400** is used where no fouling is expected due to the content of the feed stream, an agglomerator **424** may be placed in front of the in-line cyclonic separator **422** to increase the size of the liquid droplets entering the in-line cyclonic separator. Agglomerator **424** may improve the liquid separation performance of the in-line cyclonic separator **422**. The liquid collected from the collector **423** is fed through a flash reflux line **425** to a top region of the scrub stripper column **402** for further separation therein.

[0063] The flash zone vapor stream **426** exiting the in-line cyclonic separator **422** is fed to the first co-current contacting system **421a**, which includes a droplet generator **428a**, a mass transfer section **430a**, a cyclonic separator **432a** with an optional agglomerator **434a**, and a collector **436a**. Liquid **438b** collected from a subsequent or downstream in-line co-current contacting system (such as in-line co-current contacting system **421b**) is injected into the droplet generator **428a** and mixed and combined in the mass transfer section, where heavy hydrocarbons in the flash zone vapor stream are transferred to the sprayed liquid, and light hydrocarbons in the liquid stream are transferred to the flash zone vapor stream. The liquid and vapor in the mass transfer section **430a** are separated from each other using the cyclonic separator **432a** and optional agglomerator **434a**, with the liquid being collected in the collector

436a and sent through a liquid collection line **438a** to be combined with the flash reflux line **425**. The gas stream **440a** with heavy hydrocarbons removed therefrom is sent as an input to the second co-current contacting system **421b**. The second co-current contacting system **421b** is constructed similar to first co-current contacting system **421a** and functions in a similar manner, with liquid **438c** collected from a subsequent or downstream in-line co-current contacting system (such as in-line co-current contacting system **421c**) being mixed with the gas stream **440a**. The gas stream **440b** with heavy hydrocarbons removed in the second co-current contacting system **421b** is sent as an input to the third co-current contacting system **421c**. The third co-current contacting system **421c** is constructed similar to first and second co-current contacting systems **421a**, **421b** and functions in a similar manner. The gas stream **440c** with heavy hydrocarbons removed therefrom is sent to a reflux cooler **442**, which condenses heavy hydrocarbons remaining in the gas stream, which are in turn separated in liquid form from the gas stream in a reflux drum **444**. The reflux liquid stream **446** is used as the liquid input to the third co-current contacting system **421c**, and the gas stream **448** exiting the reflux drum is sent for further processing, which may include liquefaction.

[0064] The gas fractionation system **400** may include any number of co-current contacting systems as desired or required. Further, any number of additional components can be included within the gas fractionation system **400**, depending on the details of the specific implementation. Further, the gas fractionation system **400** may include any suitable types of heaters, chillers, condensers, liquid pumps, gas compressors, blowers, bypass lines, other types of separation and/or fractionation equipment, valves, switches, controllers, and pressure-measuring devices, temperature-measuring devices, level-measuring devices, or flow-measuring devices, among others.

[0065] Figure 5 is a schematic diagram of another arrangement of the rectification section **404** of the gas fractionation system **400**. Shown are the separation system **418** and three scrubbing stages which comprise the first, second, and third in-line co-current contacting systems **421a**, **421b**, **421c**. For each of the separation system and the first through third in-line co-current contacting systems, Figure 5 also shows the pumps **450a**, **450b**, **450c**, **450d**, valves **452a**, **452b**, **452c**, **452d**, gas purge lines **454a**, **454b**, **454c**, **454d**, and nozzles **456a**, **456b**, **456c**, **456d** that were described with respect to Figure 2. Figure 5 shows more clearly that the disclosed aspects are operated with an overall countercurrent flow of the liquid from previous scrubbing stages, with co-current contacting in individual scrub stages.

[0066] Figure 6A is a side view of a single stage multiple co-current contactor

configuration **600** that may be used as part or all of a rectification section in a gas fractionation system as previously disclosed. The single stage multiple co-current contactor configuration **600** is generally contained within a vessel **602** which may form a unitary (single and/or common) pressure boundary for the compact contacting occurring therein. The vessel **602** may be configured to withstand in excess of (may have a pressure vessel rating of) about 500 psia (about 34 bar) of pressure, e.g., from about 600 psia (about 41 bar) to about 3,000 psia (about 207 bar), from about 800 psia (about 48 bar) to about 3,000 psia (about 207 bar), about 600 psia (about 41 bar) to about 2,000 psia (about 138 bar), from about 800 psia (about 48 bar) to about 2,000 psia (about 138 bar) from about 600 psia (about 41 bar) to about 1,000 psia (about 70 bar), from about 800 psia (about 48 bar) to about 1,000 psia (about 70 bar), from about 1,000 psia (about 70 bar) to about 3,000 psia (about 207 bar), from about 1,000 psia (about 70 bar) to about 2,000 psia (about 138 bar), from about 2,000 psia (about 138 bar) to about 3,000 psia (about 207 bar), or any range there between. The differential pressure across the length of the vessel **602**, e.g., between the gas stream **604** and natural gas stream **606**, may be about 200 psia (about 14 bar) to about 700 psia (about 48 bar), about 300 psia (about 21 bar) to about 600 psia (about 41 bar), about 400 psia (about 28 bar) to about 500 psia (about 34 bar), about 200 psia (about 14 bar) to about 600 psia (about 41 bar), about 300 psia (about 21 bar) to about 600 psia (about 41 bar), about 400 psia (about 28 bar) to about 600 psia (about 41 bar), about 500 psia (about 34 bar) to about 600 psia (about 41 bar), about 200 psia (about 14 bar) to about 500 psia (about 34 bar), about 300 psia (about 21 bar) to about 500 psia (about 34 bar), about 200 psia (about 14 bar) to about 400 psia (about 28 bar), about 300 psia (about 21 bar) to about 400 psia (about 28 bar), about 200 psia (about 14 bar) to about 300 psia (about 21 bar), or any range therebetween. The vessel **602** generally contains a single stage bundle of substantially parallel separation units or compact contactors comprising contacting units **608a-608n**, also referred to herein as separation units. Those of skill in the art will understand that the number of contacting units **608a-608n** in the bundle of compact contactors may be optionally selected based on the desired design characteristics, including desired flow rate, separation unit diameter, etc., and could number from anywhere between one to 300 or more units. The use of the letter nomenclature (i.e., 'a', 'b', 'n', etc.) in conjunction with the numerical reference characters is for ease of reference only and is not limiting. For example, those of skill in the art will understand that an illustrated set of contacting units **608a-608n** may, in various embodiments, comprise two, four, five, twenty, or several hundred contacting units. The vessel **602** comprises an inlet manifold **610** having droplet generators **612a-612n** in the inlet section **614** of the single

stage multiple co-current contactor configuration **600**. The inlet section **614** is configured to receive the natural gas stream **604** in a common inlet plenum through which the natural gas stream **604** may be distributed substantially equally across the contacting units **608a-608n**. While a gas stream **604**, gas stream **606**, etc. are discussed herein, those of skill in the art will appreciate that generally the same principles may be applied to any fluid stream, including with respect to liquid-liquid contacting. Consequently, use of the phrases “gas stream,” “gas inlet,” “gas outlet,” etc. are to be understood as non-limiting and may optionally be replaced with “fluid stream,” “fluid inlet,” “fluid outlet,” and so forth in various embodiments within the scope of this disclosure. Use of the phrases “gas stream,” “gas inlet,” “gas outlet,” etc. are for the sake of convenience only. The contacting units **608a-608n** may be of a suitable size depending on the design requirements. For example, the contacting units **608a-608n** may have an individual diameter from about 2 inches (in) (about 5 centimeters (cm)) to about 24 in (about 61 cm), about 3 in (about 7.6 cm) to about 20 in (about 50 cm), about 4 in (about 10.1 cm) to about 18 in (about 45 cm), about 6 in (about 15.3 cm) to about 12 in (about 30 cm), about 6 in (about 15.3 cm) to about 18 in (about 45 cm), about 12 in (about 30 cm) to about 18 in (about 45 cm), about 18 in (about 45 cm) to about 24 in (about 61 cm), or any range there between. The inlet manifold **610** is configured to receive a liquid stream **212** and pass the liquid stream **212** to the droplet generators **612a-612n**, where the liquid stream **212** may be atomized. Droplet generators **612a-612n** are similar to the droplet generator **208** or contacting device **300** as previously described. The droplet generators **612a-612n** may serve to entrain the atomized liquid stream in the gas stream **604**, and the mixed stream of atomized solvent and natural gas may be passed to the mass transfer section **616** where absorption occurs. Each contacting unit **608a-608n** has a recycle gas inlet **618a-618n** supplied by recycle gas collected and returned, e.g., from a common boot **620**. The boot **620** may be optionally included in low liquid rate applications to improve liquid rate flow control. As depicted, the boot **620** may have an internal vortex breaker **622** or other appropriate internals. For ease of viewing, the recycle gas supply lines for each of the recycle gas inlets **618a-618n** are not depicted, but may be similar to gas purge line **232** as previously described. As will be understood by those of skill in the art, the recycle gas inlets **618a-618n** are optional, and recycle gas may additionally or alternatively be sent downstream in other aspects. Liquid exiting the contacting units **608a-608n** via liquid outlets **624a-624n** may drain into a common liquid degassing section or common liquid collection plenum **626**. The plenum **626** may provide sufficient residence time for desired degassing, may reduce liquid surges coming with the natural gas stream **604**, and may provide

a liquid seal to a cyclonic separation occurring in a contacting section **628** of each contacting unit **608a-608n**. The residence time provided by the plenum **626** can vary from 5 seconds to 5 minutes, depending on the operation of the process, or from 30 seconds to 1 minute in various aspects. The vessel **602** contains a mist eliminator **630**, e.g., a wire mesh, vane pack plates, baffles, or other internal devices to reduce liquid droplet carry over from degassing gas, leaving the liquid in the plenum **626**. The mist eliminator **630** may also serve as a momentum breaker for the liquid exiting each contacting unit **608a-608n** to minimize aeration of the liquid. In aspects installed in offshore facilities or floating facilities or otherwise subject to motion, the mist eliminator **630** may mitigate wave motion effects in the bottom portion of the vessel **602**.

Each contacting unit **608a-608n** has a treated gas outlet **632a-632n** and a liquid outlet **624a-624n** in a separation section **633**. The vessel **602** has a vent **634** for expelling degassing gas, e.g., gas degassed from liquid collected in the plenum **626** that may be fed upstream or downstream of the multiple co-current contacting unit, depending on the process configuration. The treated gas outlets **632a-632n** couple to an outlet manifold **636**. The vessel **602** also contains level control ports **638a** and **638b** for coupling a level control system (not depicted) and controlling the amount of liquid **640** exiting the boot **620**. Liquid **640** exiting the boot **620** may be sent to a rectification section of a fractionation system, as previously described.

[0067] Figure 6B is a cross-sectional end view of the single stage multiple co-current contactor configuration **600** of Figure 6A taken at the inlet manifold **610**. Figure 6B shows an example arrangement of the contacting units in the vessel **602**, although for the sake of simplicity only the droplet generators **612a-612n** associated with the contacting units are shown. Other acceptable arrangements will be readily apparent to those of skill in the art. Figure 6B also shows a location of the mist eliminator **630**, the plenum **626**, the vent **634**, the boot **620**, the level control ports **638a** and **638b**, and the liquid stream **640**.

[0068] Figures 6A and 6B depict a single stage multiple co-current contactor configuration. Additional stages may also be included in a multiple co-current contactor, as disclosed in co-owned U.S. Patent Application Publication No. US2016/0199774 titled “Separating Impurities from a Fluid Stream Using Multiple Co-current Contactors”, the disclosure of which is incorporated herein by reference in its entirety. Additionally, any of the in-line co-current contacting systems **421a**, **421b**, **421c** of the gas fractionation system depicted in Figures 4 and 5 may be replaced by a single stage or multiple stage multiple co-current contactor as described herein.

[0069] Figure 7 is a method **700** of removing heavy hydrocarbons in a gas stream according

to aspects of the disclosure. At block **702** a feed gas stream is introduced into a feed gas inlet. At block **704** a predominantly liquid phase of the feed gas stream is received into a stripping section. At block **706** a predominantly vapor phase of the feed gas stream is received into a first co-current contacting system located in-line within a pipe with a second co-current contacting system. Each of the first and second co-current contacting systems comprise a co-current contactor including a droplet generator and a mass transfer section, and a separation system. At block **708**, using each droplet generator, droplets from a liquid are generated and dispersed into a gas stream. At block **710**, in each mass transfer section a mixed, two-phase flow is provided having a vapor phase and a liquid phase. At block **712**, in each separation system the vapor phase from the liquid phase are separated. The vapor phase of the co-current contactor in the first co-current contacting system comprises the gas stream for the co-current contactor in the second co-current contacting system. The liquid phase of the co-current contactor in the second co-current contacting system comprises the liquid from which droplets are generated in the co-current contactor of the first co-current contacting system.

[0070] Figure 8 is a method **800** of a method of removing heavy hydrocarbons in a gas stream. At block **802** a feed gas stream is introduced into a feed gas inlet. At block **804** a predominantly liquid phase of the feed gas stream is received into a stripping section. At block **806** a predominantly vapor phase of the feed gas stream is received into a first co-current contacting system located in-line within a pipe with a second co-current contacting system. At least one of the first and second co-current contacting systems including a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary. The compact contacting bundle includes a plurality of substantially parallel contacting units. Each of the plurality of contacting units has a droplet generator and a mass transfer section, and a separation system. At block **808** the liquid is distributed to each droplet generator of the plurality of contacting units. At block **810**, using each droplet generator, droplets are generated from a liquid and dispersing the droplets into a gas stream. At block **812**, in each mass transfer section, a mixed, two-phase flow is provided having a vapor phase and a liquid phase. At block **814**, in each separation system, the vapor phase is separated from the liquid phase. The vapor phase of the first co-current contacting system comprises the gas stream for the second co-current contacting system, and the liquid phase of the second co-current contacting system comprises the liquid from which droplets are generated in the first co-current contacting system.

[0071] The disclosed aspects may be varied in many ways. For example, the compact co-current contacting systems have been shown in the Figures as being connected to each other in

series, but for additional turndown flexibility one or more of the compact co-current contacting systems may be connected to each other in parallel. The separation systems disclosed herein may also be varied. Instead of the disclosed single cyclonic separator, in-line demisting cyclones may be used. Additional in-line demisting cyclones may be installed after the last
5 scrubbing stage if further liquid separation is desired or required. Other known mist-eliminating devices may replace the cyclonic separator. The methods, processes, and/or functions described herein can be implemented and/or controlled by a computer system appropriately programmed.

[0072] Moreover, it is contemplated that features from various examples described herein
10 can be combined together, including some but not necessarily all the features provided for given examples. Furthermore, the features of any particular example are not necessarily required to implement the present technological advancement.

[0073] The disclosed aspects replace the large diameter packed rectification section of known LNG scrub columns. An advantage of the disclosed aspects is that the disclosed aspects
15 may be used with many different LNG processes with scrub column schemes. Another advantage is that the compact co-current contacting systems can be horizontally oriented, vertically oriented, or in a mixed orientation as required or desired to best meet the limitations of an existing plot or module space.

[0074] Other advantages of the disclosed aspects may be seen through reduced capital costs
20 and potentially enhanced processing capacity in space-limited retrofit and de-bottlenecking opportunities. Due to the operating pressure of conventional LNG Scrub columns (~ 60 bar, 850 psia) and the low operating processing temperatures of the system (-20 °C), the column must be constructed of very expensive stainless steel with a very thick wall. For example, a scrub column where the top/rectification section of a conventional packed stainless steel scrub
25 column has a diameter of 4.2 m, approximately 12.6 m height (including a flash zone) and 105 mm wall thickness, can be replaced with the disclosed scrubbing system enclosed in a pipe having a 24 inch (60.96 cm) diameter. This may result in an approximately 75% reduction in capital expenditures, not to mention additional savings in transportation, civil and structural supports, when compared to known scrub columns.

[0075] Additionally, the rectification function may be used in many applications, such as:
30 new LNG facilities requiring a scrub column; LNG production on floating facilities, as the disclosed aspects are not susceptible to tower motion inefficiencies; any fractionation

application (stripping and/or rectification section) having a low liquid flow rate; a brownfield LNG Scrub Column where the existing rectification section is a bottleneck to the capacity of the column; and LNG production in populated areas where height is to be minimized for visual pollution reasons.

- 5 **[0076]** Aspects of the disclosure may include any combinations of the methods and systems shown in the following numbered paragraphs. This is not to be considered a complete listing of all possible aspects, as any number of variations can be envisioned from the description above.

10 A1. A fractionation system for removing heavy hydrocarbons in a gas stream, comprising:
a feed gas inlet through which a feed gas stream is introduced;
a stripping section configured to receive a predominantly liquid phase of the feed gas stream; and

first and second co-current contacting systems located in-line within a pipe, the first co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, each of the first and second co-current contacting systems comprising:

15 a co-current contactor including a droplet generator and a mass transfer section, the droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and the mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase; and

20 a separation system configured to separate the vapor phase from the liquid phase;

wherein the vapor phase of the co-current contactor in the first co-current contacting system comprises the gas stream for the co-current contactor in the second co-current contacting system, and wherein the liquid phase of the co-current contactor in the second co-current contacting system comprises the liquid from which droplets are generated in the co-current contactor of the first co-current contacting system.

25 A2. The fractionation system of paragraph A1, wherein the droplet generator in the co-current contactor in at least one of the first and second co-current contacting systems comprises:

an annular support ring securing the droplet generator in-line within the pipe;
30 a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes; and
a gas entry cone supported by the plurality of spokes and configured to allow

a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

a second portion of the gas stream to flow around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream.

A3. The fractionation system of paragraph A2, wherein a downstream portion of the gas entry cone comprises a blunt ended cone.

A4. The fractionation system of paragraph A2, wherein a downstream portion of the gas entry cone comprises a tapered ended cone.

A5. The fractionation system of paragraph A1 or paragraph A2, further comprising an in-line flash separator arranged to receive the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the first co-current contacting system, the in-line flash separator configured to separate liquids from the predominantly vapor phase.

A6. The fractionation system of paragraph A5, further comprising a flash reflux line connected to the in-line flash separator and to the stripping section, the flash reflux line configured to convey liquids separated from the predominantly vapor phase in the in-line flash separator to the stripping section.

A7. The fractionation system of paragraph A5, wherein the in-line flash separator comprises a cyclonic separator.

A8. The fractionation system of paragraph A5, further comprising an agglomerator situated at an input of the in-line flash separator.

A9. The fractionation system of any of paragraphs A1-A8, wherein the separation system of at least one of the first and second co-current contacting systems comprises a cyclonic separator.

A10. The fractionation system of any of paragraphs A1-A9, further comprising:

a plurality of co-current contacting systems connected in series, said plurality of co-current contacting systems including the first and second co-current contacting systems and a last co-current contacting system; and

a reflux drum configured to receive a vapor phase from the last co-current contacting system and separate a reflux liquid from said vapor phase;

wherein the last co-current contacting system comprises

a co-current contactor including a droplet generator and a mass transfer section,

the droplet generator configured to generate droplets from the reflux liquid and to disperse the droplets into a gas stream received from a previous co-current contacting system, and the mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase; and

5 a separation system configured to separate the vapor phase from the liquid phase, wherein the vapor phase is sent to the reflux drum and the liquid phase comprises the liquid from which droplets are generated in a co-current contactor of a previous co-current contacting system.

A11. The fractionation system of paragraph A10, further comprising a reflux cooler situated
10 between the last co-current contacting system and the reflux drum, the reflux cooler configured to cool the vapor phase of the last co-current contacting system prior to being sent to the reflux drum.

A12. The fractionation system of any of paragraphs A1-A11, wherein the feed gas stream comprises a natural gas stream, and wherein the heavy hydrocarbons comprise at least one of
15 propane, butane, hexane, and heptane.

A13. A method of removing heavy hydrocarbons in a gas stream, comprising:
 introducing a feed gas stream into a feed gas inlet;
 receiving a predominantly liquid phase of the feed gas stream into a stripping section;
 receiving a predominantly vapor phase of the feed gas stream into a first co-current
20 contacting system located in-line within a pipe with a second co-current contacting system, each of the first and second co-current contacting systems comprising a co-current contactor including a droplet generator and a mass transfer section, and a separation system;
 using each droplet generator, generating droplets from a liquid and dispersing the droplets into a gas stream;

25 in each mass transfer section, providing a mixed, two-phase flow having a vapor phase and a liquid phase; and

 in each separation system, separating the vapor phase from the liquid phase;
 wherein the vapor phase of the co-current contactor in the first co-current contacting system comprises the gas stream for the co-current contactor in the second co-current
30 contacting system, and wherein the liquid phase of the co-current contactor in the second co-current contacting system comprises the liquid from which droplets are generated in the co-current contactor of the first co-current contacting system.

A14. The method of paragraph A13, wherein the droplet generator in the co-current contactor

in at least one of the first and second co-current contacting systems includes an annular support ring securing the droplet generator in-line within the pipe, a plurality of spokes extending from the annular support ring, and a gas entry cone supported by the plurality of spokes, the method further comprising:

5 flowing a liquid stream through liquid channels disposed in the annular support stream, through the plurality of spokes, and out of injection orifices disposed on the plurality of spokes; and

 flowing a first portion of a gas stream through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

10 flowing a second portion of the gas stream around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream.

A15. The method of paragraph A13, further comprising:

 receiving the predominantly vapor phase of the feed gas stream in an in-line flash separator prior to sending the predominantly vapor phase through the first co-current contacting system; and

 separating liquids from the predominantly vapor phase in the in-line flash separator.

A16. The method of paragraph A15, further comprising:

 conveying liquids separated from the predominantly vapor phase in the in-line flash separator to the stripping section via a flash reflux line.

A17. The method of paragraph A15, further comprising:

 feeding the predominantly vapor phase of the feed gas stream into an agglomerator prior to the predominantly vapor phase of the feed gas stream being received by the in-line flash separator.

25 A18. The method of paragraph A13 or paragraph A14, further comprising:

 arranging a plurality of co-current contacting systems in series, the plurality of co-current contacting systems including the first and second co-current contacting systems and a last co-current contacting system that has a co-current contactor and a separation system, wherein the co-current contactor of the last co-current contacting system has a droplet generator and a mass transfer section;

30 in a reflux drum, separating a vapor phase of the last co-current contacting system from a reflux liquid;

 generating droplets from the reflux liquid in the droplet generator of the co-current

contactor of the last co-current contacting system;

dispersing said droplets into a gas stream received from a previous co-current contacting system;

5 in the mass transfer section of the co-current contactor of the last co-current contacting system, providing a mixed, two-phase flow having a vapor phase and a liquid phase;

in the separation system of the co-current contactor of the last co-current contacting system, separating the vapor phase from the liquid phase of the mixed, two-phase flow;

sending the vapor phase of the mixed, two-phase flow to the reflux drum; and

10 using the liquid phase of the mixed, two-phase flow to generate droplets in a co-current contactor of a previous co-current contacting system.

A19. The method of paragraph A18, further comprising:

cooling the vapor phase of the mixed, two-phase flow generated by the separation system of the co-current contactor of the last co-current contacting system prior to sending said vapor phase to the reflux drum.

15 A20. A fractionation system for removing heavy hydrocarbons in a gas stream, comprising: a feed gas inlet through which a feed gas stream is introduced, the feed gas comprising a natural gas stream;

a stripping section configured to receive a predominantly liquid phase of the feed gas stream;

20 first and second co-current contacting systems located in-line within a pipe, the first co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, each of the first and second co-current contacting systems comprising:

25 a co-current contactor including a droplet generator and a mass transfer section, the droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and the mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase, wherein the droplet generator includes

an annular support ring securing the droplet generator in-line within the pipe;

30 a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes; and

a gas entry cone supported by the plurality of spokes and configured to allow

a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

5 a second portion of the gas stream to flow around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream; and

a separation system configured to separate the vapor phase from the liquid phase;

10 wherein the vapor phase of the co-current contactor in the first co-current contacting system comprises the gas stream for the co-current contactor in the second co-current contacting system, and wherein the liquid phase of the co-current contactor in the second co-current contacting system comprises the liquid from which droplets are generated in the co-current contactor of the first co-current contacting system;

15 an in-line flash separator arranged to receive the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the first co-current contacting system, the in-line flash separator configured to separate liquids from the predominantly vapor phase; and

a flash reflux line connected to the in-line flash separator and to the stripping section, 20 the flash reflux line configured to convey liquids separated from the predominantly vapor phase in the in-line flash separator to the stripping section.

B1. A fractionation system for removing heavy hydrocarbons in a gas stream, comprising: a feed gas inlet through which a feed gas stream is introduced;

a stripping section configured to receive a predominantly liquid phase of the feed gas 25 stream; and

a co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, the co-current contacting system comprising:

a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle including a plurality of substantially 30 parallel contacting units, each of the plurality of contacting units having

a droplet generator and a mass transfer section, each droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section configured to provide a mixed, two-

phase flow having a vapor phase and a liquid phase, and

a separation system configured to separate the vapor phase from the liquid phase; and

an inlet manifold configured to distribute the liquid to each droplet generator of the plurality of contacting units;

wherein a concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units.

B2. The fractionation system of paragraph B1, wherein the co-current contacting system is a first co-current contacting system in a plurality of co-current contacting systems, the plurality of co-current contacting systems including additional co-current contacting systems arranged in series with the first co-current contacting system, each of the additional co-current contacting systems having a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of each of the additional co-current contacting systems including a plurality of substantially parallel contacting units having

a droplet generator and a mass transfer section, each droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase, and

a separation system configured to separate the vapor phase from the liquid phase; and

an inlet manifold configured to distribute the liquid to each droplet generator of the plurality of contacting units;

wherein the vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems, and wherein the liquid phase of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in one of

the first co-current contacting system, and

the first of the additional co-current contacting systems.

B3. The fractionation system of paragraph B2, wherein the additional co-current contacting systems includes a last co-current contacting system; and

a reflux drum configured to receive a vapor phase from the last co-current contacting

system and separate a reflux liquid from said vapor phase;

wherein the last co-current contacting system comprises

5 a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of the last co-current contacting system including a plurality of substantially parallel contacting units, each of the plurality of contacting units having a droplet generator and a mass transfer section, the droplet generator configured to generate droplets from the reflux liquid and to disperse the droplets into a gas stream received from one of the plurality of co-current contacting systems arranged previously in series with the last co-current contacting system, and
10 the mass transfer section configured to provide a mixed, two-phase flow having said vapor phase and a liquid phase; and

a separation system configured to separate said vapor phase from the liquid phase, wherein said vapor phase is sent to the reflux drum and the liquid phase comprises the liquid from which droplets are generated in a co-current contacting system of another of the plurality
15 of co-current contacting systems.

B4. The fractionation system of paragraph B3, further comprising a reflux cooler situated between the last co-current contacting system and the reflux drum, the reflux cooler configured to cool the vapor phase of the last co-current contacting system prior to being sent to the reflux drum.

20 B5. The fractionation system of paragraph B2, wherein the vessel is a first vessel, and further comprising one or more additional vessel arranged in series or in parallel to the first vessel, each of the one or more additional vessels having disposed therein one or more additional co-current contacting systems being arranged in parallel within the respective vessel.

25 B6. The fractionation system of paragraph B1, wherein at least one of the droplet generators in the plurality of contacting units in the compact contacting bundle comprises:

an annular support ring securing the droplet generator in-line within the pipe;

a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes; and

30 a gas entry cone supported by the plurality of spokes and configured to allow

a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

a second portion of the gas stream to flow around the gas entry cone and

between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream.

B7. The fractionation system of paragraph B6, wherein a downstream portion of the gas entry cone comprises a blunt ended cone.

5 B8. The fractionation system of paragraph B6, wherein a downstream portion of the gas entry cone comprises a tapered ended cone.

B9. The fractionation system of paragraph B1, further comprising a flash separator arranged to receive the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the co-current contacting system, the flash separator configured
10 to separate liquids from the predominantly vapor phase.

B10. The fractionation system of paragraph B9, further comprising a flash reflux line connected to the flash separator and to the stripping section, the flash reflux line configured to convey liquids separated from the predominantly vapor phase in the flash separator to the stripping section.

15 B11. The fractionation system of paragraph B9, wherein the flash separator comprises a cyclonic separator.

B12. The fractionation system of paragraph B9, further comprising an agglomerator situated at an input of the flash separator.

B13. The fractionation system of paragraph B1, wherein the separation system of the co-current contacting system comprises a cyclonic separator.
20

B14. The fractionation system of any of paragraphs B1-B13, wherein the feed gas stream comprises a natural gas stream, and wherein the heavy hydrocarbons comprise at least one of propane, butane, hexane, and heptane.

B15. A method of removing heavy hydrocarbons in a gas stream, comprising:
25 introducing a feed gas stream into a feed gas inlet;
receiving a predominantly liquid phase of the feed gas stream into a stripping section;
receiving a predominantly vapor phase of the feed gas stream into a co-current contacting system including a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle including a plurality of
30 substantially parallel contacting units, each of the plurality of contacting units having a droplet generator and a mass transfer section, and a separation system arranged in-line within a pipe;
distributing the liquid to each droplet generator of the plurality of contacting units;
using each droplet generator, generating droplets from a liquid and dispersing the

droplets into a gas stream;

in each mass transfer section, providing a mixed, two-phase flow having a vapor phase and a liquid phase; and

in each separation system, separating the vapor phase from the liquid phase;

5 wherein a concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units.

10 B16. The method of paragraph B15, wherein the co-current contacting system is a first co-current contacting system in a plurality of co-current contacting systems, the plurality of co-current contacting systems including additional co-current contacting systems arranged in series with the first co-current contacting system, the method further comprising:

15 successively flowing the vapor phase of the first co-current contacting system through each of the additional co-current contacting systems, each of the additional co-current contacting systems having a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of each of the additional co-current contacting systems including a plurality of substantially parallel contacting units having

20 a droplet generator and a mass transfer section, each droplet generator generating droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section providing a mixed, two-phase flow having a vapor phase and a liquid phase, and

a separation system that separates the vapor phase from the liquid phase;

and

25 an inlet manifold that distributes the liquid to each droplet generator of the plurality of contacting units;

wherein the vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems, and wherein the liquid phase of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in one of

30 the first co-current contacting system, and

the first of the additional co-current contacting systems.

B17. The method of paragraph B15, wherein each droplet generator in the plurality of contacting units includes an annular support ring securing the droplet generator in-line within

the respective pipe, a plurality of spokes extending from the annular support ring, and a gas entry cone supported by the plurality of spokes, the method further comprising:

flowing a liquid stream through liquid channels disposed in the annular support stream, through the plurality of spokes, and out of injection orifices disposed on the plurality of spokes;

5 and

flowing a first portion of a gas stream through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

flowing a second portion of the gas stream around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first
10 portion of the gas stream.

B18. The method of paragraph B15, further comprising:

receiving the predominantly vapor phase of the feed gas stream in a flash separation system prior to sending the predominantly vapor phase through the co-current contacting system; and

15 separating liquids from the predominantly vapor phase in the flash separation system.

B19. The method of paragraph B18, further comprising:

conveying liquids separated from the predominantly vapor phase in the flash separation system to the stripping section via a flash reflux line.

B20. The method of paragraph B19, further comprising:

20 feeding the predominantly vapor phase of the feed gas stream into an agglomerator prior to the predominantly vapor phase of the feed gas stream being received by the flash separation system.

B21. The method of paragraph B15, wherein the co-current contacting system is a first co-current contacting system in a plurality of co-current contacting systems arranged in series, the
25 plurality of co-current contacting systems including the first co-current contacting systems and a last co-current contacting system that has a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of the last co-current contacting system including a plurality of substantially parallel contacting units, each of the plurality of contacting units of the last co-current contacting system having a droplet
30 generator and a mass transfer section;

in a reflux drum, separating a vapor phase of the last co-current contacting system from a reflux liquid;

generating droplets from the reflux liquid in the droplet generators of the contacting

units of the last co-current contacting system;

dispersing said droplets into a gas stream received from a previous co-current contacting system;

5 in each mass transfer section of the plurality of contacting units of the last co-current contacting system, providing a mixed, two-phase flow having a vapor phase and a liquid phase;

in each separation system of the plurality of contacting units of the last co-current contacting system, separating the vapor phase from the liquid phase of the mixed, two-phase flow;

sending the vapor phase of the mixed, two-phase flow to the reflux drum; and

10 using the liquid phase of the mixed, two-phase flow to generate droplets in a co-current contactor or contacting units of a previous co-current contacting system.

B22. The method of paragraph B21, further comprising:

cooling the vapor phase of the mixed, two-phase flow generated by the separation system of the co-current contactor of the last co-current contacting system prior to sending said
15 vapor phase to the reflux drum.

B23. A fractionation system for removing heavy hydrocarbons in a gas stream, comprising:

a feed gas inlet through which a feed gas stream is introduced, the feed gas comprising a natural gas stream;

20 a stripping section configured to receive a predominantly liquid phase of the feed gas stream;

a plurality of co-current contacting systems connected in series and including a first co-current contacting system and additional co-current contacting systems, the first co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, each of the plurality of co-current contacting systems comprising:

25 a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle including a plurality of substantially parallel contacting units, each of the plurality of contacting units having a droplet generator and a mass transfer section, the droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and the mass
30 transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase, wherein at least one of the droplet generators includes

an annular support ring securing the droplet generator in-line within the pipe;

a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes; and

5 a gas entry cone supported by the plurality of spokes and configured to allow

a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

10 a second portion of the gas stream to flow around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream; and

a separation system configured to separate the vapor phase from the liquid phase;

wherein the vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems, and wherein the liquid phase
15 of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in one of

the first co-current contacting system, and

the first of the additional co-current contacting systems;

20 an in-line flash separator arranged to receive the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the first co-current contacting system, the in-line flash separator configured to separate liquids from the predominantly vapor phase; and

25 a flash reflux line connected to the in-line flash separator and to the stripping section, the flash reflux line configured to convey liquids separated from the predominantly vapor phase in the in-line flash separator to the stripping section.

[0077] While the present techniques can be susceptible to various modifications and alternative forms, the examples described above are non-limiting. It should again be understood that the techniques is not intended to be limited to the particular embodiments disclosed herein. Indeed, the present techniques include all alternatives, modifications, and
30 equivalents falling within the true spirit and scope of the appended claims.

CLAIMS

1. A fractionation system for removing heavy hydrocarbons in a gas stream, comprising:
a feed gas inlet through which a feed gas stream is introduced;

5 a stripping section configured to receive a predominantly liquid phase of the feed gas stream; and

a co-current contacting system configured to receive a predominantly vapor phase of the feed gas stream, the co-current contacting system comprising:

10 a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle including a plurality of substantially parallel contacting units, each of the plurality of contacting units having

15 a droplet generator and a mass transfer section arranged in-line within a pipe, each droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase, and

a separation system configured to separate the vapor phase from the liquid phase; and

20 an inlet manifold configured to distribute the liquid to each droplet generator of the plurality of contacting units;

wherein a concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units; and further comprising:

25 a flash separator arranged to receive the predominantly vapor phase of the feed gas stream prior to said predominantly vapor phase being sent through the co-current contacting system, the flash separator configured to separate liquids from the predominantly vapor phase; and

30 a flash reflux line connected to the flash separator and to the stripping section, the flash reflux line configured to convey liquids separated from the predominantly vapor phase in the flash separator to the stripping section.

2. The fractionation system of claim 1, wherein the co-current contacting system is a first

co-current contacting system in a plurality of co-current contacting systems, the plurality of co-current contacting systems including additional co-current contacting systems arranged in series with the first co-current contacting system, each of the additional co-current contacting systems having a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of each of the additional co-current contacting systems including a plurality of substantially parallel contacting units having

a droplet generator and a mass transfer section, each droplet generator configured to generate droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section configured to provide a mixed, two-phase flow having a vapor phase and a liquid phase, and

a separation system configured to separate the vapor phase from the liquid phase; and

an inlet manifold configured to distribute the liquid to each droplet generator of the plurality of contacting units;

wherein the vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems, and wherein the liquid phase of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in one of

the first co-current contacting system, and

the first of the additional co-current contacting systems.

3. The fractionation system of claim 2, wherein the additional co-current contacting systems includes a last co-current contacting system; and

a reflux drum configured to receive a vapor phase from the last co-current contacting system and separate a reflux liquid from said vapor phase;

wherein the last co-current contacting system comprises

a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of the last co-current contacting system including a plurality of substantially parallel contacting units, each of the plurality of contacting units having a droplet generator and a mass transfer section, the droplet generator configured to generate droplets from the reflux liquid and to disperse the droplets into a gas stream received from one of the plurality of co-current contacting systems arranged previously in series with the last co-current contacting system, and

the mass transfer section configured to provide a mixed, two-phase flow having said vapor phase and a liquid phase; and

a separation system configured to separate said vapor phase from the liquid phase, wherein said vapor phase is sent to the reflux drum and the liquid phase comprises the liquid from which droplets are generated in a co-current contacting system of another of the plurality of co-current contacting systems.

4. The fractionation system of claim 3, further comprising a reflux cooler situated between the last co-current contacting system and the reflux drum, the reflux cooler configured to cool the vapor phase of the last co-current contacting system prior to being sent to the reflux drum.

5. The fractionation system of claim 2, wherein the vessel is a first vessel, and further comprising one or more additional vessel arranged in series or in parallel to the first vessel, each of the one or more additional vessels having disposed therein one or more additional co-current contacting systems being arranged in parallel within the respective vessel.

6. The fractionation system of any of claims 1 to 5, wherein at least one of the droplet generators in the plurality of contacting units in the compact contacting bundle comprises:

an annular support ring securing the droplet generator in-line within the pipe;

a plurality of spokes extending from the annular support ring, the annular support ring having a plurality of liquid channels configured to allow a liquid stream to flow through the plurality of spokes and out of injection orifices disposed on the plurality of spokes; and

a gas entry cone supported by the plurality of spokes and configured to allow

a first portion of a gas stream to flow through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

a second portion of the gas stream to flow around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream.

7. The fractionation system of claim 6, wherein a downstream portion of the gas entry cone comprises a blunt ended cone.

8. The fractionation system of claim 6, wherein a downstream portion of the gas entry

cone comprises a tapered ended cone.

9. The fractionation system of any of claims 1 to 8, wherein the flash separator comprises a cyclonic separator.

5

10. The fractionation system of any of claims 1 to 9, further comprising an agglomerator situated at an input of the flash separator.

11. The fractionation system of any of claims 1 to 10, wherein the separation system of the co-current contacting system comprises a cyclonic separator.

10

12. The fractionation system of any of claims 1 to 13, wherein the feed gas stream comprises a natural gas stream, and wherein the heavy hydrocarbons comprise at least one of propane, butane, hexane, and heptane.

15

13. A method of removing heavy hydrocarbons in a gas stream, comprising:
introducing a feed gas stream into a feed gas inlet;
receiving a predominantly liquid phase of the feed gas stream into a stripping section;
receiving a predominantly vapor phase of the feed gas stream into a co-current
20 contacting system comprising a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle including a plurality of substantially parallel contacting units, each of the plurality of contacting units having a droplet generator and a mass transfer section, and a separation system arranged in-line within a pipe;
distributing the liquid to each droplet generator of the plurality of contacting units;
25 using each droplet generator, generating droplets from a liquid and dispersing the droplets into a gas stream;
in each mass transfer section, providing a mixed, two-phase flow having a vapor phase and a liquid phase; and
in each separation system, separating the vapor phase from the liquid phase;
30 wherein a concentration of heavy hydrocarbons in the vapor phase provided by each mass transfer section of the plurality of contacting units is lower than a concentration of heavy hydrocarbons in the liquid phase provided by each mass transfer section of the plurality of contacting units;

receiving the predominantly vapor phase of the feed gas stream in a flash separation system prior to sending the predominantly vapor phase through the co-current contacting system;

separating liquids from the predominantly vapor phase in the flash separation system;
5 and
conveying liquids separated from the predominantly vapor phase in the flash separation system to the stripping section via a flash reflux line.

14. The method of claim 13, wherein the co-current contacting system is a first co-current contacting system in a plurality of co-current contacting systems, the plurality of co-current contacting systems including additional co-current contacting systems arranged in series with the first co-current contacting system, the method further comprising:

successively flowing the vapor phase of the first co-current contacting system through each of the additional co-current contacting systems, each of the additional co-current contacting systems having a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of each of the additional co-current contacting systems including a plurality of substantially parallel contacting units having

a droplet generator and a mass transfer section, each droplet generator generating droplets from a liquid and to disperse the droplets into a gas stream, and each mass transfer section providing a mixed, two-phase flow having a vapor phase and a liquid phase, and

a separation system that separates the vapor phase from the liquid phase;
and

an inlet manifold that distributes the liquid to each droplet generator of the plurality of contacting units;

wherein the vapor phase of the first co-current contacting system comprises the gas stream for a first of the additional co-current contacting systems, and wherein the liquid phase of a second of the additional co-current contacting systems comprises the liquid from which droplets are generated in one of

the first co-current contacting system, and
the first of the additional co-current contacting systems.

15. The method of claim 13 or 14, wherein each droplet generator in the plurality of

contacting units includes an annular support ring securing the droplet generator in-line within the respective pipe, a plurality of spokes extending from the annular support ring, and a gas entry cone supported by the plurality of spokes, the method further comprising:

5 flowing a liquid stream through liquid channels disposed in the annular support ring, through the plurality of spokes, and out of injection orifices disposed on the plurality of spokes; and

 flowing a first portion of a gas stream through a hollow section of the gas entry cone and through gas exit slots included in the plurality of spokes, and

10 flowing a second portion of the gas stream around the gas entry cone and between the plurality of spokes, wherein the second portion of the gas stream is separate from the first portion of the gas stream.

16. The method of any of claims 13 to 15, further comprising:

15 feeding the predominantly vapor phase of the feed gas stream into an agglomerator prior to the predominantly vapor phase of the feed gas stream being received by the flash separation system.

17. The method of any of claims 13 to 16, wherein the co-current contacting system is a first co-current contacting system in a plurality of co-current contacting systems arranged in series, the plurality of co-current contacting systems including the first co-current contacting systems and a last co-current contacting system that has a compact contacting bundle disposed within a vessel that forms a unitary pressure boundary, the compact contacting bundle of the last co-current contacting system including a plurality of substantially parallel contacting units, each of the plurality of contacting units of the last co-current contacting system having a droplet generator and a mass transfer section;

20

25

 in a reflux drum, separating a vapor phase of the last co-current contacting system from a reflux liquid;

 generating droplets from the reflux liquid in the droplet generators of the contacting units of the last co-current contacting system;

30 dispersing said droplets into a gas stream received from a previous co-current contacting system;

 in each mass transfer section of the plurality of contacting units of the last co-current contacting system, providing a mixed, two-phase flow having a vapor phase and a liquid phase;

in each separation system of the plurality of contacting units of the last co-current contacting system, separating the vapor phase from the liquid phase of the mixed, two-phase flow;

sending the vapor phase of the mixed, two-phase flow to the reflux drum; and

5 using the liquid phase of the mixed, two-phase flow to generate droplets in the contacting units of a previous co-current contacting system.

18. The method of claim 17, further comprising:

10 cooling the vapor phase of the mixed, two-phase flow generated by the separation system of the contacting units of the last co-current contacting system prior to sending said vapor phase to the reflux drum.