



(51) International Patent Classification:
E21B 33/04 (2006.01) *E21B 33/047* (2006.01)

Texas 77429 (US). **REED, Ken, M.** [US/US]; 12306
Arkansas Post Ln., Humble, Texas 77346 (US).

(21) International Application Number:
PCT/US2010/020810

(74) Agent: **SWANSON, Tait, R.**; 7915 FM 1960 West, Suite
330, Houston, TX 77070 (US).

(22) International Filing Date:
12 January 2010 (12.01.2010)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/153,189 17 February 2009 (17.02.2009) US

(71) Applicant (*for all designated States except US*):
CAMERON INTERNATIONAL CORPORATION
[US/US]; 1333 W Loop South, Suite 1700, Houston,
Texas 77027 (US).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **VANDERFORD,
Delbert, E.** [US/US]; 12311 Pine Glen Ln., Cypress,

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,

[Continued on next page]

(54) Title: POSITIVE LOCKED SLIM HOLE SUSPENSION AND SEALING SYSTEM WITH SINGLE TRIP DEPLOYMENT AND RETRIEVABLE TOOL



(57) Abstract: A tool is provided for installing a mandrel in a wellhead assembly. The tool includes an assembly having multiple independently translatable and rotatable members. The tool includes an inner member disposed in an inner sleeve. The inner member may be disposed in a first position and second position, such that in the first position the inner sleeve freely rotates and in the second position rotation of the inner sleeve causes rotation of the inner member. An outer sleeve is disposed over the inner sleeve and may be coupled to a hold down ring. The inner member may be coupled to mandrel. The tool may be inserted into a wellhead assembly and the outer rotated to engage the hold down ring, the inner and outer sleeve may be translated axially to allow rotation of the inner member to disengage the tool from the mandrel.



TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

— *with international search report (Art. 21(3))*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*