


(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
19 November 2009 (19.11.2009)(10) International Publication Number
WO 2009/138849 A1

- (51) International Patent Classification:
E21B 34/04 (2006.01) *E21B 34/16* (2006.01)
- (21) International Application Number:
PCT/IB2009/005567
- (22) International Filing Date:
12 May 2009 (12.05.2009)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20082217 14 May 2008 (14.05.2008) NO
- (71) Applicant (for all designated States except US): **VETCO GRAY SCANDINAVIA AS** [NO/NO]; P.O. Box 423, N-1302 Sandvika (NO).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GRIMSETH, Tom** [NO/NO]; Giskehagen 25, N-0376 Oslo (NO). **BORCH-GREVINK, Christian** [NO/NO]; Bjartunv. 3, N-1405 Langhus (NO). **FLIDH, Jon** [NO/NO]; Storgata 11, N-3050 Mjøndalen (NO). **PETERSEN, Jan Olav** [NO/NO]; Hartmanns vei 33 C, 0284 Oslo (NO).
- (74) Agent: **VETCO GRAY SCANDINAVIA AS**; c/o Fransson, Henrik, Forskargränd 8, B194, S-72226 Västerås (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
- with international search report (Art. 21(3))
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: A SUB SEA HYBRID VALVE ACTUATOR SYSTEM AND METHOD



(57) Abstract: A sub sea valve actuator system is disclosed, comprising a piston (25) and cylinder (H) assembly and a return spring (29) arranged in an actuator housing (21, 22), a hydraulic pump (3) and electric motor (1) assembly associated with 5 the piston (25) and cylinder (11) assembly, hydraulic flow lines (42, 43) for hydraulic medium driving the piston and cylinder in relative displacement against the force of the return spring (29). The valve actuator system is characterized in that detection means arranged for detecting an end-of-stroke position of the piston (25) and cylinder (11) assembly, said detection means is at 0 least one of: a motor current monitoring circuit unit (94); a hydraulic medium pressure sensor unit (98); a position sensor unit (99); and a linear variable differential transformer unit (100), wherein an electromechanical arresting mechanism is arranged to be energized for releasably arresting the return spring in a compressed state in result of the detected end-of-stroke position. A method 5 for operation of a sub sea valve actuator system is likewise disclosed, by which an end-of-stroke position for a piston (25) and cylinder (11) assembly in a sub sea valve actuator system can be determined.