

SYSTEM AND METHOD FOR THE COUPLING OF A HEAD FRAME

Field of Invention

The invention relates to spreaders and head frames, or head blocks, used for the transportation of shipping containers. In particular, the invention relates to systems and methods for coupling a head frame and spreader prior to engaging a container.

Background

Head blocks or head frames are mechanical devices having sheaves on an upper side and engagement devices, such as twist locks or connecting pins, on a lower side. The engagement devices are intended to come into contact with a spreader so as to couple the head frame and spreader. This is typically used for swapping spreaders for maintenance purposes. Other purposes include switching between a twin spreader arrangement to a single spreader arrangement such as for a system disclosed in WO2006/083230, WO2008/136766 and WO2008/136767, the contents of which are incorporated herein by reference. The pin or twist lock connections allow a spreader to be attached to the head frame or removed from it for maintenance or other purposes.

Unlike the twist lock arrangements used for a spreader to engage a container, the twist lock and pin connection of a head frame are normally engaged manually. This manual engagement, as compared to a powered arrangement, is a reflection of the frequency with which a spreader is removed from a head frame. Whilst a spreader will engage many containers in a single day, maintenance may occur only once every several months. Consequently, there is no pressing need to include a powered system in order to

engage and disengage the twist locks or other engagement devices coupling a head frame to a spreader.

In any event, even if the engagement device was automated at some point, it would be
5 necessary for a manual operation as the electrical connection between the head frame and the spreader also needs to be disconnected and reconnected on engagement which again must be manually perform.

Summary of Invention

10 In general terms, the present invention provides for an automated system and method for the coupling and connection of a head frame to a spreader.

In a first aspect, the invention provides a system for mounting a head frame to a spreader comprising: a sheave assembly connecting the head frame to a crane so as to
15 permit the lowering of said head frame; mutually cooperating engagement devices for coupling the head frame and the spreader; an actuator arranged to connect mutually engageable transmission connectors on the head frame and spreader; and; a registration device for registering the coupling of the head frame and the spreader; wherein the registration device is arranged to prevent engagement of the transmission connector
20 until said head frame and spreader are coupled.

In a second aspect, the invention provides a method for mounting a head frame to a spreader comprising the steps of: lowering the head frame into contact with the spreader; operating engagement devices and so coupling the head frame to the spreader;

activating an actuator to connect mutually engageable power supply connectors on the head frame and spreader so as to provide a power communication between said head frame and spreader.

- 5 In a third aspect, accordingly, the invention provides for registering the coupling of the head frame and spreader so as to permit the connection of a power supply data transmission or telecommunication.

In a fourth aspect, the invention provides a spreader assembly comprising a head frame
10 comprising a main frame and a sub frame; a spreader mounted to said sub frame; said main frame and sub frame having mutually engageable connecting members in sliding engagement; wherein said mutually engageable connecting members provide relative longitudinal movement between said head frame and spreader.

- 15 Whilst maintenance may be infrequent, the growing use of twin spreaders for a single head frame is a significant segment of the industry and therefore the need to switch between single spreaders and twin spreaders is a pressing need. Providing an automated or semi-automated process to this increasingly more common procedure has economic advantage through reduced downtime on the capital equipment.

20

The connectors may provide electrical, hydraulic, data or telecommunication transmission. In operation, they may include a plug, actuated by a cylinder to project linearly to engage a socket. The plug and bell mouth socket may be properly engaged and guided before the 2 halves of the multi-pin connectors in the two parts start to

engage. There may be sufficient clearance for the socket to move laterally (up-and-down and left-and-right) and aligned with the plug when engaged. The close tolerance between the inner diameter of the socket sleeve and plug may ensure good angular tolerance and the key and keyway on the plug and socket respectively ensure the rotational alignment of the connectors.

Other design features may include:

1. A rain-cover above the connectors to prevent the ingress of rain water.
2. The twist lock and auto-connector may be electrically actuated instead of hydraulic actuator so that a hydraulic power pack is not required on the head frame.

Brief Description of Drawings

It will be convenient to further describe the present invention with respect to the accompanying drawings that illustrate possible arrangements of the invention. Other arrangements of the invention are possible and consequently the particularity of the accompanying drawings is not to be understood as superceding the generality of the preceding description of the invention.

20

Figures 1 to 6 are sequential elevation views of a single spreader application according to one embodiment of the present invention;

Figures 7 to 12 are sequential elevation views of a twin spreader application according to a further embodiment of the present invention;

Figures 13 to 17 are sequential elevation views of a twin spreader application according to a further embodiment of the present invention;

Figures 18 to 20 are various views of mutually engageable transmission connectors according to a still further embodiment of the present invention;

5 Figures 21A to 21C are various views of a head frame to spreader coupling according to one embodiment of the present invention;

Figures 22A to 22B are various views of the head frame to spreader coupling of Figure 21A and;

Figures 23A to 23B are various views of the head frame to spreader coupling of Figure
10 21A.

Detailed Description

Figures 1 to 6 show an application where a single spreader corresponds to a single head
15 frame with the transmission connector, or connector assembly, corresponding to the single design. An alternative design, as shown in Figures 7 to 12, corresponds to an application using two spreaders and two head frames where under some circumstances it may be preferable to switch between a single and twin spreader arrangement. A still further design, as shown in Figures 13 to 17, involves a single head frame with movable
20 sheaves in order to engage either a single spreader or two spreaders.

Considering the single spreader arrangement shown in Figures 1 to 6, we see a head frame 5 attached to a crane (not shown) through cables 35 and sheaves 40 so as to raise

and lower the head frame 5 and subsequently raise and lower the spreader, after coupling.

The spreader 10 may be resting on the ground or on a frame ready for coupling with the head frame 5. Characteristic of the head frame 5 are engagement devices 15, in this case twist locks 15, which are engageable with apertures 20 in the spreader 10. The spreader 10 further has engagement devices 45 for subsequent engagement of a shipping container.

The present invention further provides for mutually engageable connectors 25, 30 mounted on the head frame 5 and spreader 10. One such mutually engageable electrical connector may include 3-phase 415V power supply, signal and communication plug and socket. Alternatively, the connectors may be inter-engageable hydraulic connection for a hydraulic power pack. Figures 18 to 20 show a further embodiment of a connector assembly according to one embodiment of the present invention.

In this case Figure 18 shows a male connector 220 of the transmission connector. An actuator 225 is arranged to project a plug 230 from an aperture 245 so as to be engageable with the corresponding female connector. The plug 230 includes a key 250 to engage with the female connector on projecting from an orifice plate 240. The plug 230 includes individual pins 235 which may be arranged to transmit any or all of electrical power, telecommunication or data subject to the purpose of the transmission connector. The female connector 255 includes the socket 260 with the pins inserted into receiving recesses 261. Surrounding the socket 260 is a bell mouth spigot 265 which is

sized to provide a tolerance for receiving the male plug 230. As the male plug enters the spigot 265, it reaches a cylindrical portion 270 which prevents lateral movement of the male plug 230 to further assist in alignment. The spigot 265 is mounted to a plate 280 which is also movable so as to permit a self alignment between the plugs 230, 260
5 and so allow for a relatively small misalignment such as 10 to 15mm. It will be appreciated that the bell mouth 265 and mounting plate 280 may also be arranged to accommodate a larger tolerance or misalignment.

The key 250 of the male plug 230 is arranged to fit within a recess 275 within the spigot
10 265 and so prevent rotational misalignment of the plug so as to ensure the individual plugs 235 correspond to the receiving recesses 261. To this end the key recess 275 is flared outwards to receive the key 250 and gradually align the key into the recess 275.

Figure 20 shows the opposite side of the female connector 255 showing the end portion of the plug recesses 261. In this case the plug recesses feed into individual plugs which
15 can then be plugged into a flexible cable connecting the transmission connector.

Returning to the application of the transmission connector to the head frame/spreader, Figure 2 shows a male portion 60 of a connector 25 mounted to the head frame 5, which is arranged to engage the female connector, or socket 65, mounted to the spreader. It
20 will be appreciated that the plug may instead be mounted to the spreader and the socket mounted to the head frame, and still fall within the present invention.

The head frame connector 25 comprises an actuator 50 arranged to linearly project and retract a plug 60 mounted within a housing 55. The actuator 50 is further arranged to

retract and extend the plug 60 along an axis 56 representing the centerline of the plug 60. Corresponding to the head frame connector 25 is a spreader connector 30 having a socket 65 with a centerline 64 which is intended to align with the centerline 56 of the head frame connector 25. The spreader connector 30 further includes a bell mouth
5 spigot or sleeve 70 which increases the diameter of the socket to receive the plug 60 so that misalignment of the male and female connectors is accommodated.

Figure 3 shows the next step in the process with the twist lock having be actuated, and so locking the head frame 5 and spreader 10 with Figure 4 showing an alignment of the
10 centerlines 56, 64 of the connectors 25, 30. At this point a registration device (not shown) will be activated so as to communicate to the actuator that connection of the plug to the socket is permissible. At this point, the actuator may automatically operate so as to project the plug to engage the socket. Alternatively, the registration device may operate to allow manual operation of the connector. That is, the registration device may
15 act as a "GO NO-GO" such that the actuator may be prevented from being operated until the registration device registers the engagement of the head frame and spreader. On such registration, manual operation may then be permissible, with the connector in standby mode to receive the manual instruction to commence engagement. The registration device may include a limit switch to register the coupling of the head frame
20 and spreader. It may also include a control system for detecting the coupling and operate the actuator automatically.

Figures 5 and 6 show the activation of the actuator whereby the plug 60 has extended as a result of the ram 51 extending from the actuator 50.

Figure 6 demonstrates one possible arrangement whereby the centerlines 56, 64 are not perfectly aligned but are within the required tolerance. Here the plug may fit within the bell mouth 70 with the plug at an extreme upper portion 75 leaving a gap 80 for the bell mouth. Thus the mounting plate to which the bell mouth is mounted will move laterally to accommodate this misalignment of the centerline 56, 64 and still maintain an electrical, telecommunication or data connection between the head frame and spreader.

Figures 7 to 12 show a further embodiment of a multiple spreader system. Figure 7 in particular shows an expandable head frame arrangement having two head frames 80, 85 in a retracted position so as to engage with a single spreader 90. As before, the first head frame 80 includes twist locks 106 to engage with apertures 121, with the second head frame 85 having twist lock 115 to engage with a second set of apertures 120. As before the spreader includes a connector portion 110 which is engageable with a connector portion 105 mounted to the first head frame 80. Where this embodiment differs from the embodiment of Figure 1 is having on the second head frame 85 a second connector portion 100. In this arrangement, the two connected portions 100, 105 are capable of engaging connected portions associated with two spreaders. In the embodiment shown in Figure 7 however, only the connected portion 105 associated with the first head frame 80 is required for the single spreader application.

Figure 8 shows the next step in the engagement whereby the twist locks 106, 115 have coupled to the corresponding apertures 120, 121 so as to couple the head frame to the

spreader. As will be seen the two connected portions 105, 110 are now aligned ready for engagement.

Figure 9 shows a further step whereby the first connected portion 105 of the head frame
5 has now projected the plug into the socket of the connected portion 110 of the spreader
so as to provide a connection for the power supply, data or telecommunication signal
between the head frame and the spreader. In an alternative arrangement, the head frames
80, 85 are expandable by an expanding assembly 125 so as to mount distinct spreaders
90, 130. It will be noted that each of the spreaders 90, 130 have connected portions 110,
10 135 for engagement with the connected portion or plugs mounted to the respective head
frames 80, 85.

Figures 11 and 12 show the subsequent steps following coupling of the head frames to
the spreaders whereby the connected portions are now aligned due to the locking of the
15 head frame to spreader with Figure 12 in particular showing the extension of the
actuator so as to engage the plug with the socket 105, 110 for the first head frame 80
engaged with the first spreader 90. Correspondingly, the second head frame 85 engaged
with the second spreader 130 involves connection of the second plug 100 with the
second socket 135. Thus the embodiments shown in Figure 9 and Figure 12 show the
20 uses of the invention where the head block or head frame can accommodate coupling
with a single spreader and further with two spreaders.

Figures 13 to 17 show a further embodiment of the present invention whereby a
master/slave arrangement is adopted for the spreaders. In this case, a master spreader

160 to which is mounted a master head frame 175 is used for a single spreader arrangement. In this arrangement, two sets of sheaves 195, 200 are mounted to the master head frame 175. Power is provided to the master head frame/spreader and so the transmission connector according to the present invention is required when coupling
5 to a slave head frame/spreader. Figure 14 shows the transfer arrangement from the single spreader to the double spreader arrangement. A sliding mechanism 210 moves the second sheave 195 from the master head frame 175 to the slave head frame 180. Figure 15 shows the completion of the transfer of the sheave 195 to the slave head frame 180 so as to position the male connector 190 proximate to the female connector
10 185. Figure 16 shows the movement 202 of the first sheave 200 so as to be centralized on the master head frame 175 with figure 17 showing the connection of the transmission connector 185, 190 so as to provide power, telecommunication or data connection to the slave head frame 180.

15 Thus, whilst the invention involves the transmission connection of a spreader to a head frame, in the case of Figures 13 to 17, the spreader in this case is a slave spreader 165 with the connection to the head frame being the engagement of the second sheave 195 with the slave head frame 180 so as to complete the connection of sheave/head frame/spreader. In this case the registration device is arranged to register the coupling
20 of the second sheave 195 to the slave head frame 180 and so whilst the slave head frame 180 is already mounted to the slave spreader 165, the complete connection cannot occur until the slave head frame 180 has fully coupled the second sheave 195 and so with the positioning of the second sheave 195 to the slave head frame 180, the full connection of the head frame to the spreader is therefore, achieved.

Figures 21A to 21C show an embodiment of one aspect of the present invention. Here a spreader assembly 301 comprises a head frame 300 mounted to a spreader 305. In this embodiment the head frame 300 comprises a main frame 303 and a subframe 313. The
5 main frame 303 and subframe 313 are in longitudinal sliding engagement through cooperating members 310, 315.

The head frame 300 coupling arrangement has the advantage of precisely positioning the relative positions of the head frame and spreader whilst still providing relative
10 movement between the head frame and spreader should it be required.

By way of example of the sliding engagement, Figures 22A/B and 23A/B show sequential views of the twin spreader assemblies 301, 302 of Figures 21A to C.

15 To achieve the relative offset between the adjacent spreaders 305, 335 and actuator 340 is position having one end 350 connected to the sub frame 313 of the master spreader assembly 301. The other end of 345 of the actuator 340 is connected to the master head block main frame 303. The actuator 340 is arranged to move the head block sub frame 313 and consequently the attached spreader 305 relative to head block main frame 303
20 using the sliding coupling 310, 315 between the two elements. The relative position of the head block and spreader is shown in Figures 21B and 21C in an initial position whereby the adjacent spreaders 305, 335 are level. Figures 22A and 22B show the effect on activation of the actuator 340 whereby the master spreader 305 moves 355

relative to the head block 300 creating an offset 356 between the adjacent spreaders 305, 335.

Figures 23A and 23B show the opposite movement whereby the actuator 340 is
5 retracted and so causing a relative movement 360 between the head block and spreader
and so creating an offset 361 between the adjacent spreaders.

CLAIMS

1. A spreader assembly comprising
a head frame comprising a main frame and a sub frame;
5 a spreader mounted to said sub frame;
said main frame and sub frame having mutually engageable connecting members
in sliding engagement;
wherein said mutually engageable connecting members provide relative
longitudinal movement between said head frame and spreader.
10
2. The assembly according to claim 1 wherein said connecting members are
arranged longitudinally on said main frame and sub frame such that the
sliding engagement is arranged horizontally.
- 15 3. The assembly according to claim 1 or 2 wherein the connecting members on
the main frame are articulated so as to permit an opening and closing action
so as to clamp the corresponding connecting member on said sub frame.