

Description

The present invention relates to an improved multibeam electron gun for a cathode-ray tube as disclosed in the first part of claim 1, and particularly to an electron gun having a modular Beam-Forming Region (BFR) assembly comprising a plurality of cathode assemblies, a control grid electrode and a screen grid electrode. The electrodes have aligned apertures and are attached to a common ceramic support member. The screen grid electrode is positioned relative to the control grid electrode by support means which also accurately locates the BFR assembly relative to a main focusing lens of the electron gun.

U.S. Patent US-A-4 298 818 issued to McCandless on November 3, 1981, discloses such an electron gun having a modular beam-forming region (BFR) assembly similar to that of the present invention, in that it also comprises a plurality of cathode assemblies and at least two successive electrodes including a control grid (G1) electrode and a screen grid (G2) electrode. Unlike the present invention, the successive electrodes of the patented beam-forming region are individually attached directly to metallized patterns on the surface of a common ceramic support member. The longitudinal spacing between the G1 and G2 electrodes is determined by the flange heights of the electrodes. A support bracket is embedded into the glass support rods of the electron gun in spaced relation to a main focusing lens. The screen grid electrode is welded to the support bracket to secure the modular BFR assembly in spaced relation to the main focusing lens. A drawback of the patented electron gun is that irregularities on the surface of the support ceramic or variations on the heights of the flange portions of the control grid or screen grid electrodes will cause variations in the longitudinal spacing between the successive electrodes. Proper operation of a multibeam cathode-ray tube utilizing such an electron gun requires that the spacing and alignment between the successive electrodes of the BFR assembly be accurately maintained. Apertures that are misaligned by as little as 0.0127 mm (0.5 mil) can cause distorted beam shapes and degrade the performance of the tube.

U.S. Patent US-A-4 500 808 issued to McCandless on February 19, 1985, describes an improved electron gun similar to that of U.S. Patent US-A-4 298 818 except that the screen grid electrode of the modular beam-forming region assembly comprises a composite structure including a metal support plate and three individual apertured plates. The metal support plate is brazed directly to a metallized pattern on one surface of a ceramic support member in spaced relation to a control grid

electrode which is also brazed directly to a separate metallized pattern on the same surface of the ceramic support member. The metal support plate has a window therein opposite each of the apertures in the control grid electrode. The individual apertured plates are brazed to the metal support plate and close the windows therein. Each of the apertured plates has a single electron beam-defining aperture therein which is separately aligned with one of the apertures in the G1 electrode. This structure provides more accurate alignment of the G1 and G2 electrode apertures than previous structures; however, the longitudinal spacing between the G1 and G2 electrodes continues to depend on the flatness of the surface of the ceramic member and the flange heights of the G1 and G2 electrodes. Additionally, the longitudinal spacing between the G2 electrode and the main focusing lens depends upon the thickness and flatness of the individual apertured plates brazed to the metal support plate of the G2 electrode.

An improved modular BFR assembly for an electron gun is described in US-A-4 629 934 (This document was not pre-published). The electron gun of that application includes a modular BFR assembly and a main focus lens, both of which are affixed to a pair of insulative support rods. The BFR assembly includes a plurality of cathode assemblies; a control grid electrode and a screen grid electrode. The main focus lens includes a first focusing (G3) electrode and a second focusing (G4) electrode. The cathode assemblies and the G1 and G2 electrodes are individually held in position from a common ceramic member. A transition member, having a flat first part and a second part electrically isolated from the first part, is attached to a metallized pattern formed on one surface of the ceramic member. The second part of the transition member has a flat portion brazed to the metallized pattern, and two upright portions that are substantially perpendicular to the flat portion and parallel to each other. The G1 electrode is attached to the first part of the transition member, and the G2 electrode is disposed between and attached to the upright portions of the second part of the transition member by means of a plurality of L-shaped support members. The longitudinal spacing between the G1 and G2 electrodes is set by means of a removable spacer. Each L-shaped support member has one end welded to the surface of the G2 electrode adjacent to the G3 electrode, and the other end welded to the upright support portions of the transition member. The upright support portions of the transition member permit a greater range in positioning the G2 electrode longitudinally in spaced relation to the G1 electrode than was available heretofore when each electrode was a precision formed part. The L-shaped supports allow the

G2 electrode to be narrower than the width between the upright portions of the transition member so that the G2 electrode can be laterally positioned to align the electron beam-forming apertures with the corresponding apertures in the G1 electrode. The BFR assembly of the application reduces the precision with which the G1 electrode and the surface of the ceramic member must be made, since the upright portions of the transition member provide a longitudinal tolerance not available in the prior electron guns described heretofore. A drawback of the structure, however, is that, since the BFR assembly is attached to the glass support rods by metal bead support members affixed at one end to the glass support rods and at the other end to the flat portion of the second part of the transition member, the spacing between the G2 and G3 electrodes is indirectly established with relation to the flat portion of the transition member. Thus, if the height of the G1 electrode or the flatness of the surface of the ceramic support member were to vary beyond the optimum range, corresponding variations in the location of the G2 electrode to maintain the G1 to G2 longitudinal spacing would result in an inverse variation in the G2 to G3 longitudinal spacing. The ends of the bead support members attached to the transition flange of the BFR assembly can be bent to provide the required G2 to G3 electrode spacing; however, such an expedient can cause cracking of the glass support rods or a subsequent change in G2-G3 electrode spacing as a result of the restorative force in the metal bead support members. An alternative is to provide electron guns having the bead support members attached to the glass support rods with a range of spacings between the ends of the bead support members and the G3 electrode to compensate for variations in the location of the G2 electrode. This is not practical in a high volume operation.

According to the present invention, an electron gun for a cathode-ray tube comprises the features of claim 1 comprising, among other things, a modular beam-forming region assembly and a main focusing lens which are affixed to at least two insulative support rods. The modular beam-forming region assembly includes a plurality of cathode assemblies, a control grid electrode and a screen grid electrode. The electrodes have aligned apertures therethrough for passage of a plurality of electron beams from the cathode assemblies. The cathode assemblies and the electrodes are individually held in position from a common ceramic member. The ceramic member has a first major surface and an oppositely disposed second major surface with a metallized pattern formed on at least a portion of each major surface. The control grid electrode and the screen grid electrode are at-

tached to the first major surface, and the cathode assemblies are attached to the second major surface. A transition member is disposed between the metallized pattern on the first major surface of the ceramic member and the screen grid electrode. The transition member includes a substantially flat portion attached to the metallized pattern and two upright portions substantially perpendicular to the flat portion and substantially parallel to each other. The screen grid electrode comprises at least one plate-like member disposed between the upright portions and connected thereto by a plurality of step-like support members. Each of the step-like support members includes a screen grid electrode contact portion, a bead support contact portion and a central riser portion extending between the contact portions. The screen grid electrode contact portion of each step-like support member is attached to the screen grid electrode. The screen grid electrode is longitudinally spaced from the control grid electrode, and the central riser portion of each step-like support member is attached to the upright portions of the transition member. The bead support contact portion of each step-like support member is attached to a different one of a plurality of bead support members affixed to the insulative support rods, whereby the screen grid electrode is longitudinally spaced from the main focusing lens.

In the drawings:

FIGURE 1 is a partially cut-away, side elevational view of a preferred embodiment of the inventive electron gun.

FIGURE 2 is an enlarged plan view of the BFR assembly of the electron gun taken along line 2-2 of FIGURE 1.

FIGURE 3 is a sectional view of the BFR assembly taken along line 3-3 of FIGURE 2.

FIGURE 4 is a plan view of a transition member.

FIGURE 5 is a sectional view of another BFR assembly not constructed according to the invention as disclosed in the independent claim.

As shown in FIGURE 1, an improved electron gun 10 includes a modular beam-forming region (BFR) assembly 12 secured to a pair of glass support rods 14, also called beads, by a plurality of metal bead support members 15. The modular BFR assembly 12 includes three equally spaced inline cathode assemblies 16, one for each electron beam (only one of which is shown in the view of FIGURE 1), a control grid (G1) electrode 18 and a screen grid (G2) electrode 20. Longitudinally spaced from the BFR assembly 12 is a main focusing lens comprising a first focusing (G3) electrode 22 and a second focusing (G4) electrode 24.

The first focusing electrode 22 comprises a substantially rectangularly cup-shaped lower first member 28 and a similarly shaped upper first

member 30 joined together at their open ends. The closed ends of the members 28 and 30 have three apertures therethrough, although only the center apertures are shown in FIGURE 1. The apertures in the first focusing electrode 22 are aligned with the apertures in the control and screen grid electrodes 18 and 20. The second focusing electrode 24 comprises a rectangularly cup-shaped member 32 and an apertured plate member 34. Three inline apertures also are formed in the ends of the members 32 and 34.

Each of the cathode assemblies 16 comprises a substantially cylindrical cathode sleeve 38 closed at the forward end and having an electron emissive coating (not shown) thereon. The cathode sleeve 38 is supported at its open end within a cathode eyelet 40. A heater coil 42 is positioned within the sleeve 38 in order to indirectly heat the electron emissive coating. The heater coil 42 has a pair of legs 44 which are welded to heater straps 46 which, in turn, are welded to support studs 48 that are embedded in the glass support rods 14.

The modular BFR assembly 12, shown in FIGURES 2 and 3, includes a ceramic member 50, having an alumina content of about 99%, to which the cathode assemblies 16 and the control grid and screen grid electrodes 18 and 20 are attached. The ceramic member 50 includes a first major surface 52 and an oppositely disposed substantially parallel second major surface 54. The ceramic member has a thickness of about 1.5 mm (0.06 inch). At least a portion of the first major surface 52 has metallizing patterns 56a and 56b formed thereon to permit attachment thereto of the electrodes 18 and 20, respectively. The metallized patterns 56a and 56b comprise discrete areas that are electrically isolated from each other. A plurality of electrically isolated metallizing patterns (only one of which, 56c, is shown) are provided on the second major surface 54 to permit attachment of the cathode assemblies 16 thereto. The metallizing of a ceramic member is well known in the art and needs no further explanation. The major surfaces 52 and 54 may include lands, as shown in FIGURE 3, which facilitate application of the electrically isolated metallizing patterns thereto. The control grid electrode 18 is essentially a flat plate having two parallel flanges 58 on opposite sides of the three inline, precisely spaced, beam-defining apertures 60, only one of which is shown. The screen grid electrode 20 may comprise three separate plate-like portions each of which has a beam-defining aperture 62 therethrough, or a single plate with three precisely located apertures may be used. The outer portions of the screen grid electrode 20 are designated 20a and 20b and the center portion is designated 20c. A recess 64 is formed in the surface of the screen grid electrode 20 that is

adjacent to the lower first member 28 of the first focusing electrode 22. The recess 64 provides a horizontal convergence correction for the outer electron beams to compensate for changes in focus voltage. Such structure is described in U.S. Patent US-A-4 520 292 issued to van Hekken et al. on May 28, 1985. The separate portions 20a, 20b and 20c of the screen grid electrode 20 can be individually positioned so that the apertures 62 in the screen grid electrode 20 are aligned with the corresponding apertures 60 in the control grid electrode 18.

In U.S. Patents US-A-4 298 818 and US-A-4 500 808 cited above, the control and screen grid electrodes are brazed directly to the metallized patterns on the ceramic surfaces. The brazing of a plurality of formed metal parts tends to distort at least some of the parts and introduce stress into the ceramic member. If the stress is sufficiently great, the ceramic member will crack, rendering the cathode-grid assembly unusable.

Our European Application EP-A-0 202 876 discloses a substantially flat, bimetal transition member which is brazed to the metallized pattern on the ceramic member. The control and screen grid electrodes are then welded to the transition member. The thickness of the transition member is limited to about 20% of the thickness of the ceramic member so that minimal stress is introduced into the ceramic member during brazing.

As shown in FIGURES 3 and 4 here, a first transition member 66 having a substantially flat first part 68 and a second part 70, having an L-shaped cross-section, is brazed to the metallized patterns 56a and 56b on the first major surface 52 simultaneously with the brazing of a second transition member 72 to the metallizing pattern 56c on the second major surface 54. The second part 70 of the first transition member has a substantially flat first portion 74 in contact with the metallized pattern 56b and upright portions 76 which are substantially perpendicular to the flat portion 74. The first part 68 and the second part 70 of the first transition member 66 and the second transition member 72 include each a break-away frame similar to those described in the above-cited European Application. As shown in FIG. 4, the first transition member 66 includes frame portions 78 which are connected to the first and second parts 68 and 70 by V-notched bridge regions 80. Breaking away the frame portions 78 of the first transition member 66 at the bridge regions 80 electrically isolates the first part 68 and the second part 70. As shown in FIG. 3, the second part 70 of the first transition member 66 extends along both sides of the first major surface 52 of the ceramic member 50 so that the screen grid electrode 20 can be disposed between the substantially parallel upright portions 76.

The control grid electrode 18 is welded to the first part 68 of the first transition member 66. The height of the upright portions 76 of the first transition member is sufficient to permit longitudinal variations in the locations of the screen grid electrode portions 20a, 20b and 20c to accommodate variations in the height of the control grid 18, or irregularities in the flatness of the ceramic member 50. In other words, neither the first major surface 52 of the ceramic member 50 nor the control grid electrode 18 is required to be a precision part since the plate-like screen grid electrode portions 20a, 20b and 20c can be longitudinally located by means of appropriate removable spacers (not shown) and laterally positioned to provide the desired spacing and alignment between the successive electrodes. At least two step-like support members 82 are secured to each of the screen grid electrode portions 20a, 20b and 20c, one on each side. Each of the step-like support members 82 includes a screen grid electrode contact portion 84, a bead support contact portion 86 and a central riser portion 88 of precise length, l_1 , of about 2.0 mm. The screen grid electrode contact portions 84 are attached to the plate-like portions 20a, 20b and 20c of the screen grid electrode 20. The plate-like portions 20a, 20b and 20c are disposed between the upright portions 76 of the first transition member 66. The width of the portions 20a, 20b and 20c is such that the portions can be laterally positioned between the upright portions 76 so that the apertures 82 in the screen grid electrode portions 20a, 20b and 20c can be aligned with the apertures 60 in the control grid electrode 18. Longitudinal spacing, l_2 , between the control grid electrode 18 and the screen grid electrode 20 is achieved by means of removable spacers (not shown) disposed therebetween. The central riser portions 88 are welded to the upright portions 76 to secure the screen grid electrode portions 20a, 20b and 20c in alignment with and in spaced relation to the control grid electrode 18.

In the present structure, the first and second transition members 66 and 72 comprise face-to-face laminated bimetal layers. The first transition member 66 comprises a first metal layer 90 formed from a nickel-iron alloy of 42% nickel and 58% iron. The first layer 90 has a thickness of about 0.2 mm (0.008 inch). A second metal layer 92, preferably formed of copper, has a thickness of about 0.025 mm (0.001 inch). The melting point of the copper layer 92 is about 1033°C, and the melting point of the nickel-iron layer 90 is about 1427°C. The copper layer 92 is in contact with the metallized layers 56a and 56b on the first major surface 52. The second transition member 72 also comprises a face-to-face laminated bimetal formed of a 0.2 mm thick nickel-iron layer 94 and a 0.025 mm

thick copper layer 96 which is brazed directly to the metallized layer 56c on the second major surface 54. The BFR assembly 12 is attached to the electron gun 10 by welding the bead support members 15 to the bead support contact portions 86.

With respect to FIGURE 3, the longitudinal spacing, l_2 , between the control grid electrode 18 and the screen grid electrode 20 is established by means of spacers disposed between the electrodes 18 and 20 during the welding of the central riser portions 88 of the support members 82 to the upright portions 76 of the first transition member 66. Since each of the support members 82 is formed so that the central riser portion 88 has a precise length, l_1 , measured from the top of the bead support contact portion 86 to the top of the screen grid electrode contact portion 84, the distance, l_3 , from the top of the screen grid electrode 20 to the top of the bead support contact portion 86 is also precisely fixed for each BFR assembly 12. During the beading operation in which the G3 and G4 electrodes 22 and 24 are secured to the glass support rods 14, the bead support members 15 are also affixed to the support rods 14 a precise distance from the G3 electrode 22. Thus, when the bead support contact portions 86 of the BFR assembly 12 are attached to the bead support members 15, the proper longitudinal spacing, l_4 , between the top of the G2 electrode 20 and the bottom surface of the G3 electrode 22 is established without having to bend or otherwise deform the bead support members 15.

FIGURE 5 shows a modular BFR assembly 112 that is disclosed in the above-cited U.S. Patent US-A-4629934. The BFR assembly 112 differs from the present BFR assembly 12 in that the BFR assembly 112 utilizes a plurality of L-shaped support members 182 to secure a screen grid (G2) electrode 120 to upright portions 176 of a first transition member 166. Each of the L-shaped members includes a screen grid electrode contact portion 184 and a transition upright contact portion 188. The BFR assembly 112 is connected to the electron gun by means of a plurality of bead support members 115 which are embedded in a pair of glass support rods 114 and have their free ends welded to a flat surface 174 of the transition member 166. In this structure, as in the present structure, the G1 to G2 longitudinal spacing, l_5 , between a control grid (G1) electrode 118 and the screen grid electrode 120 is provided by a removable spacer (not shown). Unlike the present structure, however, the G2-G3 longitudinal spacing, l_6 , between the screen grid electrode 120 and a first focusing (G3) electrode 122 of the main focus lens also is established when the G1-G2 spacing is set since the bead support members 115 are attached to the surface 174 of the transition member 166. As

shown in FIGURE 5, when the G1-G2 spacing l_5 is established, the height l_7 of the top of the screen grid electrode 120 above the surface 174 also is established. Since the bead support members 115 are attached to the glass support rods 114 at the same time that the main electron lens is attached to the support rods 114, the total spacing between the attachment surface of the bead support members 115 and the first focusing electrode 122 is $l_6 + l_7$. Clearly, if the G1-G2 spacing l_5 varies from the optimum range, because of variations in the surface flatness of the ceramic member 150, or variations in the height of the flange of the control grid electrode 118, then l_7 varies directly with changes in l_5 , and l_6 varies inversely with changes in l_7 . In order to maintain the optimum G2-G3 longitudinal spacing l_6 , a removable shim (not shown) may be placed between the top surface of the screen grid electrode 120 and the bottom surface of the first focusing electrode 122 when the bead support members 115 are welded to the surface 174 of the transition member 166. The ends of the bead support members 115 in contact with the surface 174 may be bent sufficiently to hold the shim between the facing surfaces of the screen grid electrode 120 and the first focusing electrode 122. However, such an expedient should be avoided since bending may crack the glass support beads 114. An alternative method of obtaining the optimum G2-G3 longitudinal spacing, l_6 , is to relocate the bead support members 115 in the glass support beads 114 to compensate for variations in the G1-G2 spacing, l_5 . This, however, requires a large number of electron guns of different spacing and is less practical than the present structure.

Claims

1. A multibeam electron gun (10) for a cathode-ray tube, comprising a modular beam-forming region assembly (12) and a main focusing lens which are affixed to at least two insulative support rods (14), said beam-forming region assembly including a plurality of cathode assemblies (16), a control grid electrode (18) and a screen grid electrode (20), said electrodes having aligned apertures (60,62) therethrough for passage of a plurality of electron beams from said cathode assemblies, said cathode assemblies and said electrodes being individually held in position from a common ceramic member (50) having a first (52) and a second (54) major surface, with a metallized pattern (56a,56b,56c) formed on at least a portion of each major surface, said electrodes being attached to said first major surface, and said cathode assemblies being attached to said

second major surface; characterized in that:

a transition member (66) is disposed between the metallized pattern (56a,56b) on said first major surface of said ceramic member and said screen grid electrode, said transition member including a substantially flat portion (74) attached to said metallized pattern (56b) and two upright portions (76) substantially perpendicular to said flat portion and substantially parallel to each other;

said screen grid electrode has at least one plate-like member aligned with the space between said upright portions of said transition member; and

a plurality of step-like support members (82) interconnect said screen grid electrode and said upright portions of said transition member, each of said step-like support members having a screen grid electrode contact portion (84), a bead support contact portion (86) and a central riser portion (88) extending between said contact portions, said screen grid electrode contact portion of each of said step-like support members being attached to said screen grid electrode, and said central riser portion of each of said step-like support members being attached to said upright portions of said transition member in longitudinal spaced relation to said control grid electrode, and said bead support contact portion of each step-like support member being attached to a different one of a plurality of bead support members (15) affixed to said insulative support rods, whereby said screen grid electrode is longitudinally spaced from said main focusing lens.

2. The multibeam electron gun (10) of claim 1, characterized in that:

said transition member (66) is attached to said metallized pattern (56a,56b) on said first major surface (52) of said ceramic member (50), said transition member including a substantially flat first part (68) and a second part (70) electrically isolated from said first part, said second part having said substantially flat portion (74); and

said control grid electrode (18) is attached to said first part of said transition member.

3. The multibeam electron gun (10) of claim 2, wherein said beam-forming region assembly (12) includes three inline cathode assemblies (16), each of said electrodes (18,20) has three aligned apertures (60,62) therethrough for passage of three electron beams from said cathode assemblies; characterized in that:

said transition member (66) comprises bi-metal layers (90,92); and

shown in FIGURE 5, when the G1-G2 spacing l_5 is established, the height l_7 of the top of the screen grid electrode 120 above the surface 174 also is established. Since the bead support members 115 are attached to the glass support rods 114 at the same time that the main electron lens is attached to the support rods 114, the total spacing between the attachment surface of the bead support members 115 and the first focusing electrode 122 is $l_6 + l_7$. Clearly, if the G1-G2 spacing l_5 varies from the optimum range, because of variations in the surface flatness of the ceramic member 150, or variations in the height of the flange of the control grid electrode 118, then l_7 varies directly with changes in l_5 , and l_6 varies inversely with changes in l_7 . In order to maintain the optimum G2-G3 longitudinal spacing l_6 , a removable shim (not shown) may be placed between the top surface of the screen grid electrode 120 and the bottom surface of the first focusing electrode 122 when the bead support members 115 are welded to the surface 174 of the transition member 166. The ends of the bead support members 115 in contact with the surface 174 may be bent sufficiently to hold the shim between the facing surfaces of the screen grid electrode 120 and the first focusing electrode 122. However, such an expedient should be avoided since bending may crack the glass support beads 114. An alternative method of obtaining the optimum G2-G3 longitudinal spacing, l_6 , is to relocate the bead support members 115 in the glass support beads 114 to compensate for variations in the G1-G2 spacing, l_5 . This, however, requires a large number of electron guns of different spacing and is less practical than the present structure.

Claims

1. A multibeam electron gun (10) for a cathode-ray tube, comprising a modular beam-forming region assembly (12) and a main focusing lens which are affixed to at least two insulative support rods (14), said beam-forming region assembly including a plurality of cathode assemblies (16), a control grid electrode (18) and a screen grid electrode (20), said electrodes having aligned apertures (60,62) therethrough for passage of a plurality of electron beams from said cathode assemblies, said cathode assemblies and said electrodes being individually held in position from a common ceramic member (50) having a first (52) and a second (54) major surface, with a metallized pattern (56a,56b,56c) formed on at least a portion of each major surface, said electrodes being attached to said first major surface, and said cathode assemblies being attached to said

second major surface; characterized in that:

a transition member (66) is disposed between the metallized pattern (56a,56b) on said first major surface of said ceramic member and said screen grid electrode, said transition member including a substantially flat portion (74) attached to said metallized pattern (56b) and two upright portions (76) substantially perpendicular to said flat portion and substantially parallel to each other;

said screen grid electrode has at least one plate-like member aligned with the space between said upright portions of said transition member; and

a plurality of step-like support members (82) interconnect said screen grid electrode and said upright portions of said transition member, each of said step-like support members having a screen grid electrode contact portion (84), a bead support contact portion (86) and a central riser portion (88) extending between said contact portions, said screen grid electrode contact portion of each of said step-like support members being attached to said screen grid electrode, and said central riser portion of each of said step-like support members being attached to said upright portions of said transition member in longitudinal spaced relation to said control grid electrode, and said bead support contact portion of each step-like support member being attached to a different one of a plurality of bead support members (15) affixed to said insulative support rods, whereby said screen grid electrode is longitudinally spaced from said main focusing lens.

2. The multibeam electron gun (10) of claim 1, characterized in that:

said transition member (66) is attached to said metallized pattern (56a,56b) on said first major surface (52) of said ceramic member (50), said transition member including a substantially flat first part (68) and a second part (70) electrically isolated from said first part, said second part having said substantially flat portion (74); and

said control grid electrode (18) is attached to said first part of said transition member.

3. The multibeam electron gun (10) of claim 2, wherein said beam-forming region assembly (12) includes three inline cathode assemblies (16), each of said electrodes (18,20) has three aligned apertures (60,62) therethrough for passage of three electron beams from said cathode assemblies; characterized in that:

said transition member (66) comprises bi-metal layers (90,92); and



said screen grid electrode (20) comprises three separate plate-like portions (20a, 20b, 20c), each portion having one of said apertures (62) therein.

Patentansprüche

1. Mehrstrahl-Elektronenkanone (10) für eine Kathodenstrahlröhre, mit einer einen strahlformenden Bereich bildenden modularen Anordnung (12) und einer Hauptfokussierungslinse, die an wenigstens zwei isolierenden Tragstäben (14) befestigt sind, wobei die den strahlformenden Bereich bildende Anordnung eine Vielzahl von Kathodenanordnungen (16), eine Steuergitterelektrode (18) und eine Schirmgitterelektrode (20) enthält, wobei die Elektroden fluchtende Öffnungen (60, 62) zum Durchlaß einer Vielzahl von Elektronenstrahlen von den Kathodenanordnungen aufweisen, wobei die Kathodenanordnungen und die Elektroden einzeln mittels eines Keramikelements (50), das eine erste (52) und eine zweite (54) Hauptfläche aufweist, in ihrer Position gehalten werden und eine metallisierte Struktur (56a, 56b, 56c) an wenigstens einem Teil jeder Hauptfläche gebildet ist, wobei die Elektroden an der ersten Hauptfläche und die Kathodenanordnungen an der zweiten Hauptfläche angebracht sind, dadurch gekennzeichnet,

daß zwischen der metallisierten Struktur (56a, 56b) auf der ersten Hauptfläche des keramischen Elements und der Schirmgitterelektrode ein Übergangselement (66) angeordnet ist, wobei das Übergangselement ein im wesentlichen flaches Teil (74), das an der metallisierten Struktur (56b) angebracht ist und zwei aufrechte Teile (76) enthält, die im wesentlichen senkrecht zu dem flachen Teil und im wesentlichen parallel zueinander angeordnet sind;

daß die Schirmgitterelektrode wenigstens ein plattenförmiges Element aufweist, das mit dem Zwischenraum zwischen den aufrechten Teilen des Übergangselements fluchtet; und

daß eine Vielzahl von stufenförmigen Tragelementen (82) die Schirmgitterelektrode mit den aufrechten Teilen des Übergangselements verbindet, wobei jedes der stufenförmigen Tragelemente ein Schirmgitterelektroden-Kontaktteil (84), ein Tragstab-Tragelement-Kontaktteil (86) und ein sich zwischen den Kontaktteilen erstreckendes mittleres Zwischenstück (88) aufweist, wobei der Schirmgitterelektroden-Kontaktteil jedes der stufenförmigen Tragelemente an der Schirmgitterelektrode angebracht ist, das mittlere Verbindungsstück jedes der stufenförmigen Trag-

elemente an den aufrechten Teilen des Übergangselements in longitudinaler Abstandsbeziehung zur Steuergitterelektrode angebracht ist, und die Tragstab-Tragelement-Kontaktteile der stufenförmigen Tragelemente jeweils an verschiedenen der an den isolierenden Tragstäben befestigten Tragstab-Tragelemente (15) angebracht sind, wobei die Schirmgitterelektrode in longitudinalem Abstand von der Hauptfokussierungslinse angeordnet ist.

2. Mehrstrahl-Elektronenkanone (10) nach Anspruch 1, dadurch gekennzeichnet,

daß das Übergangselement (66) an der metallisierten Struktur (56a, 56b) auf der ersten Hauptfläche (52) des Keramikelements (50) angebracht ist, wobei das Übergangselement einen im wesentlichen ebenen ersten Teil (68) und einen zweiten, von dem ersten Teil isolierten Teil (70) enthält, der den im wesentlichen ebenen Teil (74) aufweist; und

daß die Steuergitterelektrode (18) an dem ersten Teil des Übergangselements angebracht ist.

3. Mehrstrahl-Elektronenkanone (10) nach Anspruch 2, bei der die den strahlformenden Bereich bildende Anordnung (12) drei Inline-Kathodenanordnungen (16) enthält, wobei jede Elektrode (18, 20) drei fluchtende Öffnungen (60, 62) zum Durchlaß von drei Elektronenstrahlen von den Kathodenanordnungen enthält, dadurch gekennzeichnet,

daß das Übergangselement (66) Bimetallschichten (90, 92) enthält; und

daß die Schirmgitterelektrode (20) drei getrennte plattenförmige Teile (20a, 20b, 20c) enthält, von denen jeder eine der Öffnungen (62) enthält.

Revendications

1. Canon à électrons à faisceaux multiples (10) pour un tube à rayons cathodiques, comprenant un assemblage modulaire de zone de formation du faisceau (12) et une lentille de focalisation principale qui sont fixés à au moins deux tiges de support isolantes (14), ledit assemblage de zone de formation du faisceau incluant une pluralité d'assemblages de cathode (16), une électrode de grille de commande (18) et une électrode de grille-écran (20), lesdites électrodes portant à travers elles des ouvertures pour le passage d'une pluralité de faisceaux d'électrons venant desdits assemblages de cathode, lesdits assemblages de cathode et lesdites électrodes étant individuellement maintenus en position à



partir d'un élément céramique commun (50) présentant une première (52) et une seconde (54) surface principale avec un motif métallisé (56a, 56b, 56c) formé sur au moins une partie de chaque surface principale, lesdites électrodes étant fixées à ladite première surface principale, et lesdits assemblages de cathode étant fixés à ladite seconde surface principale, caractérisé en ce que :

un élément de transition (66) est disposé entre le motif métallisé (56a, 56b) sur ladite première surface principale dudit élément céramique et ladite électrode de grille-écran, ledit élément de transition incluant une partie sensiblement plane (74) fixée audit motif métallisé (56b) et deux parties verticales (76) sensiblement perpendiculaires à ladite partie plane et sensiblement parallèles l'une à l'autre ;

ladite électrode de grille-écran comporte au moins un élément en forme de plaque aligné avec l'espace entre lesdites parties verticales dudit élément de transition ; et

une pluralité d'éléments supports en forme de marche (82) relie ladite électrode de grille-écran et lesdites parties verticales dudit élément de transition, chacun desdits éléments supports en forme de marche possédant une partie de contact avec l'électrode de grille (84), une partie de contact avec le support à rebord (86) et une partie montante centrale (88) s'étendant entre lesdites parties de contact, ladite partie de contact avec l'électrode de grille-écran de chacun desdits éléments supports en forme de marche étant fixée à ladite électrode de grille-écran et ladite partie montante centrale de chacun desdits éléments supports en forme de marche étant fixée auxdites parties verticales dudit élément de transition en relation d'espacement longitudinal avec l'électrode de grille de commande et ladite partie de contact avec le support à rebord de chaque élément support en forme de marche étant fixée à un élément différent d'une pluralité d'éléments supports à rebord (15) fixés auxdites tiges de support isolantes par quoi ladite électrode de grille-écran est espacée de façon longitudinale de ladite lentille de focalisation principale.

2. Canon à électrons à faisceaux multiples (10) selon la revendication 1, caractérisé en ce que :

ledit élément de transition (66) est fixé audit motif métallisé (56a, 56b) sur ladite première surface principale (52) dudit élément céramique (50), ledit élément de transition incluant une première partie sensiblement plane (68) et une seconde partie (70) isolée électri-

quement de ladite première partie, ladite seconde partie comportant ladite partie sensiblement plane (74); et

ladite électrode de grille de commande (18) est fixée à ladite première partie dudit élément de transition.

3. Canon à électrons à faisceaux multiples (10) selon la revendication 2, dans lequel ledit assemblage de zone de formation du faisceau (12) inclut trois assemblages de cathode de ligne (16), chacune desdites électrodes (18, 20) possède trois ouvertures alignées (60, 62) pour le passage à travers elles de trois faisceaux d'électrons à partir desdits assemblages de cathode ; caractérisé en ce que :

ledit élément de transition (66) comprend des couches bimétalliques (90, 92) ; et

ladite électrode de grille-écran (20) comprend trois parties en forme de plaque séparées (20a, 20b, 20c), chaque partie comportant une desdites ouvertures (62).

