

Description

Field of the Invention

The present invention relates to a mounting device for rotating saw cutting blades. More specifically, the invention relates to a specially configured arbor and correspondingly configured aperture in a circular concrete saw blade to prevent the cutting blade from being mismounted on the saw.

Background of the Invention

Circular saw blades are normally driven by rotating shafts connected to motors. In many applications, the rotating cutting blades have circular holes through the center for acceptance of a circular drive shaft. The shafts often have a smaller diameter mounting portion which extends from a larger primary portion of the drive shaft to form a shoulder. The blades are typically pressed over the smaller diameter mounting portion until they are stopped against the shoulder formed by the main drive portion of the shaft. The blade is then locked onto the shaft by clamping it between the shoulder on the main portion of the drive shaft and either a threaded locking nut which is threaded onto the end of the small diameter mounting portion or a bolt threaded into a threaded hole in the end of the shaft. The friction from the clamping force prevents the blade from rotating with the shaft.

Often times, material is allowed to enter the hole in which the clamping bolt is threaded. This prevents the bolt from being tightened sufficiently into the threaded hole in the shaft. When this occurs, there is an insufficient clamping force to hold the rotating cutting blade against the shoulder, and because the mounting is circular, the blade may slip. When the blade slips with respect to the shaft, the blade speed often decreases rapidly, causing spalling or chipping of the concrete surface adjacent groove being cut.

In order to remedy this problem, non-circular arbor sleeves, or cutting blade mounting members, can be attached to the drive shafts. The arbor sleeves are normally securely mounted to the drive shaft, so they do not rotate. For example they can be clamped, welded, pinned to the shaft, keyed, or held by set screws. A surface of the arbor sleeve is used as the surface upon which the rotating cutting blade is then mounted. The cutting blade is configured to have a mounting hole of the same size and shape of the arbor to allow it to be positioned over the arbor to be driven by the motor drive shaft.

Arbor sleeves are normally square or a circular shaft with symmetric flutes, although they may have other symmetric configurations. The shape of the arbor sleeve is symmetrical on its outer sur-

face, in order that the cutting blade may be easily mounted on it without much alignment effort. When a non-circular arbor sleeve is employed, the cutting blade may not slip, as the hole of the blade and the outside of the arbor sleeve have sides which contact one another.

Alternatively, the drive shaft can be configured to have a symmetric non-circular end, and the cutting blade configured to have a correspondingly shaped hole through which the arbor can be inserted. While it is possible to have the blade mounting area of the drive shaft, or arbor, itself be machined into the desired shape, sleeves are more easily machined at lower cost.

Because the arbors or arbor sleeves are symmetrical in shape, the cutting blade may be mounted so that either side of the cutting blade faces the saw. Normally, the person installing the saw will orientate the cutting blade so the teeth on the blade are in the correct orientation relative to the direction the saw is to travel during cutting. For wood cutting saw, the saw teeth orientation is apparent, and the blade can be easily orientated to rotate in the correct direction relative to the direction that the saw will travel during cutting.

With concrete cutting saws, however, the teeth do not have a readily apparent directional orientation. Concrete cutting saw blades are made with diamond impregnated cutting segments that are symmetrically shaped. When used to cut hardened concrete and when water lubricated, the blades can be used in either orientation, or with either side of the blade toward the saw when the saw is traveling in the same direction. Thus the orientation of the water lubricated blade on the saw does not matter for cured, hardened concrete.

When the same blade is used to cut wet or very green concrete without water lubrication, however, the blade orientation is important. The cutting segments are formed by having harder cutting media, such as diamond chips or tungsten carbide particles, being placed in a softer support or binding matrix, such as bronze or other softer metals. The cutting segments are either formed on the metal support disk, or formed separately and then bonded to the support disk. After the cutting segments are on the disk, the cutting segments are dressed by slightly abrading the cutting segments to remove enough of the binding matrix to expose the cutting particles. This dressing typically leaves one side of the cutting particles exposed while the opposite side has a trail of the softer binding matrix extending from the cutting particle (FIG. 10). If the cutting blade is rotated so that the exposed side of the particles face the direction of the blade rotation, the blade cuts well. If, however, the blade is orientated the other way so that the exposed portion of the cutting particles face away from the direction of

the blade rotation, then the cutting blade will not cut well because only the binding material and not the cutting particles contact the concrete. This will also occur if the blade is not dressed sufficiently and the cutting particles are not exposed adequately before cutting. When the blade is mis-mounted or is insufficiently dressed, chattering of the blade and spalling and/or chipping of the concrete occurs when the blade is used to cut the concrete. Further, because the blade is not water lubricated when cutting wet or very green concrete, the friction created between the concrete and the binding material causes extreme heat build-up, causing the blade to warp, which in turn damages the surface of the concrete surrounding the cutting blade. In some cases, the heat build-up combined with the chattering of the warped blade will cause the cutting segments to detach from the blade. This situation is dangerous, as the cutting segments may be propelled into the user and cause injury, or be propelled into and damage the saw.

Previously, cutting blades used to cut wet concrete were labeled with notices such as "this side out," to insure correct orientation of the blade on the saw. That labeling, however, is not always effective. There is thus needed a way to insure correct orientation of a circular concrete cutting jaw blade on the saw, and a way to guard against rotation of the saw blade relative to the drive shaft.

European Document No. 0 028 285 to Robert Bosch GmbH and German Document No. 1 878 647 to Baier each describes the mounting of a saw blade on a shaft such that the unidirectionality of the cutting teeth of the blade is respected. Both documents provide a mounting surface of nonsymmetric shape, a cutting blade having a mounting hole of a corresponding shape, and a method for mounting the blade with a given orientation on the shaft. However, neither of these documents discloses or suggests a mounting surface generally in the shape of a nonsymmetric triangle or trapezium.

Summary of the Invention

In accordance with one aspect of the present invention, there is provided a specially shaped mounting for use with rotating cutting blades and cutting saws having drive shafts, which is especially suitable for concrete cutting saws and blades. The mounting is preferably located on an arbor sleeve, although it may be located on an arbor itself. The sleeve is configured so that its shape cooperates with a hole in the cutting blade to allow the blade to be mounted on the sleeve in only one orientation. The hole in the cutting blade may be generally in the shape of either a triangle or a trapezium. The arbor sleeve of the present invention is located on a drive shaft of a saw and used

to rotate the cutting blade. The drive shaft of the saw has a shoulder, and a threaded portion, all along a longitudinal axis.

The arbor sleeve has a proximal and distal end, the proximal end being located nearer the saw. The arbor sleeve has a shaft mounting member with a longitudinal hole therein sized to accommodate the insertion of at least a portion of the drive shaft. A flange extends radially outward from the shaft mounting member. The flange prevents the cutting blade from sliding along the shaft.

A blade mounting member or mounting surface is also provided on the arbor sleeve. The blade mounting member is the mounting surface on which the cutting blade is mounted. The blade mounting member is located distal of the flange on the sleeve. The blade mounting member has a primarily triangular exterior or outer surface and a circular bore in its middle for acceptance of a motor drive shaft. Two of the triangular sides of the blade mounting member are substantially straight, these two sides being advantageously connected at their intersection by a generally rounded or arcuate corner. The third side of the triangular blade mounting member is convex in shape, and connects with the first and second sides at generally rounded or arcuate corners. The three sides of the triangle are of unequal length.

The blade mounting member thus has a non-symmetrical shape about an axis orthogonal to the longitudinal axis through the center of the hole, and about which the mounting member rotates during cutting.

The arbor sleeve of the present invention is designed to be used with a rotating cutting blade having a plurality of concrete cutting segments located about the periphery of the disc. The blade has a first side and a second side, and a mounting hole therein for mounting the blade to the drive shaft for rotation of the blade about a longitudinal axis through the hole.

The hole in the blade, when viewed from the first side, is the same as the shape of the blade mounting member. The hole is non-symmetric in shape, however, such that when viewed from one direction along the longitudinal axis can not be rotated about the longitudinal axis so as to coincide with the shape of the hole when viewed from the other direction along the longitudinal axis. Thus, the blade will fit onto the arbor sleeve in only one orientation.

One specific configuration of the blade mounting member has a center point with a horizontal and vertical axis therethrough. For orientation purposes, it is to be understood that "in front of" the vertical axis means to the right of the vertical axis or in the positive horizontal direction, and "behind" the vertical axis means the opposite thereof;

"above the horizontal" means on top of the horizontal axis or in the positive vertical direction, and "below" the horizontal means the opposite thereof. A first corner of the triangle is located at a radius R1 which emanates from a point located a distance D1 away from the center point in front of the vertical and along the horizontal axis. A second corner is located at a radius R2 such that R2 approximately equals 1.2 R1, and emanates from a point located behind the vertical axis a distance D2 away from the center point and at an angle θ of about 54 degrees above the horizontal axis. The distance D2 approximately equals .93 D1. A third corner of the triangle has a radius R3 such that R3 approximately equals 1.06 R1, and emanates from a point located behind the vertical axis a distance D3 away from the center point and at an angle α of about 66 degrees below the horizontal axis. The distance D3 approximately equals .89 D1. A first side of the triangle tangentially connects the outside of the first and second corners, and a second side tangentially connects the outside of said second and third corners. A third side, having a radius R4 emanating from a point located in front of the vertical axis a distance D4 away from the center point and at an angle β of about 9 degrees above the horizontal axis. D4 approximately equals 1.32 D1, where said third side tangentially connects the outside of said first and third corners.

In accordance with another aspect of the present invention, there is provided a method of orienting the rotating concrete cutting blade on the drive shaft in the correct orientation. The method comprises providing a blade mounting member which is non-symmetrical when rotated 180 degrees about an axis orthogonal to the longitudinal axis of the drive shaft about which the blade rotates during cutting. A hole, which is generally in the shape of a triangle or a trapezium, is provided in the blade, where the hole when viewed from the first side of the blade is the same as the shape of the blade mounting member, but not when viewed from the opposite side of the blade. The blade is then placed on the blade mounting member so that the hole in the blade coincides with and fits over the blade mounting member, and the blade is secured to the shaft. Advantageously, the blade is secured by placing a washer on the shaft distal of the blade, and then placing a nut on the threaded portion of the shaft whereby the nut provides a clamping force to clamp the blade between the washer and the flange of the sleeve.

This method and apparatus prevents the user from attaching the rotating cutting blade to the arbor sleeve in an incorrect orientation. Thus, cutting blades used to cut wet or green concrete may not be mismounted so as to cut in the wrong direction and cause chipping and spalling, and will

not overheat and warp, further causing damage to the concrete. The arbor sleeve of the present invention will also help prevent the use of a cutting blade which is not designed for use with a concrete saw which is fitted with this arbor. In this manner, users will be prevented from accidentally using a cutting blade which was not intended for use with the particular concrete saw.

Further objects, features, and advantages of the present invention will become apparent from the detailed description of the drawings which follows, when considered with the attached figures.

Brief Description of the Drawings

Figure 1 is a perspective view of an arbor sleeve, washer, nut, drive shaft and motor, and a cutting blade with a mounting hole therein in accordance with the present invention.

Figure 2 is a front view of the arbor sleeve of Figure 1.

Figure 3 is a sectional side view of the arbor sleeve of Figure 1.

Figure 4 is a front view of the cutting blade of Figure 1 mounted on the arbor sleeve of Figure 1.

Figure 5 is a rear view of the cutting blade of Figure 1 laid over the arbor sleeve of Figure 1.

Figure 6 is a sectional view of the shaft, arbor sleeve, washer and nut along line 6-6 of Figure 1.

Figure 7 is a dimensional front view of a blade mounting member.

Figure 8 is a front view of a blade mounting member having a trapezium shape.

Figure 9 is a perspective view of an arbor sleeve, drive shaft, motor, cutting blade, washer, and mounting bolt in accordance with an alternate embodiment of the present invention.

Figure 10 is a partial perspective view of a cutting blade as known in the prior art.

Detailed Description of the Illustrated Embodiment

Referring to FIGS. 1-3 and 6-7, there is shown the mounting of the present invention in the form of an arbor sleeve 10. The arbor sleeve 10 is for use with a saw, such as a concrete saw 12 having a motor 14. A drive shaft 16 is rotated by the motor 14 about the longitudinal axis of the shaft 16. The drive shaft 16 has a free end 18 for acceptance of a cutting blade 21. The free end 18 of the drive shaft 16 extends to a shoulder 19 with a smaller threaded shaft 20 extending longitudinally from the shoulder 19 away from the saw 12. In the context of a concrete cutting saw, such as that described in U.S. Patent No. 5,056,499, the drive shaft 16 is turned such that the blade 21 will cut in an up-cut direction, as shown relative to the direction of travel 27 of the saw 12. In general, the arbor sleeve 10

has a proximal end 23 and a distal end 25 relative to the saw 12, with the proximal end 23 being closer to the saw 12 and the distal end 25 being further away. The arbor sleeve 10 also has a shaft mounting portion 22, a blade mounting member 24, and a central bore 26 therethrough.

The shaft mounting portion 22 is generally cylindrical in shape, and is located at the proximal end 23 of the arbor sleeve 10. The shaft mounting portion 22 has an outer diameter of about .81 inches (20.6 mm) and a length of about .39 inches (9.9 mm). The length is primarily a function of the desired contact area between the drive shaft 16 and the arbor sleeve 10. The outer diameter is only slightly larger than the diameter of the shaft 16 upon which the arbor sleeve 10 is mounted. The shaft mounting portion 22 is the part of the arbor sleeve 10 which is used to connect the sleeve to the free end 18 of the drive shaft 16. The shaft mounting portion 22, as illustrated, is secured to the free end 18 of the drive shaft 16. The mounting portion 22 may be welded, or attached by screws, pins, friction or other means known to those skilled in the art so as to prevent rotation of arbor sleeve 10 relative to shaft 16. When the arbor sleeve 10 is mounted onto the drive shaft 16, the shoulder 19 advantageously abuts with the distal end 23 of the sleeve.

A blade support flange 30 extends radially outward from between the shaft mounting member 24 and the blade mounting member 26. The blade support flange 30 is also cylindrical in shape, but has a larger diameter than the mounting portion 22. The flange 30, as illustrated, has an outer diameter of about 1.5 inches (38.1 mm). The flange 30 has a thickness of about .22 inches (5.6 mm). The flange 30 is sized to prevent the cutting blade 21 from sliding past the blade mounting member 24 and along the drive shaft 16. The central bore 26 passes through the center of the flange 30 as well.

The blade mounting member 24 contains a specially shaped mounting surface of the arbor sleeve 10. The blade mounting member 24, as illustrated, is generally triangular in shape, with three sides of unequally length and rounded corners. Advantageously, two of the sides are substantially straight while the third side is convex. The blade mounting member 24 thus has three sides 34, 36, 38, joined at three corners 40, 42, 44, and with the central bore 26 running therethrough. The mounting member 24 may be defined from a center point 28 located at the center of the bore 26 and an arbitrary horizontal axis H and vertical axis V running through this center point. For orientation purposes, it is to be understood that "in front of" the vertical axis V means to the right of the vertical axis V or in the positive horizontal direction, and "behind" the vertical axis V means the opposite

thereof; "above the horizontal" means on top of the horizontal axis H or in the positive vertical direction, and "below" the horizontal axis H means the opposite thereof. The longitudinal axis of rotation passes through the center point 28.

Referring to FIG. 7, the first corner 40 is, as illustrated, rounded, having a radius R1 of about .135 inches (3.4 mm), the radius extending from a first point 41 located in front of the vertical along the horizontal axis H (or at an angle of 0 degrees along the horizontal axis H) a distance D1 of about .487 inches (12.4 mm) from the center point 28. The second corner 42 is also rounded, having a radius R2 of about .163 inches (4.1 mm). The radius of the second corner 42 extends from a second point 43 located behind the vertical axis V, being a distance D2 of about .447 inches (11.4 mm) from the center point 28 and at an angle θ of about 54 degrees above horizontal axis H. The third corner 44 is also rounded, having a radius R3 of about .143 inches (3.6 mm). The radius of the third corner 44 extends from a third point 45 located behind the vertical axis V, being about .432 inches (11.0 mm) from the center point 28 and at an angle α of about 66 degrees below the horizontal axis H.

The first side 34 is substantially straight, and as illustrated, connects the first corner 40 and second corner 42 in a tangent fashion, thus having a length of about .830 inches (21.1 mm). The second side 36 is also generally straight, connecting the first corner 42 and third corner 44 in a tangential fashion, thus having a length of about .771 inches (1.96 mm).

The third side 38 is arcuate in shape, having a radius R4 of about 1.095 inches (27.8 mm). The radius of the third side 38 extends from a fourth point 46 located in front of the vertical axis V, being a distance D4 of about .644 inches (16.4 mm) from the center point 28 and at an angle β of about 9 degrees above the horizontal axis H. The third side 38 intersects the second corner 42 and third corner 44 in a tangential fashion.

The central bore 26 has a radius of about .313 inches (7.9 mm), radiating about the center point 28. The shaft bore 26 may, of course, be a different diameter, depending on the diameter of the drive shaft 16 on which it is to be mounted.

As defined from the center point 28 the dimensions of the blade mounting member 24 may be assigned as follows. The first corner 40 radius (R1), second corner 42 radius (R2) and third corner 44 radius (R3) have a relation such that R2 approximately equals 1.2 R1 and R3 approximately equals 1.06 R1. The distance from the center point 28 to the first point 41 (D1), second point 42 (D2) and third point 43 (D3) is such that D2 approximately equals .93 D1 and D3 approximately equals

.89 D1 when the lines from the center point 28 to each point 41, 43, 45 are along about the same angle as defined above.

The first side 36 and second side 34 are of such a length as to intersect the outside of corners 40, 42, 44 in a tangential fashion. The third side 38 is of such a radius as to intersect the outside of the second corner 42 and third corner 44 in a tangential fashion, when the fourth point 46 is along the angle defined above and a distance D4 of about 1.32 D1. The central bore 26 has a radius RB equal to about 2.32 times R1.

While blade mounting member 24 is generally triangular in shape, it is not symmetric. Scalene triangular shapes, where each side is a different length, are believed advantageous.

Referring to FIGS. 1, 4 & 5, the cutting blade 21 has a first distal side 48, second proximal side 50, and a mounting hole 52 therein. The mounting hole 52 is shaped so that when the cutting blade 21 is viewed from its distal side 48, the hole 52 has the same shape as the blade mounting member 24 and is only larger in size to the extent necessary to allow the blade to be positioned on the mounting member 24. A tolerance of about .002 to .003 inches (.05 to .08 mm) between the size of the hole 52 and mounting member 24 works well. In this manner, the cutting blade 21 may be mounted on the blade mounting member 24 of arbor sleeve 10 as illustrated in FIG. 4.

Referring to FIGS. 1 and 6, once placed on the arbor sleeve 10, the blade 21 is secured by placing a washer 54 distally of the blade on the threaded end 20 of the drive shaft 16. The washer 54 is, as illustrated in FIG. 6, a metal disk having a hollow center section which faces the blade and a center hole to allow the passage of the smaller diameter threaded shaft 20 therethrough. A nut 56 is then positioned on the threaded smaller shaft 20 of the drive shaft 16 and tightened so as to press the blade 21 between the peripheral portion of washer 54 and the flange 30 of the arbor sleeve 10. As shown in FIG. 6, friction from the clamping force exerted by nut 56 prevents rotation of the sleeve 10 and blade 21. Alternatively, the sleeve 10 can be secured to shaft 16 as previously described. For illustration, a set screw 55 is shown in phantom in FIG. 6 being inserted into hole 57 in shaft 16. The nut 56 and washer 54 could also be combined into one part rather than two separate pieces.

As illustrated in FIG. 9, the blade 21 may alternatively be secured by a threaded bolt 58 engaging a threaded hole 59. In this embodiment, the drive shaft 16 does not have a threaded portion 20, and instead has the threaded hole 59 in its end along its longitudinal axis. The blade 21 is pressed between the flange 30 of the sleeve 10 and the washer 54 by the bolt 58 which is tightened into

the hole 59 in the shaft 16. Once again, the washer 54 and the bolt 58 could be formed as one piece and operate in the same manner.

The mounting hole 52, as illustrated, corresponds in shape to the blade mounting member 24 and will not be repeated in detail. The hole 52 is created by punching from the cutting blade 21 the mounting member 24 shape. The hole 52 could also be created by machining. It is to be understood that the dimensions detailed above for the sleeve 10 and for the hole 52 may be varied moderately and still achieve the same shapes and tolerances.

As can be seen in FIGS. 1, 4 & 5, the blade 21 can only be mounted upon the arbor sleeve 10 in one orientation. As stated previously, the cutting blade 21 is manufactured so that it will only cut properly if rotating in one specific direction. As illustrated, the cutting blade 21 is machined such that when the first side 48 faces away from the saw 12, the blade will cut in the correct up-cut direction. As shown in FIG. 5, if a user attempts to position the cutting blade 21 on the arbor sleeve 10 in a position where the second side 50 of the blade faces away from the saw 12, the blade 21 will not fit on the mounting member 24. This is because when the blade 21 is flipped over, the blade mounting member 24 and the hole 52 in the blade 21 have shapes that no longer coincide. This feature is provided by having the blade mounting member 28 of the arbor sleeve 10 and the mounting hole 52 in the cutting blade 21 be non-symmetrical, so that the mirror image of the hole 52 or member 24 is not the same as the shape of the hole 52 or member 24 viewed directly.

It will now be apparent to one skilled in the art given the above disclosure, that in order to accomplish the desired task of preventing the cutting blade 21 from being mismounted, any number of shapes for blade mounting member 24 are possible. The primary requirement in order to prevent mismounting is that the blade mounting member 28 and corresponding mounting hole 52 be of a non-symmetrical shape when viewed from opposite sides along the longitudinal axis, as illustrated by comparing FIGS. 4 & 5 where the blade 21 is rotated 180 degrees about vertical axis V (FIG. 7). This can be accomplished by the asymmetric triangular shape discussed above, but four or more sided figures will also work. In particular, an arbor or arbor sleeve with blade mounting member having a trapezium shape could work (FIG. 8). Such shapes also need not necessarily have straight sides, as the mounting above does not. A three sided arbor or arbor sleeve 10 is preferred, however, because it reduces machining costs. Further, the fewer number of sides makes it easier for the user to mount the blade 21 on the sleeve 10, as

there are fewer blade 21 and sleeve 10 positions which must be either visually or manually eliminated in order to find the correct alignment.

As will be apparent to one skilled in the art, the shape of the blade mounting member 24 may be machined directly on the end of the drive shaft 16 itself (not shown), instead of being formed on a sleeve 10 which is then secured to the shaft 16.

Further, while the mounting has been described here in use with a concrete cutting saw 12 and corresponding concrete cutting blade 21, it is contemplated that the mounting have uses in conjunction with various other cutting methods and devices.

There is thus provided a means and method for preventing a cutting blade from being mismounted on a saw. There is provided an arbor or arbor sleeve 10 on the drive shaft 16 of a saw 12. The blade mounting member 24 of the arbor sleeve 10 has a mounting surface 24 shaped so that when viewed directly and in a mirror, the shapes cannot coincide. The mounting hole 52 in the cutting blade's 21 first side 48 has a shape which corresponds to that of the mounting member 24. The cutting blade 21 is pressed onto the mounting member 24 of the sleeve 10 with the first side 48 facing away from the saw 12, as is the only orientation in which the blade 21 will fit onto the sleeve 10. The washer 54 is then placed on the shaft 16 against the first side 48 of the blade 21, and the nut 56 is threaded onto the smaller portion of the shaft 20 to secure the blade 21 to the sleeve 10 between the washer 54 and the flange 30.

Alternatively, the blade 21 may be secured by inserting the threaded bolt 58 into the hole 59 in the shaft 16 in order to press the blade 21 between the washer 54 and the flange 30, as was discussed above.

It will be understood that the above described arrangements of apparatus and the methods therefrom are merely illustrative of applications of the principles of this invention and many other embodiments and modifications may be made without departing from the scope of the invention as defined in the claims.

Claims

1. A mounting surface for use with a concrete cutting saw having a circular cutting blade that rotates about a longitudinal axis, said mounting surface being configured so that it has a generally triangular shape with three sides of unequal length and generally rounded corners joining the sides.
2. The mounting surface of Claim 1, wherein the surface comprises two substantially straight

sides having different lengths and an arcuate third side, each side being connected to one another by arcuate corners.

3. The mounting surface of Claims 1 or 2, wherein said surface includes a rotating blade mounting member with a center point on the axis of rotation with a horizontal axis and vertical axis therethrough, said mounting surface comprising a first corner with a radius of about 3.4 mm, said radius extending from a point located in front of the vertical axis and about 12.4 mm from the center point and at an angle of about 0 degrees from the horizontal axis, a second corner with a radius of about 4.1 mm, said radius extending from a point located behind the vertical axis and about 11.4 mm from the center point and at an angle of about 54 degrees above the horizontal axis, a third corner with a radius of about 3.6 mm, said radius extending from a point located behind the vertical axis and about 11.0 mm from the center point and at an angle of about 66 degrees below the horizontal axis, a first side which tangentially connects the outside of said first and second sides, a second side which tangentially connects the outside of said second arc third sides, and a third side which is arcuate, having a radius of about 27.8 mm and which tangentially connects the outside of said first and third sides.
4. The mounting surface of Claims 1 or 2, wherein said surface includes a rotating blade mounting member having a center point on the axis of rotation with a horizontal axis and vertical axis therethrough, said mounting comprising a first corner having a radius R1 which emanates from a point located a distance D1 away from the center point in front of the vertical axis and along the horizontal axis, a second corner having a radius R2 such that R2 approximately equals 1.2 R1 which emanates from a point located behind the vertical axis a distance D2 away from the center point and at an angle of about 54 degrees above the horizontal axis, where D2 approximately equals .93 D1, a third corner having a radius R3 such that R3 approximately equals 1.06 R1 which emanates from a point located behind the vertical axis a distance D3 away from the center point and at an angle of about 66 degrees below the horizontal axis, where D3 approximately equals .89 D1, a first side which tangentially connects the outside of said first and second corners, a second side which tangentially connects the outside of said second and third corners, and a third side having a radius R4 emanating from a



there are fewer blade 21 and sleeve 10 positions which must be either visually or manually eliminated in order to find the correct alignment.

As will be apparent to one skilled in the art, the shape of the blade mounting member 24 may be machined directly on the end of the drive shaft 16 itself (not shown), instead of being formed on a sleeve 10 which is then secured to the shaft 16.

Further, while the mounting has been described here in use with a concrete cutting saw 12 and corresponding concrete cutting blade 21, it is contemplated that the mounting have uses in conjunction with various other cutting methods and devices.

There is thus provided a means and method for preventing a cutting blade from being mismounted on a saw. There is provided an arbor or arbor sleeve 10 on the drive shaft 16 of a saw 12. The blade mounting member 24 of the arbor sleeve 10 has a mounting surface 24 shaped so that when viewed directly and in a mirror, the shapes cannot coincide. The mounting hole 52 in the cutting blade's 21 first side 48 has a shape which corresponds to that of the mounting member 24. The cutting blade 21 is pressed onto the mounting member 24 of the sleeve 10 with the first side 48 facing away from the saw 12, as is the only orientation in which the blade 21 will fit onto the sleeve 10. The washer 54 is then placed on the shaft 16 against the first side 48 of the blade 21, and the nut 56 is threaded onto the smaller portion of the shaft 20 to secure the blade 21 to the sleeve 10 between the washer 54 and the flange 30.

Alternatively, the blade 21 may be secured by inserting the threaded bolt 58 into the hole 59 in the shaft 16 in order to press the blade 21 between the washer 54 and the flange 30, as was discussed above.

It will be understood that the above described arrangements of apparatus and the methods therefrom are merely illustrative of applications of the principles of this invention and many other embodiments and modifications may be made without departing from the scope of the invention as defined in the claims.

Claims

1. A mounting surface for use with a concrete cutting saw having a circular cutting blade that rotates about a longitudinal axis, said mounting surface being configured so that it has a generally triangular shape with three sides of unequal length and generally rounded corners joining the sides.
2. The mounting surface of Claim 1, wherein the surface comprises two substantially straight

sides having different lengths and an arcuate third side, each side being connected to one another by arcuate corners.

3. The mounting surface of Claims 1 or 2, wherein said surface includes a rotating blade mounting member with a center point on the axis of rotation with a horizontal axis and vertical axis therethrough, said mounting surface comprising a first corner with a radius of about 3.4 mm, said radius extending from a point located in front of the vertical axis and about 12.4 mm from the center point and at an angle of about 0 degrees from the horizontal axis, a second corner with a radius of about 4.1 mm, said radius extending from a point located behind the vertical axis and about 11.4 mm from the center point and at an angle of about 54 degrees above the horizontal axis, a third corner with a radius of about 3.6 mm, said radius extending from a point located behind the vertical axis and about 11.0 mm from the center point and at an angle of about 66 degrees below the horizontal axis, a first side which tangentially connects the outside of said first and second sides, a second side which tangentially connects the outside of said second arc third sides, and a third side which is arcuate, having a radius of about 27.8 mm and which tangentially connects the outside of said first and third sides.
4. The mounting surface of Claims 1 or 2, wherein said surface includes a rotating blade mounting member having a center point on the axis of rotation with a horizontal axis and vertical axis therethrough, said mounting comprising a first corner having a radius R1 which emanates from a point located a distance D1 away from the center point in front of the vertical axis and along the horizontal axis, a second corner having a radius R2 such that R2 approximately equals 1.2 R1 which emanates from a point located behind the vertical axis a distance D2 away from the center point and at an angle of about 54 degrees above the horizontal axis, where D2 approximately equals .93 D1, a third corner having a radius R3 such that R3 approximately equals 1.06 R1 which emanates from a point located behind the vertical axis a distance D3 away from the center point and at an angle of about 66 degrees below the horizontal axis, where D3 approximately equals .89 D1, a first side which tangentially connects the outside of said first and second corners, a second side which tangentially connects the outside of said second and third corners, and a third side having a radius R4 emanating from a



- point located in front of the vertical axis a distance D4 away from the center point and at an angle of about 9 degrees above the horizontal axis, such that D4 approximately equals 1.32 D1 and said third side tangentially connects the outside of said first and third corners.
5. The mounting surface of Claim 1, wherein said surface is in the shape of a trapezium.
 6. The mounting surface of Claim 1, wherein said surface is in the shape of a scalene triangle.
 7. The mounting surface of any of Claims 1-6, in which the generally triangular surface is located on an arbor sleeve.
 8. The mounting surface of any of Claims 1-6, in which the surface is located on an arbor.
 9. The mounting surface of any of Claims 1-8, wherein the generally triangular surface is located on an arbor sleeve having a distal and proximal end, comprising:
 - a bore centered therein for acceptance of said saw drive shaft;
 - a flange extending radially from said sleeve and positioned proximal of said mounting member for engaging one side of said cutting blade;
 - a shaft mounting portion located proximal of said flange for securing said arbor sleeve to said shaft; and means for securing said blade to said mounting member.
 10. A rotating concrete cutting blade which rotates about a longitudinal axis for use with a concrete cutting saw having a drive shaft with a blade mounting member, the blade having a first side and a second side on said blade, and a mounting hole therethrough, said blade characterized by being adapted for rotation about said axis by a blade mounting member with a generally triangular shape with three sides of unequal length and generally rounded corners joining the sides.
 11. The rotating concrete cutting blade of Claim 10, wherein said triangular shape comprises a scalene triangle.
 12. The rotating concrete cutting blade as defined in Claim 11, wherein said triangular shape comprises two substantially straight sides and one convex side.
 13. The rotating cutting blade of Claims 10-12, wherein said mounting hole when viewed from the first side has a center point with a horizontal axis and vertical axis therethrough, a first corner with a radius of about 3.4 mm, said radius extending from a point located in front of the vertical axis and about 12.4 mm from the center point and at an angle of about 0 degrees from the horizontal axis, a second corner with a radius of about 4.1 mm, said radius extending from a point located behind the vertical axis and about 11.4 mm from the center point and at an angle of about 54 degrees above the horizontal axis, a third corner with a radius of about 3.6 mm, said radius extending from a point located behind the vertical axis and about 11.0 mm from the center point and at an angle of about 66 degrees below the horizontal axis, a first side which tangentially connects the outside of said first and second sides, a second side which tangentially connects the outside of said second and third sides, and a third side which is arcuate, having a radius of about 27.8 mm and which tangentially connects the outside of said first and third sides.
 14. The cutting blade of Claims 10-12, wherein said mounting hole when viewed from the first side has a center point with a horizontal axis and vertical axis therethrough, a first corner having a radius R1 which emanates from a point located a distance D1 away from the center point in front of the vertical axis and along the horizontal axis, a second corner having a radius R2 such that R2 approximately equals 1.2 R1 which emanates from a point located behind the vertical axis a distance D2 away from the center point and at an angle of about 54 degrees above the horizontal axis, where D2 approximately equals .93 D1, a third corner having a radius R3 such that R3 approximately equals 1.06 R1 which emanates from a point located behind the vertical axis a distance D3 away from the center point and at an angle of about 66 degrees below the horizontal axis, where D3 approximately equals .89 D1, a first side which tangentially connects the outside of said first and second corners; a second side which tangentially connects the outside of said second and third corners, and a third side having a radius R4 emanating from a point located in front of the vertical axis a distance D4 away from the center point and at an angle of about 9 degrees above the horizontal axis, such that D4 approximately equals 1.32 D1 and said third side tangentially connects the outside of said first and third corners.



15. A method of orientating a rotating concrete cutting blade having a first and second side so that the blade is always mounted in a predetermined orientation on a drive shaft having a longitudinal axis about which the blade rotates, comprising:

providing a blade mounting member which is non-symmetrical when rotated 180 degrees about an axis orthogonal to the longitudinal axis of the shaft, said mounting surface having a generally triangular shape with three sides of unequal length;

providing a mounting hole in said blade adapted to be rotated by said triangular shaped blade mounting member;

placing said blade on said blade mounting member so that the hole in the blade coincides with the blade mounting member; and

securing said blade to rotate with said shaft.

16. The method of Claim 15, in which the securing step comprises placing a washer against said first side of said blade and then securing a nut onto said shaft against said washer to clamp the blade between said washer and said drive shaft.

17. An apparatus for mounting rotating concrete cutting blades on a rotating drive shaft, comprising:

a sleeve having a longitudinal hole sized to accommodate the insertion of at least a portion of the drive shaft into the hole, the sleeve having a blade mounting portion onto which the cutting blade is to be mounted, the blade mounting portion having a non-symmetrical shape about any axis orthogonal to the rotating drive shaft when the sleeve is mounted on the shaft, said shape comprising a generally triangular shape with three sides of unequal length.

18. An apparatus as defined in Claim 17, further comprising a flange extending radially from the sleeve and positioned adjacent the blade mounting portion so that the flange abuts the blade when the blade is installed on the sleeve.

19. An apparatus as defined in Claim 17 or 18, further comprising a threaded fastener cooperating with a threaded portion on the rotating shaft to provide a clamping force to clamp the blade against the flange.

20. The apparatus of any of Claims 17-19, further including:

a means for removably securing said cut-

ting blade to said sleeve.

Patentansprüche

- 5 1. Befestigungsfläche an einer Betonsäge mit einem um eine Längsachse rotierenden Kreissägeblatt, wobei die Befestigungsfläche in einer allgemein dreieckigen Form mit drei Seiten unterschiedlicher Länge und drei die Seiten verbindenden, generell abgerundeten Ecken ausgebildet ist.
- 10 2. Befestigungsfläche nach Anspruch 1, bei der die Fläche zwei im wesentlichen gerade Seiten mit unterschiedlichen Längen und eine bogenförmige dritte Seite aufweist, wobei jede Seite mit einer anderen durch bogenförmige Ecken verbunden ist.
- 15 3. Befestigungsfläche nach Anspruch 1 oder 2, bei der die Fläche ein Kreissägeblatt-Befestigungsteil mit einem Mittelpunkt auf der Drehachse und einer dadurch verlaufenden horizontalen Achse und vertikalen Achse aufweist, die Befestigungsfläche eine erste Ecke mit einem Radius von etwa 3,4 mm aufweist, der von einem Punkt vor der vertikalen Achse und etwa 12,4 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 0 Grad gegenüber der horizontalen Achse ausgeht, eine zweite Ecke mit einem Radius von etwa 4,1 mm, der von einem Punkt hinter der vertikalen Achse und etwa 11,4 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 54 Grad über der horizontalen Achse ausgeht, eine dritte Ecke mit einem Radius von etwa 3,6 mm, der von einem Punkt hinter der vertikalen Achse und etwa 11,0 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 66 Grad unter der horizontalen Achse ausgeht, eine erste Seite, die tangential die Außenseite der ersten und der zweiten Seite verbindet, eine zweite Seite, die tangential die Außenseite der zweiten und der dritten Seite verbindet, und eine dritte Seite, die bogenförmig mit einem Radius von etwa 27,8 mm ausgebildet ist und tangential die Außenseite der ersten und der dritten Seite verbindet.
- 20 4. Befestigungsfläche nach Anspruch 1 oder 2, bei der die Fläche ein Kreissägeblatt-Befestigungsteil mit einem Mittelpunkt auf der Drehachse und einer dadurch verlaufenden horizontalen Achse und vertikalen Achse aufweist, die Befestigungsfläche eine erste Ecke mit einem Radius R1 aufweist, der von einem Punkt mit einem Abstand D1 vom Mittelpunkt entfernt vor der vertikalen Achse und auf der horizontalen
- 25
- 30
- 35
- 40
- 45
- 50
- 55



- Achse ausgeht, eine zweite Ecke mit einem Radius R_2 , der ungefähr gleich $1,2 R_1$ ist und von einem Punkt hinter der vertikalen Achse in einem Abstand D_2 vom Mittelpunkt entfernt und in einem Winkel von etwa 54 Grad über der horizontalen Achse ausgeht, wobei D_2 ungefähr gleich $0,93 D_1$ ist, eine dritte Ecke mit einem Radius R_3 , der ungefähr gleich $1,06 R_1$ ist und von einem Punkt hinter der vertikalen Achse in einem Abstand D_3 vom Mittelpunkt entfernt und in einem Winkel von etwa 66 Grad unter der horizontalen Achse ausgeht, wobei D_3 ungefähr gleich $0,89 D_1$ ist, eine erste Seite, die tangential die Außenseite der ersten und der zweiten Ecke verbindet, eine zweite Seite, die tangential die Außenseite der zweiten und der dritten Ecke verbindet, und eine dritte Seite mit einem Radius R_4 , der von einem Punkt vor der vertikalen Achse in einem Abstand D_4 vom Mittelpunkt entfernt und in einem Winkel von etwa 9 Grad über der horizontalen Achse ausgeht, wobei D_4 ungefähr gleich $1,32 D_1$ ist und die dritte Seite tangential die Außenseite der ersten und der dritten Ecke verbindet.
5. Befestigungsfläche nach Anspruch 1, bei der die Fläche die Form eines Trapezes hat.
 6. Befestigungsfläche nach Anspruch 1, bei der die Fläche die Form eines schiefwinkligen Dreiecks hat.
 7. Befestigungsfläche nach einem der Ansprüche 1 bis 6, bei der die generell dreieckige Fläche sich auf einer Wellenbüchse befindet.
 8. Befestigungsfläche nach einem der Ansprüche 1 bis 6, bei der die Fläche sich auf einer Welle befindet.
 9. Befestigungsfläche nach einem der Ansprüche 1 bis 8, bei der die generell dreieckige Fläche sich auf einer Wellenbüchse mit einem distalen und einem proximalen Ende befindet, mit: einer inneren zentralen Bohrung zur Aufnahme der Antriebswelle 16; einem Flansch, der von der Büchse radial vorragt und proximal zu dem Befestigungsteil liegt, um in Eingriff mit einer Seite des Sägeblattes zu kommen; einem proximal zu dem Flansch liegenden Wellenbefestigungsteil zum Festlegen der Wellenbüchse an der Welle, und einer Einrichtung zum Festlegen des Blattes an dem Befestigungsteil.
 10. Beton-Kreissägeblatt, das zum Einsatz an einer Betonkreissäge mit einer ein Blattbefestigungsteil aufweisenden Antriebswelle um eine Längsachse rotiert, wobei das Blatt eine erste Seite und eine zweite Seite sowie eine durchgehende Befestigungsöffnung aufweist, dadurch gekennzeichnet, daß das Blatt zur Drehung um die Achse mit einem Blattbefestigungsteil ausgestattet ist, das eine generell dreieckige Form mit drei Seiten unterschiedlicher Länge und die Seiten verbindende, generell abgerundete Ecken aufweist.
 11. Beton-Kreissägeblatt nach Anspruch 10, bei dem die Dreiecksform ein schiefwinkliges Dreieck ist.
 12. Beton-Kreissägeblatt nach Anspruch 11, bei dem die Dreiecksform zwei im wesentlichen gerade Seiten und eine konvexe Seite aufweist.
 13. Beton-Kreissägeblatt nach den Ansprüchen 10 bis 12, bei dem die Befestigungsöffnung von der ersten Seite aus gesehen einen Mittelpunkt mit einer dadurch verlaufenden horizontalen und einer vertikalen Achse aufweist, ferner eine erste Ecke mit einem Radius von etwa 3,4 mm, der von einem Punkt vor der vertikalen Achse und etwa 12,4 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 0 Grad gegenüber der horizontalen Achse ausgeht, eine zweite Ecke mit einem Radius von etwa 4,1 mm, der von einem Punkt hinter der vertikalen Achse und etwa 11,4 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 54 Grad über der horizontalen Achse ausgeht, eine dritte Ecke mit einem Radius von etwa 3,6 mm, der von einem Punkt hinter der vertikalen Achse und etwa 11,0 mm vom Mittelpunkt entfernt und in einem Winkel von etwa 66 Grad unter der horizontalen Achse ausgeht, eine erste Seite, die tangential die Außenseite der ersten und der zweiten Seite verbindet, eine zweite Seite, die tangential die Außenseite der zweiten und der dritten Seite verbindet, und eine dritte Seite, die bogenförmig mit einem Radius von etwa 27,8 mm ausgebildet ist und tangential die Außenseite der ersten und der dritten Seite verbindet.
 14. Beton-Kreissägeblatt nach den Ansprüchen 10 bis 12, bei dem die Befestigungsöffnung von der ersten Seite aus gesehen einen Mittelpunkt mit einer dadurch verlaufenden horizontalen und einer vertikalen Achse aufweist, ferner eine erste Ecke mit einem Radius R_1 , der von einem Punkt mit einem Abstand D_1 vom Mit-



- telpunkt entfernt vor der vertikalen Achse und auf der horizontalen Achse ausgeht, eine zweite Ecke mit einem Radius R_2 , der ungefähr gleich $1,2 R_1$ ist und von einem Punkt hinter der vertikalen Achse in einem Abstand D_2 vom Mittelpunkt entfernt und in einem Winkel von etwa 54 Grad über der horizontalen Achse ausgeht, wobei D_2 ungefähr gleich $0,93 D_1$ ist, eine dritte Ecke mit einem Radius R_3 , der ungefähr gleich $1,06 R_1$ ist und von einem Punkt hinter der vertikalen Achse in einem Abstand D_3 vom Mittelpunkt entfernt und in einem Winkel von etwa 66 Grad unter der horizontalen Achse ausgeht, wobei D_3 ungefähr gleich $0,89 D_1$ ist, eine erste Seite, die tangential die Außenseite der ersten und der zweiten Ecke verbindet, eine zweite Seite, die tangential die Außenseite der zweiten und der dritten Ecke verbindet, und eine dritte Seite mit einem Radius R_4 , der von einem Punkt vor der vertikalen Achse in einem Abstand D_4 vom Mittelpunkt entfernt und in einem Winkel von etwa 9 Grad über der horizontalen Achse ausgeht, wobei D_4 ungefähr gleich $1,32 D_1$ ist und die dritte Seite tangential die Außenseite der ersten und der dritten Ecke verbindet.
15. Verfahren zum Ausrichten eines Beton-Kreissägeblattes mit einer ersten und einer zweiten Seite in der Weise, daß das Blatt stets in einer bestimmten Ausrichtung auf einer Antriebswelle mit einer Längsachse, um welche das Blatt rotiert, ausgerichtet ist, durch:
Bereitstellen eines Blattbefestigungsteils, das nicht symmetrisch ist, wenn es um eine orthogonal zur Längsachse der Welle verlaufende Achse um 180 Grad gedreht wird, wobei die Befestigungsfläche eine allgemein dreieckige Form mit drei Seiten eines schiefwinkligen Dreiecks aufweist;
Vorsehen einer Befestigungsöffnung, die von dem dreieckförmigen Blattbefestigungsteil gedreht werden kann, in dem Blatt;
Aufsetzen des Blattes auf das Blattbefestigungsteil in der Weise, daß die Öffnung in dem Blatt mit dem Blattbefestigungsteil übereinstimmt;
Festlegen des Blattes zur Drehung mit der Welle.
16. Verfahren nach Anspruch 15, bei dem der Schritt des Festlegens das Anlegen einer Unterlegscheibe gegen die erste Seite des Blattes und anschließendes Festlegen einer Schraube auf der Welle gegen die Unterlegscheibe einschließt, um das Blatt zwischen der Unterlegscheibe und der Antriebswelle einzuklemmen.
17. Vorrichtung zum Anbringen von Beton-Kreissägeblättern an einer drehbaren Antriebswelle, mit:
einer Büchse mit einer Längsöffnung von einer Größe, die das Einführen wenigstens eines Teiles der Antriebswelle in die Öffnung ermöglicht, wobei die Büchse ein Blattbefestigungsteil aufweist, an dem das Sägeblatt zu befestigen ist, wobei das Blattbefestigungsteil eine nicht symmetrische Form um eine beliebige Achse orthogonal zu der Antriebswelle aufweist, wenn die Büchse auf der Welle angebracht ist, wobei die Form generell dreieckig mit drei Seiten unterschiedlicher Länge ausgebildet ist.
18. Vorrichtung nach Anspruch 17, bei der ein Flansch radial von der Büchse vorragt und angrenzend an das Blattbefestigungsteil angeordnet ist, so daß der Flansch an dem Blatt anliegt, wenn das Blatt auf der Büchse angebracht ist.
19. Vorrichtung nach Anspruch 17 oder 18, mit einem ein Gewinde aufweisenden Befestigungsteil, das mit einem Gewindeteil an der Drehwelle zusammenwirkt, um eine Klemmkraft zum Festklemmen des Blattes gegen den Flansch zu erzeugen.
20. Vorrichtung nach einem der Ansprüche 17 bis 19, mit:
einer Einrichtung zum lösbaren Festlegen des Sägeblattes an der Büchse.
- Revendications**
1. Surface de montage destinée à une scie de découpage du béton ayant une lame de coupe circulaire qui tourne autour d'un axe longitudinal, la surface de montage étant configurée de telle sorte qu'elle présente une forme générale triangulaire avec trois côtés de longueurs inégales et des sommets à forme générale arrondie raccordant les côtés.
2. Surface de montage selon la revendication 1, comportant deux côtés sensiblement rectilignes ayant des longueurs différentes et un troisième côté en forme d'arc, chaque côté étant raccordé aux autres par des sommets arrondés.
3. Surface de montage selon la revendication 1 ou 2, comportant un élément rotatif de montage de lame ayant un point central situé sur l'axe de rotation et traversé par un axe horizontal et un axe vertical, ladite surface de



- montage comportant un premier sommet présentant un rayon d'environ 3,4 mm qui part d'un point situé en avant de l'axe vertical et à environ 12,4 mm du point central et à un angle d'environ 0 degré de l'axe horizontal, un deuxième sommet présentant un rayon d'environ 4,1 mm qui part d'un point situé en arrière de l'axe vertical et à environ 11,4 mm du point central et à un angle d'environ 54 degrés au-dessus de l'axe horizontal, un troisième sommet présentant un rayon d'environ 3,6 mm qui part d'un point situé en arrière de l'axe vertical et à environ 11,0 mm du point central et à un angle d'environ 66 degrés au-dessous de l'axe horizontal, un premier côté qui raccorde tangentielllement l'extérieur desdits premier et deuxième côtés, un deuxième côté qui raccorde tangentielllement l'extérieur desdits deuxième et troisième côtés, et un troisième côté qui est en forme d'arc ayant un rayon d'environ 27,8 mm qui raccorde tangentielllement l'extérieur desdits premier et troisième côtés.
4. Surface de montage selon la revendication 1 ou 2, comportant un élément rotatif de montage de lame ayant un point central situé sur l'axe de rotation et traversé par un axe horizontal et un axe vertical, ladite surface de montage comportant un premier sommet présentant un rayon R1 qui part d'un point situé à une distance D1 du point central en avant de l'axe vertical et le long de l'axe horizontal, un deuxième sommet présentant un rayon R2 tel que R2 égal approximativement 1,2 R1 et qui part d'un point situé en arrière de l'axe vertical à une distance D2 du point central et à un angle d'environ 54 degrés au-dessus de l'axe horizontal, où D2 égale approximativement 0,93 D1, un troisième sommet présentant un rayon R3 tel que R3 égale approximativement 1,06 R1 et qui part d'un point situé en arrière de l'axe vertical à une distance D3 du point central et à un angle d'environ 66 degrés au-dessous de l'axe horizontal, avec D3 égale approximativement 0,89 D1, un premier côté qui raccorde tangentielllement l'extérieur desdits premier et deuxième sommets, un deuxième côté qui raccorde tangentielllement l'extérieur desdits deuxième et troisième sommets, et un troisième côté ayant un rayon R4 qui part d'un point situé en avant de l'axe vertical à une distance D4 du point central et à un angle d'environ 9 degrés au-dessus de l'axe horizontal, de sorte que D4 égale approximativement 1,32 D1 et que le troisième côté raccorde tangentielllement l'extérieur desdits premier et troisième sommets.
 5. Surface de montage selon la revendication 1, ayant la forme d'un trapèze.
 6. Surface de montage selon la revendication 1, ayant la forme d'un triangle scalène.
 7. Surface de montage selon l'une des revendications 1 à 6, où la surface à forme générale triangulaire se trouve sur un manchon d'arbre.
 8. Surface de montage selon l'une des revendications 1 à 6, où la surface se trouve sur un arbre.
 9. Surface de montage selon l'une des revendications 1 à 8, où la surface à forme générale triangulaire se trouve sur un manchon d'arbre ayant une extrémité distale et une extrémité proximale, comportant :
 - un alésage centré agencé pour recevoir l'arbre d'entraînement de la scie;
 - un flasque s'étendant radialement sur ledit manchon et placé sur une zone proximale dudit élément de montage pour être en prise avec un côté de ladite lame de coupe;
 - une partie de montage d'arbre située du côté proximal dudit flasque pour fixer le manchon d'arbre à l'arbre; et
 - des moyens pour fixer ladite lame audit élément de montage.
 10. Lame rotative de coupe du béton qui tourne autour d'un axe longitudinal et destinée à une scie de découpage du béton ayant un arbre d'entraînement pourvu d'un élément de montage de lame, la lame comportant un premier côté, un second côté et un trou de montage qui la traverse, la lame étant caractérisée par le fait qu'elle est agencée pour tourner autour dudit axe au moyen d'un élément de montage de lame ayant une forme générale triangulaire avec trois côtés de longueurs inégales et des sommets à forme générale arrondie raccordant les côtés.
 11. Lame rotative selon la revendication 10, dans laquelle ladite forme triangulaire est un triangle scalène.
 12. Lame rotative selon la revendication 11, dans laquelle ladite forme triangulaire comporte deux côtés sensiblement rectilignes et un côté convexe.
 13. Lame rotative selon les revendications 10 à 12, dans laquelle ledit trou de montage, vu du premier côté, comporte un point central traversé par un axe horizontal et un axe vertical,



comportant un premier sommet présentant un rayon d'environ 3,4 mm qui part d'un point situé en avant de l'axe vertical et à environ 12,4 mm du point central et à un angle d'environ 0 degré de l'axe horizontal, un deuxième sommet présentant un rayon d'environ 4,1 mm qui part d'un point situé en arrière de l'axe vertical et à environ 11,4 mm du point central et à un angle d'environ 54 degrés au-dessus de l'axe horizontal, un troisième sommet présentant un rayon d'environ 3,6 mm qui part d'un point situé en arrière de l'axe vertical et à environ 11,0 mm du point central et à un angle d'environ 66 degrés au-dessous de l'axe horizontal, un premier côté qui raccorde tangentielllement l'extérieur desdits premier et deuxième côtés un deuxième côté qui raccorde tangentielllement l'extérieur desdits deuxième et troisième côtés, et un troisième côté qui est en forme d'arc ayant un rayon d'environ 27,8 mm qui raccorde tangentielllement l'extérieur desdits premier et troisième côtés.

14. lame de coupe selon les revendications 10 à 12, dans laquelle ledit trou de montage, vu du premier côté, comporte un point central traversé par un axe horizontal et un axe vertical, comportant un premier sommet présentant un rayon R1 qui part d'un point situé à une distance D1 du point central en avant de l'axe vertical et le long de l'axe horizontal, un deuxième sommet présentant un rayon R2 tel que R2 égale approximativement 1,2 R1 et qui part d'un point situé en arrière de l'axe vertical à une distance D2 du point central et à un angle d'environ 54 degrés au-dessus de l'axe horizontal, où D2 égale approximativement 0,93 D1, un troisième sommet présentant un rayon R3 tel que R3 égale approximativement 1,06 R1 et qui part d'un point situé en arrière de l'axe vertical à une distance D3 du point central et à un angle d'environ 66 degrés au-dessous de l'axe horizontal, où D3 égale approximativement 0,89 D1, un premier côté qui raccorde tangentielllement l'extérieur desdits premier et deuxième sommets, un deuxième côté qui raccorde tangentielllement l'extérieur desdits deuxième et troisième sommets, et un troisième côté ayant un rayon R4 qui part d'un point situé en avant de l'axe vertical à une distance D4 du point central et à un angle d'environ 9 degrés au-dessus de l'axe horizontal, de sorte que D4 égale approximativement 1,32 D1 et que le troisième côté raccorde tangentielllement l'extérieur desdits premier et troisième sommets.

15. Procédé d'orientation d'une lame rotative de coupe du béton ayant un premier et un second côté, de façon que la lame soit toujours montée dans une orientation prédéterminée sur un arbre d'entraînement ayant un axe longitudinal autour duquel tourne la lame, dans lequel :

on prévoit un élément de montage de lame qui n'est pas symétrique par rotation de 180 degrés autour d'un axe orthogonal à l'axe longitudinal de l'arbre, ladite surface de montage ayant une forme générale triangulaire avec trois côtés de longueurs inégales;

on ménage dans ladite lame un trou de montage agencé pour être entraîné en rotation par ledit élément de montage de lame à forme triangulaire;

on place ladite lame sur ledit élément de montage de lame de façon que le trou de la lame coïncide avec l'élément de montage de lame; et

on fixe ladite lame pour qu'elle tourne avec ledit arbre.

16. Procédé selon la revendication 15, dans lequel, dans l'étape de fixation, on place une rondelle contre le premier côté de la lame et l'on fixe ensuite un écrou sur l'arbre contre ladite rondelle pour serrer la lame entre la rondelle et l'arbre d'entraînement.

17. Dispositif pour le montage de lames rotatives de coupe du béton sur un arbre d'entraînement rotatif, comportant :

un manchon ayant un trou longitudinal calibré pour permettre l'insertion d'au moins une partie de l'arbre d'entraînement dans le trou, le manchon comportant une partie de montage de lame sur laquelle la lame de coupe est destinée à être montée, la partie de montage de lame ayant une forme non symétrique par rapport à n'importe quel axe orthogonal à l'arbre d'entraînement rotatif quand le manchon est monté sur l'arbre, ladite forme comprenant une forme générale triangulaire avec trois côtés de longueurs inégales.

18. Dispositif selon la revendication 17, comportant en outre un flasque s'étendant radialement sur le manchon dans une position adjacente à la partie de montage de lame, de sorte que le flasque sert de butée à la lame quand celle-ci est installée sur le manchon.

19. Dispositif selon la revendication 17 ou 18, comportant en outre un organe de fixation fileté qui coopère avec une partie filetée de l'arbre rotatif pour produire une force de serrage de la lame contre le flasque.



20. Dispositif selon l'une des revendications 17 à 19, comportant en outre :
un moyen pour fixer de manière amovible la lame de coupe au manchon.

5

10

15

20

25

30

35

40

45

50

55

14