



- (51) International Patent Classification:
E21B 33/12 (2006.01) *E21B 17/00* (2006.01)
- (21) International Application Number:
PCT/US2014/031613
- (22) International Filing Date:
24 March 2014 (24.03.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant: **HALLIBURTON ENERGY SERVICES, INC.** [US/US]; 10200 Bellaire Boulevard, Houston, TX 77072 (US).
- (72) Inventors: **FOONG, Ryan Zhe, Cong**; 112 Commonwealth Crescent, #09-308, Singapore 140112 (SG). **WONG, Daniel Lornng, Yon**; Block 274, Toh Guan Road, #01-137, Singapore 600274 (SG). **KAM, Iris Sok, Yee**; 987d Jurong West Street 93, #16-589, Singapore 644987 (SG). **CHUA, Yit Long, Raymond**; 20-130, Block 158, Bishan Street 13, Singapore 570156 (SG).
- (74) Agent: **SMITH, Marlin, R.**; Smith Ip Services, P.C., P.O. Box 997, Rockwall, TX 75087 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: CUT-TO-RELEASE PACKER WITH LOAD TRANSFER DEVICE TO EXPAND PERFORMANCE ENVELOPE




FIG. 1

(57) Abstract: A packer can include a mandrel having a longitudinal section, the packer being releasable in response to the section being severed, a slip support and a load transfer device that extends longitudinally across the section, the device being secured to the mandrel on one side of the section, and the device being secured to the member on an opposite side of the section. A method of constructing a releasable packer can include assembling a mandrel, at least one slip, a slip support and a load transfer device, the mandrel having a longitudinal section, and the packer being releasable in response to the section being severed. The assembling can include preventing relative longitudinal displacement between the device and the mandrel on one side of the section while preventing relative longitudinal displacement between the device and the member on an opposite side of the section.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

— *of inventorship (Rule 4.17(iv))*

Declarations under Rule 4.17:

Published:

— *as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii))*

— *with international search report (Art. 21(3))*