

INTERFACE DISPLAY METHOD, APPARATUS, TERMINAL, AND STORAGE MEDIUM

RELATED APPLICATION

[0001] This application claims priority to Chinese Patent Application No. 202010721105.1, entitled "INTERFACE DISPLAY METHOD, APPARATUS, TERMINAL, AND STORAGE MEDIUM" and filed with the National Intellectual Property Administration, PRC on July 24, 2020, which is incorporated herein by reference in its entirety.

FIELD OF THE TECHNOLOGY

[0002] This application relates to the field of computer and Internet technologies, and in particular, to an interface display technology.

BACKGROUND OF THE DISCLOSURE

[0003] At present, a user may control a first virtual object to initiate an attack on a hostile virtual object in a game. The hostile virtual object is in a different camp from the first virtual object.

[0004] In the related art, when the first virtual object uses a skill to attack a hostile virtual object outside a screen display picture, the user may comprehensively observe an attack range of the skill by sliding a game picture, and then control the first virtual object to cast the skill when determining that the skill can attack the hostile virtual object.

[0005] However, in the foregoing related art, the user needs to slide the display picture to learn whether the skill is aimed at the hostile virtual object located outside the screen display picture, so that the operation is complex and has low timeliness.

SUMMARY

[0006] Embodiments of this application provide an interface display method, apparatus, terminal, and storage medium, which can implement visualization of a hittable virtual object corresponding to a target operation in a map display control, reduce interactions between a user and a terminal, greatly reduce resource consumption of the terminal, and improve a running speed of a game. In addition, the operation is simple and has high timeliness. The technical solutions are as follows.

[0007] According to an aspect of the embodiments of this application, an interface display method is provided, performed by a terminal, the method including:

- [0008]** displaying a display picture corresponding to a virtual environment and a target operation control, the target operation control being configured to control a first virtual object to perform a target operation;
- [0009]** displaying an indication graph of the target operation in the display picture in response to a touch operation for the target operation control, the indication graph being used for indicating an effective range of the target operation; and
- [0010]** marking, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control, the map display control being a user interface (UI) control for displaying a virtual environment map.
- [0011]** According to an aspect of the embodiments of this application, an interface display apparatus is provided, deployed on a terminal, the apparatus including:
- [0012]** a picture display module, configured to display a display picture corresponding to a virtual environment and a target operation control, the target operation control being configured to control a first virtual object to perform a target operation;
- [0013]** a graph display module, configured to display an indication graph of the target operation in the display picture in response to a touch operation for the target operation control, the indication graph being used for indicating an effective range of the target operation; and
- [0014]** an object marking module, configured to mark, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control, the map display control being a UI control for displaying a virtual environment map.
- [0015]** According to an aspect of the embodiments of this application, a terminal is provided and includes a processor and a memory, the memory storing at least one instruction, at least one program, a code set, or an instruction set, and the at least one instruction, the at least one program, the code set, or the instruction set being loaded and executed by the processor to implement the foregoing interface display method.
- [0016]** According to an aspect of the embodiments of this application, a computer-readable storage medium is provided. The storage medium stores at least one instruction, at least one program, a code set, or an instruction set, the at least one instruction, the at least one program, the code set, or the instruction set being loaded and executed by a processor to implement the foregoing interface display method.
- [0017]** According to an aspect of the embodiments of this application, a computer program product or a computer program is provided, the computer program product or the computer program

including computer instructions, the computer instructions being stored in a computer-readable storage medium. A processor of a computer device reads the computer instructions from the computer-readable storage medium, and executes the computer instructions, to cause the computer device to perform the foregoing interface display method.

[0018] The technical solutions provided in the embodiments of this application may bring the following beneficial effects:

[0019] In response to a hittable virtual object in the effective range of the target operation, the hittable virtual object is marked in the map display control, to implement visualization of the hittable virtual object corresponding to the target operation in the map display control, provide a possibility for the target operation to accurately hit a virtual object outside a screen display picture, reduce interactions between a user and the terminal, greatly reduce resource consumption of the terminal, and improve a running speed of the game. In addition, due to the visualization of the hittable virtual object corresponding to the target operation in the map display control, sliding operations of the user on the display picture when attacking a hostile virtual object outside the screen display picture are reduced. The operation is simple and has high timeliness. The user can directly obtain an influence target of the target operation by using the map display control, reducing a probability of an operation error of the target operation, and ensuring the accuracy of the target operation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] To describe the technical solutions in embodiments of this application more clearly, the following briefly describes the accompanying drawings required for describing the embodiments. Apparently, the accompanying drawings in the following description show merely some embodiments of this application, and a person of ordinary skill in the art may still derive other accompanying drawings from these accompanying drawings without creative efforts.

[0021] FIG. 1 is a schematic diagram of a running environment of an application according to an embodiment of this application.

[0022] FIG. 2 is a flowchart of an interface display method according to an embodiment of this application.

[0023] FIG. 3 is a schematic exemplary diagram of a UI.

[0024] FIG. 4, FIG. 5, and FIG. 6 are schematic exemplarily diagrams of map display controls.

[0025] FIG. 7 is a schematic exemplary diagram of an execution flow of a minimap manager.

[0026] FIG. 8 is a schematic exemplary diagram of an execution flow of another minimap manager.

[0027] FIG. 9 is a block diagram of an interface display apparatus according to an embodiment of this application.

[0028] FIG. 10 is a block diagram of an interface display apparatus according to another embodiment of this application.

[0029] FIG. 11 is a structural block diagram of a terminal according to an embodiment of this application.

DESCRIPTION OF EMBODIMENTS

[0030] To make objectives, technical solutions, and advantages of this application clearer, the following further describes implementations of this application in detail with reference to the accompanying drawings.

[0031] FIG. 1 is a schematic diagram of a running environment of an application according to an embodiment of this application. The running environment of the application may include a terminal 10 and a server 20.

[0032] The terminal 10 may be an electronic device such as a mobile phone, a tablet computer, a game console, an ebook reader, a multimedia player, a wearable device, or a personal computer (PC). A client of an application may be installed on the terminal 10. The application may be an application that needs to be downloaded and installed, or may be a click-to-use application, and this is not limited in this embodiment of this application.

[0033] In this embodiment of this application, the application may be any application that can provide a virtual environment for a virtual object substituted and operated by a user to perform activities in the virtual environment. Typically, the application is a game application, such as a multiplayer online battle arena (MOBA) game, a battle royale (BR) game, and a third-person shooting game (TPS), a first-person shooting game (FPS) and a multiplayer gun battle survival game. Certainly, in addition to the game applications, another type of application may also present a virtual object to a user and provide a corresponding function for the virtual object. For example, the foregoing application may be a virtual reality (VR) application, an augmented reality (AR) application, a three-dimensional (3D) map application, a military simulation application, a social

application, an interactive entertainment application, or the like, and this is not limited in this embodiment of this application. Besides, virtual objects provided in different applications have different forms and corresponding functions, which may be preset according to an actual requirement, and this is not limited in this embodiment of this application. Optionally, a client of the foregoing application is run on the terminal 10. In some embodiments, the application is an application developed based on a 3D virtual environment engine. For example, the virtual environment engine is a Unity engine. The virtual environment engine may construct a 3D virtual environment, virtual objects, virtual props, and the like, to bring a more immersive gaming experience to the user.

[0034] The foregoing virtual environment is a scene displayed (or provided) when a client of an application (such as a game application) runs on a terminal. The virtual environment refers to a scene created for a virtual object to perform activities (such as game competition), such as a virtual house, a virtual island, a virtual map, or a virtual building. The virtual environment may be a simulated environment of a real world, or may be a semi-simulated and semi-fictional environment, or may be a completely fictional environment. The virtual environment may be a two-dimensional (2D) virtual environment, a 2.5-dimensional virtual environment, or a 3D virtual environment, and this is not limited in this embodiment of this application.

[0035] The foregoing virtual object may be a virtual character controlled by a user account in an application, or may be a virtual character controlled by a computer program in the application. For example, the application is a game application. The virtual object may be a game character controlled by the user account in the game application, or may be a game monster controlled by a computer program in the game application. The virtual object may be in a human form, an animal form, a cartoon form, or another form, and this is not limited in this embodiment of this application. The virtual object may be presented in a 3D form or a 2D form, and this is not limited in this embodiment of this application. Optionally, in response to the virtual environment being a 3D virtual environment, the virtual object is a 3D model created based on a skeletal animation technology. Each virtual object has a respective shape and size in the 3D virtual environment, and occupies some space in the 3D virtual environment.

[0036] In a possible implementation, the foregoing virtual objects include virtual objects in the same camp and virtual objects in different camps, that is, in the application, the virtual objects are divided into different camps. A MOBA game is used as an example. 10 users are divided into two teams of a red team and a blue team to play a game, that is, every five people form a team. In this case, the red team and virtual objects in the red team are in the same camp and are teammates,

the blue team and virtual objects in the blue team are in the same camp and are teammates, and the virtual objects in the red team and the blue team are in different camps and are in a hostile relationship.

[0037] In this embodiment of this application, the user account may control a first virtual object to attack a second virtual object. The first virtual object and the second virtual object are in different camps and are in a hostile relationship. The user account controls the first virtual object to cast a skill to attack the second virtual object. In a possible implementation, in a process of preparing to cast a skill by the first virtual object, the terminal 10 obtains an effective range of the skill and the second virtual object within the effective range. The terminal 10 marks the effective range and the second virtual object within the effective range on a map display control of a UI.

[0038] The server 20 is configured to provide a backend service for the client of the application in the terminal 10. For example, the server 20 may be a backend server of the application. The server 20 may be one server, a server cluster including a plurality of servers, or a cloud computing service center. The server 20 provides backend services for applications in a plurality of terminals 10. The terminal 10 may communicate with the server 20 through a network 30.

[0039] FIG. 2 is a flowchart of an interface display method according to an embodiment of this application. The method may be applied to a terminal. For example, an execution entity of each step may be the terminal 10 (referred to as the "client" below) in the running environment of the application shown in FIG. 1. The method may include the following steps (201 to 205):

[0040] Step 201: Display a display picture corresponding to a virtual environment and a target operation control.

[0041] A virtual environment is a scene created by an application for virtual objects to perform activities. The virtual environment includes virtual islands, virtual maps, and virtual buildings. A user may control a virtual object to interact with the virtual environment through a user account, such as entering a virtual building in the virtual environment, and attacking other virtual objects in the virtual environment. The application may be an application that needs to be downloaded and installed, or may be a click-to-use application.

[0042] The display picture is a picture on which the virtual environment is displayed to the user on the UI. The display picture is a picture captured by a virtual camera from the virtual environment. In a possible implementation, the virtual camera obtains a picture of the virtual environment from a third perspective. Generally, the virtual camera is set obliquely above the first

virtual object. The client uses the virtual camera to observe the virtual environment with the first virtual object as the center, obtains a picture of the virtual environment with the first virtual object as the center, generates the display picture corresponding to the virtual environment, and displays the display picture corresponding to the virtual environment in the UI. In another possible implementation, the virtual camera obtains a picture of the virtual environment from a first perspective. Generally, the virtual camera is set directly in front of the first virtual object. The client observes the virtual environment from the perspective of the first virtual object, obtains a picture of the virtual environment with the first virtual object as the first perspective, generates the display picture corresponding to the virtual environment, and displays the picture corresponding to the virtual environment in the UI. Certainly, in other possible implementations, the placement position of the virtual camera is adjustable in real time. The user may adjust the location of the virtual camera through a control operation for the UI, and then observe the display picture corresponding to the virtual environment at different locations. For example, the user may adjust the location of the virtual environment through a picture operation (such as a drag operation) for the UI. The UI is a picture of the foregoing application displayed to the user on the client.

[0043] In this embodiment of this application, after receiving a user-triggered start instruction for the application, the client controls the application to run, and upon receiving a game start instruction, calls the virtual camera to display the display picture corresponding to the virtual environment in the UI. While displaying the display picture corresponding to the virtual environment, the client may display the target operation control in the UI. The target operation control is configured to control the first virtual object to perform a target operation. For example, the user may click/tap the target operation control to control the first virtual object to perform the target operation, or may press a key (for example, the R key) corresponding to the target operation control to control the first virtual object to perform the target operation. In different applications, target operations corresponding to the target operation control are different.

[0044] In a possible implementation, the target operation is to cast a skill, that is, the target operation control is configured to control the first virtual object to cast a skill. For example, after receiving an execution instruction of the target operation, the client controls the first virtual object to cast a skill corresponding to the target operation control. In actual application, the UI may include a plurality of operation controls for casting skills, and different operation controls are configured to cast different skills.

[0045] In another possible implementation, the target operation is to use a virtual item, that is, the target operation control is configured to control the first virtual object to use the virtual item,

such as a virtual prop or a virtual weapon. For example, after receiving the execution instruction of the target operation, the client controls the first virtual object to use a corresponding virtual prop. In actual application, the UI may include a plurality of operation controls for using virtual props, and different operation controls are configured to use different virtual props.

[0046] In still another possible implementation, the target operation is state switching, that is, the target operation control is configured to control the first virtual object to switch to a state. For example, after receiving the execution instruction of the target operation, the client controls the first virtual object to switch to a target state. In actual application, the UI may include a plurality of operation controls. Different operation controls may correspond to different states. Certainly, the same operation control may also correspond to different states. For example, for an operation control, if the user clicks/taps the operation control once, the first virtual object is controlled to switch to a forward jumping state; and if the user clicks/taps the operation control twice, the first virtual object is controlled to switch to a backward jumping state.

[0047] Certainly, in actual application, the application may configure the target operation corresponding to the target operation control according to an actual situation, and this is not limited in this embodiment of this application.

[0048] Step 202: Display an indication graph of the target operation in the display picture in response to a touch operation for the target operation control.

[0049] The touch operation is an operation of the user at any location on the UI. In this embodiment of this application, the touch operation is an operation performed by the user for the target operation control. For example, the user may perform the touch operation of the target operation control by clicking/tapping the target operation control in the UI, or may perform the touch operation of the target operation control by pressing a corresponding key on the keyboard (for example, the R key).

[0050] In this embodiment of this application, after displaying the UI of the application, the client may monitor the UI, and after detecting a touch operation in the UI, obtain a trigger position of the touch operation. When the trigger position is in a trigger region of the target operation control, it is determined that the touch operation is a touch operation for the target operation control.

[0051] In a possible implementation, a location of each operation control in the UI is fixed, and a fixed trigger region of each operation control is set in the application. The fixed trigger region may be any location in the UI, for example, the fixed trigger region of the target operation control is a surrounding region of the target operation control. For example, the client may determine,

according to the trigger position, whether the touch operation is located in the fixed trigger region of the target operation control. If the touch operation is located in the fixed trigger region of the target operation control, it is determined that the touch operation is the touch operation of the target operation control.

[0052] In another possible implementation, the location of each operation control in the UI is adjustable, that is, the user may adjust the location of each operation control in the UI according to an actual situation. In this case, an activity trigger region of each operation control is set in the application. The activity trigger region may be any region based on the location of the target operation control. For example, the activity trigger region of the target operation control is a region that is spaced from a center position of the target operation control by a distance less than a target value. For example, the client may determine a distance between the trigger position and the center position of the target operation control according to the trigger position. If the distance is less than the target value, it is determined that the touch operation is the touch operation of the target operation control.

[0053] In the case that the client detects the touch operation for the target operation control, the indication graph of the target operation is displayed on the display picture. The indication graph is used for indicating an effective range of the target operation, and the effective range is an actual influence range of the target operation, such as an attack range of an attack skill, a throwing position of a virtual prop, or a jumping impact range of a virtual object.

[0054] In this embodiment of this application, the indication graph may also be referred to as a surface indicator, and the surface indicator is configured to indicate an effective range of the target operation on the ground of the virtual environment. After detecting the touch operation for the target operation control, the client may obtain the effective range of the target operation corresponding to the target operation control, and map the effective range to the ground of the virtual environment in the form of an indication graph, to further display the indication graph of the target operation on the display picture.

[0055] For example, referring to FIG. 3, in a UI 30, after detecting a touch operation on a target operation control 31, the client displays an indication graph 32 of an effective range of a target operation corresponding to the target operation control 31 on the ground of the virtual environment.

[0056] The effective range may be an influence range of the target operation, or may be an intersection range of the influence range of the target operation and a screen region of the client, and this is not limited in this embodiment of this application.

[0057] Step 203: Mark, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control.

[0058] The hittable virtual object is used for indicating a virtual object to which the target operation is targeted and that has a hit probability. After determining the effective range of the target operation, the client predicts an influence target of the target operation according to the effective range, and determines the hittable virtual object corresponding to the target operation.

[0059] In this embodiment of this application, different target operations are targeted at different virtual objects. In a possible implementation, the target operation has an attack attribute, so that the virtual object targeted by the target operation is a virtual object in a hostile camp of the first virtual object. In another possible implementation, the target operation has a gain attribute, so that the virtual object targeted by the target operation is a virtual object in the same camp of the first virtual object. After determining the effective range of the target operation, the client determines that the virtual object within the effective range is a virtual object with a hit probability, and traverses the virtual object with a hit probability. If the virtual object with a hit probability is the virtual object targeted by the target operation, it is determined that there is a hittable virtual object in the effective range of the target operation. Certainly, after determining the effective range of the target operation control, the client may further obtain location information of the virtual object targeted by the target operation in the virtual environment according to attribute information of the target operation, and determine, according to the location information, whether there is a hittable virtual object in the effective range.

[0060] In this embodiment of this application, when there is a hittable virtual object in the effective range of the target operation, the client marks the hittable virtual object in the map display control. The map display control is a UI control configured to display a virtual environment map. The virtual environment map is used for expressing spatial distribution, connection, a quantity, and quality features, development and change states in time of various things in the virtual environment. The map displayed in the map display control may be in the 2D or 3D form, to quickly and intuitively reflect the current virtual environment to the user, so that the user can formulate use strategies and implement operations. A game application is used as an example. The map display control may also be referred to as a map or a minimap, which is used for displaying terrain and landforms of the virtual environment provided in the game application in the 2D or 3D form, such as positions of a base camp, an offensive line, a defensive tower, a river channel, and a tree. For example, as shown in FIG. 4, a map display control 40 includes a first virtual building 41 and a second virtual building 42 in a virtual environment. A presentation picture of the map display

control may be a dynamic picture that changes in real time. For example, when a virtual building in the virtual environment is destroyed, the presentation picture of the map display control is updated, and the updated map display control includes ruins left after the virtual building is destroyed. In a possible implementation, the map display control includes icons of virtual objects in the virtual environment, and the client may add a mark on an icon of the hittable virtual object when marking the hittable virtual object. In another possible implementation, the map display control does not include the icons of the virtual objects in the virtual environment. The client may add the icon of the hittable virtual object to the map display control when marking the hittable virtual object, thereby marking the hittable virtual object.

[0061] The map display control may display a global map of the virtual environment or a partial map of the virtual environment, and this is not limited in this embodiment of this application. For example, if the user needs to monitor a part of the virtual environment in real time, the user may set the map display control. After obtaining a display parameter corresponding to the map display control, the client controls the map display control to display only part of the virtual environment set by the user.

[0062] The map display control is a UI operation control, which can receive and respond to user operations, such as responding to clicking/tapping, dragging, and zooming operations.

[0063] In a possible implementation, the user may control a display style of the map display control in the UI through a control operation for the map display control. For example, the user may control the zoom-in or zoom-out display of the map display control through a click/tap operation or by sliding a mouse wheel. Certainly, to facilitate user operation, the map display control may be set with a default display scale, and the user may control the map display control to be displayed at the default display scale by a click/tap operation. The map display control displayed at the default display scale includes the global map of the virtual environment or the partial map set by the user. In another example, the user controls, by clicking/tapping a location on the virtual environment map in the map display control, the map display control to display a virtual environment map corresponding to the location. When receiving the click/tap operation, the client switches the presentation picture of the map display control to a display picture of the virtual environment map centered on the location.

[0064] In another possible implementation, the user may switch from the currently displayed virtual environment picture to a virtual environment picture corresponding to the location through the map display control, to observe a real-time situation of the location in the virtual environment. If the user clicks on a location of the map display control, correspondingly, after

receiving a click/tap operation for the location, the client switches the display picture of the virtual environment to a display picture corresponding to the location. The display picture corresponding to the location does not include the foregoing first virtual object. Certainly, the user may alternatively switch the display picture corresponding to the virtual environment in the UI through a drag operation for the map display control. After receiving the drag operation for the map display control, the client switches the display picture corresponding to the virtual environment in the UI to the display picture corresponding to the virtual environment indicated by the current virtual environment map according to the current virtual environment map displayed in the map display control.

[0065] It may be understood that the map display control may be displayed in the UI when the display picture corresponding to the virtual environment is displayed, or may be displayed in the UI when it is determined that there is a hittable virtual object in the effective range of the target operation. This is not limited in this embodiment of this application. Certainly, in other possible implementations, the map display control may be hidden, and a map display control icon is displayed on the UI after hiding. The user may restore the display of the map display control by operating the map display control icon.

[0066] The map display control may be displayed at any position in the UI, where the any position may be a position set by a designer or a position set by the user. This is not limited in this embodiment of this application.

[0067] In conclusion, in the technical solution provided in this embodiment of this application, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object is marked in the map display control, to implement visualization of the hittable virtual object corresponding to the target operation in the map display control, provide a possibility for the target operation to accurately hit a virtual object outside a screen display picture, reduce interactions between a user and the terminal, greatly reduce resource consumption of the terminal, and improve a running speed of the game. In addition, due to the visualization of the hittable virtual object corresponding to the target operation in the map display control, sliding operations of the user on the display picture when attacking a hostile virtual object outside the screen display picture are reduced. The operation is simple and has high timeliness. The user can directly obtain an influence target of the target operation by using the map display control, reducing a probability of an operation error of the target operation, and ensuring the accuracy of the target operation.

[0068] The following describes the specific marking method of the hittable virtual object.

[0069] In a possible implementation, the map display control includes icons of virtual objects in the virtual environment, and the client may display hittable prompt information corresponding to an icon of a second virtual object in the map display control. The second virtual object is the hittable virtual object corresponding to the target operation. In this case, the foregoing step 203 includes the following steps:

[0070] 1. Determine a virtual object list according to location information of virtual objects in the virtual environment and the effective range of the target operation.

[0071] The location information of the virtual object is used for indicating a position of the virtual object in the virtual environment. The location information of the virtual object includes position coordinates of the virtual object. In this embodiment of this application, after determining the effective range of the target operation, the client obtains the location information of the virtual objects in the virtual environment, screens out virtual objects within the effective range according to the location information of the virtual objects, and determines the virtual object list corresponding to the target operation. The virtual object list includes a target virtual object in the effective range of the target operation.

[0072] The target virtual object is a virtual object targeted by the target operation. In this embodiment of this application, the client may determine the target virtual object according to attribute information of the target operation, and the attribute information may include an attack attribute, an auxiliary attribute, and the like. For example, if the target operation has the attack attribute, the target virtual object is a virtual object in a hostile camp of the first virtual object; if the target operation has the auxiliary attribute, the target virtual object is a virtual object in the same camp as the first virtual object; and if the target operation has both the attack attribute and the auxiliary attribute, the target virtual object is a global virtual object in the virtual environment.

[0073] In a possible implementation, after detecting the touch operation for the target operation control, the client may obtain the attribute information of the target operation corresponding to the target operation control, determine the target virtual object corresponding to the target operation, obtain the location information of the target virtual object, determine the target virtual object in the effective range according to the location information of the target virtual object and the effective range of the target operation, and generate the virtual object list.

[0074] 2. Obtain a list of icons in a display state in the map display control.

[0075] The list of icons includes icons of virtual objects. The icon is used for representing a corresponding virtual object, and the icon may be a profile picture of the virtual object, a name of

the virtual object, a user account name of the virtual object, or the like. In this embodiment of this application, after determining the virtual object list, the client may obtain the list of icons in the display state in the map display control. When a virtual object is not blocked by an obstacle, an icon of the virtual object in the map display control is in a display state; and when the virtual object is blocked by an obstacle, the icon of the virtual object in the map display control is in a non-display state. The obstacle may be any virtual item in the virtual environment that blocks the perspective of the virtual object, or may be a virtual item with a shielding function set by the designer in the virtual environment, and this is not limited in this embodiment of this application.

[0076] 3. Traverse the virtual objects corresponding to the icons in the list of icons, to determine whether a virtual object corresponding to an icon in the list of icons is in the virtual object list.

[0077] In this embodiment of this application, after obtaining the list of icons, the client traverses the virtual objects corresponding to the icons in the list of icons, and determines whether the virtual object is in the virtual object list.

[0078] 4. Determine that the virtual object corresponding to the icon is the second virtual object in response to the virtual object corresponding to the icon being in the virtual object list, and display hittable prompt information corresponding to an icon of a second virtual object in the map display control.

[0079] In this embodiment of this application, after traversing the virtual objects corresponding to the icons in the list of icons, the client determines that the virtual object corresponding to the icon is the second virtual object in response to the virtual object corresponding to the icon being in the virtual object list, and displays the hittable prompt information corresponding to the icon of the second virtual object in the map display control. The hittable prompt information is used for indicating that the second virtual object is the hittable virtual object. In a possible implementation, the hittable prompt information is an indication identifier. For example, the client may add an indication identifier on the icon of the second virtual object, and the indication identifier is used for indicating that the second virtual object is a hittable virtual object. As shown in FIG. 3, after determining a second virtual object 33, the client adds an indication identifier 36 to an icon 35 of the second virtual object in a map display control 34 to indicate that the second virtual object 33 is a hittable virtual object. In another possible implementation, the hittable prompt information is color information. Correspondingly, the client may add any color to the icon of the second virtual object, and the color is used for indicating that the second virtual object is a hittable virtual object.

[0080] In this embodiment of this application, the client cancels the display of the hittable prompt information corresponding to the icon of the second virtual object in the map display control in response to the second virtual object not being the hittable virtual object.

[0081] In a possible implementation, after marking the second virtual object, the client monitors the position of each virtual object in the virtual environment. If the second virtual object moves outside the effective range, it is determined that the second virtual object is not a hittable virtual object, and the display of the hittable prompt information corresponding to the icon of the second virtual object is canceled in the map display control. Certainly, if there is another target object that moves to the effective range, the another target object is determined to be the second virtual object, and the hittable prompt information corresponding to the icon of the second virtual object is displayed in the map display control.

[0082] In another possible implementation, the client detects that the touch operation for the target operation control disappears, and then determines that the second virtual object is not a hittable virtual object, and cancels the display of the hittable prompt information corresponding to the icon of the second virtual object in the map display control. The touch operation of the target operation control may disappear when the user stops the touch operation for the target operation control, or may disappear when the user triggers the generation of an interception instruction for the target operation control. The interception instruction is an instruction generated through an operation cancellation control corresponding to the target operation in the UI when the user aborts the execution of the target operation.

[0083] In this embodiment of this application, if the client receives an execution instruction for the target operation, hit prompt information corresponding to the icon of the second virtual object is displayed in the map display control. The execution instruction is used for controlling the first virtual object to perform the target operation corresponding to the target operation control, and the hit prompt information is used for indicating that the target operation hits the second virtual object. For example, referring to FIG. 5, after receiving the execution instruction of the target operation control, the client converts the map display control 34 into a map display control 50, cancels the indication identifier 36 in the map display control 34, and converts a display style of the icon 35 of the second virtual object, to obtain an icon 51 of the second virtual object after the hit prompt information is added. Optionally, the execution instruction of the target operation control may be triggered to be generated when the client detects that the user stops the touch operation on the target operation control. Certainly, in this embodiment of this application, because the virtual

object may be moved, the hittable virtual object and a hit virtual object corresponding to the target operation may be the same or different.

[0084] In another possible implementation, the map display control does not include the icons of the virtual objects in the virtual environment. The client may add the icon of the hittable virtual object to the map display control when marking the hittable virtual object, thereby marking the hittable virtual object. As shown in FIG. 4, when the touch operation for the target operation control is not detected, the map display control 40 includes the first virtual building 41 and the second virtual building 42. After the touch operation for the target operation control is detected, the map display control 40 is switched to a map display control 43, where the map display control 43 includes an icon 44 of a hittable virtual object. In this case, the foregoing step 203 includes the following steps:

[0085] 1. Display the map display control.

[0086] In this embodiment of this application, to reduce the processing overhead of the terminal, the client displays the map display control on the UI after detecting the touch operation of the target operation control. The presentation picture corresponding to the map display control may be determined according to the effective range of the target operation. After determining the effective range of the foregoing target operation, the client determines a display range of the virtual environment map according to the effective range. The display range is used for indicating the display range of the virtual environment map corresponding to the map display control, and the display range is larger than the effective range. The client then determines the presentation picture corresponding to the map display control based on the display range, obtains a thumbnail parameter of the map display control, scales the presentation picture according to the thumbnail parameter to obtain the map display control, and displays the map display control. In this case, the map display control includes a complete virtual environment picture within the effective range, thereby ensuring the integrity of display information of the map display control. In addition, a virtual environment picture outside the effective range may not be displayed in the map display control, thereby reducing unnecessary overhead caused by scaling of an invalid picture. The thumbnail parameter is used for indicating a size ratio of the map display control to the presentation picture.

[0087] 2. Obtain location information of the hittable virtual object.

[0088] After displaying the map display control, the client obtains the location information of the hittable virtual object. The method for determining the hittable virtual object is described in the embodiments of FIG. 2, so the details are not repeated herein.

[0089] 3. Display an icon of the hittable virtual object in the map display control according to the location information of the hittable virtual object, and mark the icon of the hittable virtual object.

[0090] In this embodiment of this application, after obtaining the location information of the hittable virtual object, the client determines whether the hittable virtual object is blocked by an obstacle according to the location information. If the hittable virtual object is not blocked by an obstacle, it is determined that the hittable virtual object is in a hittable and displayable state, and the icon of the hittable virtual object is displayed in the map display control, to mark the icon of the hittable virtual object. If the hittable virtual object is blocked by an obstacle, it is determined that the hittable virtual object is in a hittable and undisplayable state, and the icon of the hittable virtual object is not displayed in the map display control. If the hittable virtual object is blocked by an obstacle with a blocking effect, it is determined that the hittable virtual object is in an unhittable and undisplayable state, and the icon of the hittable virtual object is not displayed in the map display control.

[0091] Certainly, in actual application, when obtaining the hittable virtual object, the client may directly obtain a virtual object in the hittable and displayable state as the hittable virtual object, and may directly display the icon of the hittable virtual object in the map display control according to the location information of the hittable virtual object after obtaining the location information of the hittable virtual object.

[0092] In this embodiment of this application, the map display control may further display a thumbnail indication graph of the target operation. For example, after detecting the touch operation for the target operation control, the client may display a thumbnail indication graph of the target operation in the map display control. The thumbnail indication graph is a simplified graphic representation of the indication graph in the map display control. As shown in FIG. 3, a thumbnail indication graph 37 in the map display control 33 is the indication graph 32 used for indicating the effective range in the UI 30. The specific steps for obtaining the thumbnail indication graph are as follows:

[0093] 1. Obtain attribute information of the touch operation.

[0094] The attribute information of the touch operation is used for indicating a display style of the indication graph of the effective range of the target operation. After detecting the touch operation for the target operation control, the client obtains the attribute information of the touch operation, where the attribute information includes a display size, a display position, and display texture of the indication graph.

[0095] 2. Generate a first graph parameter according to the attribute information of the touch operation.

[0096] The first graph parameter is used for indicating a display parameter of the thumbnail indication graph. The client may determine the display style of the indication graph in the display picture corresponding to the virtual environment according to the first graph parameter.

[0097] In this embodiment of this application, after obtaining the attribute information of the touch operation, the client generates the first graph parameter according to the attribute information of the touch operation, and determines the display style of the indication graph indicated by the attribute information in the display picture corresponding to the virtual environment according to the first graph parameter.

[0098] 3. Determine a second graph parameter based on the first graph parameter.

[0099] The second graph parameter is used for indicating a display parameter of the thumbnail indication graph. The client may determine a display style of the thumbnail indication graph in the map display control according to the second graph parameter.

[0100] In a possible implementation, after generating the first graph parameter, the client determines the second graph parameter according to the first graph parameter and a scaling coefficient of the map display control, and displays the thumbnail indication graph of the target operation in the map display control according to the second graph parameter.

[0101] In another possible implementation, the client determines the display style of the indication graph in the display picture corresponding to the virtual environment based on the first graph parameter, and maps the display style of the indication graph in the display picture corresponding to the virtual environment to the map display control according to the scaling coefficient of the map display control.

[0102] In this embodiment of this application, different target operations correspond to different thumbnail indication graphs. In a possible implementation, if the target operation is a directional operation, the thumbnail indication graph includes a straight line graph that uses an icon of the first virtual object as a starting point and that points to a selected direction of the target operation, as the thumbnail indication graph 37 shown in FIG. 3. In another possible implementation, if the target operation is a positional operation, the thumbnail indication graph includes: a range prompt graph that uses an icon of the first virtual object as a center and that corresponds to the effective range of the target operation, and a location prompt graph corresponding to a selected execution location of the target operation. The range prompt graph is

used for prompting the effective range of the target operation, and the location prompt graph is used for prompting an influence location of the target operation in the virtual environment. For example, referring to FIG. 6, the map display control 60 includes an icon 61 of the first virtual object, a range prompt graph 62, and a location prompt graph 63.

[0103] In this embodiment of this application, to ensure the accuracy of the display of the map display control, the client needs to update data of each frame of the display picture corresponding to the virtual environment, and update the map display control by using the updated data. For example, the client may obtain movement data of a virtual object and location adjustment data of a target operation in real time. According to the movement data of the virtual object, the hittable virtual object in the map display control is updated, marking of the hittable virtual object that moves out of the effective range is canceled, and the hittable virtual object that moves into the effective range is marked. Correspondingly, according to the location adjustment data of the target operation, the location of the thumbnail indication graph in the map display control is updated, an effective range after the update is determined, and the hittable virtual object after the location adjustment is marked according to the updated effective range. The location adjustment data of the target operation may be data acquired from a location adjustment region of the target operation. For example, the user generates the location adjustment data of the target operation through a sliding instruction for the location adjustment region of the target operation, and correspondingly, the client obtains the location adjustment data.

[0104] In this embodiment of this application, a minimap manager may be provided in the application. The user of the minimap manager manages the map display control, such as controlling display and disappearance of the thumbnail indication graph in the map display control, and the controlling display and disappearance of the hittable prompt information. For example, referring to FIG. 7 and FIG. 8, the minimap manager is described.

[0105] For example, when the touch operation for the target operation control is detected, the minimap manager performs the steps shown in FIG. 7. When receiving the touch operation for the target operation control, the client obtains the attribute information of the touch operation, and determines the display parameter of the thumbnail indication graph of the effective range of the target operation according to the attribute information of the touch operation; and the minimap manager displays the thumbnail indication graph on the map display control according to the display parameter of the thumbnail indication graph. The client then determines the effective range of the target operation according to the attribute information of the touch operation, determines the hittable virtual object corresponding to the target operation according to the effective range, and

generates a virtual object list according to the hittable virtual object; and the minimap manager traverses the icons of the virtual objects in the map display control according to the virtual object list, to determine whether the virtual object corresponding to the icon is in the virtual object list. If the virtual object corresponding to the icon is in the virtual object list, the icon of the virtual object is marked in the map display control; and if the virtual object corresponding to the icon is not in the virtual object list, the icon of the virtual object is not marked in the map display control.

[0106] For example, when it is detected that the touch operation for the target operation control disappears, the minimap manager performs the steps shown in FIG. 8. The client detects that the touch operation for the target operation control disappears, and the minimap manager destroys the thumbnail indication graph corresponding to the effective range of the target operation control in the map display control. The client then generates an empty list; and the minimap manager traverses the icons of the virtual objects in the map display control, and determines whether the icon of the virtual object is marked. If the icon of the virtual object is marked, the marking of the icon of the virtual object is canceled in the map display control; and if the icon of the virtual object is not marked, the icon of the virtual object is not processed.

[0107] The following is an apparatus embodiment of this application, which may be used for performing the method embodiments of this application. For details not disclosed in the apparatus embodiment of this application, reference may be made to the method embodiments of this application.

[0108] FIG. 9 is a block diagram of an interface display apparatus according to an embodiment of this application. The apparatus has functions of implementing the foregoing interface display method. The functions may be implemented by hardware, or may be implemented by hardware executing corresponding software. The apparatus may be a terminal or may be disposed in a terminal. The apparatus 900 may include a picture display module 910, a graph display module 920, and an object marking module 930.

[0109] The picture display module 910 is configured to display a display picture corresponding to a virtual environment and a target operation control, the target operation control being configured to control a first virtual object to perform a target operation.

[0110] The graph display module 920 is configured to display an indication graph of the target operation in the display picture in response to detecting a touch operation for the target operation control, the indication graph being used for indicating an effective range of the target operation.

[0111] The object marking module 930 is configured to mark, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control, the map display control being a UI control for displaying a virtual environment map.

[0112] In an exemplary embodiment, the object marking module 930 includes a first display unit.

[0113] The first display unit is configured to display hittable prompt information corresponding to an icon of a second virtual object in the map display control, the hittable prompt information being used for indicating that the second virtual object is the hittable virtual object.

[0114] In an exemplary embodiment, the object marking module 930 further includes an information cancellation unit.

[0115] The information cancellation unit is configured to cancel the display of the hittable prompt information corresponding to the icon of the second virtual object in the map display control in response to the second virtual object not being the hittable virtual object.

[0116] In an exemplary embodiment, the object marking module 930 further includes a second display unit.

[0117] The second display unit is configured to display hit prompt information corresponding to the icon of the second virtual object in the map display control in response to an execution instruction for the target operation, the hit prompt information being used for indicating that the target operation hits the second virtual object.

[0118] In an exemplary embodiment, the object marking module 930 further includes a list determining unit, a list obtaining unit, a list traversing unit, and a step execution unit.

[0119] The list determining unit is configured to determine a virtual object list according to location information of virtual objects in the virtual environment and the effective range of the target operation, the virtual object list including a target virtual object located in the effective range of the target operation.

[0120] The list obtaining unit is configured to obtain a list of icons in a display state in the map display control, the list of icons including icons of virtual objects.

[0121] The list traversing unit is configured to traverse the virtual objects corresponding to the icons in the list of icons, to determine whether a virtual object corresponding to an icon in the list of icons is in the virtual object list.

[0122] The step execution unit is configured to determine that the virtual object corresponding to the icon is the second virtual object in response to the virtual object corresponding to the icon being in the virtual object list, and perform the operation of displaying hittable prompt information corresponding to an icon of a second virtual object in the map display control.

[0123] In an exemplary embodiment, as shown in FIG. 10, the apparatus 900 further includes a thumbnail display module 940.

[0124] The thumbnail display module 940 is configured to display a thumbnail indication graph of the target operation in the map display control in response to detecting the touch operation for the target operation control, the thumbnail indication graph being a simplified graphic representation of the indication graph in the map display control.

[0125] In an exemplary embodiment, in response to the target operation being a directional operation, the thumbnail indication graph includes a straight line graph that uses an icon of the first virtual object as a starting point and that points to a selected direction of the target operation.

[0126] In an exemplary embodiment, in response to the target operation being a positional operation, the thumbnail indication graph includes: a range prompt graph that uses an icon of the first virtual object as a center and that corresponds to the effective range of the target operation, and a location prompt graph corresponding to a selected execution location of the target operation.

[0127] In an exemplary embodiment, as shown in FIG. 10, the apparatus 900 further includes an attribute obtaining module 950, a parameter generation module 960, and a parameter determining module 970.

[0128] The attribute obtaining module 950 is configured to obtain attribute information of the touch operation.

[0129] The parameter generation module 960 is configured to generate a first graph parameter according to the attribute information of the touch operation, the first graph parameter being used for indicating a display parameter of the indication graph.

[0130] The parameter determining module 970 is configured to determine a second graph parameter based on the first graph parameter, the second graph parameter being used for indicating a display parameter of the thumbnail indication graph.

[0131] In an exemplary embodiment, the object marking module 930 includes a map display unit, a location obtaining unit, and an icon display unit.

[0132] The map display unit is configured to display the map display control.

[0133] The location obtaining unit is configured to obtain location information of the hittable virtual object.

[0134] The icon display unit is configured to display an icon of the hittable virtual object in the map display control according to the location information of the hittable virtual object, and mark the icon of the hittable virtual object.

[0135] In an exemplary embodiment, the map display unit is configured to: determine a display range of the virtual environment map according to the effective range, the display range being larger than the effective range; determine a presentation picture corresponding to the map display control based on the display range; obtain a thumbnail parameter of the map display control, the thumbnail parameter being used for indicating a size ratio of the map display control to the presentation picture; scale the presentation picture according to the thumbnail parameter, to obtain the map display control; and display the map display control.

[0136] In conclusion, in the technical solution provided in this embodiment of this application, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object is marked in the map display control, to implement visualization of the hittable virtual object corresponding to the target operation in the map display control, provide a possibility for the target operation to accurately hit a virtual object outside a screen display picture, reduce interactions between a user and the terminal, greatly reduce resource consumption of the terminal, and improve a running speed of the game. In addition, due to the visualization of the hittable virtual object corresponding to the target operation in the map display control, sliding operations of the user on the display picture when attacking a hostile virtual object outside the screen display picture are reduced. The operation is simple and has high timeliness. The user can directly obtain an influence target of the target operation by using the map display control, reducing a probability of an operation error of the target operation, and ensuring the accuracy of the target operation.

[0137] When the apparatus provided in the foregoing embodiments implements functions of the apparatus, the division of the foregoing functional modules is merely an example for description. In the practical application, the functions may be assigned to and completed by different functional modules according to the requirements, that is, the internal structure of the device is divided into different functional modules, to implement all or some of the functions described above. In addition, the apparatus and method embodiments provided in the foregoing embodiments belong to the same conception. For the specific implementation process, reference may be made to the method embodiments, and details are not described herein again.

[0138] FIG. 11 is a structural block diagram of a terminal 1100 according to an embodiment of this application. The terminal 1100 may be an electronic device such as a mobile phone, a tablet computer, a game console, an ebook reader, a multimedia player, a wearable device, or a PC. The terminal is configured to implement the interface display method provided in the foregoing embodiments. The terminal may be the terminal 10 in the game running environment shown in FIG. 1. Specifically:

[0139] Generally, the terminal 1100 includes a processor 1101 and a memory 1102.

[0140] The processor 1101 may include one or more processing cores. For example, the processor may be a 4-core processor or an 8-core processor. The processor 1101 may be implemented by using at least one hardware form of a digital signal processor (DSP), a field programmable gate array (FPGA), and a programmable logic array (PLA). The processor 1101 may alternatively include a main processor and a coprocessor. The main processor is a processor that is configured to process data in an awake state and also referred to as a central processing unit (CPU), and the coprocessor is a low-power processor configured to process data in an idle state. In some embodiments, the processor 1101 may be integrated with a graphics processing unit (GPU). The GPU is configured to render and draw content that needs to be displayed on a display. In some embodiments, the processor 1101 may further include an artificial intelligence (AI) processor. The AI processor is configured to process computing operations related to machine learning.

[0141] The memory 1102 may include one or more computer-readable storage media that may be non-transitory. The memory 1102 may further include a high-speed random access memory (RAM) and a non-volatile memory, such as one or more magnetic disk storage devices or flash storage devices. In some embodiments, the non-transient computer-readable storage medium in the memory 1102 is configured to store at least one instruction, at least one program, a code set, or an instruction set, the at least one instruction, the at least one program, the code set, or the instruction set being configured to be executed by one or more processors to implement the foregoing interface display method.

[0142] In some embodiments, the terminal 1100 may alternatively include: a peripheral interface 1103 and at least one peripheral. The processor 1101, the memory 1102, and the peripheral interface 1103 may be connected through a bus or a signal cable. Each peripheral may be connected to the peripheral interface 1103 through a bus, a signal cable, or a circuit board. Specifically, the peripheral includes at least one of a radio frequency (RF) circuit 1104, a display screen 1105, a camera component 1107, an audio circuit 1107, a positioning component 1108, and a power supply 1109.

[0143] A person skilled in the art may understand that the structure shown in FIG. 11 constitutes no limitation on the terminal 1100, and the terminal may include more or fewer components than those shown in the figure, or some components may be combined, or a different component deployment may be used.

[0144] In an exemplary embodiment, a computer-readable storage medium is further provided, the storage medium storing at least one instruction, at least one program, a code set, or an instruction set, the at least one instruction, the at least one program, the code set, or the instruction set, when executed by the processor, implementing the foregoing interface display method.

[0145] Optionally, the computer-readable storage medium may include: a read-only memory (ROM), a RAM, a solid state drive (SSD), an optical disc, or the like. The RAM may include a resistance random access memory (ReRAM) and a dynamic random access memory (DRAM).

[0146] In an exemplary embodiment, a computer program product or a computer program is provided. The computer program product or the computer program includes computer instructions, and the computer instructions are stored in a computer-readable storage medium. A processor of a computer device reads the computer instructions from the computer-readable storage medium, and executes the computer instructions, to cause the computer device to perform the foregoing interface display method.

[0147] It is to be understood that "plurality of" mentioned in this specification means two or more. And/or describes an association relationship for associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: only A exists, both A and B exist, and only B exists. The character "/" generally indicates an "or" relationship between the associated objects. In addition, the step numbers described in this specification merely schematically show a possible execution sequence of the steps. In some other embodiments, the steps may not be performed according to the number sequence. For example, two steps with different numbers may be performed simultaneously, or two steps with different numbers may be performed according to a sequence contrary to the sequence shown in the figure. This is not limited in the embodiments of this application.

[0148] The foregoing descriptions are merely exemplary embodiments of this application, but are not intended to limit this application. Any modification, equivalent replacement, or improvement made within the spirit and principle of this application shall fall within the protection scope of this application.

CLAIMS

1. An interface display method, performed by a terminal, the method comprising:

displaying a display picture corresponding to a virtual environment and a target operation control, the target operation control being configured to control a first virtual object to perform a target operation;

displaying an indication graph of the target operation in the display picture in response to a touch operation for the target operation control, the indication graph being used for indicating an effective range of the target operation;

marking, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control, the map display control being a user interface (UI) control for displaying a virtual environment map;

determining a virtual object list according to location information of virtual objects in the virtual environment and the effective range of the target operation, the virtual object list comprising a target virtual object located in the effective range of the target operation;

obtaining a list of icons in a display state in the map display control, the list of icons comprising icons of virtual objects;

traversing the virtual objects corresponding to icons in the list of icons, to determine whether a virtual object corresponding to an icon in the list of icons is in the virtual object list;

determining that the virtual object corresponding to the icon is a second virtual object in response to the virtual object corresponding to the icon being in the virtual object list; and

displaying hittable prompt information corresponding to the icon of the second virtual object in the map display control,

the hittable prompt information being used for indicating that the second virtual object is the hittable virtual object.

2. The method according to claim 1, wherein after the displaying hittable prompt information corresponding to an icon of a second virtual object in the map display control, the method further comprises:

canceling displaying the hittable prompt information corresponding to the icon of the second virtual object in the map display control, in response to the second virtual object not being the hittable virtual object.

3. The method according to claim 1, wherein after the displaying hittable prompt information corresponding to an icon of a second virtual object in the map display control, the method further comprises:

displaying hit prompt information corresponding to the icon of the second virtual object in the map display control in response to an execution instruction for the target operation,

the hit prompt information being used for indicating that the target operation hits the second virtual object.

4. The method according to claim 1, further comprising:

displaying a thumbnail indication graph of the target operation in the map display control in response to the touch operation for the target operation control,

the thumbnail indication graph being a simplified graphic representation of the indication graph in the map display control.

5. The method according to claim 4, wherein in response to the target operation being a directional operation, the thumbnail indication graph comprises a straight line graph that uses an icon of the first virtual object as a starting point and that points to a selected direction of the target operation.

6. The method according to claim 4, wherein in response to the target operation being a positional operation, the thumbnail indication graph comprises: a range prompt graph that uses an icon of the first virtual object as a center and that corresponds to the effective range of the target operation, and a location prompt graph corresponding to a selected execution location of the target operation.

7. The method according to claim 4, wherein before the displaying a thumbnail indication graph of the target operation in the map display control, the method further comprises:

obtaining attribute information of the touch operation;

generating a first graph parameter according to the attribute information of the touch operation, the first graph parameter being used for indicating a display parameter of the indication graph; and

determining a second graph parameter based on the first graph parameter, the second graph parameter being used for indicating a display parameter of the thumbnail indication graph.

8. An interface display apparatus, deployed on a terminal, the apparatus comprising:

a picture display module, configured to display a display picture corresponding to a virtual environment and a target operation control, the target operation control being configured to control a first virtual object to perform a target operation;

a graph display module, configured to display an indication graph of the target operation in the display picture in response to a touch operation for the target operation control, the indication graph being used for indicating an effective range of the target operation; and

an object marking module, configured to mark, in response to a hittable virtual object in the effective range of the target operation, the hittable virtual object in a map display control, the map display control being a user interface (UI) control for displaying a virtual environment map;

wherein the object marking module is configured to determine a virtual object list according to location information of virtual objects in the virtual environment and the effective range of the target operation, the virtual object list comprising a target virtual object located in the effective range of the target operation; obtain a list of icons in a display state in the map display control, the list of icons comprising icons of virtual objects; traverse the virtual objects corresponding to icons in the list of icons, to determine whether a virtual object corresponding to an icon in the list of icons is in the virtual object list; determine that the virtual object corresponding to the icon is a second virtual object in response to the virtual object corresponding to the icon being in the virtual object list; and display hittable prompt information corresponding to the icon of the second virtual object in the map display control, the hittable prompt information being used for indicating that the second virtual object is the hittable virtual object.

9. A terminal for interface display, comprising a processor and a memory, the memory storing at least one instruction, at least one program, a code set, or an instruction set, the at least one instruction, the at least one program, the code set, or the instruction set being loaded and executed by the processor to implement the interface display method according to any one of claims 1 to 7.

10. A computer-readable storage medium, storing at least one instruction, at least one program, a code set, or an instruction set, the at least one instruction, the at least one program, the code set, or the instruction set being loaded and executed by a processor to implement the interface display method according to any one of claims 1 to 7.

11. A computer program product, the computer program product, when executed, being configured to implement the interface display method according to any one of claims 1 to 7.