



CONTACTOR APPARATUS COMPRISING MEANS FOR AUTOMATICALLY
OPENING POWER CIRCUITS AND A LOCAL CONTROL DEVICE

Description

The invention relates to a contactor apparatus comprising an electromagnet controlling power contacts and having means for automatically opening these power contacts each of which responds, on the one hand, to the appearance
5 of short circuit currents in one of the power circuits through a first coil and a striker and, on the other hand, to the appearance of overload currents either instantaneous or of a longer duration through a second coil associated with a plate and, respectively, with a bimetallic strip, each power contact
10 being adapted to cooperate, after striking, with a locking member which holds it in the open position, this apparatus having a local control member adapted to reset the automatic opening means and to close again a control switch placed in series with the coil of the electromagnet.

15 Such contactors, which are intended for ensuring simultaneously the power supply of consumer apparatus and the rapid protection thereof as well as that of the lines which feed them, avoid the series connection of two apparatus each having a system of switches one of which carries
20 out the on and off operation while the other ensures the protection ; it is in fact known that such an association between these two systems of switches requires a coordination which it is difficult to obtain because of the radically different properties which are required not only insofar as
25 their closing powers are concerned, but also their opening

speeds. This coordination is all the more delicate to achieve since each of these types of switches may be offered to the public by different suppliers and since their properties are not always known by the users.

5 In a known apparatus, corresponding to the general construction mentioned above, the striking devices and the magnetic devices which must respond to the appearance of excess currents of different values and duration use one and the same coil, so that the adjustments of the above-
10 mentioned thresholds are not totally independent ; moreover, this known apparatus is not concerned with the whole of the functions which it would be desirable to reserve for the local control.

When it is provided for the resetting of the apparatus
15 to take place by means of a control, whether this be local or remote, it is necessary to take measures for providing total decoupling between members which ensure the automatic safety function and those which, either simultaneously or subsequently to an automatic break, must be actuated for
20 opening the circuits and respectively putting the apparatus into service or putting it again into service ; the aim of this decoupling is, on the one hand, to avoid a local closing action performed on the local control member, in the presence of a fault, from being followed by an effect and,
25 on the other hand, to ensure that an automatic break causing the movement of certain indispensable parts is not accompanied by the movement of other mechanical elements not required for accomplishing the safety function.

According to the invention, the result sought is attained because the local control member is subjected to an internal elastic force and cooperates

- on the one hand with a first sudden tripping mechanism of which it forms part and which is adapted to retain it in a first stable position "F", given by external means, and which effects closure of the control switch for this single position "F", and

- cooperates on the other hand with a second sudden tripping mechanism, either so as to maintain a second stable position "O" which is given to the control member by external means, or so as to assume automatically a third stable position "D" located between the preceding ones, when the first mechanism is tripped by the second mechanism, this second mechanism being tripped by thrusts exerted without connection,

- either directly by a means reacting when the mobile contact of the power contact is locked following the energization of said first coil associated with the striker and placed in series with the power contact,

- or indirectly by a third sudden tripping mechanism which is released by the movements supplied by a plate of said second coil or respectively by a bimetallic strip, placed in series with the first coil and with the power contact,

- these second and third mechanisms receiving a resetting movement supplied by the local control member when this latter is brought by external means into a fourth position "R", which is opposite the first position.

The invention, as well as other aims and other measures relating to complementary results such as matching to the current of use current detector members using coils and/or bimetallic strips which act on the third mechanism 5 will be better understood from reading the following description.

In the accompanying drawings :

- figures 1a and 1b show respectively a first and a second general electromechanical diagram of the apparatus of 10 the invention ;

- figure 2 illustrates a schematical view of the apparatus in which appear the different functions and the respective arrangement of the elements which provide them ;

- figure 3 shows schematically one embodiment where 15 the apparatus is formed by the association of mechanical subassemblies mounted beforehand, and

- figure 4 shows a nonlimiting embodiment of the means used for achieving the different functions.

In the general diagram showing an apparatus in accordance with the invention and shown in figure 1a, an electromagnet 1 provides actuation of one or a multiplicity n of power contacts such as 2 ; this actuation is unidirectional because a return spring 36 of an armature 29 of this electromagnet pushes back, without connection, a mobile contact 25 12 of each power contact against the action of a contact pressure spring 15 which bears on the case 20 of the apparatus and which tends to close the contact ; this unidirectional action is indicated by f when the armature is

attracted and the contact is closed and $\bar{f}$ in the opposite case.

The electromagnet comprises a coil 3 which is placed in series with the control switch 4 in a control circuit 7 5 having terminals 6 and 5 adapted to receive an external voltage when the power contacts are to be closed.

The electromagnet and the power contacts are similar to those of a contactor with a view to effecting the corresponding functions.

10 A power circuit 8, passing through the power contact 2 is connected between the connection terminals 10 and 9 for connection to a network and respectively to a consumer apparatus, not shown.

Circuit 8 comprises, in series with the contact 2, a 15 coil 11 with which is associated a striker 28 which is moved very rapidly when the circuit has flowing therethrough currents such as those which appear during a full short circuit downstream of the apparatus.

This striker, in this case, may push back the mobile 20 contact 12, independently of the armature of the electromagnet, as far as an open position greater than that which is provided by the springs of the armature. This action is shown by the reference a.

In this position, the mobile contact 12 cooperates 25 with a resilient bolt 16 which is adapted to retain it so as to prevent reclosure of the circuit after the appearance of such a fault.

Circuit 8 further comprises in series a second coil 13

which cooperates, in a way known per se, with a plate 34 or a plunger core, not shown, so as to communicate thereto a rapid movement shown by b, when there appear in this circuit high instantaneous currents such as those which are met with 5 during overloads of short duration or when impeding short circuits occur.

A bimetallic strip 14 is also placed in series in circuit 8 and supplies a deflection indicated by c when there appear in this circuit currents, smaller than the preceding ones, but of longer duration such as those which develop during small but prolonged overloads.

A first resettable sudden tripping mechanism 31 is associated mechanically by a transmission means, shown schematically by 32, to a local control member 18 and receives 15 from this latter a unidirectional elastic force delivered by a spring 35.

This mechanism 31, of which the transmission means 32 forms part, is adapted to retain, by an action m, the local control member in a first stable position "F" which is communicated thereto from the outside, for example by manual 20 action on this member ; member 18 is released by an action $\bar{m}$ when this first mechanism 31 is tripped by internal means p of the apparatus which will be described subsequently.

This first mechanism 31 further governs the closing 25 and opening states of the control switch 4 through actions e and respectively $\bar{e}$, closing being provided only when this mechanism secures the position "F" of the control member.

When switch 4 is closed, the electromagnet 1 may be energized by an order signal applied to terminals 5 and 6

for closing the power contacts 2.

The control member 18 also cooperates, for example, through the same transmission 32, with a second sudden tripping mechanism 17 through contact actions shown by j.

5 This second sudden tripping mechanism 17 is adapted to deliver the action p when it is tripped by one of the two movements g or d provided by internal means during an internal automatic opening procedure of the apparatus.

The action shown generally by g results from energization of coil 11 by a very high current and could thus be delivered by the striker 28 itself or by a plate (not shown) which would be associated with coil 11.

In a preferred embodiment of the invention, illustrated below, action g is delivered by bolt 16 as soon as
15 this latter has assumed a position corresponding to the effective locking of the mobile contact 12, so that the appearance of action g corresponds effectively to the appearance, in coil 11, of a current of sufficient intensity for the striker to bring the mobile contact into a locked
20 endmost open position.

The action shown by d is delivered by a third sudden tripping mechanism 19, when this latter is released by the appearance of one of the two actions b or c defined above. These two actions g and d are unidirectional, that is to say
25 that they transmit movements without permanent connection of the two parts, preferably by a thrust. The two sudden tripping mechanisms 17, 19 are reset, one by the other, by means of a local control member 18 through actions shown by

J and respectively K when a particular resetting position "R" is communicated thereto ; this resetting movement also exerts an unlocking action h transmitted by the second mechanism 17 for releasing the mobile contact 12 of the 5 resilient bolt 16.

While the resetting operation is being carried out, which is transmitted from the second sudden tripping mechanism 17 to the third sudden tripping mechanism 19, switch 4 remains open.

10 Furthermore, resetting of the second mechanism 17 can only take place if the third mechanism 19 is in a condition to be reset, i.e. in the absence of actions b and c ; as for the resetting position, switch 4 is open, the power contact 2 is necessarily open so that only an action c developed by 15 bimetallic strip 14, which is still hot, may in fact prevent immediate resetting of the second mechanism 19.

The local control member 18 moves between two opposite endmost positions, "F" corresponding to the closing of switch 4 and "R" corresponding to the resetting operation. A 20 local external, for example manual, stable open position "O" of switch 4 is placed between these two endmost positions. This opening of switch 4 is achieved because, when the local control member leaves position "F", an action $\bar{m}$ is established between the transmission 32 and the first mechanism 25 31.

When a fault, of whatever nature it may be, appears in the power circuit 8, the second sudden tripping mechanism 17 immediately causes switch 4 to be opened by the first mechanism 31, but then assumes an intermediate tripped

condition which confers on the local control member 18 by action j a stable intermediate position "D" located between positions "F" and "0" ; this position cannot be given to the local control member by manual action thereon. Positions 5 "F", "D" and "0" are then all three stable positions of the control member so that this member 18 restores not only an exact image of the states of the apparatus, but also informs the user about the nature of the events by which they were produced : local external action or internal automatic 10 opening.

Position "R" is on the contrary unstable and can only be obtained by maintaining a permanent force, manual or otherwise, on the local control member and, possibly, against a second resilient action of a spring shown by 30.

15 If we assume that the apparatus has been originally placed in the closed position "F" and that there then appears a short circuit current, the local control member assumes an automatic tripped condition "D" ; resetting of the apparatus requires this control member to be moved, by 20 external means, first of all to position "0" then to position "R" (and then brought to the position "F"). Since, for a fault of this nature, the bimetallic strip has not been sufficiently deformed and since coil 13 has not had sufficient time to act, the third mechanism 19 is not released, 25 the second mechanism has first of all been reset (action j) and has then been able to release the mobile contact 12 of its bolt 16 (action h) ; since switch 4 can only be closed by the first mechanism 31 because of action e when the local

control member reaches position "F", this closure will cause (if voltage is still present at terminals 5, 6) energization of the electromagnet and so closure of the power contact 2. If the short circuit is still present, coil 11 will energize 5 the striker 28 which will again open the mobile contact 12 and will cause release of the first sudden tripping mechanism, which will cause immediate reopening of switch 4 and so that of the power contacts 2. However, in the case of previous action of mechanism 17, mechanism 31 maintains 10 action $\bar{e}$ opening contact 4 so that the voluntary holding of member 18 in position F does not produce, should a permanent fault occur, the forced reclosure of contact 4.

If, on the contrary, the apparatus was originally placed in position "F" and if a slow overload then appears 15 which causes the thermal deflection of the bimetallic strips 14, the control member assumes an automatic tripped position "D" but action c maintains its state during a certain time required for cooling these bimetallic strips.

As long as the bimetallic strips have not cooled down, 20 neither the third sudden tripping mechanism 19 nor, consequently, the second mechanism 17 can be reset, when the control member 18 is placed in position "R". The result is that, since action p is still present, the first sudden tripping mechanism 31 cannot be reset by an action m which 25 will be communicated thereto by the control member 18 when this latter reaches position D.

In the general diagram shown in figure 1a, the un-

locking h and resetting k actions or movements communicated to bolt 16 and respectively to the third sudden tripping mechanism 19 follow separate paths from those which are followed by the tripping actions g and respectively d.

5 The invention includes however a variation shown in figure 1b in which the actions g and h respectively d and K are transmitted by two paths q, $\bar{q}$, and respectively r, $\bar{r}$ which thus use the same transmission means, shown by the continuous line and a dotted line.

10 As in the preceding cases, the transmission of orders q, $\bar{q}$, and that of orders r, $\bar{r}$ must occur without mechanical connection between 11 and 17 or between 19 and 17, for example by a thrust. In the variation illustrated, bolt 16 transmits the action q to mechanism 17 and receives from
15 this latter action $\bar{q}$; bolt 16 may in its turn lock either directly the mobile contact 12, or indirectly this latter, by engaging a part which communicates the movement thereto, for example the striker 28 or a rod for transmitting action a.

20 An advantageous embodiment of the apparatus of the invention is shown in figure 2 which illustrates how the different members are respectively arranged in a case and how they cooperate with each other.

 The tripping mechanisms 31, 17 and 19 as well as the
25 transmission means 32 are disposed in an upper region 37 of the case which has a front face 26 and the local control member 18 cooperating with a scale 33 indicating the positions "F", "D", "O" and "R".

 The switching members comprising the power contacts 2,

24

coils 11 and bolts 16 are distributed in a central region 38 and between this upper region 37 and a lower fixing face 25 opposite the front face 26.

The main parts of the electromagnet 1 common to all 5 the contacts 2 are disposed in a first lateral region 39 between region 37 and the rear face 25.

The assembly of the coils 13 and bimetallic strips 14 is disposed in a second lateral region 40 opposite the first lateral region.

10 In an embodiment derived from figure 2 and shown in figure 3, the apparatus comprises several associated subassemblies namely : a base 20 having the rear face 25 in which opens a multiplicity n of pockets 41 adapted to receive removable cartridges 24 each comprising a power contact 2, a 15 coil 11, a striker 28 and a bolt 16. A bearing surface 42 of the base receives a mechanical plate 22 containing the members 31, 32, 17, 18 and at least a fixed or mobile part of the control switch 4, which allows easy previous assembly of these members. A removable subassembly 21 placed laterally 20 receives at least a part of the electromagnet 1 comprising for example a fixed yoke and giving access to coil 3 for replacement thereof, the coil being also able to come with this subassembly. The mobile parts of the electromagnet 1, such as the armature 29, the return spring 36 and a mobile 25 part of pusher integral with, or driven by, the armature will then be fixed on the base of the apparatus so as to be located opposite the assembly of the mobile contacts 12 of the power contacts 2, adjustment screws disposed on this

mobile pusher, respectively opposite each mobile contact, will further permit actuation of these contacts to be effected simultaneously.

In a more detailed diagram shown in figure 4, where 5 the elements which have just been described bear the same references, the transmission principle shown symbolically in figure 1b is put into practice.

The electromagnet 1 comprises a fixed yoke 44 and the mobile armature 29 cooperates with a pusher 45 having a 10 first arm 46 and a second arm 47. The first arm 46 acts on a first tripper device 48 adapted to separate the mobile contact 12 from the fixed contacts 49, 50 of the power contact 2. Striker 28 transmits its movement to a second pivoting pusher 51 having a spring 52 and having a first arm 15 53 adapted to raise the same tripper device 48, independently of 46 ; a second arm 54 cooperates with a surface 55 of a bolt 16 which is compressed by a spring 56 and which has a movement transmission end 57. A dotted line surrounding by 24 the parts which have just been described represents the contents of the power contact cartridge 24. When coil 11 attracts the rapid striker 28, the second pusher 51 is rocked and raises the tripper device 48. Because of the retraction of end 54, surface 55 is released and bolt 16 holds, by means of a lateral bearing surface 58, the second 20 pusher 51 in the position which it has just assumed. At the same time, end 57 transmits an action q to the second sudden tripping mechanism 17.

A removable protection module 23 contains the bimetallic strips 14 and their heaters 58 as well as coils 13 and their plates 59. The deflections c and movements b are transmitted to the third sudden tripping mechanism 19, which
5 comprises a pusher 60 receiving actions b and c and cooperating with a locking lever 61 subjected to the action of a spring 62 for locking and holding in position by its nose 63 a flange 67 which belongs to a rod 64. This latter is compressed by a spring 65 and has an end 66 adapted to
10 communicate to the second sudden tripping mechanism 17 an action r.

The second sudden tripping mechanism 17 comprises a pusher 68 receiving the actions q and r and cooperating with a locking lever 69 subjected to a spring 70 for locking, by
15 means of its nose 71, a flange 72 which belongs to a rod 73. This latter is compressed by a spring 74 and has, on the one hand, a heel 75 adapted to communicate to the first sudden tripping mechanism 31 and action p and, on the other hand, an end 76 placed opposite a surface 77 of pusher 68. Rod 73
20 further has an external pin 78 adapted to communicate and receive actions or movements j and respectively j̄ by cooperation with mobile part 32.

The first sudden tripping mechanism 31 comprises a locking device 79 subjected to the action of a spring 80
25 which gives thereto a rest position by abutment against a stop 81. This lever 79 has an insulating pusher 84 adapted to open the mobile contact 82 of the control switch 4 and a locking tooth 83 adapted to cooperate with the mobile part

32 to communicate thereto and to receive therefrom actions m and $\bar{m}$. The mobile part 32 which is subjected to the action of return spring 35 and which is integral with the local control member 18 has a finger 85 adapted to cooperate with a spring 30 and, on the other hand, a multiplicity of ramps and surfaces adapted to cooperate with a tooth 83 and with the pin 78. In the position of part 32 corresponding to position "F" of the local control member, switch 4 is closed and, in the presence of a voltage signal at terminals 5,6, the armature 29 is attracted so that the power contacts 2 are also closed ; the apparatus is thus brought into service. For this stable position, which has been provided by an external action on 18, a ramp 86 of 32 is applied resiliently in direction S against tooth 83 and is retained by this latter. The appearance of a fault, either by action q, or by action r, shifts the second mechanism 17 whose heel 75 raises the end 87 of lever 79. Cooperation of the tooth 83 and the inclined ramp 86 causes sudden tripping of 31 which opens switch 4 and releases part 32 ; in this movement, tooth 83 then comes to bear on a holding surface 88 of part 32 and lever 79 is in a working position in which switch 4 remains open. When heel 75 has moved, pin 78 has taken up a higher position, shown with a dotted line, which allows it to cooperate with a second inclined ramp 89 when this latter moves in direction S ; part 32 is thus stopped by the pin in a stable position "D" corresponding to the appearance of a fault.

If an external action is communicated in direction S

to the control member 18, the ramp 89 escapes from the pin, which it pushes back slightly, so that this latter, after sliding against surface 90, comes into abutment against the beginning of a third inclined ramp 91 ; part 32 is then held
5 in a stable position "0" corresponding to opening of the apparatus by external means. In this position "0", finger 85 comes into the neighbourhood of spring 30. If a movement in direction S is imparted to the part 32 by the control member 18, this latter may reach an unstable position "R" opposite
10 "F" in which spring 30 is compressed ; in this latter movement, the inclined ramp 91 exerts on pin 78 a resetting action] which pushes it back downwards of the figure. The movement of rod 73 is transmitted by heel 76 to the surface 77 and to pusher 68 which, in its turn, transmits the
15 movement received to ends 57 and 66. The second sudden tripping mechanism 17 is reset during this operation when nose 71 catches on flange 72. The movements of bolt 16 and rod 64 then allow, on the one hand, bolt 54 to be unlocked and contact 2 to be closed and, on the other hand, the third
20 mechanism 19 to be reset if the bimetallic strips have cooled down. If, in the presence of a non-cooled bimetallic strip, a movement is imparted to part 32 from position "R" to position "F", tooth 83 of locking lever 79 will remain in a working position under the effect of the thrust P of heel
25 75 mechanisms 17, 19 not having been able to be reset. For this working position of lever 79, tooth 83 cannot cooperate with ramp 86 so that switch 4 will remain open and power contacts 2 cannot close. The only stable position which the

local control member 18 may assume will then be the position "D", or the position "0" if a corresponding action is exerted on this member.

Accessorily, the apparatus may be used for putting 5 into effect measures for effecting forced opening of the power contacts 2, more especially should they be welded together. Such forced opening is achieved automatically by a procedure set off by a fault, or by an action, for example manual, on the local control member, between positions "F" 10 and "0". To this end, part 32 has a fourth ramp 92 adapted to cooperate between positions "F" and "0", with a transmission rod or other means 93 for exerting on the arm 47 of lever 45 an action comparable to that which is exerted by spring 36, but of a greater strength. A voluntary movement of part 32 15 in direction S, by action on the control member 18, may obviously be obtained from position "F" towards position "0" to make the apparatus inoperative. During this operation, ramp 86 pushes back tooth 83 while causing abrupt rocking of the lever which produces instantaneous opening of switch 4.

20 It should moreover be understood that, although in figure 4 the surfaces or ramps 88, 86, 89, 90, 91 have been physically separated so as to make their respective functions clearer, some of them could be combined so as to make the construction of part 32 simpler ; such a combination 25 would for example be possible if tooth 83 and pin 73 were placed closer to one another or if their movements were not parallel.

The movements, assumed rectilinear in figure 4, may be

obtained by means of guide surfaces not shown ; movements along adjacent or curved paths could also be used and obtained by known means, for example if part 32 is a disc carrying the ramps and pivoting about an axis YY'.

- 5 Generally, the invention may be implemented by using locking or tripping means which provide the same functions or which react in a way comparable to those which have been shown schematically by way of nonlimiting example.



CLAIMS

1. A contactor apparatus comprising an electromagnet
(1) for controlling power contacts (2) and means for automati-
cally opening these power contacts (2) which each respond, on
the one hand, to the appearance of short circuit currents in
5 one of the power circuits through a first coil (11) and a stri-
ker (22), and, on the other hand, to the appearance of overload
currents either instantaneous or of longer duration through a
second coil (13) associated with a plate (34) and, respectively
with a bimetallic strip (14), each power contact (2) being adap-
10 ted to cooperate, after striking, with a locking member (16)
which holds it in the open position, this apparatus having a
local control member (18) adapted to reset the automatic open-
ing means and to close again a control switch (4) placed in se-
ries with the coil (3) of the electromagnet (1), characterized
15 in that the local control member (18) is subjected to an intern-
al resilient force (35) and cooperates :

- on the one hand with a first sudden tripping mecha-
nism (31) of which it forms part (32) and which is adapted to
hold it in a first stable position (F), obtained by external
20 means, and which effects closure (e) of the control switch
(4) for this single position (F), and

- cooperates, on the other hand, (j) with a second
sudden tripping mechanism (17), either so as to maintain a
second stable position (O) which is given to the control
25 member by external means, or so as to assume automatically
a third stable position (D) between the preceding ones, when
the first mechanism is tripped by the second mechanism, this



second mechanism being tripped by thrusts (g, d) exerted without connection,

- or directly by means (16) reacting when the mobile contact (28) of the power contact (2) is locked following energization of the first coil (11) associated with the striker (28) placed in series with the power contact (2),

- or indirectly by a third sudden tripping mechanism (19) which is released by the movements (b, c) supplied by a plate of said second coil (13) or respectively a bimetallic strip (14), placed in series with the first coil and with the power contact (2) ;

- the second and third mechanisms (17, 19) receiving a resetting movement ($\bar{j}$, K) supplied by the local control member (18) when this latter is brought by external means into a fourth position (R) which is opposite the first position.

2. The contactor apparatus according to claim 1, characterized in that the sudden tripping of the first mechanism (31) is obtained by the cooperation of a locking lever (79) with a surface (86) carried by a mobile part (32) which is associated with the local control member (18), this lever cooperating also with the second sudden tripping mechanism (17).

3. The contactor apparatus according to one of claims 1 or 2, characterized in that the resetting ($\bar{r}$ or k) and unlocking ($\bar{q}$ or h) movements applied to the third sudden tripping mechanism (19) and respectively to the bolt (16) which maintains a power contact (2) in the open position,



23

after a short circuit, are transmitted by the second sudden tripping mechanism (17).

4. The contactor apparatus according to claim 3, characterized in that the resetting ($\bar{r}$) and unlocking ($\bar{q}$) movements are transmitted by the same paths as those which communicate the tripping actions (r and respectively q) the second sudden tripping mechanism (17).

5. The contactor apparatus according to one of claims 1 to 4, characterized in that it comprises a base (20) 10 having a multiplicity (n) of pockets (41) adapted each to receive a removable power contact cartridge (24) containing the fixed and mobile elements (49, 50, 12, 15) of the contact (2), a coil (11), a pusher (48), a bolt (16) and its return spring (56) and a striker (28).

15 6. The contactor apparatus according to claim 5, characterized in that the removable protection module (23), containing a multiplicity (n) of bimetallic strips (13) and coils (14) and the third sudden tripping mechanism (19), is fixed to the base and is connected elec- 20 trically to the coils (11).

7. The contactor apparatus according to claim 5 or 6, characterized in that a mechanical plate (22) containing the first and second sudden tripping mechanisms (31) respectively (17), the control member (18) and a trans- 25 mission part or means (32), is fixed to the base (20).

8. The contactor apparatus according to claim 7, characterized in that this plate (22) contains at least a



34

part of the fixed or mobile elements of the control switch (4).

9. The contactor apparatus according to claim 8, characterized in that a removable subassembly (21) containing at least a part (44) (3) of the fixed elements of the electromagnet (1) is removably fixed to the base (20) to give access to the coil (3) of the electromagnet (1).

10. The contactor apparatus according to one of claims 2 to 9, characterized in that the mobile transmission part (32) occupies the said first position (F) through the cooperation of a surface (86) with a locking tooth (83) of the first tripping mechanism (31) and assumes said third and second positions (D and 0) through the cooperation of a pin (78) of the second mechanism (17) with other surfaces (89, 91) carried by this mobile part (32).

11. The contactor apparatus according to claim 10, characterized in that said pin (78) receives from a surface (91) of the mobile transmission part (32) a resetting action acting on the second sudden tripping mechanism (17).

12. The contactor apparatus according to one of claims 2 to 11, characterized in that movement transmission means (93) are adapted to cooperate with a mobile part (45) of the electromagnet (1) and with a particular surface (92) of the mobile part (32) so as to effect forced opening of the power contacts (2) between said first and second positions (F and 0) of the local control member.