



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B66B 13/26		A1	(11) International Publication Number: WO 00/47511
			(43) International Publication Date: 17 August 2000 (17.08.00)
(21) International Application Number: PCT/NZ00/00013		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 11 February 2000 (11.02.00)			
(30) Priority Data: 334144 11 February 1999 (11.02.99) NZ 502037 23 December 1999 (23.12.99) NZ			
(71) Applicant (for all designated States except US): TL JONES LIMITED [NZ/NZ]; 46b Halwyn Drive, Christchurch (NZ).			
(72) Inventors; and (75) Inventors/Applicants (for US only): WATSON, Russell [NZ/NZ]; 19 Birdwood Avenue, Beckenham, Christchurch (NZ). WOODHEAD, Ian [NZ/NZ]; McDurys Road, Ladbrooks RD4, Christchurch (NZ). VISSCHEDIJK, Harrie [NL/NZ]; 45 Norwood Street, Beckenham, Christchurch (NZ). BURKITT, Dave [GB/NZ]; 63 Evesham Crescent, Spreydon, Christchurch (NZ).			
(74) Agents: HAWKINS, Michael, Howard et al.; Baldwin Shelston Waters, NCR Building, 342 Lambton Quay, Wellington (NZ).			

Published

With international search report.

(54) Title: OBSTRUCTION DETECTION SYSTEM

(57) Abstract

The invention provides for a method of detecting objects in an area, the method including obtaining one or more images of the area, using an edge detection technique in such a way as to highlight substantially dominant linear features in the image(s), and determining if any dominant linear features intersect linear features defining the area. The method may also include detecting parallax in at least two images, the parallax being produced by the presence of 3-dimensional objects in the area.

