

- 1 -

SPECIFICATION

5 **SYSTEM FOR MONITORING WATER CONSUMING STRUCTURES
AND THEIR HEAT USE IN AN INDIVIDUAL UNIT OF A MULTI-
UNIT BUILDING AND A SYSTEM FOR BILLING THEREFOR****BACKGROUND OF THE INVENTION**

10 The present invention relates to a system for
monitoring the water consumption and energy use of
water consuming devices and monitoring the energy use
of water operated heating and cooling devices in
multi-unit building complexes where the individual
units are supplied water from a common source and
more particularly to a system which will calculate
the water consumption and water related energy use of
15 the individual units so that water, sewer and energy
costs can be fairly apportioned to the units to
encourage conservation. The invention also relates
to monitoring unusual water usage to detect leaks and
open valves.

20 **SUMMARY AND OBJECTS OF THE INVENTION**

The individual units of a multi-unit building
such as an apartment building are supplied water from
a common source (the outlet of the building water
meter). The water inlet is split into hot and cold
25 water lines with the hot water line passing through
a heater (typically there are separate hot water and
heating boilers) which heat the water to the required
temperature. In conventional construction, multiple
vertical risers supply stacked bathrooms, kitchens
30 and heating/cooling devices. As a result the water
supplied to an individual unit can not be metered
without substantial, very costly, plumbing
infrastructure changes.

It is an object of the present invention to
35 measure the water consumption and the water heat

energy use in an individual unit in a multi-unit building so that the individual unit can be assigned responsibility therefor without substantial plumbing infrastructure changes.

5 It is another object of the present invention to monitor the condition of a water consuming structure so that leaks can be serviced and erroneously open lines can be closed.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring to the drawings:

Figure 1 is a schematic illustration of the water consuming devices of a four unit apartment building wherein each unit has a bathroom with a sink (including any associated tub/shower) and a toilet and a kitchen with a sink (including associated appliances such as a dishwasher) and wherein each pipe supplying the water consuming devices includes a monitor made in accordance with the teachings of the present invention;

Figure 2 is a schematic illustration of the heating/cooling system for the same apartment building wherein each apartment has one or more heating/cooling devices each having upstream and downstream monitors, one monitoring temperature and volumetric flow and the other monitoring temperature;

Figure 3 is a schematic illustration of a monitor shown in figures 1-2;

Figure 4 is a logic diagram for the volume/temperature functions of a monitor;

Figure 5 is a logic diagram for a monitor which will issue an alarm signal when the water using device is continuously open;

Figure 6 is a schematic illustration of a system for a multi story building including a receiver on each floor for receiving and outputting data from the

monitors on its floor;

Figure 7 is a logic diagram for a monitor which will issue a maintenance signal when a water device is leaking;

5 Figure 8 is a schematic illustration for a home system;

Figure 9 is a logic diagram for comparing the output of a common monitor with the outputs of all the dedicated monitors to identify a leak;

10 Figure 10 is a schematic illustration of a system for a building that has a plurality of local receivers that are hard wired in series with the base local receiver outputting data;

15 Figure 11 is a schematic illustration of a system similar to that of figure 6, with individual local receivers hard wired or phone linked in parallel to a base local computer;

Figure 12 is a schematic illustration of a system having a plurality of local receivers linked in series or in parallel to a remote receiver; and

20 Figure 13 is a schematic illustration of a system having a plurality of local and remote receivers which are linked to a data base.

DESCRIPTION OF THE PREFERRED EMBODIMENT

25 Utility provided water 10 (fig. 1) generally is metered by a water meter WM 11 as it enters a building such as an apartment house or office building. A portion of the water branches off to supply the building cold water supply line 12 and the
30 other portion is supplied to a hot water heater H 13 which supplies the hot water supply line 14 of the building. The building has a number of similar units (in a two story apartment house, there could be four one bedroom apartments, two on each floor, for
35 example) each having a sink (including associated tub/shower) and toilet in the powder room and a

second sink (including any associated appliances such as a dishwasher) in the kitchen. Each sink is supplied by separate hot and cold water lines (the hot and cold water lines of the kitchen sink may also supply a dishwasher) and each toilet is supplied by a single cold water line. Stacked kitchens and bathrooms are supplied via vertical risers 15. In each water line (or just downstream in the mixed water line) is located a monitor M 19. Figure 2 shows the heating/cooling system for the same units. Water (hot in the winter or cold in the summer) is supplied by a suitable source such as a heat pump HP 13A (discrete sources such as a boiler for hot water and a chiller for cold water could be utilized) to a feed line 16 which supplies the individual heating or cooling units H/C 23 through multiple vertical risers 17. The water is returned to the source HP by suitable return lines 18. Located upstream and downstream of each heating or cooling unit H/C is a monitor M.

A monitor M (fig. 3) which can be located in each line by a plumber, is a unitary battery operated structure, which is fully sealed to reduce tampering and water damage. The monitor can have a universal set of fittings to simplify installation. A monitor may include a pipe 20 in which may be permanently secured a gearbox 21 such as the type found in lawn sprinkler heads to control the movement of the water spray. The gear box has axial input 22 and output 24 shafts which are connected to a turbine wheel drive propeller 26 and a copper or other metal axially extending partial cylindrical portion paddle wheel 28. Water entering the pipe, passes through a set of orifices 30 which direct the water at the propeller blades thereby efficiently driving the gearbox. The gear ratio of the gearbox is selected so that the partial cylindrical portion 28 will make no more than

about half a rotation during a sampling time (a rate of rotation that will assure that an oscillator (OSC - 25) will sense the presence of the partial cylindrical portion (the target) 28 twice each revolution). The gear ratio may be different for different devices (full flow for a toilet is very different than full flow for a tub, for example). Coil 29 will change inductance twice each revolution changing the frequency of the oscillator. The microprocessor uc 31 or custom specialized electronic circuit can therefore count a pulse each time the target 28 is located at 0° and 180° and each pulse equates to a unit volume of liquid. Referring to figure 4, if a reading is to be taken approximately once per "X" time (a minute, for example) based on a timer circuit 33 associated with the microprocessor (see figure 3), the gear ratio will be selected so that the target will rotate less than 180°, during one minute with maximum flow through the pipe. Alternately, other sensors could be used such as a rotating magnet and Hall effect sensor, reed switch, capacitive sensor, optical sensor, inductive sensor with ferrite rotator, etc. When, during that time interval, the target has been sensed, a volume counter will be updated to a new total of volume units and at some other regular time interval "y" (once a day, for example), the total volume count will be transmitted by the radio transmitter 34. The updated count is representative of the total volumetric flow through the pipe. Limiting the rate of rotation of the target with the gear box so that a reading need only be taken once per minute, prolongs battery life since the microprocessor uc only has to be turned on once per minute. The flow measuring system could also be an ultrasonic Doppler flowmeter, a magnetic flowmeter, an electronic mass flowmeter, or a vortex flowmeter, for example.

The energy use of the hot water used in a water using device may be computed by multiplying the volumetric volume of the associated hot water pipe by the temperature that hot water is supplied where the monitor is receiving hot water from the hot water heater. Optionally, the monitor can include a heat thermistor 32 (or a thermocouple, etc.) attached to the pipe to sense the temperature of the fluid flowing through the monitor. The microprocessor uc 31 may multiply the temperature by that unit volumetric flow to define a heat content number (BTU use - figure 4) and will then update the total heat content totalizator. By subtracting the total heat count at one side of a heating/cooling unit H/C from the simultaneous total heat count at the other side (the subtraction made by a local receiver which receives the data from both monitors - Figure 7, for example), the energy use of the heating/cooling unit can be determined. Alternately, one of the monitors on either side of a heating/ cooling unit can monitor only temperature and be connected to the other monitor with that monitor making both computations such as by subtracting out the temperature reading from the other to compute the heat change. Should electrical power be available or should the battery economics permit, the position of the target could be sampled continuously and the gear box would not be required.

Once every day (or some other time interval) which equates to "Y" time interval, the microprocessor will operate the transmitter (which is a radio transmitter 33 in the preferred embodiment but could be an ultra sonic or infrared transmitter, etc.) to transmit the then current count of the register which is representative of volumetric flow, the then current total of the heat content totalizator, identifier data which identifies the apartment

unit, the water using device, etc. and any pulse count data used to chronologically locate the transmission.

5 The microprocessor uc can also determine that a water consuming device has been left open (a tub running continuously, for example). For example, the microprocessor should detect the presence of the target once a minute while the tub is being filled at the fully open condition. Even at a slow fill rate
10 the target should be sensed once every "X" minutes (figure 5). If "X" is five minutes, for example, the filling process should be complete within twenty minutes (four multiples of "X"). Accordingly, according to the algorithm expressed in figure 5,
15 when the water has been running for "X" minutes and the target has been sensed, the counter is incremented and the process is repeated. When the target has been sensed in the next "X" minutes the counter again increments and so forth. If the count
20 reaches 15 ("Y"), for example, the water has run for a time beyond that which was required to fill the tub and this can mean that someone has failed to turn the water off, etc. Should the microprocessor determine that flow has continued for more "Y" increments of
25 "X", the microprocessor will direct the transmitter to transmit an alarm signal, identifying the water consuming device, to the receiver which indicates that the device has been left open so that immediate action can be taken to correct the problem. The
30 alarm signal can be transmitted to a local receiver which could be a general alarm system for the home which would announce the condition or it could be further transmitted to a remote receiver which could be at a home security company which could take
35 appropriate action or it could be a part of the water usage system for a multiple unit building as described herein. This algorithm can also be

computed with a number of "X" and "Y" values ("X1" and "Y1", "X2" and "Y2", for example) since the fill rate can be chosen at widely different rates. These variables can also be defined during installation by programming non volatile memory in the monitor.

In the apartment illustrated in figures 1 and 2, a radio (local) receiver (a microprocessor, for example) which can receive and decode the transmitted radio signal can be located on each floor (figure 6) for receiving the data transmitted from all of the monitors on its floor. As shown in figure 6, the local receiver may compute daily, weekly, monthly, quarterly, etc., totals for the volumetric flow and energy (BTU) use for each unit, and can issue alarm signals (by audible alarm or telephone to a security location, for example, identifying the unit and the water consuming device subject to the alarm signal. Each receiver could, for example, have a visual readout or it could be connectable to a hand held terminal which can read out the data. By transmitting volumetric flow data from the monitors to the receiver each day, the receiver can determine that a monitor is not operating which could indicate that the monitor battery has died, etc., or that the monitor has been tampered with.

The local receiver may also implement the algorithm disclosed in figure 7. It can determine a rolling volumetric flow average/unit of time ("T" may be 30 or 60 days for example) and first compare that with the calculated current volumetric flow/unit of time. Where it exceeds the rolling average by X% which indicates the a faucet is leaking, for example, the local receiver will send a maintenance signal. A second comparison can also be made to determine whether the current volumetric flow/unit of time exceeds by Y% a standard for that device. Should the difference exceed this variance, the local receiver

will issue a maintenance signal.

5 The receiver, in its simplest form, could contain an information system (or a part of a larger information system) for an individual unit or a home (figure 8). A monitor which would not have to monitor temperature, could be placed in each line supplying the water consuming devices so that volumetric flow data could be transmitted to a local receiver which would determine whether any device was
10 leaking or open and would issue an appropriate alarm or maintenance signal for that device. This figure also illustrates a monitor downstream of the water meter WM - 11. This monitor can implement the algorithm of figure 5 to detect a break in any
15 downstream water line such as could happen as a result of earthquake or freeze damage, for example. By comparing the volumetric flow/unit of time of this common monitor (figure 9), with the total/unit of time of all the dedicated monitors, an internal leak
20 can be identified (a variance of X% would indicate an internal leak). Maintenance and alarm signals can be issued by the local receiver and optionally the local receiver can communicate with a remote receiver in the form of a security company or to the monitoring
25 or billing system to obtain assistance..

As shown in figure 10, the multi-unit building may have a plurality of local receivers hard wired in series (or connected on a phone line) to a base local receiver (the local receiver located on the
30 superintendents' floor for example), with the base local receiver presenting the data for all the local receivers. Instead of phone lines or wires, a radio (custom or PCS system) could transmit the data from one local receiver to other local/remote receivers.
35 The total volumetric flow and energy use for an individual unit can be computed by each of the local receivers or all computations can be performed by the

base local receiver. Alternately, such a base local receiver can be connected in parallel with the other local receivers (figure 11). The base receiver may not receive data from a monitor but only receive data
5 from local receivers (receivers receiving data from monitors (figure 12). The base receiver is then a remote receiver. The remote receiver (figure 13) can provide a database which communicates via phone lines with any number of local and/or remote receivers and
10 a receiver (a local receiver, a base local receiver or a remote receiver) can operate on the data and prepare, bills for water, energy and sewer use for each reporting unit which can be sent directly to the individual units or to the buildings for distribution
15 as well as support reporting of leaks and open faucets, etc.



CLAIMS :

1. A system for monitoring a water consuming structure supplied by a water pipe comprising

means for determining that a selected volume of water has flowed through the pipe during a period of time not exceeding a predetermined period of time, and

means for transmitting an alarm signal in the event that said determining means determines that said selected volume of water has flowed through the pipe to said water consuming structure during a period of time not exceeding said predetermined period of time.

2. A system for monitoring a water consuming structure according to claim 1, further comprising

remote receiver means for receiving said signal.

3. A system for monitoring a water consuming structure according to claim 2, wherein said remote receiver means comprises

first remote receiver means for receiving and retransmitting the signal, and

second remote receiver means for receiving the retransmitted signal from said first remote receiver means.

4. A system for monitoring a water consuming structure according to claim 1, wherein said transmitting means comprises an RF transmitter.

5. A system for monitoring a water consuming structure according to claim 3, wherein said first remote receiver for receiving and retransmitting the alarm signal comprises

an RF receiver for receiving the alarm signal transmitted from said transmitting means and

telephone means for retransmitting the signal and wherein

said second remote receiver comprises telephone receiver means.



6. A system for monitoring a water consuming structure supplied by a water pipe comprising

means for determining the volume of water flowing through the pipe during a predetermined period of time,

means for comparing the determined volume of water for said predetermined period of time with a reference volume for said same predetermined period of time, and

means for transmitting a maintenance signal in the event that said determined current volume of flow during said predetermined period of time exceeds said reference volume for said same predetermined period of time.

7. A system for monitoring a water consuming structure according to claim 6, further comprising

remote receiver means for receiving said maintenance signal.

8. A system for monitoring a water consuming structure according to claim 7, wherein said remote receiver means comprises

first remote receiver means for receiving and retransmitting the maintenance signal, and

second remote receiver means for receiving the retransmitted maintenance signal from said first remote receiver means.

9. A system for monitoring a water consuming structure according to claim 6, wherein said reference volume is a selected volume above a rolling volumetric flow average.

10. A system for monitoring a water consuming structure supplied by a water pipe according to claim 1, wherein said determining means comprises

a flow monitoring device having a target which will be displaced past a selected location every time a predetermined volume of water has flowed through the water pipe



and a sensor for sensing said target each time it is located at said selected location,

an increment counter for incrementing the count each time said sensor senses said target, and

means for operating said transmitting means in the event the count of said increment counter reaches a selected count in a period of time not exceeding said predetermined period of time.

11. A system for monitoring a water consuming structure supplied by a water pipe comprising

means for determining the volume of water that flows through the pipe during a single period of continuous flow, and

means for transmitting an alarm signal in the event that the volume of water determined to have flowed through the pipe during the single period of continuous flow exceeds a predetermined volume of flow.

12. A system for monitoring a water consuming structure according to claim 11, further comprising remote receiver means for receiving said signal.

13. A system for monitoring a water consuming structure according to claim 12, wherein said remote receiver means comprises

first remote receiver means for receiving and retransmitting the signal, and

second remote receiver means for receiving the retransmitted signal from said first remote receiver means.