

Description

This invention relates to an electrical connector. More specifically, it relates to an electrical connector and electrical connector assembly useful for the efficient spatial arrangement of electrical interconnections between circuit-bearing substrates.

The trend in circuit board design has been towards fitting more and more electrical circuitry in smaller and smaller areas. Connector assemblies are used to interconnect printed circuit boards or similar substrates. Known connector assemblies are unsuitable where circuit board space is limited or a specific design is required. In certain cases the most space-efficient placement of connector assemblies between particular circuit boards is prevented by the obstructing design of the connector assemblies currently available.

One type of known connector assembly uses multi-wire flexible cables. A multi-wire flexible cable is a substantially flat means for carrying electrical current. Current is carried from one end of the multi-wire flexible cable to the other along its length by many parallel conductors. Although a multi-wire flexible cable is somewhat bendable along its length, it may not bend sufficiently to permit a desired configuration of multiple assemblies without damage to the parallel conductors or to contact connections enclosed in connector housings at either end of each multi-wire flexible cable. Furthermore, known assemblies with multi-wire flexible cables exiting horizontally from a connector obstruct placement of a neighboring connector assembly. As a result of the obstruction, the surface area of the circuit board is not used efficiently, design flexibility is limited, and the maximum density of electrical connections is not achievable. Pressure to remove these limitations is felt in the industry as illustrated by the following existing art.

Connectors are known having a multi-level terminal block retaining multiple rows of contacts. Dahlgren *et al.* (US-A- 3,007,131) show the use of a multi-level terminal block for use with a multi-wire flexible cable. The multi-level arrangement permits an increased density of contacts per assembly. However, Dahlgren *et al.* teach nothing about a housing for the terminal block that solves the problem of how to arrange a number of terminal blocks for maximum density on a circuit board.

Massitt *et al.* (US-A- 4,684,181) disclose a terminal block enclosed by a connector housing with a horizontal opening for multi-wire flexible cables. This patent discloses multiple flexes attached at each end to respective levels of a multi-level support within a connector. The deficiency that is readily apparent in this device is that the side-exiting multi-wire flexible cable obstructs placement of a second identical connector positioned immediately side-by-side to the first. Therefore, the surface area needed to position the

connectors cannot be less than a certain area without damage to the multi-wire flexible cables.

Adams (US-A- 4,776,806) discloses a low profile connector with a horizontal exit from the housing for a single flexible cable. "low-profile" feature of Adams guides a flexible cable over longitudinally aligned connectors. This design is useful for decreasing the space needed between separate circuit boards to accommodate connector assemblies connected to circuit-bearing substrates in a single plane. However, it does not permit the high density of contacts possible with multiple flexible cables associated with a single connector assembly.

The present invention solves all of these difficulties with an electrical connector permitting the immediate side-by-side placement of high density electrical assemblies. The connector is designed with a housing containing a terminal block which may be multi-tiered for use with multi-wire flexible cables. The housing has a ramp and a chute on opposing sides. By placing two connectors so that the chute of the first connector is aligned with the ramp of the second connector, a flexible cable emerging from the first connector is not obstructed by the second connector, but instead is directed over the second connector by means of the ramp. This positioning of connectors is what is meant by the phrase "angled chute-to-ramp relationship."

The proximity of the two connectors in this "angled chute-to-ramp relationship" may be so close that they touch. Thus, positioning of connectors on circuit-bearing substrates more densely than with previously known connectors is possible. In addition, damage to multi-wire flexible cables is prevented. This result is obtained by using in combination as specified below a connector housing with a multi-level terminal block for retaining contacts which are attached to the ends of the multi-wire flexible cable conductors.

According to the invention there is provided an electrical connector adapted to electrically connect a circuit board with a multi-wire electrical cable, the connector having an underside adapted for connection to a circuit board, characterised in that the connector has a chute in one side of the connector adapted to receive a multi-wire flexible cable and a ramp opposite the chute, the ramp being arranged in relation to the chute such that in an arrangement in use of a first such connector adjacent a second such connector, a multi-wire cable emerging from the chute of the first connector may be directed over the second connector by the ramp of the second connector.

There now follows, by way of example only, a description of an embodiment of the present invention with reference to the accompanying drawings, in which:

Figure 1 is a perspective view looking upwardly toward the electrical contact side of a connector of the circuit assembly in accordance with the present in-

vention.

Figure 2 is an enlarged sectional view through a central portion of two connectors of separate assemblies illustrating an angled chute-to-ramp relationship of the connectors in normal operative position in accordance with the present invention.

Figure 3 represents a perspective view looking upwardly toward the gripping planes and the pedestal supports of the first piece of the connector housing in accordance with the present invention.

Figure 4 represents a perspective view looking downwardly toward the gripping planes and the opening of the second piece of the connector housing in accordance with the present invention.

Figure 5 represents a side elevation view of two assemblies in an angled chute-to-ramp relationship secured to circuit-bearing substrates in accordance with the present invention.

Figure 1 represents a connector of the present invention designated generally therein by the reference character 8. As shown, connector 8 terminates the end of a multi-wire flexible cable 10 of the type having a plurality of parallel conductors 12 across its width W. The connector 8 includes a connector housing 14 in the form of a parallelepiped and contains various sub-components described more fully in relation to Figures 2,3,4 and 5. The connector housing 14 has a ramp 16 joining a first face 18 and a second face 20 by truncating one corner of the connector housing 14, and a third face 22 defining an opening 24. The connector housing 14 is divided into a first housing piece 26 and second housing piece 28 which enclose one end of multi-wire flexible cable 10. First housing piece 26 includes ramp 16. Second housing piece 28 includes opening 24. Housing pieces 26 and 28 are formed of suitable materials such as die-cast zinc or aluminum and are held together with fastening means such as joining screws 30. Connector 8 is oriented on a circuit-bearing substrate 32 with positioning means such as guide pins 34 which fit into recesses 36. Once positioned, fastening means such as jack screws 38 are tightened into threaded apertures 40 in the circuit-bearing substrate 32 to secure connector 8. Deflection supports 42 cushion the housing upon attachment of the connector 8 to the circuit-bearing substrate 32.

Fig. 1 further illustrates the spacer comb 44 which is supported within the opening 24 of the second housing piece 28. Spacer comb 44 is made of suitable materials, preferably a non-conductive polyester material, and has a plurality of through passages 46.

Figure 2 illustrates, in accordance with the present invention, an enlarged sectional view through the central portion of two substantially similar connectors 8 and 8'.

In Figure 2, first housing piece 26 and second housing piece 28 are joined to form internal cavity 48.

The fourth face 50 of the connector housing 14 includes an angled chute 52 which is defined by gripping planes 54 and 55 running between the exterior wall 56 and the interior wall 57 of the connector housing 14. Within the internal cavity 48, the first housing piece 26 includes pedestal supports 58 which brace the end of the multi-wire flexible cable 10 against the load generated as the connector 8 is mounted on the circuit-bearing substrate 32. Fig. 3 shows in a perspective view the interior wall 57 of the first housing piece 26 with pedestal supports 58. In other embodiments of the present invention, the number of pedestal supports 58 corresponds to the number of multi-wire flexible cables 10 terminating in a connector 8. Other means for bracing the multi-wire flexible cable 10 are also envisaged.

The connectors 8 and 8' are shown in Fig. 2 in the normal operative position of a chute-to-ramp relationship. The expression "chute-to-ramp relationship" means that the chute 52 of connector 8 fits immediately adjacent to the ramp 16' of connector 8', permitting the multi-wire flexible cable 10 to exit from chute 52 without obstruction. The ramp 16 and chute 52 permit the correct spatial relationship of neighboring connectors so that there are no deforming stresses or pressures on elements of the invention produced by the geometry of the connector configuration on the circuit-bearing substrate 32. The multi-wire flexible cable 10 of connector 8 is instead guided over the connector 8' by the ramp 16'. The angle and direction of the ramp 16' and the angle and direction of the chute 52 are substantially the same when measured with reference to the third face 22 of the connector housing 14. i.e. the angle and the direction of these elements differ with respect to immediately adjacent connectors by no more than 20 degrees in preferred embodiments. The angle accommodates the number of the levels of the terminal block 60' and the total height of the connector 8'. Additionally, the height of chute 52 from the third face 22 corresponds to the height of ramp 16' from the third face 22' such that the chute-to-ramp relationship of the connectors 8 and 8' is maintained.

Figure 2 additionally shows spacer comb 44 supporting terminal block 60 within the connector housing 14. The terminal block 60 is formed of a suitable non-conductive material such as polyetherimide or liquid crystal polymer. In the embodiment shown in Fig. 2, the terminal block 60 has a tiered surface with two levels or steps 62a and 62b, each level 62 to support the attachment of one end of a multi-wire flexible cable 10. The term "tiered" means that the terminal block has more than one level arranged in steadily ascending order. Other embodiments of the present invention may have a terminal block 60 with a single level or with multiple levels the number of levels of any terminal block 60 corresponding to the number of multi-wire flexible cables 10 received into the chute 52.

The terminal block 60 retains contacts 64 in a plurality of through passages 66. The contacts 64 are made of a suitable material such as beryllium copper. The contacts 64 may include suitable forms such as a pin-and-spring, cylindrical, triple beam, square pins, blade and bifurcated fork type, and other contact types. The pin-and-spring type of contact 64 is illustrated in Fig. 2, the pin end 68 protruding from the tiered surface of the terminal block 60 into the internal cavity 48 of the connector housing 14 for attachment to a corresponding conductor 12 of a multi-wire flexible cable 10. One embodiment of the present invention has a multi-wire flexible cable with parallel conductors 12 between laminae (not illustrated) made of a polyimide and ground planes (not illustrated) preferably made of a silver epoxy. The spring end 70 of each contact 64 protrudes from the opposite side of the terminal block 60 through opening 24 for contact with the circuit-bearing substrate 32. The spacer comb 44 protects the contacts 64 from damage upon attachment of the connector 8 to a circuit-bearing substrate 32.

The contacts 64 are organized in a subarray of rows and columns (unnumbered) of alternating signal and ground contact pairs with a ground column preferably in the outside or end position. Each contact column is separated from an adjacent column by a suitable distance. Each contact row is separated from an adjacent row by a suitable distance. The contacts 64 are further arranged so that one subarray of contacts 64 is retained in each level 62 of the terminal block 60 as illustrated in Fig. 2. A subarray of contacts 64 is attached at their pin end 68 by known means to the conductors 12 of the corresponding multi-wire flexible cable 10. The circuit-bearing substrate 32 contains conductive traces (not shown) aligned for connection with contacts 64.

A separator 72 is positioned over the joining of the contact pin end 68 with the multi-wire flexible cable 10 to protect an adjacent multi-wire flexible cable 10 from damage during handling, placement, and connection to the circuit-bearing substrate 32. The separator 72 also protects the joining of the pin end 68 and the multi-wire flexible cable 10 from damage.

Figs. 3 and 4, are, respectively, perspective views of the interior wall 57 of the first housing piece 26 and second housing piece 28, and also illustrate the placement of various passages in the connector housing 14. Jack screw 38 fits through passage 39 for securing into threaded aperture 40 in the circuit-bearing substrate. Joining screws 30 are introduced into threaded housing apertures 31 in the first housing piece 26 and the second housing piece 28. Guide pins fit into cylindrical spaces 35 in the first housing piece 26 and the second housing piece 28. The end of the guide pin 34 which protrudes from the third face 22 of the connector 8 fits into the substrate recess 36. Deflection supports 42 fit into recesses 43 in the third face of the connector housing 14. Figs. 3 and 4 also

show gripping planes 54 and 55 which guide the multi-wire flexible cable as it exists from the connector housing 14.

In a preferred embodiment of the invention, the number of levels 62 on the terminal block 60 equals the number of multi-wire flexible cables 10 received into the chute 52 and also equals the number of pedestal supports 58 of each connector. The distance between gripping planes 54 and 55 of chute 52 is at least as thick as the thickness of the total number of multi-wire flexible cables 10 received by associated connector 8.

Two electrical assemblies in accordance with the instant invention are shown in Fig. 5 and designated generally therein by the reference characters 74 and 74'. As shown, assembly 74 includes at least one multi-wire flexible cable 10 connected at each end to a connector 8. The length or the direction of the flexible cable 10 can be altered to offset the placement of the connector 8 at each end of the flexible cable 10. This feature also enhances variety in design of assembly configurations. Assembly 74' fits immediately side-by-side with assembly 74 efficiently using space for the stacking of the assemblies. Fig. 5 also illustrates how the ramp 16 of the connector 8a permits the unobstructed exit of the multi-wire flexible cables 10' from connector 8'a. The width dimension of the ramp 16 is larger than the cross section width dimension W of the flexible cable 10. The ramp 16 supports and guides the flexible cable 10 in immediate side-by-side configurations of the connectors 8 of the present invention. Fig. 5 illustrates how assemblies 74 and 74' may interconnect the circuit-bearing substrates 32 and 32' which are in two different planes. Assemblies may also interconnect circuit-bearing substrates in the same plane.

Those skilled in the art, having the benefit of the teachings of the present invention as described, can effect numerous modifications thereto. These modifications are to be construed as being encompassed within the scope of the present invention as set forth in the appended claims and interpreted by the description and drawings.

Claims

1. An electrical connector (8) adapted to electrically connect a circuit board with a multi-wire electrical cable (10), the connector having an underside adapted for connection to a circuit board, characterised in that the connector has a chute (52) in one side of the connector adapted to receive a multi-wire flexible cable and a ramp (16) opposite the chute, the ramp being arranged in relation to the chute such that in an arrangement in use of a first such connector (8) adjacent a second such connector (8'), a multi-wire cable emerging from



The terminal block 60 retains contacts 64 in a plurality of through passages 66. The contacts 64 are made of a suitable material such as beryllium copper. The contacts 64 may include suitable forms such as a pin-and-spring, cylindrical, triple beam, square pins, blade and bifurcated fork type, and other contact types. The pin-and-spring type of contact 64 is illustrated in Fig. 2, the pin end 68 protruding from the tiered surface of the terminal block 60 into the internal cavity 48 of the connector housing 14 for attachment to a corresponding conductor 12 of a multi-wire flexible cable 10. One embodiment of the present invention has a multi-wire flexible cable with parallel conductors 12 between laminae (not illustrated) made of a polyimide and ground planes (not illustrated) preferably made of a silver epoxy. The spring end 70 of each contact 64 protrudes from the opposite side of the terminal block 60 through opening 24 for contact with the circuit-bearing substrate 32. The spacer comb 44 protects the contacts 64 from damage upon attachment of the connector 8 to a circuit-bearing substrate 32.

The contacts 64 are organized in a subarray of rows and columns (unnumbered) of alternating signal and ground contact pairs with a ground column preferably in the outside or end position. Each contact column is separated from an adjacent column by a suitable distance. Each contact row is separated from an adjacent row by a suitable distance. The contacts 64 are further arranged so that one subarray of contacts 64 is retained in each level 62 of the terminal block 60 as illustrated in Fig. 2. A subarray of contacts 64 is attached at their pin end 68 by known means to the conductors 12 of the corresponding multi-wire flexible cable 10. The circuit-bearing substrate 32 contains conductive traces (not shown) aligned for connection with contacts 64.

A separator 72 is positioned over the joining of the contact pin end 68 with the multi-wire flexible cable 10 to protect an adjacent multi-wire flexible cable 10 from damage during handling, placement, and connection to the circuit-bearing substrate 32. The separator 72 also protects the joining of the pin end 68 and the multi-wire flexible cable 10 from damage.

Figs. 3 and 4, are, respectively, perspective views of the interior wall 57 of the first housing piece 26 and second housing piece 28, and also illustrate the placement of various passages in the connector housing 14. Jack screw 38 fits through passage 39 for securing into threaded aperture 40 in the circuit-bearing substrate. Joining screws 30 are introduced into threaded housing apertures 31 in the first housing piece 26 and the second housing piece 28. Guide pins fit into cylindrical spaces 35 in the first housing piece 26 and the second housing piece 28. The end of the guide pin 34 which protrudes from the third face 22 of the connector 8 fits into the substrate recess 36. Deflection supports 42 fit into recesses 43 in the third face of the connector housing 14. Figs. 3 and 4 also

show gripping planes 54 and 55 which guide the multi-wire flexible cable as it exists from the connector housing 14.

In a preferred embodiment of the invention, the number of levels 62 on the terminal block 60 equals the number of multi-wire flexible cables 10 received into the chute 52 and also equals the number of pedestal supports 58 of each connector. The distance between gripping planes 54 and 55 of chute 52 is at least as thick as the thickness of the total number of multi-wire flexible cables 10 received by associated connector 8.

Two electrical assemblies in accordance with the instant invention are shown in Fig. 5 and designated generally therein by the reference characters 74 and 74'. As shown, assembly 74 includes at least one multi-wire flexible cable 10 connected at each end to a connector 8. The length or the direction of the flexible cable 10 can be altered to offset the placement of the connector 8 at each end of the flexible cable 10. This feature also enhances variety in design of assembly configurations. Assembly 74' fits immediately side-by-side with assembly 74 efficiently using space for the stacking of the assemblies. Fig. 5 also illustrates how the ramp 16 of the connector 8a permits the unobstructed exit of the multi-wire flexible cables 10' from connector 8'a. The width dimension of the ramp 16 is larger than the cross section width dimension W of the flexible cable 10. The ramp 16 supports and guides the flexible cable 10 in immediate side-by-side configurations of the connectors 8 of the present invention. Fig. 5 illustrates how assemblies 74 and 74' may interconnect the circuit-bearing substrates 32 and 32' which are in two different planes. Assemblies may also interconnect circuit-bearing substrates in the same plane.

Those skilled in the art, having the benefit of the teachings of the present invention as described, can effect numerous modifications thereto. These modifications are to be construed as being encompassed within the scope of the present invention as set forth in the appended claims and interpreted by the description and drawings.

Claims

1. An electrical connector (8) adapted to electrically connect a circuit board with a multi-wire electrical cable (10), the connector having an underside adapted for connection to a circuit board, characterised in that the connector has a chute (52) in one side of the connector adapted to receive a multi-wire flexible cable and a ramp (16) opposite the chute, the ramp being arranged in relation to the chute such that in an arrangement in use of a first such connector (8) adjacent a second such connector (8'), a multi-wire cable emerging from



the chute (52) of the first connector may be directed over the second connector by the ramp (16') of the second connector.

2. An electrical connector as claimed in claim 1 further comprising:

a connector housing (14) in the form of a parallelepiped having the ramp (16) joining a first face (18) and a second face (20) by truncating one corner of the connector housing (14), the parallelepiped having an internal cavity (48), the internal cavity accessed through an opening (24) in a third face (22) of the connector housing opposite to the first face of the connector housing, the internal cavity also accessed through the chute (52) in a fourth face (50) opposite to the second face of the connector housing, the angle of the ramp and the angle of the chute being about the same as measured with respect to the third face (22) of the connector housing and the distance from the third face to the chute on the fourth face corresponding to the distance from the third face to the ramp on the second face;

a terminal block (60) positioned within the internal cavity (48) and adapted for attachment to one end of a flexible cable;

an array of electrical contacts (64) supported by the terminal block, one end of the contacts protruding from the terminal block and extending through the opening in the third face for engagement with the electrical circuit-bearing substrate, the other end of the contacts protruding from the terminal block for attachment with one end of the multi-wire flexible cable.

3. An electrical connector as claimed in claim 1 or 2, wherein the chute (52) is dimensioned to permit passage of a plurality of flexible cables into the internal cavity, and the terminal block (60) is tiered for attachment of each flexible cable to a separate step of the tier.

4. An electrical connector as claimed in claim 1, 2 or 3 wherein a spacer comb (44) is located within the internal cavity.

5. An electrical connector as claimed in any of claims 1 to 4, wherein the connector housing comprises a first piece (26) and a second piece (28) joined together to define the internal cavity (48), the first piece including the first face, the ramp, part of the second face, and the upper portion of the fourth face, and the second piece including the third face, the remainder of the second face, and a lower portion of the fourth face.

6. An electrical connector as claimed in any preceding claim wherein the chute comprises an array

of gripping teeth.

7. An electrical connector as claimed in any of claims 2 to 6, wherein the first piece (26) of the housing has a pedestal support (58) directed into the internal cavity, the pedestal support having a width approximately as wide as and running transverse to the multi-wire flexible cable so that the pedestal support braces the multi-wire flexible cable and the terminal block and counters the load generated upon the securing of the connector to a circuit substrate.

8. An electrical connector as claimed in any preceding claim, wherein said ramp (16) and chute (52) are arranged with respect to each other such that, in an arrangement in use of the chute of a first such connector adjacent the ramp of a second such connector, the connectors may touch without the second connector obstructing the emergence of a multi-wire flexible cable from the chute of the first connector.

9. A series of electrical connectors comprising two or more of the connectors as claimed in any preceding claim placed in adjacent, angled chute-to-ramp relationship on an electrical circuit-bearing substrate.

10. An electrical connector assembly for interconnecting electrical circuit-bearing substrates comprising:

a multi-wire flexible cable having a plurality of parallel conductors across its width; and

a connector as set forth in any of claims 1 to 8 attached at one or both of the ends of the multi-wire flexible cable.

11. An electrical connector assembly as claimed in claim 10 wherein said cable is formed integral with one or both of the connectors.

Patentansprüche

1. Elektrischer Verbinder (8), der dafür ausgebildet ist, eine Leiterplatte mit einem vieladrigen elektrischen Kabel (10) zu verbinden, wobei der Verbinder eine Unterseite aufweist, die dafür geeignet ist, um eine Verbindung mit einer Leiterplatte herzustellen, dadurch gekennzeichnet, daß der Verbinder einen Schacht (52) in einer Seite des Verbinders aufweist, der dafür ausgebildet ist, um ein flexibles vieladriges Kabel aufzunehmen, und eine Rampe (16) gegenüber dem Schacht aufweist, wobei die Rampe in Relation zu dem Schacht so angeordnet ist, daß bei einer Anordnung, in der ein erster derartiger Verbinder (8) ne-



- ben einem zweiten derartigen Verbinder (8') verwendet wird, ein aus dem Schacht (52) des ersten Verbinders herausragendes vieladriges Kabel durch die Rampe (16') des zweiten Verbinders über den zweiten Verbinder gelenkt wird.
- 5
2. Elektrischer Verbinder nach Anspruch 1, mit:
 einem Verbinder-Gehäuse (14) in Form eines Parallelipeds mit einer Rampe (16), die sich an eine erste Fläche (8) und eine zweite Fläche (20) anschließt, indem eine Ecke des Verbinder-Gehäuses (14) abgeflacht ist, wobei das Paralleliped einen internen Hohlraum (48) aufweist und der interne Hohlraum über eine Öffnung (24) in einer dritten Fläche (22) des Verbinders-Gehäuses gegenüber der ersten Fläche des Verbinders-Gehäuses zugänglich ist, und wobei der innere Hohlraum auch über den Schacht (52) in einer vierten Fläche (50) gegenüber der zweiten Fläche des Verbinders-Gehäuses zugänglich ist, wobei der Winkel der Rampe oder Rampenfläche und der Winkel des Schachtes etwa gleich sind und zwar gemessen in bezug auf die dritte Fläche (22) des Verbinders-Gehäuses, und wobei der Abstand von der dritten Fläche zu dem Schacht in der vierten Fläche dem Abstand von der dritten Fläche zur Rampe an der zweiten Fläche entspricht,
- 10
- einem Terminal-Block (60), der innerhalb des internen Hohlraums (48) angeordnet ist und für eine Befestigung an einem Ende eines flexiblen Kabels ausgebildet ist,
- 15
- einer Anordnung von elektrischen Kontakten (64), die durch den Terminal-Block gehalten sind, wobei ein Ende der Kontakte aus dem Terminal-Block herausragt und sich durch die Öffnung in der dritten Fläche hindurch erstreckt für einen Angriff an das eine elektrische Schaltung tragende Substrat und wobei das andere Ende der Kontakte aus dem Terminal-Block herausragt für eine Befestigung an einem Ende des flexiblen vieladrigen Kabels.
- 20
3. Elektrischer Verbinder nach Anspruch 1 oder 2, bei dem der Schacht (52) so dimensioniert ist, um den Durchgang einer Vielzahl flexibler Kabel in den internen Hohlraum hinein zu erlauben, und bei dem der Terminal-Block (60) gestapelt ausgebildet ist für eine Befestigung jedes flexiblen Kabels an einer getrennten Stufe des Stapels.
- 25
4. Elektrischer Verbinder nach Anspruch 1, 2 oder 3, bei dem ein Abstandshalter-Kamm (44) innerhalb des internen Hohlraums gelegen ist.
- 30
5. Elektrischer Verbinder nach irgendeinem der Ansprüche 1 bis 4, bei dem das Verbinder-Gehäuse ein erstes Gehäuseteil (26) und ein zweites Gehäuseteil (28) aufweist, die aneinandergesetzt sind, um den internen Hohlraum (48) zu definieren, wobei das erste Gehäuseteil eine erste Fläche, die Rampe, einen Teil der zweiten Fläche und den oberen Abschnitt der vierten Fläche, und das zweite Gehäuseteil die dritte Fläche, den Rest der zweiten Fläche und einen unteren Abschnitt der vierten Fläche umfaßt.
- 35
6. Elektrischer Verbinder nach irgendeinem der vorhergehenden Ansprüche, bei dem der Schacht eine Anordnung von Greif-Zähnen aufweist.
- 40
7. Elektrischer Verbinder nach irgendeinem der Ansprüche 2 bis 6, bei dem das erste Gehäuseteil (26) des Gehäuses eine Fußstütze (58) besitzt, die in den internen Hohlraum hineingerichtet ist, wobei die Fußstütze eine Weite oder Breite besitzt, die etwa genauso weit oder breit ist wie das flexible vieladrige Kabel und quer zu diesem verläuft, so daß die Fußstütze das flexible vieladrige Kabel und den Terminal-Block aneinander klammert und der Belastung entgegenwirkt, die nach Befestigung des Verbinders an einem Schaltungssubstrat erzeugt wird.
- 45
8. Elektrischer Verbinder nach irgendeinem der vorhergehenden Ansprüche, bei dem die Rampe (16) und der Schacht (52) relativ zueinander derart angeordnet sind, daß bei einer Anordnung, bei der der Schacht eines ersten solchen Verbinders nahe der Rampe eines zweiten solchen Verbinders verwendet wird, sich die Verbinder berühren können, ohne daß der zweite Verbinder den Austritt des flexiblen vieladrigen Kabels aus dem Schacht des ersten Verbinders behindert.
- 50
9. Eine Reihe von elektrischen Verbindern mit zwei oder mehreren der Verbinder, nach irgendeinem der vorhergehenden Ansprüche, die in einer benachbarten, abgewinkelten Schacht-zu-Rampen-Beziehung auf einem eine elektrische Schaltung tragenden Substrat angeordnet sind.
- 55
10. Elektrische Verbinder-Anordnung zum Verbinden von elektrischen Schaltungen tragenden Substraten, mit
 einem flexiblen vieladrigen Kabel, welches eine Vielzahl von parallelen Leitern über seine Breite hinweg aufweist, und
 mit einem Verbinder nach irgendeinem der Ansprüche 1 bis 8, der an einem oder an beiden Enden des flexiblen vieladrigen Kabels angebracht ist.
- 6
11. Elektrische Verbinderanordnung nach Anspruch 10, bei der das Kabel einstückig mit einem oder beiden Verbindern ausgebildet ist.



Revendications

1. Connecteur électrique (8) conçu pour relier électriquement une plaquette de circuit imprimé avec un câble électrique multiconducteur (10), le connecteur ayant une partie de dessous conçue pour être reliée à une plaquette de circuit imprimé, caractérisé en ce que le connecteur comporte un conduit incliné (52), d'un côté du connecteur, conçue pour recevoir un câble multiconducteur souple et une rampe (16) à l'opposé de la déclivité, la rampe étant disposée par rapport au conduit incliné de telle façon que, dans une disposition d'utilisation d'un tel premier connecteur (8) adjacent à un tel second connecteur (8'), un câble multiconducteur débouchant du conduit incliné (52) du premier connecteur peut être dirigé au-dessus du second connecteur par la rampe (16') du second connecteur.

5

10

15

20
2. Connecteur électrique selon la revendication 1, comprenant en outre:

un boîtier de connecteur (14) ayant la forme d'un parallélépipède comportant une rampe (16) reliant une première face (18) et une deuxième face (20) en tronquant un coin du boîtier de connecteur (14), le parallélépipède comportant une cavité interne (48), accédant par une ouverture (24) à une troisième face (22) du carter de connecteur à l'opposé de la première face de ce carter de connecteur, la cavité interne accédant aussi par le conduit incliné (52) à une quatrième face (50) à l'opposé de la seconde face de ce carter de connecteur, l'angle formé par la rampe et l'angle formé par le conduit incliné par rapport à la troisième face (22) étant à peu près les mêmes, et la distance entre la troisième face et le conduit incliné sur la quatrième face correspondant à la distance entre la troisième face et la rampe sur la seconde face;

25

30

35

40

45

50

un bloc de connexion (60) disposé à l'intérieur de la cavité interne (48) et conçu pour être fixé à une extrémité d'un câble souple;

55

une rangée de contacts électriques (64) supportés par le bloc de connexion, une extrémité des contacts faisant saillie à partir du bloc de connexion et s'étendant par l'ouverture prévue dans la troisième face pour venir en prise avec le substrat portant le circuit imprimé électrique, l'autre extrémité des contacts faisant saillie à partir du bloc de connexion pour venir en prise avec l'extrémité du câble multiconducteur souple.

7
3. Connecteur électrique selon la revendication 1 ou 2, dans lequel le conduit incliné (52) est dimensionné pour permettre le passage d'une pluralité de câbles souples à l'intérieur de la cavité interne, et le bloc de connexion (60) forme des marches pour la fixation de chaque câble souple à un niveau distinct des marches.

5
4. Connecteur électrique selon la revendication 1, 2 ou 3, dans lequel un peigne d'écartement (44) est disposé à l'intérieur de la cavité interne.

10
5. Connecteur électrique selon l'une quelconque des revendications 1 à 4, dans lequel le carter de connecteur comprend une première pièce (26) et une seconde pièce (28) reliées l'une à l'autre pour définir la cavité interne (48), la première pièce comprenant la première face, la rampe, une partie de la deuxième face, et la partie supérieure de la quatrième face, la seconde pièce comprenant la troisième face, le reste de la deuxième face, et une partie inférieure de la quatrième face.

15

20
6. Connecteur électrique selon l'une quelconque des revendications précédentes, dans lequel le conduit incliné comprend une rangée de dents d'accrochage.

25
7. Connecteur électrique selon l'une quelconque des revendications 2 à 6, dans lequel la première pièce (26) du boîtier comporte un support de base (58) qui fait saillie dans la cavité interne, ce support de base ayant une largeur approximativement aussi importante que celle du câble souple multiconducteur et se trouvant en travers de celui-ci, de sorte que le support de base serre le câble souple multiconducteur et le bloc de connexion et s'oppose à la charge créée lors de la fixation du connecteur sur un substrat de circuit imprimé.

30

35
8. Connecteur électrique selon l'une quelconque des revendications précédentes, dans lequel ladite rampe (16) et ledit conduit incliné (52) sont disposés l'un par rapport à l'autre de sorte que, dans une disposition d'utilisation du conduit incliné d'un tel premier connecteur adjacent à la rampe d'un tel deuxième connecteur, les connecteurs peuvent se toucher sans que le second connecteur empêche la sortie d'un câble multiconducteur souple du conduit incliné du premier connecteur.

40

45

50
9. Série de connecteurs électriques comprenant deux ou plusieurs connecteurs selon l'une quelconque des revendications précédentes, installés de telle façon que les conduits inclinés sont adjacents aux rampes avec la même pente, sur un substrat porteur de circuit imprimé électrique.

55
10. Ensemble de connecteurs électriques pour relier

7



des substrats porteurs de circuit imprimé électrique comprenant:

un câble souple multiconducteur ayant une pluralité de conducteurs parallèles en travers de sa largeur; et

un connecteur tel que présenté dans l'une quelconque des revendications 1 à 8, fixé à l'une des extrémités ou aux deux extrémités du câble souple multiconducteur.

11. Ensemble de connecteurs électriques selon la revendication 10, dans lequel ledit câble est d'une seule pièce avec l'un des connecteurs ou avec les deux.

5

10

15

20

25

30

35

40

45

50

55

8