

PAYMENT RECONCILIATION IN MIXED-OWNERSHIP LOW-POWER MESH NETWORKS

BACKGROUND

5 Modern networks can comprise a variety of devices, which may be connected in a variety of ways. A network can be, for example, centralized or ad hoc. In the latter case, each networked device, or node, can act as a router to forward data from other nodes, in addition to communicating its own data. These networks however have their limitations. For example, wireless devices powered by batteries may require frequent battery changes due to the high
10 power cost of wireless data transmission. Further, in many instances it may be prohibitively expensive to keep route and/or manipulate information associated with payment reconciliation for devices that serve to forward data from other nodes.

SUMMARY

15 Systems and methods that enable scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network.

For example, in an aspect, a method for enabling payment reconciliation in a mixed-ownership low-power mesh network is disclosed. The method may include or comprise
20 monitoring packet traffic routed by a particular node of the mesh network; identifying an originator node address and a number of units of data for each particular packet of the packet traffic; and sending, in response to a trigger, data to another particular node of the mesh network that represents a total number of units of data routed by the particular node for each originator node address.

25 In another aspect, a network device for communicating data in a mixed-ownership low-power mesh network is disclosed. The network device may include or comprise a battery; a wireless interface; and a processing unit coupled with the battery and the wireless interface. The processing unit may be configured to cause the network device to: track packet traffic routed by the network device to other network devices at least temporarily connected
30 to the mesh network; record an originator network device address and a number of units of data for each particular packet of the packet traffic; and transfer, in response to a detected command, data over the mesh network to another network device at least temporarily connected to the mesh network that represents a total number of units of data routed by the network device for each originator network device address.

In another aspect, a computer-implemented method is disclosed. The method may include or comprise monitoring, by a particular node connected to a mixed-ownership low-power mesh network, packet traffic routed by the particular node over the mesh network; identifying, by the particular node, an originator node address and ownership thereof and a number of units of data for each particular packet of the packet traffic; and detecting, by the particular node, a command to send data to another particular node of the mesh network that represents a sum total number of units of data routed by the particular node for each originator node address.

Although not so limited, an appreciation of the various aspects of the present disclosure may be gained from the following discussion in connection with the drawings.

DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a first example wireless network in accordance with the disclosure.

FIG. 2 shows a second example wireless network in accordance with the disclosure.

FIG. 3 shows an example gateway device in accordance with the disclosure.

FIG. 4 shows an example wireless sensor device in accordance with the disclosure.

FIG. 5 shows a first example nodal network for payment reconciliation.

FIG. 6 shows a second example nodal network for payment reconciliation.

FIG. 7 shows an example method in accordance with the disclosure.

FIG. 8 shows an example computing system or device.

DETAILED DESCRIPTION

The present disclosure is directed to or towards systems and methods that enable scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network. The phrase “payment reconciliation” in the context of present disclosure may refer to one or more actions associated with compensating a particular device owner for allowing the particular device to serve as a router for another device(s). It is contemplated that the type or form of compensation is a business decision, and could embody virtually any type or form of reimbursement as desired.

Payment reconciliation in typical or conventional mesh network implementations is prohibitively expensive, in terms of both the financial and computing resources needed to route and/or manipulate payment reconciliation information. Aspects of the present disclosure address or remedy such issues by accumulating routing information on a node-

node basis, and then forwarding such information to a centralized system as needed or requested so that financial and computing resources are more intelligently leveraged.

The wireless networks and wireless network devices, including wireless sensor devices, or WSDs, of the present disclosure may be configured in a variety of ways, in a variety of contexts. Example configurations include mesh, point-to-point, and/or ad hoc networks, among others. The flexible nature of these networks, enabling network devices, or nodes, to join and leave these networks dynamically, together with WSDs configured to collect and communicate sensor and payment reconciliation information, enables these networks to provide end-to-end security and management of transportation and/or logistical systems. Although disclosed embodiments focus on wireless technologies, the techniques described herein can be applied to wired networks, such as an ad hoc serial interface, for example.

For example, a wireless network can comprise a plurality of WSDs providing sensor information relating to a plurality of cargo containers located in a depot or on a train and/or payment reconciliation information relating to data traffic routed through a particular WSD for one or more other particular WSDs. In general, the sensor information can include data from a variety of sensors, which can indicate the temperature and/or humidity of a container, whether the container door is or has been opened, whether the container is experiencing or has experienced a shock, the location of the container, whether the container is moving, and more. The payment reconciliation information in general can include a consolidated set of data that at least identifies an originator node address and a number of units of data (e.g., bits, bytes, etc.,) for each particular packet of packet traffic routed by a particular WSD, as discussed further below.

The wireless network further can include a gateway device that collects the sensor and payment reconciliation information and provides it to systems outside the wireless network. As WSD-equipped containers enter and leave the depot, the wireless network will adjust accordingly, enabling WSDs of containers entering the depot to join the wireless network while the WSDs of containers leaving the depot are dropped from the wireless network. Furthermore, WSDs can act as routers to relay sensor and payment reconciliation information from other WSDs that are not in direct communication with the depot's gateway device.

Low-power wireless networks can be advantageous in transportation, logistical, and similar applications where network devices are mobile devices operating on battery power. Although many battery-operated mobile devices utilize wireless technologies, most mobile devices exhaust their batteries in a matter of hours or days. The term “low-power wireless

networks” may refer to wireless networks utilizing technologies that enable battery-powered devices to operate for a year or more without exhausting their batteries. This can include technologies associated with the IEEE 802.15.4 and/or ISO/IEC 18000-7 standards, as well as various proprietary technologies, among others.

Referring now to **FIG. 1**, a block diagram of an example logistical management system **100** is shown in accordance with the disclosure. In this embodiment, a plurality of WSDs **102** are networked together to generate and communicate, among other things, sensor data and/or payment reconciliation data. For example, a particular WSD **102** gathering sensor data can communicate sensor data toward a gateway **104** using a particular wired and/or wireless communication connection **106**. Similarly, a particular WSD **102** gathering payment reconciliation data can communicate payment reconciliation data toward a gateway **104** using a particular communication connection **106**. In general, each of the devices or systems within the example system **100** includes a reconciliation module **108** that enables scalable, cost-effective payment reconciliation between owners of the respective devices or systems based on gathered or acquired payment reconciliation data.

For example, a particular instance of a reconciliation module **108** may be configured to monitor packet traffic routed by an associated WSD **102**. For example, the reconciliation module **108** associated with the WSD **102a** as shown in **FIG. 1** may be configured to monitor packet traffic routed by the WSD **102a**, as received from one or more of the WSDs **102b-c**, to the gateway **104** for further processing. In this example, the reconciliation module **108** associated with the WSD **102a** may further identify an originator node address and a number of units of data for each particular packet of the packet traffic. For example, the reconciliation module **108** associated with the WSD **102a** may identify an address and/or other identifier associated with the WSD **102b**, so that the reconciliation module **108** associated with the WSD **102a** may uniquely identify the WSD **102b**. These and other processes performed by the reconciliation module **108** associated with the WSD **102a** in the present discussion in connection with the WSD **102b** are similarly applicable to the WSD **102c**.

Further, the reconciliation module **108** associated with the WSD **102a** may identify a number of bytes of data and/or a number of packets of data transferred from the WSD **102b** to the WSD **102a**, which in this case may serve as a data router for the WSD **102b**. For example, the reconciliation module **108** associated with the WSD **102a** may over a particular period of time identify or log 10 data packets, each comprising 100 bytes data, as having been received from the WSD **102b**. In general, this information may be stored by the reconciliation module **108** associated with the WSD **102a** within a particular data structure or record. In this

manner, the reconciliation module **108** associated with the WSD **102a** may keep track of the number of bytes of data and/or the number of packets of data transferred from the WSD **102b** to the WSD **102a**, so that an owner (e.g., an individual, an organization, etc.) of the WSD **102a** may derive revenue for allowing or enabling the WSD **102a** to serve as a data router for the WSD **102b**. This is assuming that an owner of the WSD **102a** is an entity different than an owner of the WSD **102b**.

Still further, the reconciliation module **108** associated with the WSD **102a** may send, in response to a trigger or signal, data to another particular WSD **102** or the gateway **104** that represents a total number of units of data routed by the WSD **102a** for each originator node address. For example, the reconciliation module **108** associated with the WSD **102a** may as part of a periodic or at least an intermittent process, or in response to the WSD **102a** running out of memory or power or some other critical or limited resource, or in response to a specific command received from another system or device such as the gateway **104** or other device, and etc., send a particular file or set of data to the gateway **104** that specifies that the WSD **102a** served as a router for the WSD **102b** for a particular period of time, and in that particular period of time received and routed a total of 1000 bytes data for the WSD **102b**. These and other such actions associated with payment reconciliation performed by the reconciliation module **108** are discussed in further detail below.

If there are one or more WSDs **102** communicatively linked between a particular WSD **102** originating the sensor data and/or payment reconciliation data and the gateway **104**, the one or more WSDs **102** will relay the sensor data and/or payment reconciliation data until it reaches the gateway **104**. The example system **100** depicted in **FIG. 1** is shown as an example and is not limiting. The sensor network **110** can be configured in a variety of ways. For instance, the gateway **104** can connect with multiple ones of the WSDs **102**, and the WSDs **102** can have more or fewer wireless connections than indicated in **FIG. 1**. Moreover, multiple instances of the gateway **104** and/or multiple instances of the sensor network **110** may be included in the example system **100**.

In the example embodiment, the gateway **104** provides connectivity between the sensor network **110**, comprising the gateway **104** and WSDs **102**, and a device management server (DMS) **112**. Communication between the gateway **104** and the DMS **112** can be relayed through the Internet **114**, or any other Wide Area Network (WAN). Additionally or alternatively, other networks, such as Local Area Networks (LANs), can be used. Other configurations can include a gateway **104** communicating directly with the DMS **112** without a separate network. The DMS **112** itself provides an interface between the sensor network

110 that can be used by a human user or another system, by utilizing, for example, a graphical user interface (GUI) and/or an application programmable interface (API). The DMS 112 can collect and store information from the WSDs 102. The data communicated between the DMS 112 and the gateway 104 can be securely communicated in encrypted packets, and the DMS 112 can provide secure management of the collected data.

One or more of a variety of physical layers may be used to provide the wireless connections of the sensor network 110. According to one embodiment, the WSDs 102 and gateway 104 communicate using a protocol stack based on IEEE 802.15.4 standard at 2.4 GHz using all 16 channels available in that standard. This physical layer enables the sensor network 110 to operate using very low power and/or predictable power consumption, which can be an important consideration for embodiments in which the WSDs 102 and/or gateway 104 operate on battery power. Nonetheless, other wireless technologies may be used, including IEEE 802.15.4 at 900 MHz; IEEE 802.11; Bluetooth.RTM.; IEEE 802.16; Ultra Wideband (UWB); 433 MHz Industrial, Scientific, and Medical (ISM) Band; cellular; optical; and more, using multiple RF channels (e.g., narrow-band frequency hopping) or a single RF channel. The gateway 104 can communicate with the Internet 114 through a wired connection and/or a wireless connection, as shown in FIG. 2.

Other embodiments of the logistical management system 100 of FIG. 1 are possible. For example, FIG. 2 is a block diagram of another example logistical management system 200 in accordance with the disclosure. In this embodiment, the gateway 104 can communicate with the Internet 114 wirelessly, through wireless communications with a satellite 202 and/or a cellular tower 204. The use of such a wireless interface between the gateway 104 and the Internet 114 can be a factor of available Internet connectivity and desired mobility of the sensor network 110, among other considerations.

Referring now to FIG. 3, a block diagram of an embodiment of the gateway 104 of FIGS. 1-2 is shown. This block diagram, as with other figures shown herein, is provided as an example only, and is not limiting. The gateway 104 can be configured in alternate ways by, for example, including a global positioning system (GPS) unit and/or other components not shown in FIG. 3. In the example shown, the gateway 104 includes a processing unit 302, an Internet interface 304, one or more sensors 306, a configuration port 308, a memory 310, a power source 312, and a wireless interface 314.

The processing unit 302 lies at the heart of the gateway 104. The processing unit 302 can be comprised of one or more processors, microprocessors, and/or specialized integrated circuits. The processing unit 302 can gather information from the other components of the

gateway **104** and/or from other devices of the above-described example system **100** as shown in **FIG. 1** and the example system **200** as shown in **FIG. 2**, and process the information in accordance with software **316** disposed in memory **310**. Depending on desired functionality of the gateway **104** and the capabilities of the processing unit **302**, the software **316** can include an operating system with one or more executable programs. Additionally, or alternatively, the software **316** can include lower-level instructions, such as firmware and/or microcode, for the processing unit **302** to execute. An example of such may include instructions to implement functionality of the reconciliation module **108** of the present disclosure. Still other embodiments are possible.

The power source **312** supplies power to the components of the gateway **104** and may provide additional information (e.g., battery charge, voltage levels, etc.) to the processing unit **302**. When the gateway **104** is a mobile device, the power source **312** can comprise one or more batteries. When the gateway **104** is a fixed or stationary device the power source **312** can include a power converter, transformer, and/or voltage regulator. Still other embodiments are possible.

The wireless interface **314** enables communication with the WSDs **102** of **FIGS. 1-2**. As indicated above, this communication can be effectuated using any of a variety of technologies, including radio frequency (RF) and/or optical communication technologies. Where RF technologies are used, the wireless interface **314** may be coupled to an antenna (not shown). Still other embodiments are possible.

The configuration port **308** may allow a computing device to be connected to the gateway **104** for the purpose of configuring the gateway **104**. The configuration port **308** can comprise universal serial bus (USB) connector, serial port, optical, or other connector to input information from an external device. Depending on the functionality of the gateway **104** and/or WSDs **102**, the configuration port **308** may be used to configure device information and reporting, sensor parameters, software, security, network parameters, power consumption, GPS parameters, file management, payment reconciliation parameters and/or setting, and much more.

The Internet interface **304** can be any of a variety of interfaces, depending on desired functionality. As indicated in **FIGS. 1-2**, the gateway **104** can have a wired connection with the Internet **114**, in which case the Internet interface **304** can include an Ethernet or other wired interface. Additionally or alternatively, the gateway **104** can have a wireless connection with the Internet **114**. In this case, the Internet interface **304** can comprise one or more

wireless radios, such as a dual-mode WAN radio enabling cellular and satellite communication. Still other embodiments are possible.

The one or more sensors **306** may enable the gateway **104** to collect sensor information similar to the WSDs **102**. This sensor information can include information relating to temperature, humidity, motion, light, battery charge, shock, and application-specific information (e.g. the state of a door, open or closed, on a cargo container). Depending on desired functionality, the processing unit **210** may collect, process, and/or record the sensor information, or the processing unit **210** simply may send unprocessed sensor information to the DMS **112** using the Internet interface **304**.

Referring now to **FIG. 4**, is a block diagram of an embodiment of a WSD **102** is shown. In general, the WSD **102** is configured and/or arranged in a manner similar to the gateway **104**. For example, the WSD **102** may be configured to include a processing unit **402**, one or more sensors **404**, a memory **406**, a battery **408**, a GPS unit **410**, and a wireless interface **412**. Here, however, the components may be less complex than corresponding components of the gateway **104**, due to power and functionality considerations. Additionally, it can also be noted that the WSD **102** and/or the gateway **104** can include an interface (not shown) to provide a user with information. Such an interface can comprise a liquid-crystal display (LCD), one or more light emitting diodes (LEDs), etc. Other embodiments are possible. For example, in some embodiments, the WSD **102** may be configured exactly similar to the gateway **104** as shown in **FIG. 3**. In other words, in some embodiments, the WSDs **102** and the gateway **104** as discussed throughout may be the same type of device, so that that gateway **104** itself is a WSD **102**, or vice versa.

The processing unit **402** can comprise a microprocessor and the memory **406** and software **414** can comprise programmed logic of the microprocessor. Among other things, the software **414** may include instructions to implement functionality of the reconciliation module **108** of the present disclosure, discussed further below.

With respect to the battery **408**, because the wireless network can provide lower-power consumption, a battery having a long shelf life, e.g., an alkaline-, silver-oxide-, or lithium-based battery, can provide for operability of the WSD **102** without the need to change batteries for several years. According to one embodiment, the WSD **102** uses up to 4 A-size 3.6 volt (V) batteries, each battery rated at approximately 3600 milliamp hours (mAh). Some embodiments of the WSD **102** have an operating power of under 2 milliwatts (mW); other embodiments of the WSD **102** operate under 1 mW. Therefore, depending on the shelf life

and capacity of the battery **408**, as well as the configuration of the WSD **102**, the WSD **102** could operate for 10 years or more without the need to change the battery **408**.

Further, the GPS unit **410** may provide location information. Location information can be particularly useful where or when the sensor network **110** shown in **FIGS. 1-2** is spread over a relatively large geographical area. Moreover, the GPS unit **410** can be used to sense motion of the WSD **102** by determining, by the GPS unit **410** and/or the processing unit **402** a change in location over time.

Similar to that mentioned above, embodiments of the present disclosure provide a methodology for payment reconciliation between device owners for routing services in infrastructure-free (i.e., ad hoc) mesh networks, without putting a burden on resource constrained, low-power devices. Conventional mobile networks typically rely on public-key infrastructure (PKI)-based authentication to enable roaming payments. This is possible because the cellular link is high bandwidth, tower networks bandwidth is even higher, processing power on the mobile devices is not resource constrained for PKI operations, and mobile devices only communicate through cellular networks and never through each other on a regular basis.

In the environment however where a single network can have tens of thousands of resource constrained devices connected into a mesh network, belonging to hundreds of different owners, full PKI authentication is prohibitively expensive in terms of power consumption and bandwidth. The type of currency is expected to be as low as micro-dollars, therefore it is contemplated that the cost of payment reconciliation process must match that in order to be viable, and aspects of the present disclosure achieve this. Among other advantages, embodiments can provide extremely low processing accounting leveraging routing methods, extremely compact data storage for accounting data, and/or a reliable and inexpensive method for accounting data reporting to an accounting backend. Moreover, embodiments may also be used in data traffic pattern analysis, security audits, and/or many other applications.

In general, and referring now to **FIG. 5** which shows a first example simplified mesh network **500** of a plurality of interconnected nodes, routing history in accordance with the present disclosure may be represented as a correspondence table, as shown in **Table 1** below, where a packet originator node address and the router address which leads the path to the originator node are stored. Each node as shown in **FIG. 5** is intrinsically a router, and each connection shown is intrinsically a bi-directional communication path or connection. Further, each connection shown in **FIG. 5** is not necessarily permanent. Rather, new connections may

be made and old connections may be broken as nodes (i.e., devices such as those shown above in **FIGS. 1-2**) connect or disconnect with or from one another in the context of the example mesh network **500**.

Originator Node Address (OA)	Router Originator Leading Address (RA)
A	X
B	X
C	Y
D	Y

Table 1

The actual data structure of the routing history need not necessarily be a table, as shown in **Table 1**. Rather, it is contemplated that the data structure may be another type of structure as desired, such as a binary tree, hash table, etc., and that the data structure may be formatted, modified, compressed, consolidated, etc., so that that the bandwidth required to pass the data structure or at least a portion thereof over the mesh network **500** may be minimized. This and other benefits as described throughout may be realized by the features or aspects of the present disclosure. Additionally, other columns may be include in **Table 1** such as, for example, a time to live (TTL) column wherein when no updates are made to the record for TTL, the record is purged. In the example embodiment, every time a data packet travels through a particular mesh node (e.g., Node X) a particular action may occur such as, for example: a) A new record is added to the routing history shown in **Table 1**, if the packet is from a new originator (e.g., Node A); b) The record is updated with new leading router information if applicable (TTL is reset); or c) No action if the correspondence is the same (TTL is reset). Additionally, or alternatively, whenever the leading router is lost, all records associated therewith are purged. Other embodiments are possible.

It is contemplated that **Table 1** may be modified so as to provide for a routing method with accounting according to the principles of the present disclosure. In particular, routing history may still comprise of a correspondence table, where the packet originator node address and the router address which leads the path to the originator node can be stored. As shown in **Table 2** below, however, additional field(s) may represent a packet or/and byte counter. In some embodiments, there may be two different columns representing packet and byte counters separately. It is however contemplated that the number and/or types of columns additional to that as shown in **Table 2** may be implementation-specific, where ultimately the

simplicity and/or minimized size of **Table 2** may be considered its most attractive, useful, and efficient characteristic.

OA	RA	# of packets transferred/# of bytes transferred
A	X	0/0
B	X	122/13904
C	Y	45/6554
D	Y	2/179

Table 2

The values shown in **Table 2** are for example purposes only. Further, it is contemplated that the routing table as shown in **Table 2** may be collapsed, consolidated, or otherwise reformatted so as to only include that information ultimately necessary to enable scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure. Specifically, an accounting file F, as shown in **Table 3** below, may be derived from the routing table shown in **Table 2**.

OA	# of packets transferred/# of bytes transferred
A	0/0
B	122/13904
C	45/6554
D	2/179

Table 3

The values shown in **Table 3** are for example purposes only. Further, the simplicity and/or minimized size of the accounting file F as shown in **Table 3** may be considered its most attractive, useful, and efficient characteristic. It is contemplated that the accounting file F may be established when a particular device is initiated or initialized. Additionally, the actual data structure of the routing history may not necessarily be a table, as shown in **Table 3**. Rather, it is contemplated that the data structure may be another type of structure as desired, such as a binary tree, hash table, etc., to enable for “fast” search, replacement, deletion, and other operations. Additionally, it is contemplated that the data structure may be formatted, modified, compressed, consolidated, etc., so that that the bandwidth required to pass the data structure or at least a portion thereof over the mesh network may be minimized.

Additionally, similar to the above-discussion, records (e.g., **Tables 1-3** may be considered to be a record, file, data structure, etc.) may have a time to live TTL column (e.g., additional column in **Table 2**). When no updates are made to the record for TTL, the record may be updated in or appended to the accounting file F as shown in **Table 3**, and then
5 purged. Further, in the example embodiment, every time a data packet travels through a particular mesh node such as those nodes shown in **FIG. 5**, a particular action may occur such as, for example: a) A new record is added to routing history, if the packet is from a new originator node, and corresponding “starting” accounting values are established; b) The record is updated with the new leading router information if applicable, and the counter is
10 updated and not reset due to the leading router change, and TTL reset; c) When correspondence is the same, the accounting counter is updated, TTL reset. Other embodiments are possible.

Additionally, it is contemplated that when any leading router is lost, before all record associated with it are purged from the table, they can be stored in the accounting file F as
15 shown in simplified form in **Table 3**. Storing in this case may refer to either appending the accounting file F with new records or modifying the counter values for the originator nodes that are already in the accounting file F. Modification in this case may refer to the current value in the accounting file F plus a new value from the routing history. Additionally, counters can be stored in the accounting file F periodically, and after this operation the
20 counters in the routing history may be reset to zero. Furthermore, such operations as discussed in connection with **Tables 1-3** may be performed as blocking operations where no updates to routing history are made during execution of one or more particular operations. Advantageously, this may prevent losses in accounting wherein certain information may otherwise be lost during the finite period of time needed to update and/or send the accounting
25 file F or an equivalent data structure, possibly compressed to further conserve bandwidth and/or other system or device resources, to another node within the mesh network of **FIG. 5** for further processing.

Those and other operations as discussed in connection with **FIG. 5** are discussed in further detail below. For example, it is contemplated that the accounting file F may be
30 transferred to an accounting back end periodically, on request, or upon a trigger (e.g. file system or memory is running out of space). Further, file transfer can be a lengthy operation. One or more of the following processes may assist to assure correct accounting and cleanup of the accounting file F: a) At the time of reporting a copy of the accounting file F may be created in the file system; b) The accounting file F may continue to be updated independent

of the file transfer; c) The copy may be transferred to the accounting backend associated with a particular node address; c) When positive confirmation is received for the copy transfer, the values within the copy may be subtracted from the accounting file F as a blocking operation. If the new value is zero, the record is purged from the accounting file F and the copy file is deleted. Other embodiments are possible.

Referring now to **FIG. 6**, a second example simplified mesh network **600** of a plurality of interconnected nodes is shown in accordance with the present disclosure. Example details associated with how respective elements within the example mesh network **600** communicate with and amongst each other in a manner consistent with the context and principles of the present disclosure is or are discussed in U.S. Patent Number 8,416,726, and U.S. Patent Application Serial Numbers 13/023,673, 13/096,127, 13/096,745, 13/553,466, and 13/551,477, wherein the entirety of each of these patent documents is hereby incorporated by reference. In the example of **FIG. 6**, the mixed-ownership nature of the interconnected nodes is represented whereby those nodes or devices (e.g., WSDs **102**, gateway **104**, etc.) owned by a particular entity A are indicated as such by the “triangle-shaped” nodes, those nodes or devices owned by a particular entity B are indicated as such by the “circle-shaped” nodes, and those nodes or devices owned by a particular entity C are indicated as such by the “square-shaped” nodes. Also shown is a first database **604**, a second database **606**, and a third database **608**. For discussion purposes, it is assumed that the first database **604** is owned by the particular entity A, the second database **606** is owned by the particular entity B, and the third database **608** is owned by the particular entity C. Other embodiments are possible.

In the current state of the mesh network **600**, as represented in **FIG. 6** by the shown connectivity between particular nodes, a first node **610** associated with the particular entity A, a second node **612** associated with the particular entity B, and a third node **614** associated with the particular entity C, are essentially or may be referred to as leading nodes, as those nodes alone have a direct connection to the Internet **616**. In practice, at least those nodes may serve as routers to other nodes connected thereto, and the nodes connected thereto may change in time due to the ad hoc nature of the mesh network **600**. For example, the first node **610** in time may serve as a router for a number of different nodes within the mesh network **600**, and may keep track of each originator node address as well as a number of units of data for each particular packet of packet traffic passed by the first node **610** when the first node **610** serves as router to route the packet traffic.

In this example, the first node **610** at some point in time may detect a trigger that commands the first node **610** to send an accounting file or at least a copy thereof to the first database **604**, so that the particular entity A may ultimately derive revenue for allowing or enabling the first node **610** to serve as a data router for other nodes. In general, the accounting file may be derived from a particular record, where the record might include a plurality of data that specifies that the first node **610** served as a router for data for a plurality of nodes associated with each of the particular entities A-C. It will be appreciated, however, that the first node **610** may not necessarily be concerned with the resources expended when serving as a router for nodes associated with the particular entity A, since the first node **610** is owned by the particular entity A and it might be unlikely that the particular entity A would charge itself for those services.

Accordingly, in response to the trigger, the first node **610** may delete or otherwise ignore the data that specifies that the first node **610** served as a router for data for a plurality of nodes associated with the particular entity A. However, in this scenario, the first node **610** may aggregate or consolidate the data that specifies that the first node **610** served as a router for data for a plurality of nodes associated with each of the particular entity B and C, since the particular entity A may wish to be reimbursed for allowing or enabling the first node **610** to serve as a router for data for a plurality of nodes associated with those entities (i.e., entity B and entity C). The first node **610** may then send that data to the first database **604** as part of process for payment reconciliation as discussed in the context of the present disclosure.

An original or unmodified data structure or file managed or maintained by the first node **610** may, for example, contain data as shown in **Table 4**:

OA	# of packets transferred/# of bytes transferred
A	56/56345
B	29/8648
C	33/634543
D	5/58
E	45/456456
F	78/34524
G	23/907
...	...

Table 4

The values shown in **Table 4** are for example purposes only. In this example, the first node **610** may query a local resource, such as a look-up table or external device or system to determine ownership of those devices associated with node addresses A-G. Here, the first node **610** may determine for example that node addresses A-C are associated with the particular entity A, and may ignore associated data. The first node **610** may further determine for example that node addresses D-E are associated with the particular entity B, and that node addresses F-G are associated with the particular entity C. A modified data structure or file based on that may be generated by the first node **610** and may, for example, contain data as shown in **Table 5**:

Entity	# of packets transferred/# of bytes transferred
B	50/456514
C	101/35431
...	...

Table 5

In this example, the first node **610** has compressed or otherwise consolidated the original data structure or file so that the first node **610** may use as little bandwidth, power, resources, etc., to transfer the data to the first database **604** as part of process for payment reconciliation as discussed in the context of the present disclosure. Other embodiments are possible.

Referring now to **FIG. 7**, an example method **700** is shown in accordance with the present disclosure. In general, steps of the method **700** may be implemented by any particular reconciliation module **108** as shown in the Figures and discussed above as part of process for payment reconciliation. Other embodiments are possible.

At step **702**, accounting information may be appended as desired to a particular routing record each time a packet travels through a particular mesh network node. For example, each time a packet is routed by the WSD **102a** as shown and discussed above in connection with at least **FIG. 1**, the reconciliation module **108** associated with the WSD **102a** may either create a new entry for a particular originator node address if not already contained within a routing table (e.g., a table similar to that shown in **Table 3**), and associate a particular number of bytes of data and/or a number of packets of data with the new entry, or update an existing entry for a particular originator node address if already contained within a routing table, and associate a particular number of bytes of data and/or a number of packets of data with the existing entry. Other embodiments are possible.

At step **704**, a trigger may be detected that instantiates a process whereby certain accounting information within the record mentioned above in connection with step **702** may be sent or transferred from the particular mesh network node to another particular mesh network node. For example, the reconciliation module **108** associated with the WSD **102a** may as part of a periodic process, or in response to the WSD **102a** running out of memory or power or some other critical or limited resource, or in response to a specific command received from another system or device such as the gateway **104** or other device, and etc., instantiate a process whereby the WSD **102a** aggregates or consolidates data that specifies that the WSD **102a** served as a router for data for a plurality of nodes associated with a particular entity other than one associated with the WSD **102a**. Other embodiments are possible.

At step **706**, accounting information within the record mentioned above in connection with step **702** may be modified, reformatted, compressed, etc., as desired to minimize the amount of data and amount or number resources required to send such information over a network connection. More specifically, it is contemplated that this process will be implemented so as to minimize the amount of power, memory, and other resources of the particular mesh network node. For example, the reconciliation module **108** associated with the WSD **102a** may modify and/or compress data contained within its routing table, so that certain data may be deleted or otherwise ignored that specifies that the WSD **102a** served as a router for data for a plurality of nodes associated with the particular entity also associated with the WSD **102a**, and other data may be consolidated in manner as shown and described above in connection with **Table 5**. Other embodiments are possible. At step **708**, the accounting information as modified in connection with step **706** may be sent to the another particular mesh network node as discussed in connection with step **704**. Last, at step **710**, the accounting information within the record mentioned above in connection with step **702** may be purged so as to maximally utilize memory and possibly other resources of the particular mesh network node. Other embodiments are possible.

As mentioned above, payment reconciliation in typical or conventional mesh network implementations is prohibitively expensive, in terms of both the financial and computing resources needed to route and/or manipulate payment reconciliation information. Aspects of the present disclosure address or remedy such issues by accumulating routing information on a node-node basis, and then forwarding such information to a centralized system as needed or requested so that financial and computing resources are more intelligently leveraged.

For example, systems, devices, computer-program products, and methods for enabling payment reconciliation in a mixed-ownership, low-power mesh network are disclosed. In practice, it is contemplated that packet traffic routed by a particular node of the mesh network may be monitored, an originator node address and a number of units of data for each particular packet of the packet traffic may be identified, and data may be sent, in response to a detected trigger, to another particular node of the mesh network that represents a total number of units of data routed by the particular node for each originator node address.

For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network is intrinsically a router, and may be configured and/or arranged to exhibit features or functionality that permit each particular network node or device itself to monitor, observe, track, keep an accounting record of, etc., on a packet-by-packet basis, packet traffic routed by the same on behalf of other network nodes or devices within or at least temporarily connected to the mesh network. Additionally, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to access a stored, possibly periodically or at least intermittently updated, look-up table or any other organized data structure, and/or parse each particular routed data packet, to derive or identify a unique network address associated with another particular node of the mesh network for which packet traffic has been routed. Further, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to precisely determine and send to another node or device a total (e.g., summed) number of units of data routed for each originator node address. In general, this may be likened to an accounting process whereby a running total of bits, bytes, etc., associated with another particular node of the mesh network for which packet traffic has been routed is maintained and/or managed. Other embodiments, implementations, aspects, features, etc., are possible as well.

For example, additionally, or alternatively, the method may include or comprise identifying ownership for each originator node address, summing the number of units of data for each originator node address with shared ownership, and sending the summed number of units of data to the another particular node with an identifier of ownership. Advantageously, such a feature may, among other things, minimize the amount of bandwidth needed to transfer data across the mesh network, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise compressing the data that represents the total number of units of data routed by the particular node for each originator node address prior to sending. For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to implement a particular data compression algorithm (e.g., lossless or lossy) to encode using as few bits as possible any and all data transferred or sent to other nodes or device within or at least temporarily connected to the mesh network. Advantageously, such a feature may, among other things, minimize the amount of bandwidth needed to transfer data across the mesh network, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise encrypting and authenticating the data that represents the total number of units of data routed by the particular node for each originator node address prior to sending. For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to implement a particular encryption and/or authentication algorithm. Advantageously, such a feature may, among other things, introduce one or more security measures into the system, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise nullifying data that represents the total number of units of data routed by the particular node for at least one particular originator node address prior to sending other data to the another particular node. Additionally, or alternatively, the method may include or comprise determining ownership of the another particular node, and sending the data that represents the total number of units of data routed by the particular mesh for each originator node address when a fee for routing data by the another particular node is determined to be zero. Advantageously, such a feature(s) may, among other things, allow a particular node or device to ignore accounting data that might normally not be necessary to keep track of, such as accounting data associated with a particular in-common ownership entity, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a

particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise receiving notification from the another particular node confirming receipt of the data that represents the total number of units of data routed by the particular node for each originator node address. For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to send a confirmation message indicating receipt of accounting data from another network node or device. Advantageously, such a feature may, among other things, allow a particular network node or device to implement housekeeping or clean-up activities to a particular accounting file following confirmation of data transfer, to generally minimize the size of the file and thus minimize the amount of bandwidth needed to transfer data across the mesh network, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise continuing monitoring packet traffic routed by the particular node of the mesh network during the sending, and identifying originator node address and number of units of data for each particular packet of the packet traffic during the sending. For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to continue with bookkeeping or accounting activities even during the process of sending and/or manipulating bookkeeping or accounting information, so as to at all times keep track of routed packet traffic. Advantageously, such a feature may, among other things, allow a particular node or device to maintain and/or manage an accurate running account of bookkeeping or accounting information, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise modifying an existing data structure maintained by the particular node to include the total number of units of data routed by the particular node for each originator node address. Additionally, or alternatively, the method may include or comprise modifying an existing data structure maintained by the particular node to include a particular originator node address and a total number of units of data routed by the particular node for particular originator node address.

For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to maintain and/or manage a distinct bookkeeping or accounting file or data structure, so as to at all allow for a system wide account or accounting of routed packet traffic. Advantageously, such a feature may, among other things, allow a particular node or device to maintain and/or manage an accurate running account of bookkeeping or accounting information, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

Additionally, or alternatively, the method may include or comprise sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a periodic trigger instantiated by the particular node. Additionally, or alternatively, the method may include or comprise sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a trigger instantiated by the particular node based on a particular resource condition of the particular node. Additionally, or alternatively, the method may include or comprise sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a particular command received by the particular node from a different node connected to the mesh network. For example, in accordance with the disclosure, each particular network node or device within or at least temporarily connected to the mesh network may be configured and/or arranged to report its bookkeeping or accounting file or data structure to another particular network node or device within or at least temporarily connected to the mesh network in response to any of a number of different types of commands or triggers. Advantageously, such a feature may, among other things, introduce flexibility into the system, thereby enabling scalable, cost-effective payment reconciliation between owners of devices at least temporarily connected in or to a particular low-power, ad hoc mesh network in accordance with the principles of the present disclosure.

FIG. 8 shows an example computer system or device **800** in accordance with the present disclosure. An example of a computer system or device includes a wireless sensor device, an enterprise server, blade server, desktop computer, laptop computer, tablet computer, personal data assistant, and/or any other type of machine configured for performing calculations. The computer system **800** may be wholly or at least partially incorporated as part of previously-described computing devices, such as any of the respective

elements of at least **FIGS. 1-2**. Further, the computer device **800** may be configured to perform and/or include instructions that, when executed, cause the computer system **800** to perform the method of **FIG. 7**. Still further, the computer device **800** may be configured to perform and/or include instructions that, when executed, cause the computer system **800** to instantiate and implement functionality of the reconciliation module **108** of at least **FIGS. 1-2**.

The computer device **800** is shown comprising hardware elements that may be electrically coupled via a bus **802** (or may otherwise be in communication, as appropriate). The hardware elements may include a processing unit with one or more processors **804**, including without limitation one or more general-purpose processors and/or one or more special-purpose processors (such as digital signal processing chips, graphics acceleration processors, and/or the like); one or more input devices **806**, which may include without limitation a remote control, a mouse, a keyboard, and/or the like; and one or more output devices **808**, which may include without limitation a presentation device (e.g., television), a printer, and/or the like.

The computer system **800** may further include (and/or be in communication with) one or more non-transitory storage devices **810**, which may comprise, without limitation, local and/or network accessible storage, and/or may include, without limitation, a disk drive, a drive array, an optical storage device, a solid-state storage device, such as a random access memory, and/or a read-only memory, which may be programmable, flash-updateable, and/or the like. Such storage devices may be configured to implement any appropriate data stores, including without limitation, various file systems, database structures, and/or the like.

The computer device **800** might also include a communications subsystem **812**, which may include without limitation a modem, a network card (wireless or wired), an infrared communication device, a wireless communication device, and/or a chipset (such as a Bluetooth™ device, an 802.11 device, a WiFi device, a WiMax device, cellular communication facilities (e.g., GSM, WCDMA, LTE, etc.), and/or the like. The communications subsystem **812** may permit data to be exchanged with a network (such as the network described below, to name one example), other computer systems, and/or any other devices described herein. In many embodiments, the computer system **800** will further comprise a working memory **814**, which may include a random access memory and/or a read-only memory device, as described above.

The computer device **800** also may comprise software elements, shown as being currently located within the working memory **814**, including an operating system **816**, device drivers, executable libraries, and/or other code, such as one or more application programs **818**, which may comprise computer programs provided by various embodiments, and/or may be designed to implement methods, and/or configure systems, provided by other embodiments, as described herein. By way of example, one or more procedures described with respect to the method(s) discussed above, and/or system components might be implemented as code and/or instructions executable by a computer (and/or a processor within a computer); in an aspect, then, such code and/or instructions may be used to configure and/or adapt a general purpose computer (or other device) to perform one or more operations in accordance with the described methods.

A set of these instructions and/or code might be stored on a non-transitory computer-readable storage medium, such as the storage device(s) **810** described above. In some cases, the storage medium might be incorporated within a computer system, such as computer system **800**. In other embodiments, the storage medium might be separate from a computer system (e.g., a removable medium, such as flash memory), and/or provided in an installation package, such that the storage medium may be used to program, configure, and/or adapt a general purpose computer with the instructions/code stored thereon. These instructions might take the form of executable code, which is executable by the computer device **800** and/or might take the form of source and/or installable code, which, upon compilation and/or installation on the computer system **800** (e.g., using any of a variety of generally available compilers, installation programs, compression/decompression utilities, etc.), then takes the form of executable code.

It will be apparent that substantial variations may be made in accordance with specific requirements. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software, firmware (including portable software, such as applets, etc.), or each. Further, connection to other computing devices such as network input/output devices may be employed.

As mentioned above, in one aspect, some embodiments may employ a computer system (such as the computer device **800**) to perform methods in accordance with various embodiments of the disclosure. According to a set of embodiments, some or all of the procedures of such methods are performed by the computer system **800** in response to processor **804** executing one or more sequences of one or more instructions (which might be incorporated into the operating system **816** and/or other code, such as an application program

818) contained in the working memory **814**. Such instructions may be read into the working memory **814** from another computer-readable medium, such as one or more of the storage device(s) **810**. Merely by way of example, execution of the sequences of instructions contained in the working memory **814** may cause the processor(s) **804** to perform one or more procedures of the methods described herein.

The terms “machine-readable medium” and “computer-readable medium,” as used herein, may refer to any non-transitory medium that participates in providing data that causes a machine to operate in a specific fashion. In an embodiment implemented using the computer device **800**, various computer-readable media might be involved in providing instructions/code to processor(s) **804** for execution and/or might be used to store and/or carry such instructions/code. In many implementations, a computer-readable medium is a physical and/or tangible storage medium. Such a medium may take the form of a non-volatile media or volatile media. Non-volatile media may include, for example, optical and/or magnetic disks, such as the storage device(s) **810**. Volatile media may include, without limitation, dynamic memory, such as the working memory **814**.

Example forms of physical and/or tangible computer-readable media may include a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, a RAM, a PROM, EPROM, a FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer may read instructions and/or code. Various forms of computer-readable media may be involved in carrying one or more sequences of one or more instructions to the processor(s) **804** for execution. By way of example, the instructions may initially be carried on a magnetic disk and/or optical disc of a remote computer. A remote computer might load the instructions into its dynamic memory and send the instructions as signals over a transmission medium to be received and/or executed by the computer system **800**.

The communications subsystem **812** (and/or components thereof) generally will receive signals, and the bus **802** then might carry the signals (and/or the data, instructions, etc. carried by the signals) to the working memory **814**, from which the processor(s) **804** retrieves and executes the instructions. The instructions received by the working memory **814** may optionally be stored on a non-transitory storage device **810** either before or after execution by the processor(s) **804**.

It should further be understood that the components of computer device **800** can be distributed across a network. For example, some processing may be performed in one location using a first processor while other processing may be performed by another

processor remote from the first processor. Other components of computer system **800** may be similarly distributed. As such, computer device **800** may be interpreted as a distributed computing system that performs processing in multiple locations. In some instances, computer system **800** may be interpreted as a single computing device, such as a distinct
5 laptop, desktop computer, or the like, depending on the context.

The methods, systems, and devices discussed above are examples. Various configurations may omit, substitute, or add various method steps or procedures, or system components as appropriate. For instance, in alternative configurations, the methods may be performed in an order different from that described, and/or various stages may be added,
10 omitted, and/or combined. Also, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

Specific details are given in the description to provide a thorough understanding of
15 example configurations (including implementations). However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the
20 preceding description of the configurations will provide those of skill with an enabling description for implementing described techniques. Various changes may be made in the function and arrangement of elements without departing from the spirit or scope of the disclosure.

Also, configurations may be described as a process which is depicted as a flow
25 diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations may be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any
30 combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

Furthermore, the example embodiments described herein may be implemented as logical operations in a computing device in a networked computing system environment. The logical operations may be implemented as: (i) a sequence of computer implemented instructions, steps, or program modules running on a computing device; and (ii) interconnected logic or hardware modules running within a computing device.

Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

WHAT IS CLAIMED IS:

1. A method for enabling payment reconciliation in a mixed-ownership low-power mesh network, comprising:

monitoring packet traffic routed by a particular node of the mesh network;
identifying an originator node address and a number of units of data for each particular packet of the packet traffic; and
sending, in response to a trigger, data to another particular node of the mesh network that represents a total number of units of data routed by the particular node for each originator node address.

2. The method of claim 1, further comprising:
identifying ownership for each originator node address;
summing the number of units of data for each originator node address with shared ownership; and
sending the summed number of units of data to the another particular node with an identifier of ownership.

3. The method of claim 1, further comprising:
compressing the data that represents the total number of units of data routed by the particular node for each originator node address prior to sending.

4. The method of claim 1, further comprising:
encrypting and authenticating the data that represents the total number of units of data routed by the particular node for each originator node address prior to sending.

5. The method of claim 1, further comprising:
nullifying data that represents the total number of units of data routed by the particular node for at least one particular originator node address prior to sending other data to the another particular node.

6. The method of claim 1, further comprising:
determining ownership of the another particular node; and

sending the data that represents the total number of units of data routed by the particular mesh for each originator node address when a fee for routing data by the another particular node is determined to be zero.

7. The method of claim 1, further comprising:

receiving notification from the another particular node confirming receipt of the data that represents the total number of units of data routed by the particular node for each originator node address.

8. The method of claim 1, further comprising:

continuing monitoring packet traffic routed by the particular node of the mesh network during the sending; and

identifying originator node address and number of units of data for each particular packet of the packet traffic during the sending.

9. The method of claim 1, further comprising:

detecting the trigger and sending the data to the another particular node.

10. The method of claim 1, further comprising:

modifying an existing data structure maintained by the particular node to include the total number of units of data routed by the particular node for each originator node address.

11. The method of claim 1, further comprising:

modifying an existing data structure maintained by the particular node to include a particular originator node address and a total number of units of data routed by the particular node for particular originator node address.

12. The method of claim 1, further comprising:

sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a periodic trigger instantiated by the particular node.

13. The method of claim **1**, further comprising:

sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a trigger instantiated by the particular node based on a particular resource condition of the particular node.

14. The method of claim **1**, further comprising:

sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in response to a particular command received by the particular node from a different node connected to the mesh network.

15. The method of claim **1**, further comprising:

sending the data to the another particular node that represents the total number of units of data routed by the particular node for each originator node address in addition to data that represents a unique identifier for each originator node address.

16. A network device for communicating data in a mixed-ownership low-power mesh network, comprising:

a battery;

a wireless interface; and

a processing unit coupled with the battery and the wireless interface, configured to cause the network device to:

track packet traffic routed by the network device to other network devices at least temporarily connected to the mesh network;

record an originator network device address and a number of units of data for each particular packet of the packet traffic; and

transfer, in response to a detected command, data over the mesh network to another network device at least temporarily connected to the mesh network that represents a total number of units of data routed by the network device for each originator network device address.

17. The network device of claim **16**, the processing unit configured to cause the network device to:

transfer the data to the another network device in response to a command instantiated by the particular network device at a regular temporal interval.

18. The network device of claim **16**, the processing unit configured to cause the network device to:

transfer the data to the another network device in response to a command instantiated by the particular network device based on a particular detected resource condition of the particular network device.

19. The network device of claim **16**, the processing unit configured to cause the network device to:

transfer the data to the another network device in response to a particular command received by the particular network device from another particular network device connected to the mesh network.

20. A computer-implemented method, comprising:

monitoring, by a particular node connected to a mixed-ownership low-power mesh network, packet traffic routed by the particular node over the mesh network;

identifying, by the particular node, an originator node address and ownership thereof and a number of units of data for each particular packet of the packet traffic; and

detecting, by the particular node, a command to send data to another particular node of the mesh network that represents a sum total number of units of data routed by the particular node for each originator node address.